Package 'phyloatlas'

November 7, 2026

Type Package

Title Access to the 'Phylo-Species Atlas' of Empirical Phylogenies

Version 0.1.1

Description Provides convenience functions to fetch standardized phylogenetic trees and per-tree provenance metadata from the 'Phylo-Species Atlas' <https://github.com/franciscorichter/phylo-species-atlas> directly from R. The atlas is a curated collection of empirical species-level trees covering Bacteria, Archaea, and Eukaryota, organized into 62 partitions of life with tip labels normalized against a shared dictionary of standardized species identifiers. Functions load any of the standardized trees with species labels resolved from the dictionary, list available trees, and inspect per-tree provenance.

License MIT + file LICENSE

Encoding UTF-8

URL https://github.com/franciscorichter/phylo-species-atlas, https://franciscorichter.github.io/phylo-species-atlas/

BugReports https://github.com/franciscorichter/phylo-species-atlas/issues

Depends R (>= 4.0)

Imports ape, utils

Suggests knitr, rmarkdown, testthat (>= 3.0.0), withr

Config/testthat/edition 3

VignetteBuilder knitr

RoxygenNote 7.3.3

NeedsCompilation no

Author Francisco Richter [aut, cre] (ORCID: <https://orcid.org/0000-0002-0924-4613>)

Maintainer Francisco Richter <richtf@usi.ch>

Repository CRAN

Date/Publication 2026-11-07 22:20:14 UTC

Contents

atlas_clear_cache 2
atlas_info 2
list_trees 3
load_atlas_tree 4

Index **6**

`atlas_clear_cache` *Clear the in-memory cache*

Description

The dictionary and metadata files are downloaded once per R session and cached. Call this if you want to force a re-download (for example after switching ‘phyloatlas.base_url‘).

Usage

```
atlas_clear_cache()
```

Value

Invisibly ‘NULL‘. Called for its side effect of emptying the internal cache environment.

See Also

Other atlas: `atlas_info()`, `list_trees()`, `load_atlas_tree()`

Examples

```
# Safe to run unconditionally — just empties the in-session cache.
atlas_clear_cache()
```

`atlas_info` *Get metadata for a single tree*

Description

Get metadata for a single tree

Usage

```
atlas_info(name)
```

Arguments

name	Tree name without the ‘.nwk‘ extension (e.g. ‘"mammals"‘, ‘"birds"‘, ‘"fish"‘). Must be a length-1 non-‘NA‘ character string. Use [list_trees()] to see all available names.

Value

A one-row data frame with all metadata columns from [list_trees()], or ‘NULL‘ (with a warning) if no tree by that name exists. Also returns ‘NULL‘ (with a diagnostic message, no warning) if the atlas metadata cannot be downloaded.

See Also

Other atlas: `atlas_clear_cache()`, `list_trees()`, `load_atlas_tree()`

Examples

```
info <- atlas_info("mammals")
if (!is.null(info)) info
```

---

list_trees *List trees available in the Phylo-Species Atlas*

Description

Returns a data frame describing every standardized tree in the atlas: name, study, number of tips, whether the tree is time-calibrated, plus provenance fields (year, journal, DOI, coverage) when available.

Usage

```
list_trees()
```

Value

A data frame with one row per tree, ordered by group, with columns ‘name‘, ‘group‘, ‘study‘, ‘ntips‘, ‘dated‘, ‘year‘, ‘journal‘, ‘doi‘, ‘crown_ma‘, ‘described_species‘, ‘coverage_pct‘, ‘data_source‘, ‘download_url‘, ‘methods_brief‘, ‘notes‘, and ‘study_full‘ (the long-form study citation from the provenance file). Returns ‘NULL‘ with a single diagnostic message if the atlas metadata cannot be downloaded (e.g. no internet); never throws on network failure.

See Also

Other atlas: `atlas_clear_cache()`, `atlas_info()`, `load_atlas_tree()`

Examples

```
trees <- list_trees()
if (!is.null(trees)) {
  head(trees)
  subset(trees, dated & ntips > 1000)
}
```

`load_atlas_tree` *Load a tree from the Phylo-Species Atlas*

Description

Downloads a standardized Newick tree from the atlas and resolves its integer tip IDs to species names using the shared dictionary.

Usage

```
load_atlas_tree(name, resolve_labels = TRUE)
```

Arguments

`name`	Tree name without the ‘.nwk‘ extension (e.g. ‘"mammals"‘, ‘"birds"‘, ‘"fish"‘, ‘"condamine_Vangidae"‘). Use [list_trees()] to see all available names.
`resolve_labels`	If ‘TRUE‘ (default) tip labels are replaced with standardized species names from ‘dictionary.csv‘. Set to ‘FALSE‘ to keep the raw integer IDs (faster, avoids downloading the dictionary). Some trees of the atlas are not redistributed, because their sources state no licence (the atlas’s ‘registers/withheld_trees.csv‘). For such a name the function stops with an error that gives the address of the source, from which the tree can be downloaded; nothing is fetched.

Value

An object of class ‘"phylo"‘ from the **ape** package. If ‘resolve_labels = TRUE‘ (the default), tip labels are species names from the standardized dictionary; otherwise tip labels are integer IDs as character strings.

See Also

Other atlas: `atlas_clear_cache()`, `atlas_info()`, `list_trees()`

Examples

```
# Offline demo using a small bundled tree (does not hit the network):
demo_path <- system.file("extdata", "tree_demo.nwk", package = "phyloatlas")
tree <- ape::read.tree(demo_path)
tree


# Live atlas fetch (requires internet):
tree <- try(load_atlas_tree("mammals"), silent = TRUE)
if (!inherits(tree, "try-error")) plot(tree, show.tip.label = FALSE)

# Keep integer IDs to skip the 18 MB dictionary download:
tree <- try(load_atlas_tree("birds", resolve_labels = FALSE), silent = TRUE)
```

Index

∗ **atlas**
atlas_clear_cache, 2
atlas_info, 2
list_trees, 3
load_atlas_tree, 4

atlas_clear_cache, 2, *3, 4*
atlas_info, *2*, 2, *3, 4*

list_trees, *2, 3*, 3, *4*
load_atlas_tree, *2, 3*, 4