

Package ‘ciphertext’

July 22, 2025

Type Package

Title Classical Cryptography Methods for Words and Phrases

Version 0.1.1

Description Classical cryptography methods for words and brief phrases. Substitution, transposition and concealment (null) ciphers are available, like Caesar, Vigenère, Atbash, affine, simple substitution, Playfair, rail fence, Scytale, single column, bifid, trifid, and Polybius ciphers.

License GPL-3

URL <https://github.com/Luigi-Annic/ciphertext>

BugReports <https://github.com/Luigi-Annic/ciphertext/issues>

Encoding UTF-8

Depends R (>= 4.3.0)

RoxygenNote 7.2.3

Suggests testthat (>= 3.0.0)

Config/testthat/edition 3

NeedsCompilation no

Author Luigi Annicchiarico [cre, aut]

Maintainer Luigi Annicchiarico <luigi.annic@gmail.com>

Repository CRAN

Date/Publication 2025-01-10 15:10:05 UTC

Contents

affine	2
atbash	3
bifid_delastelle	3
caesar	4
nullcipher	5
playfair	5
polybius	6

railfence	7
scytale	8
simple_substitution	8
singlecolumn	9
trifid_delastelle	10
vigenere	11

Index	12
--------------	-----------

affine	<i>affine</i>
--------	---------------

Description

The affine cipher is a monoalphabetic substitution cipher, where each letter is enciphered with the function $(ax+b) \bmod 26$ (26 is the number of letters in the alphabet)

Usage

```
affine(word, a, b, encrypt = TRUE)
```

Arguments

word	Word or phrase to be encrypted
a	First parameter. This value and 26 must be coprime
b	Second parameter. Magnitude of the shift
encrypt	If 'TRUE' (default), the program ciphers the input word, If 'FALSE', the program decrypts it.

Value

a string

References

https://en.wikipedia.org/wiki/Affine_cipher

Examples

```
affine("Hello", 1, -1)
```

atbash	<i>atbash</i>
--------	---------------

Description

The Atbash cipher is a type of monoalphabetic cipher which takes the alphabet and maps it to its reverse. It is a particular case of the affine cipher, with $a=b=(m-1)$. As m is the number of letters and is equal to 26, it means that $a=b=25$. Encrypting and decrypting are not separate for this cipher.

Usage

```
atbash(word)
```

Arguments

word	Word or phrase to be encrypted
------	--------------------------------

Value

a string

References

<https://en.wikipedia.org/wiki/Atbash>

Examples

```
atbash("abcxyz")
```

bifid_delastelle	<i>bifid_delastelle</i>
------------------	-------------------------

Description

The bifid cipher is an encryption method that combines a substitution with a Polybius square and a transposition, and uses fractionation to achieve diffusion. It was invented by Felix Delastelle.

Usage

```
bifid_delastelle(input, key = "", period = 100, encrypt = TRUE)
```

Arguments

input	Word or phrase to be encrypted, or character vector with the sequence of coordinate numbers if we need to decrypt
key	key Word for creating the modified Polybius square
period	period length for splitting the input phrase. If greater or equal to the length of the input then the split is not executed
encrypt	If 'TRUE' (default), the program ciphers the input word, If 'FALSE', the program decrypts it.

Value

a string

References

https://en.wikipedia.org/wiki/Bifid_cipher

Examples

```
bifid_delastelle("dcode", key = "secret", period = 3, encrypt = TRUE)
bifid_delastelle("apiai", key = "secret", period = 3, encrypt = FALSE)
```

caesar

caesar

Description

caesar encryption

Usage

```
caesar(word, key = 1, encrypt = TRUE)
```

Arguments

word	Word or phrase to be encrypted
key	numeric key
encrypt	If 'TRUE' (default), the program ciphers the input word, If 'FALSE', the program decrypts it.

Value

a string

Examples

```
caesar("Hello", 1)
```

nullcipher	<i>nullcipher</i>
------------	-------------------

Description

A null cipher is an encryption method where the plaintext is mixed with a large amount of non-cipher material (decoy).

Usage

```
nullcipher(phrase, index, encrypt = FALSE)
```

Arguments

phrase	Word or phrase to be decrypted
index	letter of interest for each word in the phrase. Also a pattern vector can be entered.
encrypt	Only Decryption is possible for now, but will be updated in the future

Value

a string

References

https://en.wikipedia.org/wiki/Null_cipher

Examples

```
nullcipher("handy set false posts", c(1,2,3))
```

playfair	<i>playfair</i>
----------	-----------------

Description

The Playfair cipher is a symmetric method which encrypts pairs of letters using a modified Polybius square

Usage

```
playfair(word, key = "", added_letter = "x", encrypt = TRUE)
```

Arguments

word	Word or phrase to be encrypted or decrypted
key	Word for creating the modified Polybius square
added_letter	Letter to be added in case two letters of a pair are identical; usually "x" is used
encrypt	If 'TRUE' (default), the program ciphers the input word, If 'FALSE', the program decrypts it.

Value

a string

References

https://en.wikipedia.org/wiki/Playfair_cipher

Examples

```
playfair("instruments", "monarchy", added_letter = "z")
playfair("gatlmzclrqtx", "monarchy", added_letter = "z", encrypt = FALSE)
```

polybius

polybius

Description

The polybius square is a device which associates each letter to a pair of coordinates. The letter J is excluded and replaced with I in order to get 25 letters and create a 5x5 matrix.

Usage

```
polybius(input, encrypt = TRUE)
```

Arguments

input	Word or phrase to be encrypted, or character vector with the sequence of coordinate numbers if we need to decrypt
encrypt	If 'TRUE' (default), the program ciphers the input word, If 'FALSE', the program decrypts it.

Value

a string

References

https://en.wikipedia.org/wiki/Polybius_square

Examples

```
polybius("hello world")  
polybius("23 15 31 31 34 52 34 42 31 14", encrypt = TRUE)
```

<i>railfence</i>	<i>railfence</i>
------------------	------------------

Description

The rail fence is a transposition cipher where the text is written upwards and downwards diagonally (zigzag) on the rails of the fence

Usage

```
railfence(word, key = 3)
```

Arguments

word	Word or phrase to be encrypted
key	numeric key (number of rails)

Value

a string

References

https://en.wikipedia.org/wiki/Rail_fence_cipher

Examples

```
railfence('we are discovered flee at once',3)
```

scytale *scytale*

Description

The Scytale is a transposition cipher. The diameter of the Scytale (the number of turns) can be regarded as the key of the cipher.

Usage

```
scytale(word, key = 3, encrypt = TRUE)
```

Arguments

word	Word or phrase to be encrypted or decrypted
key	Number of turns of the band
encrypt	If 'TRUE' (default), the program ciphers the input word, If 'FALSE', the program decrypts it.

Value

a string

References

<https://en.wikipedia.org/wiki/Scytale>

Examples

```
scytale('we are discovered flee at once', 3)
```

simple_substitution *simple_substitution*

Description

simple substitution cipher. Each letter is monoalphabetically associated with a different one used for the encryption.

Usage

```
simple_substitution(word, key = "", seed = sample(1:1000, 1))
```


Arguments

word	Word or phrase to be encrypted
key	Word to be used as key for the encryption. If not provided, a random shuffle is performed
seed	Seed for reproducibility of the encryption if key is not provided

Value

a list with custom class "cipher", which modifies the printing defaults. The list contains the initial phrase (initial), the ciphered output (encrypted), and the alphabet order (keyalphabet)

Examples

```
simple_substitution("hello world", seed = 1234)
simple_substitution("hello world", key = "zebras")
```

singlecolumn	<i>singlecolumn</i>
--------------	---------------------

Description

In a columnar transposition cipher, the message is written out in rows of a fixed length, and then read out again column by column. The order of the column follows the alphabetical order of the letters present in the key

Usage

```
singlecolumn(word, key, rm.blanks = TRUE)
```

Arguments

word	Word or phrase to be encrypted
key	word key: for example, the key "bcea" suggests that the column order is "2-3-4-1"
rm.blanks	Should spaces between words be removed? By default set to 'TRUE'

Value

a string

References

<https://www.geeksforgeeks.org/columnar-transposition-cipher/>

Examples

```
singlecolumn("This is wikipedia", "cipher")
```

trifid_delastelle	<i>trifid_delastelle</i>
-------------------	--------------------------

Description

The trifid cipher is an encryption method that uses a 3-dimensional grid. It was invented by Felix Delastelle in 1902. As a 3x3x3 grid is used, 27 characters are needed. Thus, we use all the 26 alphabet letters and add the "+" sign at the bottom.

Usage

```
trifid_delastelle(input, key = "", period = 100, encrypt = TRUE)
```

Arguments

input	Word or phrase to be encrypted, or character vector with the sequence of coordinate numbers if we need to decrypt
key	key Word for creating the modified Polybius square
period	period length for splitting the input phrase. If greater or equal to the length of the input then the split is not executed
encrypt	If 'TRUE' (default), the program ciphers the input word, If 'FALSE', the program decrypts it.

Value

a string

References

https://en.wikipedia.org/wiki/Trifid_cipher

Examples

```
trifid_delastelle("secret", key = "", period = 5, encrypt = TRUE)
trifid_delastelle("sjlkzt", key = "", period = 5, encrypt = FALSE)
```

`vigenere``vigenere`

Description

Vigenère cipher is a method of encrypting alphabetic text where each letter of the plaintext is encoded with a different Caesar cipher, whose increment is determined by the corresponding letter the key

Usage

```
vigenere(word, key, encrypt = TRUE)
```

Arguments

<code>word</code>	Word or phrase to be encrypted
<code>key</code>	character key
<code>encrypt</code>	If 'TRUE' (default), the program ciphers the input word, If 'FALSE', the program decrypts it.

Value

a string

References

<https://en.wikipedia.org/wiki/Vigenere>

Examples

```
vigenere("hello world", "opla")
```

Index

affine, [2](#)

atbash, [3](#)

bifid_delastelle, [3](#)

caesar, [4](#)

nullcipher, [5](#)

playfair, [5](#)

polybius, [6](#)

railfence, [7](#)

scytale, [8](#)

simple_substitution, [8](#)

singlecolumn, [9](#)

trifid_delastelle, [10](#)

vigenere, [11](#)