

Package ‘imdbapi’

July 22, 2025

Title Get Movie, Television Data from the 'imdb' Database

Version 0.1.0

Author Daxuan Deng Yuan Li

Maintainer Yuan Li <851277048@qq.com>

Description Provides API access to the <<http://imdbapi.net>> which maintains metadata about movies, games and television shows through a public API.

Depends R (>= 3.1.1)

License GPL-3

Imports httr, dplyr, stringr

RoxygenNote 6.0.1

NeedsCompilation no

Repository CRAN

Date/Publication 2018-04-24 08:11:08 UTC

Contents

find_by_id	2
find_by_title	2
get_actors	3
get_countries	4
get_directors	4
get_genres	5
get_writers	5
omdb_api_key	6
search_by_title	6
Index	8

find_by_id	<i>Retrieve OMDb info by IMDB ID search</i>
------------	---

Description

Retrieve OMDb info by IMDB ID search

Usage

```
find_by_id(id, type = NULL, year_of_release = NULL, plot = "short",
  include_tomatoes = FALSE, api_key = omdb_api_key())
```

Arguments

id	A valid IMDb ID (e.g. tt1285016)
type	Type of result to return. One of [movie series episode game].
year_of_release	Year of release.
plot	Return short or full plot.
include_tomatoes	Include Rotten Tomatoes ratings.
api_key	OMDb API key. See omdb_api_key() & https://www.patreon.com/bePatron?u=5038490 for more information.

Value

tbl_df/data.frame of search results (an empty one if none found). Also classes as an omdb object for prettier printing

Note

The API's search results limit to 10.

find_by_title	<i>Retrieve OMDb info by title search</i>
---------------	---

Description

Retrieve OMDb info by title search

Usage

```
find_by_title(title, type = NULL, season = NULL, episode = NULL,
  year_of_release = NULL, plot = "short", include_tomatoes = FALSE,
  api_key = omdb_api_key())
```

Arguments

title	Movie title to search for.
type	Type of result to return. One of [movie series episode game].
season	if type is series or episode then it possible to search within a season AND episode (both required)
episode	if type is series or episode then it possible to search within a season AND episode (both required)
year_of_release	Year of release.
plot	Return short or full plot.
include_tomatoes	Include Rotten Tomatoes ratings.
api_key	OMDB API key. See <code>omdb_api_key()</code> & https://www.patreon.com/bePatron?u=5038490 for more information.

Value

tbl_df/data.frame of search results (an empty one if none found). Also classes as an omdb object for prettier printing

Note

The API's search results limit to 10.

See Also

<http://www.omdbapi.com/>

get_actors

Get actors from an omdb object as a vector

Description

Splits the field at commas and returns a vector of individual entries

Usage

```
get_actors(omdb)
```

Arguments

omdb an object returned by `find_by_title` or `find_by_id`

Value

A character vector of actors

Examples

```
get_actors(find_by_id("tt0031381"))
```

get_countries	<i>Get countries from an omdb object as a vector</i>
---------------	--

Description

Splits the field at commas and returns a vector of individual entries

Usage

```
get_countries(omdb)
```

Arguments

omdb an object returned by find_by_title or find_by_id

Value

A character vector of countries

Examples

```
get_countries(find_by_id("tt0031381"))
```

get_directors	<i>Get directors from an omdb object as a vector</i>
---------------	--

Description

Splits the field at commas and returns a vector of individual entries

Usage

```
get_directors(omdb)
```

Arguments

omdb an object returned by find_by_title or find_by_id

Value

A character vector of directors

Examples

```
get_directors(find_by_id("tt0031381"))
```

get_genres *Get genres from an omdb object as a vector*

Description

Splits the field at commas and returns a vector of individual entries

Usage

```
get_genres(omdb)
```

Arguments

omdb an object returned by find_by_title or find_by_id

Value

A character vector of genres

Examples

```
get_genres(find_by_id("tt0031381"))
```

get_writers *Get writers from an omdb object as a vector*

Description

Splits the field at commas and returns a vector of individual entries

Usage

```
get_writers(omdb)
```

Arguments

omdb an object returned by find_by_title or find_by_id

Value

A character vector of writers

Examples

```
get_writers(find_by_id("tt0031381"))
```

omdb_api_key	<i>Get or set OMDB_API_KEY value</i>
--------------	--------------------------------------

Description

The API wrapper functions in this package all rely on a OMDB API key residing in the environment variable OMDB_API_KEY. The easiest way to accomplish this is to set it in the `.Renviron` file in your home directory.

Usage

```
omdb_api_key(force = FALSE)
```

Arguments

`force` force setting a new OMDB API key for the current environment?

Value

atomic character vector containing the OMDB API key

Note

The "poster" API requires a separate key

search_by_title	<i>Lightweight omdb title search</i>
-----------------	--------------------------------------

Description

Lightweight omdb title search

Usage

```
search_by_title(term, type = NULL, year_of_release = NULL, page = 1,
  api_key = omdb_api_key())
```

Arguments

term	Movie title to search for.
type	Type of result to return. One of [movie series episode game].
year_of_release	Year of release.
page	1 for first 10 results, 2 for next ten, etc...
api_key	OMDB API key. See omdb_api_key() & https://www.patreon.com/bePatron?u=5038490 for more information.

Value

tbl_df/data.frame of search results (an empty one if none found)

Note

The API's search results limit to 10 at a time (see argument page).

See Also

<http://www.omdbapi.com/>

Index

`find_by_id`, 2

`find_by_title`, 2

`get_actors`, 3

`get_countries`, 4

`get_directors`, 4

`get_genres`, 5

`get_writers`, 5

`omdb_api_key`, 6

`omdb_api_key()`, 2, 3, 7

`search_by_title`, 6