

Package ‘markovchain’

February 2, 2026

Type Package

Title Easy Handling Discrete Time Markov Chains

Version 0.10.3

Maintainer Giorgio Alfredo Spedicato <spedicato_giorgio@yahoo.it>

Description Functions and S4 methods to create and manage discrete time Markov chains more easily. In addition functions to perform statistical (fitting and drawing random variates) and probabilistic (analysis of their structural properties) analysis are provided. See Spedicato (2017) <[doi:10.32614/RJ-2017-036](https://doi.org/10.32614/RJ-2017-036)>. Some functions for continuous times Markov chains depend on the suggested ctmcd package.

License MIT + file LICENSE

Depends R (>= 4.2.0), Matrix (>= 1.5-0), methods

Imports igraph, expm, stats4, parallel, Rcpp (>= 1.0.2), RcppParallel, utils, stats, grDevices

Suggests knitr, testthat, diagram, DiagrammeR, msm, Rsolnp, rmarkdown, ctmcd, bookdown, rticles, MCMCpack, microbenchmark

Enhances etm

VignetteBuilder rmarkdown, knitr, bookdown, rticles

LinkingTo Rcpp, RcppParallel, RcppArmadillo (>= 0.9.600.4.0)

SystemRequirements GNU make

LazyLoad yes

ByteCompile yes

Encoding UTF-8

BugReports <https://github.com/spedygiorgio/markovchain/issues>

URL <https://github.com/spedygiorgio/markovchain/>

RoxygenNote 7.3.3

NeedsCompilation yes

Author Giorgio Alfredo Spedicato [aut, cre] (ORCID: <<https://orcid.org/0000-0002-0315-8888>>), Tae Seung Kang [aut],

Sai Bhargav Yalamanchi [aut],
 Mildenberger Thoralf [ctb] (ORCID:
 <<https://orcid.org/0000-0001-7242-1873>>),
 Deepak Yadav [aut],
 Ignacio Cordón [aut] (ORCID: <<https://orcid.org/0000-0002-3152-0231>>),
 Vandit Jain [ctb],
 Toni Giorgino [ctb] (ORCID: <<https://orcid.org/0000-0001-6449-0596>>),
 Richèl J.C. Bilderbeek [ctb] (ORCID:
 <<https://orcid.org/0000-0003-1107-7049>>),
 Daniel Ebbert [ctb] (ORCID: <<https://orcid.org/0000-0003-3666-7205>>),
 Shreyash Maheshwari [ctb],
 Reinhold Koch [ctb]

Repository CRAN

Date/Publication 2026-02-02 06:30:37 UTC

Contents

markovchain-package	3
absorptionProbabilities	4
blanden	5
committorAB	6
conditionalDistribution	7
craigsendi	8
createSequenceMatrix	8
ctmc-class	11
ctmcFit	12
expectedRewards	13
expectedRewardsBeforeHittingA	14
ExpectedTime	15
firstPassage	16
firstPassageMultiple	17
fitHigherOrder	18
fitHighOrderMultivarMC	19
freq2Generator	20
generatorToTransitionMatrix	21
HigherOrderMarkovChain-class	22
hittingProbabilities	22
holson	23
hommc-class	24
ictmc-class	24
impreciseProbabilityatT	25
inferHyperparam	26
is.accessible	27
is.CTMCirreducible	28
is.irreducible	29
is.regular	30
is.TimeReversible	31

kullback	32
markovchain-class	32
markovchainList-class	35
markovchainListFit	36
markovchainSequence	37
meanAbsorptionTime	38
meanFirstPassageTime	39
meanNumVisits	40
meanRecurrenceTime	41
multinomialConfidenceIntervals	42
name	43
name<-	44
names,markovchain-method	44
noofVisitsDist	45
ones	46
period	46
predictHommec	48
predictiveDistribution	49
preproglucacon	50
priorDistribution	51
probabilityatT	52
rain	53
rctmc	54
rmarkovchain	55
sales	57
show,hommec-method	57
states	58
steadyStates	59
tm_abs	60
transition2Generator	60
transitionProbability	61
verifyMarkovProperty	62
zeros	64

Index	65
--------------	-----------

Description

The package contains classes and method to create and manage (plot, print, export for example) discrete time Markov chains (DTMC). In addition it provide functions to perform statistical (fitting and drawing random variates) and probabilistic (analysis of DTMC proprieties) analysis

Author(s)

Giorgio Alfredo Spedicato Maintainer: Giorgio Alfredo Spedicato <spedicato_giorgio@yahoo.it>

References

Discrete-Time Markov Models, Bremaud, Springer 1999

See Also

Useful links:

- <https://github.com/spedygiorgio/markovchain/>
- Report bugs at <https://github.com/spedygiorgio/markovchain/issues>

Examples

```
# create some markov chains
statesNames=c("a","b")
mca<-new("markovchain", transitionMatrix=matrix(c(0.7,0.3,0.1,0.9),byrow=TRUE,
nrow=2, dimnames=list(statesNames,statesNames)))

statesNames=c("a","b","c")
mcB<-new("markovchain", states=statesNames, transitionMatrix=
matrix(c(0.2,0.5,0.3,0,1,0,0.1,0.8,0.1), nrow=3,
byrow=TRUE, dimnames=list(statesNames, statesNames)))

statesNames=c("a","b","c","d")
matrice<-matrix(c(0.25,0.75,0,0,0.4,0.6,0,0,0,0.1,0.9,0,0,0.7,0.3), nrow=4, byrow=TRUE)
mcC<-new("markovchain", states=statesNames, transitionMatrix=matrice)
mcD<-new("markovchain", transitionMatrix=matrix(c(0,1,0,1), nrow=2,byrow=TRUE))

#operations with S4 methods
mca^2
steadyStates(mcB)
absorbingStates(mcB)
markovchainSequence(n=20, markovchain=mcC, include=TRUE)
```

absorptionProbabilities

Absorption probabilities

Description

Computes the absorption probability from each transient state to each recurrent one (i.e. the (i, j) entry or (j, i) , in a stochastic matrix by columns, represents the probability that the first not transient state we can go from the transient state i is j (and therefore we are going to be absorbed in the communicating recurrent class of j)

Usage

absorptionProbabilities(object)

Arguments

object	the markovchain object
--------	------------------------

Value

A named vector with the expected number of steps to go from a transient state to any of the recurrent ones

Author(s)

Ignacio Cordón

References

C. M. Grinstead and J. L. Snell. Introduction to Probability. American Mathematical Soc., 2012.

Examples

```
m <- matrix(c(1/2, 1/2, 0,
              1/2, 1/2, 0,
              0, 1/2, 1/2), ncol = 3, byrow = TRUE)
mc <- new("markovchain", states = letters[1:3], transitionMatrix = m)
absorptionProbabilities(mc)
```

Description

This table show mobility between income quartiles for father and sons for the 1970 cohort born

Usage

```
data(blanden)
```

Format

An object of class `table` with 4 rows and 4 columns.

Details

The rows represent fathers' income quartile when the son is aged 16, whilst the columns represent sons' income quartiles when he is aged 30 (in 2000).

Source

Personal reworking

References

Jo Blanden, Paul Gregg and Stephen Machin, Intergenerational Mobility in Europe and North America, Center for Economic Performances (2005)

Examples

```
data(blanden)
mobilityMc<-as(blanden, "markovchain")
```

committorAB

Calculates committor of a markovchain object with respect to set A, B

Description

Returns the probability of hitting states rom set A before set B with different initial states

Usage

```
committorAB(object,A,B,p)
```

Arguments

object	a markovchain class object
A	a set of states
B	a set of states
p	initial state (default value : 1)

Details

The function solves a system of linear equations to calculate probaility that the process hits a state from set A before any state from set B

Value

Return a vector of probabilities in case initial state is not provided else returns a number

Examples

```
transMatr <- matrix(c(0,0,0,1,0.5,
                     0.5,0,0,0,0,
                     0.5,0,0,0,0,
                     0,0.2,0.4,0,0,
                     0,0.8,0.6,0,0.5),
                     nrow = 5)
object <- new("markovchain", states=c("a","b","c","d","e"),transitionMatrix=transMatr)
committorAB(object,c(5),c(3))
```

conditionalDistribution

conditionalDistribution of a Markov Chain

Description

It extracts the conditional distribution of the subsequent state, given current state.

Usage

```
conditionalDistribution(object, state)
```

Arguments

object	A markovchain object.
state	Subsequent state.

Value

A named probability vector

Author(s)

Giorgio Spedicato, Deepak Yadav

References

A First Course in Probability (8th Edition), Sheldon Ross, Prentice Hall 2010

See Also

[markovchain](#)

Examples

```
# define a markov chain
statesNames <- c("a", "b", "c")
markovB <- new("markovchain", states = statesNames, transitionMatrix =
  matrix(c(0.2, 0.5, 0.3, 0, 1, 0, 0.1, 0.8, 0.1), nrow = 3,
  byrow = TRUE, dimnames = list(statesNames, statesNames)))
```

```
conditionalDistribution(markovB, "b")
```

craigsendi

CD4 cells counts on HIV Infects between zero and six month

Description

This is the table shown in Craig and Sendi paper showing zero and six month CD4 cells count in six brackets

Usage

`data(craigsendi)`

Format

The format is: table [1:3, 1:3] 682 154 19 33 64 19 25 47 43 - attr(*, "dimnames")=List of 2 ..\$: chr [1:3] "0-49" "50-74" "75-UP" ..\$: chr [1:3] "0-49" "50-74" "75-UP"

Details

Rows represent counts at the beginning, cols represent counts after six months.

Source

Estimation of the transition matrix of a discrete time Markov chain, Bruce A. Craig and Peter P. Sendi, Health Economics 11, 2002.

References

see source

Examples

```
data(craigsendi)
csMc<-as(craigsendi, "markovchain")
steadyStates(csMc)
```

createSequenceMatrix *Function to fit a discrete Markov chain*

Description

Given a sequence of states arising from a stationary state, it fits the underlying Markov chain distribution using either MLE (also using a Laplacian smoother), bootstrap or by MAP (Bayesian) inference.

Usage

```
createSequenceMatrix(
  stringchar,
  toRowProbs = FALSE,
  sanitize = FALSE,
  possibleStates = character()
)

markovchainFit(
  data,
  method = "mle",
  byrow = TRUE,
  nboot = 10L,
  laplacian = 0,
  name = "",
  parallel = FALSE,
  confidencelevel = 0.95,
  confint = TRUE,
  hyperparam = matrix(),
  sanitize = FALSE,
  possibleStates = character()
)
```

Arguments

stringchar	It can be a	$n \times n$
	matrix or a character vector or a list	
toRowProbs	converts a sequence matrix into a probability matrix	
sanitize	put 1 in all rows having rowSum equal to zero	
possibleStates	Possible states which are not present in the given sequence	
data	It can be a character vector or a	$n \times n$
	matrix or a	$n \times n$
	data frame or a list	
method	Method used to estimate the Markov chain. Either "mle", "map", "bootstrap" or "laplace"	
byrow	it tells whether the output Markov chain should show the transition probabilities by row.	
nboot	Number of bootstrap replicates in case "bootstrap" is used.	
laplacian	Laplacian smoothing parameter, default zero. It is only used when "laplace" method is chosen.	
name	Optional character for name slot.	

parallel	Use parallel processing when performing Bootstrap estimates.
confidencelevel	α
confint	level for confidence intervals width. Used only when method equal to "mle".
hyperparam	a boolean to decide whether to compute Confidence Interval or not.
	Hyperparameter matrix for the a priori distribution. If none is provided, default value of 1 is assigned to each parameter. This must be of size

$$k \times k$$

where k is the number of states in the chain and the values should typically be non-negative integers.

Details

Disabling confint would lower the computation time on large datasets. If data or stringchar contain NAs, the related NA containing transitions will be ignored.

Value

A list containing an estimate, log-likelihood, and, when "bootstrap" method is used, a matrix of standard deviations and the bootstrap samples. When the "mle", "bootstrap" or "map" method is used, the lower and upper confidence bounds are returned along with the standard error. The "map" method also returns the expected value of the parameters with respect to the posterior distribution.

Note

This function has been rewritten in Rcpp. Bootstrap algorithm has been defined "heuristically". In addition, parallel facility is not complete, involving only a part of the bootstrap process. When data is either a `data.frame` or a `matrix` object, only MLE fit is currently available.

Author(s)

Giorgio Spedicato, Tae Seung Kang, Sai Bhargav Yalamanchi

References

- A First Course in Probability (8th Edition), Sheldon Ross, Prentice Hall 2010
- Inferring Markov Chains: Bayesian Estimation, Model Comparison, Entropy Rate, and Out-of-Class Modeling, Christopher C. Strelcoff, James P. Crutchfield, Alfred Hubler, Santa Fe Institute
- Yalamanchi SB, Spedicato GA (2015). Bayesian Inference of First Order Markov Chains. R package version 0.2.5

See Also

[markovchainSequence](#), [markovchainListFit](#)

Examples

```

sequence <- c("a", "b", "a", "a", "a", "a", "b", "a", "b", "a", "b", "a", "a",
           "b", "b", "b", "a")
sequenceMatr <- createSequenceMatrix(sequence, sanitize = FALSE)
mcFitMLE <- markovchainFit(data = sequence)
mcFitBSP <- markovchainFit(data = sequence, method = "bootstrap", nboot = 5, name = "Bootstrap Mc")

na.sequence <- c("a", NA, "a", "b")
# There will be only a (a,b) transition
na.sequenceMatr <- createSequenceMatrix(na.sequence, sanitize = FALSE)
mcFitMLE <- markovchainFit(data = na.sequence)

# data can be a list of character vectors
sequences <- list(x = c("a", "b", "a"), y = c("b", "a", "b", "a", "c"))
mcFitMap <- markovchainFit(sequences, method = "map")
mcFitMle <- markovchainFit(sequences, method = "mle")

```

Description

The S4 class that describes ctmc (continuous time Markov chain) objects.

Arguments

states	Name of the states. Must be the same of colnames and rownames of the generator matrix
byrow	TRUE or FALSE. Indicates whether the given matrix is stochastic by rows or by columns
generator	Square generator matrix
name	Optional character name of the Markov chain

Methods

```

dim signature(x = "ctmc"): method to get the size
initialize signature(.Object = "ctmc"): initialize method
states signature(object = "ctmc"): states method.
steadyStates signature(object = "ctmc"): method to get the steady state vector.
plot signature(x = "ctmc", y = "missing"): plot method for ctmc objects

```

Note

1. ctmc classes are written using S4 classes
2. Validation method is used to assess whether either columns or rows totals to zero. Rounding is used up to 5th decimal. If state names are not properly defined for a generator matrix, coercing to ctmc object leads to overriding states name with artificial "s1", "s2", ... sequence

References

Introduction to Stochastic Processes with Applications in the Biosciences (2013), David F. Anderson, University of Wisconsin at Madison. Sai Bhargav Yalamanchi, Giorgio Spedicato

See Also

[generatorToTransitionMatrix](#), [rctmc](#)

Examples

```
energyStates <- c("sigma", "sigma_star")
byRow <- TRUE
gen <- matrix(data = c(-3, 3,
                      1, -1), nrow = 2,
                      byrow = byRow, dimnames = list(energyStates, energyStates))
molecularCTMC <- new("ctmc", states = energyStates,
                      byrow = byRow, generator = gen,
                      name = "Molecular Transition Model")
steadyStates(molecularCTMC)
## Not run: plot(molecularCTMC)
```

ctmcFit

Function to fit a CTMC

Description

This function fits the underlying CTMC give the state transition data and the transition times using the maximum likelihood method (MLE)

Usage

```
ctmcFit(data, byrow = TRUE, name = "", confidencelevel = 0.95)
```

Arguments

data	It is a list of two elements. The first element is a character vector denoting the states. The second is a numeric vector denoting the corresponding transition times.
byrow	Determines if the output transition probabilities of the underlying embedded DTMC are by row.
name	Optional name for the CTMC.
confidencelevel	Confidence level for the confidence interval construction.

Details

Note that in data, there must exist an element wise corresponding between the two elements of the list and that data[[2]][1] is always 0.

Value

It returns a list containing the CTMC object and the confidence intervals.

Author(s)

Sai Bhargav Yalamanchi

References

Continuous Time Markov Chains (vignette), Sai Bhargav Yalamanchi, Giorgio Alfredo Spedicato 2015

See Also

[rctmc](#)

Examples

```
data <- list(c("a", "b", "c", "a", "b", "a", "c", "b", "c"), c(0, 0.8, 2.1, 2.4, 4, 5, 5.9, 8.2, 9))
ctmcFit(data)
```

expectedRewards

Expected Rewards for a markovchain

Description

Given a markovchain object and reward values for every state, function calculates expected reward value after n steps.

Usage

```
expectedRewards(markovchain, n, rewards)
```

Arguments

markovchain	the markovchain-class object
n	no of steps of the process
rewards	vector depicting rewards coressponding to states

Details

the function uses a dynamic programming approach to solve a recursive equation described in reference.

Value

returns a vector of expected rewards for different initial states

Author(s)

Vandit Jain

References

Stochastic Processes: Theory for Applications, Robert G. Gallager, Cambridge University Press

Examples

```
transMatr<-matrix(c(0.99,0.01,0.01,0.99),nrow=2,byrow=TRUE)
simpleMc<-new("markovchain", states=c("a","b"),
               transitionMatrix=transMatr)
expectedRewards(simpleMc,1,c(0,1))
```

expectedRewardsBeforeHittingA

Expected first passage Rewards for a set of states in a markovchain

Description

Given a markovchain object and reward values for every state, function calculates expected reward value for a set A of states after n steps.

Usage

```
expectedRewardsBeforeHittingA(markovchain, A, state, rewards, n)
```

Arguments

markovchain	the markovchain-class object
A	set of states for first passage expected reward
state	initial state
rewards	vector depicting rewards coressponding to states
n	no of steps of the process

Details

The function returns the value of expected first passage rewards given rewards coressponding to every state, an initial state and number of steps.

Value

returns a expected reward (numerical value) as described above

Author(s)

Sai Bhargav Yalamanchi, Vandit Jain

ExpectedTime

Returns expected hitting time from state i to state j

Description

Returns expected hitting time from state i to state j

Usage

`ExpectedTime(C, i, j, useRCpp)`

Arguments

C	A CTMC S4 object
i	Initial state i
j	Final state j
useRCpp	logical whether to use Rcpp

Details

According to the theorem, holding times for all states except j should be greater than 0.

Value

A numerical value that returns expected hitting times from i to j

Author(s)

Vandit Jain

References

Markovchains, J. R. Norris, Cambridge University Press

Examples

```

states <- c("a", "b", "c", "d")
byRow <- TRUE
gen <- matrix(data = c(-1, 1/2, 1/2, 0, 1/4, -1/2, 0, 1/4, 1/6, 0, -1/3, 1/6, 0, 0, 0, 0),
nrow = 4, byrow = byRow, dimnames = list(states,states))
ctmc <- new("ctmc",states = states, byrow = byRow, generator = gen, name = "testctmc")
ExpectedTime(ctmc,1,4,TRUE)

```

firstPassage*First passage across states***Description**

This function compute the first passage probability in states

Usage

```
firstPassage(object, state, n)
```

Arguments

object	A markovchain object
state	Initial state
n	Number of rows on which compute the distribution

Details

Based on Feres' Matlab listings

Value

A matrix of size 1:n x number of states showing the probability of the first time of passage in states to be exactly the number in the row.

Author(s)

Giorgio Spedicato

References

Renaldo Feres, Notes for Math 450 Matlab listings for Markov chains

See Also

[conditionalDistribution](#)

Examples

```
simpleMc <- new("markovchain", states = c("a", "b"),
                 transitionMatrix = matrix(c(0.4, 0.6, .3, .7),
                                           nrow = 2, byrow = TRUE))
firstPassage(simpleMc, "b", 20)
```

`firstPassageMultiple` *function to calculate first passage probabilities*

Description

The function calculates first passage probability for a subset of states given an initial state.

Usage

```
firstPassageMultiple(object, state, set, n)
```

Arguments

object	a markovchain-class object
state	initial state of the process (charactervector)
set	set of states A, first passage of which is to be calculated
n	Number of rows on which compute the distribution

Value

A vector of size n showing the first time probabilities

Author(s)

Vandit Jain

References

Renaldo Feres, Notes for Math 450 Matlab listings for Markov chains; MIT OCW, course - 6.262, Discrete Stochastic Processes, course-notes, chap -05

See Also

[firstPassage](#)

Examples

```
statesNames <- c("a", "b", "c")
markovB <- new("markovchain", states = statesNames, transitionMatrix =
  matrix(c(0.2, 0.5, 0.3,
          0, 1, 0,
          0.1, 0.8, 0.1), nrow = 3, byrow = TRUE,
          dimnames = list(statesNames, statesNames)
  ))
firstPassageMultiple(markovB, "a", c("b", "c"), 4)
```

fitHigherOrder	<i>Functions to fit a higher order Markov chain</i>
----------------	---

Description

Given a sequence of states arising from a stationary state, it fits the underlying Markov chain distribution with higher order.

Usage

```
fitHigherOrder(sequence, order = 2)
seq2freqProb(sequence)
seq2matHigh(sequence, order)
```

Arguments

sequence	A character list.
order	Markov chain order

Value

A list containing lambda, Q, and X.

Author(s)

Giorgio Spedicato, Tae Seung Kang

References

Ching, W. K., Huang, X., Ng, M. K., & Siu, T. K. (2013). Higher-order markov chains. In *Markov Chains* (pp. 141-176). Springer US.

Ching, W. K., Ng, M. K., & Fung, E. S. (2008). Higher-order multivariate Markov chains and their applications. *Linear Algebra and its Applications*, 428(2), 492-507.

Examples

```
sequence<-c("a", "a", "b", "b", "a", "c", "b", "a", "b", "c", "a", "b", "c", "a", "b", "c", "a", "b", "a", "b")
fitHigherOrder(sequence)
```

fitHighOrderMultivarMC

Function to fit Higher Order Multivariate Markov chain

Description

Given a matrix of categorical sequences it fits Higher Order Multivariate Markov chain.

Usage

```
fitHighOrderMultivarMC(seqMat, order = 2, Norm = 2)
```

Arguments

seqMat	a matrix or a data frame where each column is a categorical sequence
order	Multivariate Markov chain order. Default is 2.
Norm	Norm to be used. Default is 2.

Value

an hommc object

Author(s)

Giorgio Spedicato, Deepak Yadav

References

W.-K. Ching et al. / Linear Algebra and its Applications

Examples

```
data <- matrix(c('2', '1', '3', '3', '4', '3', '2', '1', '3', '3', '2', '1',
                 c('2', '4', '4', '4', '4', '2', '3', '3', '1', '4', '3', '3')), 
                 ncol = 2, byrow = FALSE)

fitHighOrderMultivarMC(data, order = 2, Norm = 2)
```

freq2Generator	<i>Returns a generator matrix corresponding to frequency matrix</i>
----------------	---

Description

The function provides interface to calculate generator matrix corresponding to a frequency matrix and time taken

Usage

```
freq2Generator(P, t = 1, method = "QO", logmethod = "Eigen")
```

Arguments

P	relative frequency matrix
t	(default value = 1)
method	one among "QO"(Quasi optimisation), "WA"(weighted adjustment), "DA"(diagonal adjustment)
logmethod	method for computation of matrix algorithm (by default : Eigen)

Value

returns a generator matrix with same dimnames

References

E. Kreinin and M. Sidelnikova: Regularization Algorithms for Transition Matrices. Algo Research Quarterly 4(1):23-40, 2001

Examples

```
sample <- matrix(c(150,2,1,1,1,200,2,1,2,1,175,1,1,1,1,150),nrow = 4,byrow = TRUE)
sample_rel = rbind((sample/rowSums(sample))[1:dim(sample)[1]-1],c(rep(0,dim(sample)[1]-1),1))

data(tm_abs)
tm_rel=rbind((tm_abs/rowSums(tm_abs))[1:7,],c(rep(0,7),1))
## Derive quasi optimization generator matrix estimate
freq2Generator(tm_rel,1)
```

generatorToTransitionMatrix

Function to obtain the transition matrix from the generator

Description

The transition matrix of the embedded DTMC is inferred from the CTMC's generator

Usage

```
generatorToTransitionMatrix(gen, byrow = TRUE)
```

Arguments

gen	The generator matrix
byrow	Flag to determine if rows (columns) sum to 0

Value

Returns the transition matrix.

Author(s)

Sai Bhargav Yalamanchi

References

Introduction to Stochastic Processes with Applications in the Biosciences (2013), David F. Anderson, University of Wisconsin at Madison

See Also

[rctmc,ctmc-class](#)

Examples

```
energyStates <- c("sigma", "sigma_star")
byRow <- TRUE
gen <- matrix(data = c(-3, 3, 1, -1), nrow = 2,
              byrow = byRow, dimnames = list(energyStates, energyStates))
generatorToTransitionMatrix(gen)
```

HigherOrderMarkovChain-class*Higher order Markov Chains class*

Description

The S4 class that describes HigherOrderMarkovChain objects.

hittingProbabilities *Hitting probabilities for markovchain*

Description

Given a markovchain object, this function calculates the probability of ever arriving from state i to j

Usage

```
hittingProbabilities(object)
```

Arguments

object the markovchain-class object

Value

a matrix of hitting probabilities

Author(s)

Ignacio Cordón

References

R. Vélez, T. Prieto, Procesos Estocásticos, Librería UNED, 2013

Examples

```
M <- markovchain:::zeros(5)
M[1,1] <- M[5,5] <- 1
M[2,1] <- M[2,3] <- 1/2
M[3,2] <- M[3,4] <- 1/2
M[4,2] <- M[4,5] <- 1/2

mc <- new("markovchain", transitionMatrix = M)
hittingProbabilities(mc)
```

holson

Holson data set

Description

A data set containing 1000 life histories trajectories and a categorical status (1,2,3) observed on eleven evenly spaced steps.

Usage

```
data(holson)
```

Format

A data frame with 1000 observations on the following 12 variables.

```
id unique id
time1 observed status at i-th time
time2 observed status at i-th time
time3 observed status at i-th time
time4 observed status at i-th time
time5 observed status at i-th time
time6 observed status at i-th time
time7 observed status at i-th time
time8 observed status at i-th time
time9 observed status at i-th time
time10 observed status at i-th time
time11 observed status at i-th time
```

Details

The example can be used to fit a `markovchain` or a `markovchainList` object.

Source

Private communications

References

Private communications

Examples

```
data(holson)
head(holson)
```

hommc-class

An S4 class for representing High Order Multivariate Markovchain (HOMMC)

Description

An S4 class for representing High Order Multivariate Markovchain (HOMMC)

Slots

order an integer equal to order of Multivariate Markovchain
states a vector of states present in the HOMMC model
P array of transition matrices
Lambda a vector which stores the weightage of each transition matrices in P
byrow if FALSE each column sum of transition matrix is 1 else row sum = 1
name a name given to hommc

Author(s)

Giorgio Spedicato, Deepak Yadav

Examples

```

statesName <- c("a", "b")

P <- array(0, dim = c(2, 2, 4), dimnames = list(statesName, statesName))
P[,1] <- matrix(c(0, 1, 1/3, 2/3), byrow = FALSE, nrow = 2)
P[,2] <- matrix(c(1/4, 3/4, 0, 1), byrow = FALSE, nrow = 2)
P[,3] <- matrix(c(1, 0, 1/3, 2/3), byrow = FALSE, nrow = 2)
P[,4] <- matrix(c(3/4, 1/4, 0, 1), byrow = FALSE, nrow = 2)

Lambda <- c(0.8, 0.2, 0.3, 0.7)

ob <- new("hommc", order = 1, states = statesName, P = P,
          Lambda = Lambda, byrow = FALSE, name = "FOMMC")

```

ictmc-class

An S4 class for representing Imprecise Continuous Time Markovchains

Description

An S4 class for representing Imprecise Continuous Time Markovchains

Slots

states a vector of states present in the ICTMC model
Q matrix representing the generator demonstrated in the form of variables
range a matrix that stores values of range of variables
name name given to ICTMC

impreciseProbabilityatT

Calculating full conditional probability using lower rate transition matrix

Description

This function calculates full conditional probability at given time s using lower rate transition matrix

Usage

```
impreciseProbabilityatT(C, i, t, s, error, useRcpp)
```

Arguments

C	a ictmc class object
i	initial state at time t
t	initial time t. Default value = 0
s	final time
error	error rate. Default value = 0.001
useRcpp	logical whether to use RCpp implementation; by default TRUE

Author(s)

Vandit Jain

References

Imprecise Continuous-Time Markov Chains, Thomas Krak et al., 2016

Examples

```
states <- c("n", "y")
Q <- matrix(c(-1, 1, 1, -1), nrow = 2, byrow = TRUE, dimnames = list(states, states))
range <- matrix(c(1/52, 3/52, 1/2, 2), nrow = 2, byrow = 2)
name <- "testictmc"
ictmc <- new("ictmc", states = states, Q = Q, range = range, name = name)
impreciseProbabilityatT(ictmc, 2, 0, 1, 10^-3, TRUE)
```

inferHyperparam	<i>Function to infer the hyperparameters for Bayesian inference from an a priori matrix or a data set</i>
-----------------	---

Description

Since the Bayesian inference approach implemented in the package is based on conjugate priors, hyperparameters must be provided to model the prior probability distribution of the chain parameters. The hyperparameters are inferred from a given a priori matrix under the assumption that the matrix provided corresponds to the mean (expected) values of the chain parameters. A scaling factor vector must be provided too. Alternatively, the hyperparameters can be inferred from a data set.

Usage

```
inferHyperparam(transMatr = matrix(), scale = numeric(), data = character())
```

Arguments

transMatr	A valid transition matrix, with dimension names.
scale	A vector of scaling factors, each element corresponds to the row names of the provided transition matrix transMatr, in the same order.
data	A data set from which the hyperparameters are inferred.

Details

transMatr and scale need not be provided if data is provided.

Value

Returns the hyperparameter matrix in a list.

Note

The hyperparameter matrix returned is such that the row and column names are sorted alphabetically, and the elements in the matrix are correspondingly permuted.

Author(s)

Sai Bhargav Yalamanchi, Giorgio Spedicato

References

Yalamanchi SB, Spedicato GA (2015). Bayesian Inference of First Order Markov Chains. R package version 0.2.5

See Also

[markovchainFit](#), [predictiveDistribution](#)

Examples

```
data(rain, package = "markovchain")
inferHyperparam(data = rain$rain)

weatherStates <- c("sunny", "cloudy", "rain")
weatherMatrix <- matrix(data = c(0.7, 0.2, 0.1,
                                0.3, 0.4, 0.3,
                                0.2, 0.4, 0.4),
                        byrow = TRUE, nrow = 3,
                        dimnames = list(weatherStates, weatherStates))
inferHyperparam(transMatr = weatherMatrix, scale = c(10, 10, 10))
```

is.accessible	<i>Verify if a state j is reachable from state i.</i>
---------------	---

Description

This function verifies if a state is reachable from another, i.e., if there exists a path that leads to state j leaving from state i with positive probability

Usage

```
is.accessible(object, from, to)
```

Arguments

object	A markovchain object.
from	The name of state "i" (beginning state).
to	The name of state "j" (ending state).

Details

It wraps an internal function named `reachabilityMatrix`.

Value

A boolean value.

Author(s)

Giorgio Spedicato, Ignacio Cordón

References

James Montgomery, University of Madison

See Also

`is.irreducible`

Examples

```
statesNames <- c("a", "b", "c")
markovB <- new("markovchain", states = statesNames,
              transitionMatrix = matrix(c(0.2, 0.5, 0.3,
                                          0, 1, 0,
                                          0.1, 0.8, 0.1), nrow = 3, byrow = TRUE,
                                          dimnames = list(statesNames, statesNames)
                                          )
)
is.accessible(markovB, "a", "c")
```

`is.CTMCirreducible` *Check if CTMC is irreducible*

Description

This function verifies whether a CTMC object is irreducible

Usage

`is.CTMCirreducible(ctmc)`

Arguments

`ctmc` a ctmc-class object

Value

a boolean value as described above.

Author(s)

Vandit Jain

References

Continuous-Time Markov Chains, Karl Sigman, Columbia University

Examples

```
energyStates <- c("sigma", "sigma_star")
byRow <- TRUE
gen <- matrix(data = c(-3, 3,
                       1, -1), nrow = 2,
                       byrow = byRow, dimnames = list(energyStates, energyStates))
molecularCTMC <- new("ctmc", states = energyStates,
                      byrow = byRow, generator = gen,
                      name = "Molecular Transition Model")
is.CTMCirreducible(molecularCTMC)
```

is.irreducible

Function to check if a Markov chain is irreducible (i.e. ergodic)

Description

This function verifies whether a `markovchain` object transition matrix is composed by only one communicating class.

Usage

```
is.irreducible(object)
```

Arguments

object	A <code>markovchain</code> object
--------	-----------------------------------

Details

It is based on `.communicatingClasses` internal function.

Value

A boolean values.

Author(s)

Giorgio Spedicato

References

Feres, Matlab listings for Markov Chains.

See Also

[summary](#)

Examples

```
statesNames <- c("a", "b")
mca <- new("markovchain", transitionMatrix = matrix(c(0.7,0.3,0.1,0.9),
                                                 byrow = TRUE, nrow = 2,
                                                 dimnames = list(statesNames, statesNames)
                                               ))
is.irreducible(mca)
```

is.regular*Check if a DTMC is regular*

Description

Function to check whether a DTMC is regular

Usage

```
is.regular(object)
```

Arguments

object	a markovchain object
--------	----------------------

Details

A Markov chain is regular if some of the powers of its matrix has all elements strictly positive

Value

A boolean value

Author(s)

Ignacio Cordón

References

Matrix Analysis. Roger A.Horn, Charles R.Johnson. 2nd edition. Corollary 8.5.8, Theorem 8.5.9

See Also

[is.irreducible](#)

Examples

```
P <- matrix(c(0.5, 0.25, 0.25,
             0.5, 0, 0.5,
             0.25, 0.25, 0.5), nrow = 3)
colnames(P) <- rownames(P) <- c("R", "N", "S")
ciao <- as(P, "markovchain")
is.regular(ciao)
```

is.TimeReversible *checks if ctmc object is time reversible*

Description

The function returns checks if provided function is time reversible

Usage

```
is.TimeReversible(ctmc)
```

Arguments

ctmc a ctmc-class object

Value

Returns a boolean value stating whether ctmc object is time reversible
 a boolean value as described above

Author(s)

Vandit Jain

References

INTRODUCTION TO STOCHASTIC PROCESSES WITH R, ROBERT P. DOBROW, Wiley

Examples

```
energyStates <- c("sigma", "sigma_star")
byRow <- TRUE
gen <- matrix(data = c(-3, 3,
                       1, -1), nrow = 2,
                       byrow = byRow, dimnames = list(energyStates, energyStates))
molecularCTMC <- new("ctmc", states = energyStates,
                      byrow = byRow, generator = gen,
                      name = "Molecular Transition Model")
is.TimeReversible(molecularCTMC)
```

kullback

*Example from Kullback and Kupperman Tests for Contingency Tables***Description**

A list of two matrices representing raw transitions between two states

Usage

```
data(kullback)
```

Format

A list containing two 6x6 non - negative integer matrices

markovchain-class

*Markov Chain class***Description**

The S4 class that describes markovchain objects.

Arguments

states	Name of the states. Must be the same of colnames and rownames of the transition matrix
byrow	TRUE or FALSE indicating whether the supplied matrix is either stochastic by rows or by columns
transitionMatrix	Square transition matrix
name	Optional character name of the Markov chain

Creation of objects

Objects can be created by calls of the form `new("markovchain", states, byrow, transitionMatrix, ...)`.

Methods

- * `signature(e1 = "markovchain", e2 = "markovchain")`: multiply two markovchain objects
- * `signature(e1 = "markovchain", e2 = "matrix")`: markovchain by matrix multiplication
- * `signature(e1 = "markovchain", e2 = "numeric")`: markovchain by numeric vector multiplication
- * `signature(e1 = "matrix", e2 = "markovchain")`: matrix by markov chain

```

* signature(e1 = "numeric", e2 = "markovchain"): numeric vector by markovchain multiplication
[ signature(x = "markovchain", i = "ANY", j = "ANY", drop = "ANY"): ...
^ signature(e1 = "markovchain", e2 = "numeric"): power of a markovchain object
== signature(e1 = "markovchain", e2 = "markovchain"): equality of two markovchain objects
!= signature(e1 = "markovchain", e2 = "markovchain"): non-equality of two markovchain objects

absorbingStates signature(object = "markovchain"): method to get absorbing states
canonicForm signature(object = "markovchain"): return a markovchain object into canonical form
coerce signature(from = "markovchain", to = "data.frame"): coerce method from markovchain to data.frame
conditionalDistribution signature(object = "markovchain"): returns the conditional probability of subsequent states given a state
coerce signature(from = "data.frame", to = "markovchain"): coerce method from data.frame to markovchain
coerce signature(from = "table", to = "markovchain"): coerce method from table to markovchain
coerce signature(from = "msm", to = "markovchain"): coerce method from msm to markovchain
coerce signature(from = "msm.est", to = "markovchain"): coerce method from msm.est (but only from a Probability Matrix) to markovchain
coerce signature(from = "etm", to = "markovchain"): coerce method from etm to markovchain
coerce signature(from = "sparseMatrix", to = "markovchain"): coerce method from sparseMatrix to markovchain
coerce signature(from = "markovchain", to = "igraph"): coercing to igraph objects
coerce signature(from = "markovchain", to = "matrix"): coercing to matrix objects
coerce signature(from = "markovchain", to = "sparseMatrix"): coercing to sparseMatrix objects
coerce signature(from = "matrix", to = "markovchain"): coercing to markovchain objects from matrix one
dim signature(x = "markovchain"): method to get the size
names signature(x = "markovchain"): method to get the names of states
names<- signature(x = "markovchain", value = "character"): method to set the names of states
initialize signature(.Object = "markovchain"): initialize method
plot signature(x = "markovchain", y = "missing"): plot method for markovchain objects
predict signature(object = "markovchain"): predict method
print signature(x = "markovchain"): print method.
show signature(object = "markovchain"): show method.
sort signature(x = "markovchain", decreasing=FALSE): sorting the transition matrix.

```

states signature(object = "markovchain"): returns the names of states (as names).

steadyStates signature(object = "markovchain"): method to get the steady vector.

summary signature(object = "markovchain"): method to summarize structure of the markov chain

transientStates signature(object = "markovchain"): method to get the transient states.

t signature(x = "markovchain"): transpose matrix

transitionProbability signature(object = "markovchain"): transition probability

Note

1. markovchain object are backed by S4 Classes.
2. Validation method is used to assess whether either columns or rows totals to one. Rounding is used up to `.Machine$double.eps * 100`. If state names are not properly defined for a probability matrix, coercing to markovchain object leads to overriding states name with artificial "s1", "s2", ... sequence. In addition, operator overloading has been applied for `+`, `*`, `==`, `!=` operators.

Author(s)

Giorgio Spedicato

References

A First Course in Probability (8th Edition), Sheldon Ross, Prentice Hall 2010

See Also

[markovchainSequence](#), [markovchainFit](#)

Examples

```
#show markovchain definition
showClass("markovchain")
#create a simple Markov chain
transMatr<-matrix(c(0.4,0.6,.3,.7),nrow=2,byrow=TRUE)
simpleMc<-new("markovchain", states=c("a","b"),
               transitionMatrix=transMatr,
               name="simpleMc")
#power
simpleMc^4
#some methods
steadyStates(simpleMc)
absorbingStates(simpleMc)
simpleMc[2,1]
t(simpleMc)
is.irreducible(simpleMc)
#conditional distributions
conditionalDistribution(simpleMc, "b")
#example for predict method
```

```

sequence<-c("a", "b", "a", "a", "a", "a", "b", "a", "b", "a", "b", "a", "b", "b", "b", "a")
mcFit<-markovchainFit(data=sequence)
predict(mcFit$estimate, newdata="b", n.ahead=3)
#direct conversion
myMc<-as(transMatr, "markovchain")

#example of summary
summary(simpleMc)
## Not run: plot(simpleMc)

```

markovchainList-class *Non homogeneous discrete time Markov Chains class*

Description

A class to handle non homogeneous discrete Markov chains

Arguments

<code>markovchains</code>	Object of class "list": a list of markovchains
<code>name</code>	Object of class "character": optional name of the class

Objects from the Class

A `markovchainlist` is a list of `markovchain` objects. They can be used to model non homogeneous discrete time Markov Chains, when transition probabilities (and possible states) change by time.

Methods

```

[[ signature(x = "markovchainList"): extract the i-th markovchain
dim signature(x = "markovchainList"): number of markovchain underlying the matrix
predict signature(object = "markovchainList"): predict from a markovchainList
print signature(x = "markovchainList"): prints the list of markovchains
show signature(object = "markovchainList"): same as print

```

Note

The class consists in a list of `markovchain` objects. It is aimed at working with non homogeneous Markov chains.

Author(s)

Giorgio Spedicato

References

A First Course in Probability (8th Edition), Sheldon Ross, Prentice Hall 2010

See Also[markovchain](#)**Examples**

```

showClass("markovchainList")
#define a markovchainList
statesNames=c("a", "b")

mcA<-new("markovchain", name="MCA",
          transitionMatrix=matrix(c(0.7,0.3,0.1,0.9),
          byrow=TRUE, nrow=2,
          dimnames=list(statesNames,statesNames)))
)

mcB<-new("markovchain", states=c("a","b","c"), name="MCB",
          transitionMatrix=matrix(c(0.2,0.5,0.3,0,1,0,0.1,0.8,0.1),
          nrow=3, byrow=TRUE))

mcC<-new("markovchain", states=c("a","b","c","d"), name="MCC",
          transitionMatrix=matrix(c(0.25,0.75,0,0,0.4,0.6,
          0,0,0,0.1,0.9,0,0,0.7,0.3),
          nrow=4, byrow=TRUE)
)
mcList<-new("markovchainList",markovchains=list(mcA, mcB, mcC,
      name="Non - homogeneous Markov Chain"))

```

markovchainListFit *markovchainListFit*

Description

Given a data frame or a matrix (rows are observations, by cols the temporal sequence), it fits a non - homogeneous discrete time markov chain process (storing row). In particular a markovchainList of size = ncol - 1 is obtained estimating transitions from the n samples given by consecutive column pairs.

Usage

```
markovchainListFit(data, byrow = TRUE, laplacian = 0, name)
```

Arguments

data	Either a matrix or a data.frame or a list object.
byrow	Indicates whether distinct stochastic processes trajectories are shown in distinct rows.
laplacian	Laplacian correction (default 0).
name	Optional name.

Details

If data contains NAs then the transitions containing NA will be ignored.

Value

A list containing two slots: estimate (the estimate) name

Examples

```
# using holson dataset
data(holson)
# fitting a single markovchain
singleMc <- markovchainFit(data = holson[,2:12])
# fitting a markovchainList
mclistFit <- markovchainListFit(data = holson[, 2:12], name = "holsonMcList")
```

markovchainSequence *Function to generate a sequence of states from homogeneous Markov chains.*

Description

Provided any `markovchain` object, it returns a sequence of states coming from the underlying stationary distribution.

Usage

```
markovchainSequence(
  n,
  markovchain,
  t0 = sample(markovchain@states, 1),
  include.t0 = FALSE,
  useRCpp = TRUE
)
```

Arguments

<code>n</code>	Sample size
<code>markovchain</code>	<code>markovchain</code> object
<code>t0</code>	The initial state
<code>include.t0</code>	Specify if the initial state shall be used
<code>useRCpp</code>	Boolean. Should RCpp fast implementation being used? Default is yes.

Details

A sequence of size `n` is sampled.

Value

A Character Vector

Author(s)

Giorgio Spedicato

References

A First Course in Probability (8th Edition), Sheldon Ross, Prentice Hall 2010

See Also

[markovchainFit](#)

Examples

```
# define the markovchain object
statesNames <- c("a", "b", "c")
mcB <- new("markovchain", states = statesNames,
           transitionMatrix = matrix(c(0.2, 0.5, 0.3, 0, 0.2, 0.8, 0.1, 0.8, 0.1),
           nrow = 3, byrow = TRUE, dimnames = list(statesNames, statesNames)))

# show the sequence
outs <- markovchainSequence(n = 100, markovchain = mcB, t0 = "a")
```

meanAbsorptionTime *Mean absorption time*

Description

Computes the expected number of steps to go from any of the transient states to any of the recurrent states. The Markov chain should have at least one transient state for this method to work

Usage

`meanAbsorptionTime(object)`

Arguments

`object` the markovchain object

Value

A named vector with the expected number of steps to go from a transient state to any of the recurrent ones

Author(s)

Ignacio Cordón

References

C. M. Grinstead and J. L. Snell. Introduction to Probability. American Mathematical Soc., 2012.

Examples

```
m <- matrix(c(1/2, 1/2, 0,
              1/2, 1/2, 0,
              0, 1/2, 1/2), ncol = 3, byrow = TRUE)
mc <- new("markovchain", states = letters[1:3], transitionMatrix = m)
times <- meanAbsorptionTime(mc)
```

meanFirstPassageTime *Mean First Passage Time for irreducible Markov chains***Description**

Given an irreducible (ergodic) markovchain object, this function calculates the expected number of steps to reach other states

Usage

```
meanFirstPassageTime(object, destination)
```

Arguments

object	the markovchain object
destination	a character vector representing the states respect to which we want to compute the mean first passage time. Empty by default

Details

For an ergodic Markov chain it computes:

- If destination is empty, the average first time (in steps) that takes the Markov chain to go from initial state i to j . (i, j) represents that value in case the Markov chain is given row-wise, (j, i) in case it is given col-wise.
- If destination is not empty, the average time it takes us from the remaining states to reach the states in destination

Value

a Matrix of the same size with the average first passage times if destination is empty, a vector if destination is not

Author(s)

Toni Giorgino, Ignacio Cordón

References

C. M. Grinstead and J. L. Snell. Introduction to Probability. American Mathematical Soc., 2012.

Examples

```
m <- matrix(1 / 10 * c(6,3,1,
                      2,3,5,
                      4,1,5), ncol = 3, byrow = TRUE)
mc <- new("markovchain", states = c("s","c","r"), transitionMatrix = m)
meanFirstPassageTime(mc, "r")

# Grinstead and Snell's "Oz weather" worked out example
m0z <- matrix(c(2,1,1,
                2,0,2,
                1,1,2)/4, ncol = 3, byrow = TRUE)

mc0z <- new("markovchain", states = c("s", "c", "r"), transitionMatrix = m0z)
meanFirstPassageTime(mc0z)
```

meanNumVisits

Mean num of visits for markovchain, starting at each state

Description

Given a markovchain object, this function calculates a matrix where the element (i, j) represents the expect number of visits to the state j if the chain starts at i (in a Markov chain by columns it would be the element (j, i) instead)

Usage

```
meanNumVisits(object)
```

Arguments

object the markovchain-class object

Value

a matrix with the expect number of visits to each state

Author(s)

Ignacio Cordón

References

R. Vélez, T. Prieto, Procesos Estocásticos, Librería UNED, 2013

Examples

```
M <- markovchain:::zeros(5)
M[1,1] <- M[5,5] <- 1
M[2,1] <- M[2,3] <- 1/2
M[3,2] <- M[3,4] <- 1/2
M[4,2] <- M[4,5] <- 1/2

mc <- new("markovchain", transitionMatrix = M)
meanNumVisits(mc)
```

meanRecurrenceTime	<i>Mean recurrence time</i>
--------------------	-----------------------------

Description

Computes the expected time to return to a recurrent state in case the Markov chain starts there

Usage

```
meanRecurrenceTime(object)
```

Arguments

object	the markovchain object
--------	------------------------

Value

For a Markov chain it outputs is a named vector with the expected time to first return to a state when the chain starts there. States present in the vector are only the recurrent ones. If the matrix is ergodic (i.e. irreducible), then all states are present in the output and order is the same as states order for the Markov chain

Author(s)

Ignacio Cordón

References

C. M. Grinstead and J. L. Snell. Introduction to Probability. American Mathematical Soc., 2012.

Examples

```
m <- matrix(1 / 10 * c(6,3,1,
                      2,3,5,
                      4,1,5), ncol = 3, byrow = TRUE)
mc <- new("markovchain", states = c("s","c","r"), transitionMatrix = m)
meanRecurrenceTime(mc)
```

multinomialConfidenceIntervals

A function to compute multinomial confidence intervals of DTMC

Description

Return estimated transition matrix assuming a Multinomial Distribution

Usage

```
multinomialConfidenceIntervals(
  transitionMatrix,
  countsTransitionMatrix,
  confidencelevel = 0.95
)
```

Arguments

transitionMatrix	An estimated transition matrix.
countsTransitionMatrix	Empirical (conts) transition matrix, on which the transitionMatrix was performed.
confidencelevel	confidence interval level.

Value

Two matrices containing the confidence intervals.

References

Constructing two-sided simultaneous confidence intervals for multinomial proportions for small counts in a large number of cells. Journal of Statistical Software 5(6) (2000)

See Also

`markovchainFit`

Examples

```
seq<-c("a", "b", "a", "a", "a", "b", "a", "b", "a", "b", "a", "b", "a", "b", "b", "b", "a")
mcfit<-markovchainFit(data=seq,byrow=TRUE)
seqmat<-createSequenceMatrix(seq)
multinomialConfidenceIntervals(mcfit$estimate@transitionMatrix, seqmat, 0.95)
```

name	<i>Method to retrieve name of markovchain object</i>
------	--

Description

This method returns the name of a markovchain object

Usage

```
name(object)

## S4 method for signature 'markovchain'
name(object)
```

Arguments

object A markovchain object

Author(s)

Giorgio Spedicato, Deepak Yadav

Examples

```
statesNames <- c("a", "b", "c")
markovB <- new("markovchain", states = statesNames, transitionMatrix =
  matrix(c(0.2, 0.5, 0.3, 0, 1, 0, 0.1, 0.8, 0.1), nrow = 3,
  byrow = TRUE, dimnames=list(statesNames,statesNames)),
  name = "A markovchain Object"
)
name(markovB)
```

name<-	<i>Method to set name of markovchain object</i>
--------	---

Description

This method modifies the existing name of markovchain object

Usage

```
name(object) <- value

## S4 replacement method for signature 'markovchain'
name(object) <- value
```

Arguments

object	A markovchain object
value	New name of markovchain object

Author(s)

Giorgio Spedicato, Deepak Yadav

Examples

```
statesNames <- c("a", "b", "c")
markovB <- new("markovchain", states = statesNames, transitionMatrix =
  matrix(c(0.2, 0.5, 0.3, 0, 1, 0, 0.1, 0.8, 0.1), nrow = 3,
  byrow = TRUE, dimnames=list(statesNames,statesNames)),
  name = "A markovchain Object"
)
name(markovB) <- "dangerous mc"
```

names,markovchain-method	<i>Returns the states for a Markov chain object</i>
--------------------------	---

Description

Returns the states for a Markov chain object

Usage

```
## S4 method for signature 'markovchain'
names(x)
```

Arguments

- x object we want to return states for

noofVisitsDist	<i>return a joint pdf of the number of visits to the various states of the DTMC</i>
----------------	---

Description

This function would return a joint pdf of the number of visits to the various states of the DTMC during the first N steps.

Usage

```
noofVisitsDist(markovchain,N,state)
```

Arguments

markovchain	a markovchain-class object
N	no of steps
state	the initial state

Details

This function would return a joint pdf of the number of visits to the various states of the DTMC during the first N steps.

Value

a numeric vector depicting the above described probability density function.

Author(s)

Vandit Jain

Examples

```
transMatr<-matrix(c(0.4,0.6,.3,.7),nrow=2,byrow=TRUE)
simpleMc<-new("markovchain", states=c("a","b"),
               transitionMatrix=transMatr,
               name="simpleMc")
noofVisitsDist(simpleMc,5,"a")
```

ones	<i>Returns an Identity matrix</i>
------	-----------------------------------

Description

Returns an Identity matrix

Usage

`ones(n)`

Arguments

`n` size of the matrix

Value

a identity matrix

period	<i>Various function to perform structural analysis of DTMC</i>
--------	--

Description

These functions return absorbing and transient states of the `markovchain` objects.

Usage

```
period(object)
communicatingClasses(object)
recurrentClasses(object)
transientClasses(object)
transientStates(object)
recurrentStates(object)
absorbingStates(object)
canonicForm(object)
```

Arguments

object A `markovchain` object.

Value

`period` returns a integer number corresponding to the periodicity of the Markov chain (if it is irreducible)

`absorbingStates` returns a character vector with the names of the absorbing states in the Markov chain

`communicatingClasses` returns a list in which each slot contains the names of the states that are in that communicating class

`recurrentClasses` analogously to `communicatingClasses`, but with recurrent classes

`transientClasses` analogously to `communicatingClasses`, but with transient classes

`transientStates` returns a character vector with all the transient states for the Markov chain

`recurrentStates` returns a character vector with all the recurrent states for the Markov chain

`canonicForm` returns the Markov chain reordered by a permutation of states so that we have blocks submatrices for each of the recurrent classes and a collection of rows in the end for the transient states

Author(s)

Giorgio Alfredo Spedicato, Ignacio Cordón

References

Feres, Matlab listing for markov chain.

See Also

[markovchain](#)

Examples

```
statesNames <- c("a", "b", "c")
mc <- new("markovchain", states = statesNames, transitionMatrix =
  matrix(c(0.2, 0.5, 0.3,
          0, 1, 0,
          0.1, 0.8, 0.1), nrow = 3, byrow = TRUE,
          dimnames = list(statesNames, statesNames)))
)

communicatingClasses(mc)
recurrentClasses(mc)
recurrentClasses(mc)
absorbingStates(mc)
transientStates(mc)
recurrentStates(mc)
canonicForm(mc)
```

```

# periodicity analysis
A <- matrix(c(0, 1, 0, 0, 0.5, 0, 0.5, 0, 0, 0.5, 0, 0.5, 0, 0, 1, 0),
             nrow = 4, ncol = 4, byrow = TRUE)
mcA <- new("markovchain", states = c("a", "b", "c", "d"),
            transitionMatrix = A,
            name = "A")

is.irreducible(mcA) #true
period(mcA) #2

# periodicity analysis
B <- matrix(c(0, 0, 1/2, 1/4, 1/4, 0, 0,
              0, 0, 1/3, 0, 2/3, 0, 0,
              0, 0, 0, 0, 1/3, 2/3,
              0, 0, 0, 0, 1/2, 1/2,
              0, 0, 0, 0, 3/4, 1/4,
              1/2, 1/2, 0, 0, 0, 0, 0,
              1/4, 3/4, 0, 0, 0, 0, 0), byrow = TRUE, ncol = 7)
mcB <- new("markovchain", transitionMatrix = B)
period(mcB)

```

predictHommc

Simulate a higher order multivariate markovchain

Description

This function provides a prediction of states for a higher order multivariate markovchain object

Usage

```
predictHommc(hommc, t, init)
```

Arguments

hommc	a hommc-class object
t	no of iterations to predict
init	matrix of previous states size of which depends on hommc

Details

The user is required to provide a matrix of giving n previous coressponding every categorical sequence. Dimensions of the init are s X n, where s is number of categorical sequences and n is order of the homc.

Value

The function returns a matrix of size s X t displaying t predicted states in each row coressponding to every categorical sequence.

Author(s)

Vandit Jain

```
predictiveDistribution
```

predictiveDistribution

Description

The function computes the probability of observing a new data set, given a data set

Usage

```
predictiveDistribution(stringchar, newData, hyperparam = matrix())
```

Arguments

stringchar	This is the data using which the Bayesian inference is performed.
newData	This is the data whose predictive probability is computed.
hyperparam	This determines the shape of the prior distribution of the parameters. If none is provided, default value of 1 is assigned to each parameter. This must be of size kxk where k is the number of states in the chain and the values should typically be non-negative integers.

Details

The underlying method is Bayesian inference. The probability is computed by averaging the likelihood of the new data with respect to the posterior. Since the method assumes conjugate priors, the result can be represented in a closed form (see the vignette for more details), which is what is returned.

Value

The log of the probability is returned.

Author(s)

Sai Bhargav Yalamanchi

References

Inferring Markov Chains: Bayesian Estimation, Model Comparison, Entropy Rate, and Out-of-

Class Modeling, Christopher C. Strelloff, James P. Crutchfield, Alfred Hubler, Santa Fe Institute

Yalamanchi SB, Spedicato GA (2015). Bayesian Inference of First Order Markov Chains. R package version 0.2.5

See Also[markovchainFit](#)**Examples**

```
sequence<- c("a", "b", "a", "a", "a", "a", "b", "a", "b", "a", "b", "a", "a",
           "b", "b", "b", "a")
hyperMatrix<-matrix(c(1, 2, 1, 4), nrow = 2, dimnames=list(c("a","b"),c("a","b")))
predProb <- predictiveDistribution(sequence[1:10], sequence[11:17], hyperparam =hyperMatrix )
hyperMatrix2<-hyperMatrix[c(2,1),c(2,1)]
predProb2 <- predictiveDistribution(sequence[1:10], sequence[11:17], hyperparam =hyperMatrix2 )
predProb2==predProb
```

preproglucacon

*Preproglucacon DNA protein bases sequences***Description**

Sequence of bases for preproglucacon DNA protein

Usage

```
data(preproglucacon)
```

Format

A data frame with 1572 observations on the following 2 variables.

V1 a numeric vector, showing original coding

preproglucacon a character vector, showing initial of DNA bases (Adenine, Cytosine, Guanine, Thymine)

Source

Avery Henderson

References

Averuy Henderson, Fitting markov chain models on discrete time series such as DNA sequences

Examples

```
data(preproglucacon)
preproglucaconMc<-markovchainFit(data=preproglucacon$preproglucacon)
```

`priorDistribution` *priorDistribution*

Description

Function to evaluate the prior probability of a transition matrix. It is based on conjugate priors and therefore a Dirichlet distribution is used to model the transitions of each state.

Usage

```
priorDistribution(transMatr, hyperparam = matrix())
```

Arguments

<code>transMatr</code>	The transition matrix whose probability is the parameter of interest.
<code>hyperparam</code>	The hyperparam matrix (optional). If not provided, a default value of 1 is assumed for each and therefore the resulting probability distribution is uniform.

Details

The states (dimnames) of the transition matrix and the hyperparam may be in any order.

Value

The log of the probabilities for each state is returned in a numeric vector. Each number in the vector represents the probability (log) of having a probability transition vector as specified in corresponding the row of the transition matrix.

Note

This function can be used in conjunction with `inferHyperparam`. For example, if the user has a prior data set and a prior transition matrix, he can infer the hyperparameters using `inferHyperparam` and then compute the probability of their prior matrix using the inferred hyperparameters with `priorDistribution`.

Author(s)

Sai Bhargav Yalamanchi, Giorgio Spedicato

References

Yalamanchi SB, Spedicato GA (2015). Bayesian Inference of First Order Markov Chains. R package version 0.2.5

See Also

[predictiveDistribution](#), [inferHyperparam](#)

Examples

```
priorDistribution(matrix(c(0.5, 0.5, 0.5, 0.5),
                         nrow = 2,
                         dimnames = list(c("a", "b"), c("a", "b"))),
                         matrix(c(2, 2, 2, 2),
                         nrow = 2,
                         dimnames = list(c("a", "b"), c("a", "b"))))
```

probabilityatT	<i>Calculating probability from a ctmc object</i>
----------------	---

Description

This function returns the probability of every state at time t under different conditions

Usage

```
probabilityatT(C, t, x0, useRcpp)
```

Arguments

C	A CTMC S4 object
t	final time t
x0	initial state
useRcpp	logical whether to use RCpp implementation

Details

The initial state is not mandatory, In case it is not provided, function returns a matrix of transition function at time t else it returns vector of probabilities of transition to different states if initial state was x0

Value

returns a vector or a matrix in case x0 is provided or not respectively.

Author(s)

Vandit Jain

References

INTRODUCTION TO STOCHASTIC PROCESSES WITH R, ROBERT P. DOBROW, Wiley

Examples

```
states <- c("a", "b", "c", "d")
byRow <- TRUE
gen <- matrix(data = c(-1, 1/2, 1/2, 0, 1/4, -1/2, 0, 1/4, 1/6, 0, -1/3, 1/6, 0, 0, 0, 0),
nrow = 4, byrow = byRow, dimnames = list(states,states))
ctmc <- new("ctmc",states = states, byrow = byRow, generator = gen, name = "testctmc")
probabilityatT(ctmc,1,useRCpp = TRUE)
```

rain	<i>Alofi island daily rainfall</i>
------	------------------------------------

Description

Rainfall measured in Alofi Island

Usage

```
data(rain)
```

Format

A data frame with 1096 observations on the following 2 variables.

V1 a numeric vector, showing original coding

rain a character vector, showing daily rainfall millilitres brackets

Source

Avery Henderson

References

Avery Henderson, Fitting markov chain models on discrete time series such as DNA sequences

Examples

```
data(rain)
rainMc<-markovchainFit(data=rain$rain)
```

`rctmc`*rctmc*

Description

The function generates random CTMC transitions as per the provided generator matrix.

Usage

```
rctmc(n, ctmc, initDist = numeric(), T = 0, include.T0 = TRUE,  
      out.type = "list")
```

Arguments

<code>n</code>	The number of samples to generate.
<code>ctmc</code>	The CTMC S4 object.
<code>initDist</code>	The initial distribution of states.
<code>T</code>	The time up to which the simulation runs (all transitions after time T are not returned).
<code>include.T0</code>	Flag to determine if start state is to be included.
<code>out.type</code>	"list" or "df"

Details

In order to use the T0 argument, set n to Inf.

Value

Based on out.type, a list or a data frame is returned. The returned list has two elements - a character vector (states) and a numeric vector (indicating time of transitions). The data frame is similarly structured.

Author(s)

Sai Bhargav Yalamanchi

References

Introduction to Stochastic Processes with Applications in the Biosciences (2013), David F. Anderson, University of Wisconsin at Madison

See Also

[generatorToTransitionMatrix](#), [ctmc-class](#)

Examples

```
energyStates <- c("sigma", "sigma_star")
byRow <- TRUE
gen <- matrix(data = c(-3, 3, 1, -1), nrow = 2,
               byrow = byRow, dimnames = list(energyStates, energyStates))
molecularCTMC <- new("ctmc", states = energyStates,
                      byrow = byRow, generator = gen,
                      name = "Molecular Transition Model")

statesDist <- c(0.8, 0.2)
rctmc(n = Inf, ctmc = molecularCTMC, T = 1)
rctmc(n = 5, ctmc = molecularCTMC, initDist = statesDist, include.T0 = FALSE)
```

rmarkovchain

Function to generate a sequence of states from homogeneous or non-homogeneous Markov chains.

Description

Provided any `markovchain` or `markovchainList` objects, it returns a sequence of states coming from the underlying stationary distribution.

Usage

```
rmarkovchain(
  n,
  object,
  what = "data.frame",
  useRcpp = TRUE,
  parallel = FALSE,
  num.cores = NULL,
  ...
)
```

Arguments

<code>n</code>	Sample size
<code>object</code>	Either a <code>markovchain</code> or a <code>markovchainList</code> object
<code>what</code>	It specifies whether either a <code>data.frame</code> or a <code>matrix</code> (each rows represent a simulation) or a <code>list</code> is returned.
<code>useRcpp</code>	Boolean. Should RCpp fast implementation being used? Default is yes.
<code>parallel</code>	Boolean. Should parallel implementation being used? Default is yes.
<code>num.cores</code>	Number of Cores to be used
<code>...</code>	additional parameters passed to the internal sampler

Details

When a homogeneous process is assumed (`markovchain` object) a sequence is sampled of size `n`. When a non - homogeneous process is assumed, `n` samples are taken but the process is assumed to last from the begin to the end of the non-homogeneous markov process.

Value

Character Vector, `data.frame`, list or matrix

Note

Check the type of input

Author(s)

Giorgio Spedicato

References

A First Course in Probability (8th Edition), Sheldon Ross, Prentice Hall 2010

See Also

[markovchainFit](#), [markovchainSequence](#)

Examples

```
# define the markovchain object
statesNames <- c("a", "b", "c")
mcB <- new("markovchain", states = statesNames,
           transitionMatrix = matrix(c(0.2, 0.5, 0.3, 0, 0.2, 0.8, 0.1, 0.8, 0.1),
                                      nrow = 3, byrow = TRUE, dimnames = list(statesNames, statesNames)))

# show the sequence
outs <- rmarkovchain(n = 100, object = mcB, what = "list")

#define markovchainList object
statesNames <- c("a", "b", "c")
mcA <- new("markovchain", states = statesNames, transitionMatrix =
           matrix(c(0.2, 0.5, 0.3, 0, 0.2, 0.8, 0.1, 0.8, 0.1), nrow = 3,
                  byrow = TRUE, dimnames = list(statesNames, statesNames)))
mcB <- new("markovchain", states = statesNames, transitionMatrix =
           matrix(c(0.2, 0.5, 0.3, 0, 0.2, 0.8, 0.1, 0.8, 0.1), nrow = 3,
                  byrow = TRUE, dimnames = list(statesNames, statesNames)))
mcC <- new("markovchain", states = statesNames, transitionMatrix =
           matrix(c(0.2, 0.5, 0.3, 0, 0.2, 0.8, 0.1, 0.8, 0.1), nrow = 3,
                  byrow = TRUE, dimnames = list(statesNames, statesNames)))
mcList <- new("markovchainList", markovchains = list(mcA, mcB, mcC))

# show the list of sequence
```

```
rmarkovchain(100, mclist, "list")
```

sales	<i>Sales Demand Sequences</i>
-------	-------------------------------

Description

Sales demand sequences of five products (A, B, C, D, E). Each row corresponds to a sequence. First row corresponds to Sequence A, Second row to Sequence B and so on.

Usage

```
data("sales")
```

Format

An object of class `matrix` (inherits from `array`) with 269 rows and 5 columns.

Details

The example can be used to fit High order multivariate markov chain.

Examples

```
data("sales")
# fitHighOrderMultivarMC(seqMat = sales, order = 2, Norm = 2)
```

show, hommc-method	<i>Function to display the details of hommc object</i>
--------------------	--

Description

This is a convenience function to display the slots of `hommc` object in proper format

Usage

```
## S4 method for signature 'hommc'
show(object)
```

Arguments

object	An object of class <code>hommc</code>
--------	---------------------------------------

states*Defined states of a transition matrix*

Description

This method returns the states of a transition matrix.

Usage

```
states(object)

## S4 method for signature 'markovchain'
states(object)
```

Arguments

object	A discrete <code>markovchain</code> object
--------	--

Value

The character vector corresponding to states slot.

Author(s)

Giorgio Spedicato

References

A First Course in Probability (8th Edition), Sheldon Ross, Prentice Hall 2010

See Also

[markovchain](#)

Examples

```
statesNames <- c("a", "b", "c")
markovB <- new("markovchain", states = statesNames, transitionMatrix =
  matrix(c(0.2, 0.5, 0.3, 0, 1, 0, 0.1, 0.8, 0.1), nrow = 3,
  byrow = TRUE, dimnames=list(statesNames,statesNames)),
  name = "A markovchain Object"
)
states(markovB)
names(markovB)
```

steadyStates	<i>Stationary states of a markovchain object</i>
--------------	--

Description

This method returns the stationary vector in matricial form of a markovchain object.

Usage

```
steadyStates(object)
```

Arguments

object	A discrete markovchain object
--------	-------------------------------

Value

A matrix corresponding to the stationary states

Note

The steady states are identified starting from which eigenvectors correspond to identity eigenvalues and then normalizing them to sum up to unity. When negative values are found in the matrix, the eigenvalues extraction is performed on the recurrent classes submatrix.

Author(s)

Giorgio Spedicato

References

A First Course in Probability (8th Edition), Sheldon Ross, Prentice Hall 2010

See Also

[markovchain](#)

Examples

```
statesNames <- c("a", "b", "c")
markovB <- new("markovchain", states = statesNames, transitionMatrix =
  matrix(c(0.2, 0.5, 0.3, 0, 1, 0, 0.1, 0.8, 0.1), nrow = 3,
  byrow = TRUE, dimnames=list(statesNames,statesNames)),
  name = "A markovchain Object")
)
steadyStates(markovB)
```

tm_abs*Single Year Corporate Credit Rating Transition*

Description

Matrix of Standard and Poor's Global Corporate Rating Transition Frequencies 2000 (NR Removed)

Usage

```
data(tm_abs)
```

Format

The format is: num [1:8, 1:8] 17 2 0 0 0 0 0 1 455 ... - attr(*, "dimnames")=List of 2 ..\$: chr [1:8] "AAA" "AA" "A" "BBB"\$: chr [1:8] "AAA" "AA" "A" "BBB" ...

References

European Securities and Markets Authority, 2016 <https://cerep.esma.europa.eu/cerep-web/statistics/transitionMatrice.xhtml>

Examples

```
data(tm_abs)
```

transition2Generator *Return the generator matrix for a corresponding transition matrix*

Description

Calculate the generator matrix for a corresponding transition matrix

Usage

```
transition2Generator(P, t = 1, method = "logarithm")
```

Arguments

P	transition matrix between time 0 and t
t	time of observation
method	"logarithm" returns the Matrix logarithm of the transition matrix

Value

A matrix that represent the generator of P

See Also[rctmc](#)**Examples**

```
mymatr <- matrix(c(.4, .6, .1, .9), nrow = 2, byrow = TRUE)
Q <- transition2Generator(P = mymatr)
expm::expm(Q)
```

transitionProbability *Function to get the transition probabilities from initial to subsequent states.*

Description

This is a convenience function to get transition probabilities.

Usage

```
transitionProbability(object, t0, t1)

## S4 method for signature 'markovchain'
transitionProbability(object, t0, t1)
```

Arguments

object	A markovchain object.
t0	Initial state.
t1	Subsequent state.

Value

Numeric Vector

Author(s)

Giorgio Spedicato

References

A First Course in Probability (8th Edition), Sheldon Ross, Prentice Hall 2010

See Also[markovchain](#)

Examples

```
statesNames <- c("a", "b", "c")
markovB <- new("markovchain", states = statesNames, transitionMatrix =
  matrix(c(0.2, 0.5, 0.3, 0, 1, 0, 0.1, 0.8, 0.1), nrow = 3,
  byrow = TRUE, dimnames=list(statesNames,statesNames)),
  name = "A markovchain Object"
)
transitionProbability(markovB,"b", "c")
```

verifyMarkovProperty *Various functions to perform statistical inference of DTMC*

Description

These functions verify the Markov property, assess the order and stationarity of the Markov chain.

This function tests whether an empirical transition matrix is statistically compatible with a theoretical one. It is a chi-square based test. In case a cell in the empirical transition matrix is >0 that is 0 in the theoretical transition matrix the null hypothesis is rejected.

Verifies that the s elements in the input list belongs to the same DTMC

Usage

```
verifyMarkovProperty(sequence, verbose = TRUE)

assessOrder(sequence, verbose = TRUE)

assessStationarity(sequence, nblocks, verbose = TRUE)

verifyEmpiricalToTheoretical(data, object, verbose = TRUE)

verifyHomogeneity(inputList, verbose = TRUE)
```

Arguments

sequence	An empirical sequence.
verbose	Should test results be printed out?
nblocks	Number of blocks.
data	matrix, character or list to be converted in a raw transition matrix
object	a markovchain object
inputList	A list of items that can coerced to transition matrices

Value

Verification result

a list with following slots: statistic (the chi - square statistic), dof (degrees of freedom), and corresponding p-value. In case a cell in the empirical transition matrix is >0 that is 0 in the theoretical transition matrix the null hypothesis is rejected. In that case a p-value of 0 and statistic and dof of NA are returned.

a list of transition matrices?

Author(s)

Tae Seung Kang, Giorgio Alfredo Spedicato

References

Anderson and Goodman.

See Also

`markovchain`

Examples

```
sequence <- c("a", "b", "a", "a", "a", "a", "b", "a", "b",
           "a", "b", "a", "a", "b", "b", "b", "a")
mcFit <- markovchainFit(data = sequence, byrow = FALSE)
verifyMarkovProperty(sequence)
assessOrder(sequence)
assessStationarity(sequence, 1)
```

#Example taken from Kullback Kupperman Tests for Contingency Tables and Markov Chains

```
sequence<-c(0,1,2,2,1,0,0,0,0,0,0,1,2,2,2,1,0,0,1,0,0,0,0,0,0,1,1,
          2,0,0,2,1,1,0,0,0,0,0,0,0,0,0,0,0,0,0,1,1,1,1,0,0,0,0,2,1,0,
          0,2,1,0,0,0,0,0,1,1,1,2,2,0,0,2,1,1,1,1,2,1,1,1,1,1,1,1,1,0,2,
          0,1,1,0,0,0,1,2,2,0,0,0,0,0,2,2,2,1,1,1,0,1,1,1,1,0,0,2,1,1,
          0,0,0,0,0,2,2,1,1,1,1,2,1,2,0,0,0,1,2,2,2,0,0,0,1,1)
mc=matrix(c(5/8,1/4,1/8,1/4,1/2,1/4,1/4,3/8,3/8),byrow=TRUE, nrow=3)
rownames(mc)<-colnames(mc)<-0:2; theoreticalMc<-as(mc, "markovchain")

verifyEmpiricalToTheoretical(data=sequence,object=theoreticalMc)

data(kullback)
verifyHomogeneity(inputList=kullback,verbose=TRUE)
```

zeros

Matrix to create zeros

Description

Matrix to create zeros

Usage

`zeros(n)`

Arguments

`n` size of the matrix

Value

a square matrix of zeros

Index

```
!=,markovchain,markovchain-method
  (markovchain-class), 32
* classes
  ctmc-class, 11
  markovchain-class, 32
  markovchainList-class, 35
* datasets
  blanden, 5
  craigsendi, 8
  holson, 23
  kullback, 32
  preproglucacon, 50
  rain, 53
  sales, 57
  tm_abs, 60
* package
  markovchain-package, 3
* statisticalTests
  verifyMarkovProperty, 62
*,markovchain,markovchain-method
  (markovchain-class), 32
*,markovchain,matrix-method
  (markovchain-class), 32
*,markovchain,numeric-method
  (markovchain-class), 32
*,matrix,markovchain-method
  (markovchain-class), 32
*,numeric,markovchain-method
  (markovchain-class), 32
==,markovchain,markovchain-method
  (markovchain-class), 32
[,markovchain,ANY,ANY,ANY-method
  (markovchain-class), 32
[],markovchainList-method
  (markovchainList-class), 35
^,markovchain,numeric-method
  (markovchain-class), 32
absorbingStates (period), 46
absorbingStates,markovchain-method
  (markovchain-class), 32
absorptionProbabilities, 4
absorptionProbabilities,markovchain-method
  (markovchain-class), 32
assessOrder (verifyMarkovProperty), 62
assessStationarity
  (verifyMarkovProperty), 62
blanden, 5
canonicForm (period), 46
canonicForm,markovchain-method
  (markovchain-class), 32
coerce,data.frame,markovchain-method
  (markovchain-class), 32
coerce,etm,markovchain-method
  (markovchain-class), 32
coerce,markovchain,data.frame-method
  (markovchain-class), 32
coerce,markovchain,igraph-method
  (markovchain-class), 32
coerce,markovchain,matrix-method
  (markovchain-class), 32
coerce,markovchain,sparseMatrix-method
  (markovchain-class), 32
coerce,Matrix,markovchain-method
  (markovchain-class), 32
coerce,matrix,markovchain-method
  (markovchain-class), 32
coerce,msm,markovchain-method
  (markovchain-class), 32
coerce,msm.est,markovchain-method
  (markovchain-class), 32
coerce,sparseMatrix,markovchain-method
  (markovchain-class), 32
coerce,table,markovchain-method
  (markovchain-class), 32
committorAB, 6
communicatingClasses (period), 46
```

communicatingClasses,markovchain-method
 (markovchain-class), 32
 conditionalDistribution, 7, 16
 conditionalDistribution,markovchain-method
 (markovchain-class), 32
 craigsendi, 8
 createSequenceMatrix, 8
 ctmc-class, 11
 ctmcFit, 12

 dim,ctmc-method (ctmc-class), 11
 dim,markovchain-method
 (markovchain-class), 32
 dim,markovchainList-method
 (markovchainList-class), 35

 expectedRewards, 13
 expectedRewardsBeforeHittingA, 14
 ExpectedTime, 15

 firstPassage, 16, 17
 firstPassageMultiple, 17
 fitHigherOrder, 18
 fitHighOrderMultivarMC, 19
 freq2Generator, 20

 generatorToTransitionMatrix, 12, 21, 54

 HigherOrderMarkovChain-class, 22
 hittingProbabilities, 22
 hittingProbabilities,markovchain-method
 (markovchain-class), 32
 holson, 23
 hommc (hommc-class), 24
 hommc-class, 24

 ictmc (ictmc-class), 24
 ictmc-class, 24
 impreciseProbabilityatT, 25
 inferHyperparam, 26, 51
 initialize,ctmc_method (ctmc-class), 11
 initialize,markovchain-method
 (markovchain-class), 32
 is.accessible, 27
 is.accessible,markovchain,character,character-method
 (markovchain-class), 32
 is.accessible,markovchain,missing,missing-method
 (markovchain-class), 32
 is.CTMCirreducible, 28
 is.irreducible, 29, 30

 is.irreducible,markovchain-method
 (markovchain-class), 32
 is.regular, 30
 is.regular,markovchain-method
 (markovchain-class), 32
 is.TimeReversible, 31

 kullback, 32

 markovchain, 7, 36, 47, 58, 59, 61
 markovchain (markovchain-package), 3
 markovchain-class, 32
 markovchain-package, 3
 markovchainFit, 27, 34, 38, 50, 56
 markovchainFit (createSequenceMatrix), 8
 markovchainList-class, 35
 markovchainListFit, 10, 36
 markovchainSequence, 10, 34, 37, 56
 meanAbsorptionTime, 38
 meanAbsorptionTime,markovchain-method
 (markovchain-class), 32
 meanFirstPassageTime, 39
 meanFirstPassageTime,markovchain,character-method
 (markovchain-class), 32
 meanFirstPassageTime,markovchain,missing-method
 (markovchain-class), 32
 meanNumVisits, 40
 meanNumVisits,markovchain-method
 (markovchain-class), 32
 meanRecurrenceTime, 41
 meanRecurrenceTime,markovchain-method
 (markovchain-class), 32
 multinomialConfidenceIntervals, 42

 name, 43
 name,markovchain-method (name), 43
 name<-, 44
 name<-,markovchain-method (name<-), 44
 names,markovchain-method, 44
 names<-,markovchain-method
 (markovchain-class), 32
 noofVisitsDist, 45

 ones, 46
 period, 46

 plot,ctmc,missing-method (ctmc-class), 11
 plot,markovchain,missing-method
 (markovchain-class), 32

predict,markovchain-method
 (markovchain-class), 32
predict,markovchainList-method
 (markovchainList-class), 35
predictHommC, 48
predictiveDistribution, 27, 49, 51
preproglucacon, 50
print,markovchain-method
 (markovchain-class), 32
print,markovchainList-method
 (markovchainList-class), 35
priorDistribution, 51
probabilityatT, 52

rain, 53
rctmc, 12, 13, 21, 54, 61
recurrentClasses (period), 46
recurrentClasses,markovchain-method
 (markovchain-class), 32
recurrentStates (period), 46
recurrentStates,markovchain-method
 (markovchain-class), 32
rmarkovchain, 55

sales, 57
seq2freqProb (fitHigherOrder), 18
seq2matHigh (fitHigherOrder), 18
show,hommc-method, 57
show,markovchain-method
 (markovchain-class), 32
show,markovchainList-method
 (markovchainList-class), 35
sort,markovchain-method
 (markovchain-class), 32
states, 58
states,ctmc-method (ctmc-class), 11
states,markovchain-method (states), 58
steadyStates, 59
steadyStates,ctmc-method (ctmc-class),
 11
steadyStates,markovchain-method
 (markovchain-class), 32
summary, 29
summary,markovchain-method
 (markovchain-class), 32

t,markovchain-method
 (markovchain-class), 32
tm_abs, 60

transientClasses (period), 46
transientClasses,markovchain-method
 (markovchain-class), 32
transientStates (period), 46
transientStates,markovchain-method
 (markovchain-class), 32
transition2Generator, 60
transitionProbability, 61
transitionProbability,markovchain-method
 (transitionProbability), 61

verifyEmpiricalToTheoretical
 (verifyMarkovProperty), 62
verifyHomogeneity
 (verifyMarkovProperty), 62
verifyMarkovProperty, 62

zeros, 64