

# Package ‘mlr3torch’

January 31, 2026

**Title** Deep Learning with 'mlr3'

**Version** 0.3.3

**Description** Deep Learning library that extends the mlr3 framework by building upon the 'torch' package. It allows to conveniently build, train, and evaluate deep learning models without having to worry about low level details. Custom architectures can be created using the graph language defined in 'mlr3pipelines'.

**License** LGPL (>= 3)

**BugReports** <https://github.com/mlr-org/mlr3torch/issues>

**URL** <https://mlr3torch.mlr-org.com/>,  
<https://github.com/mlr-org/mlr3torch/>

**Depends** mlr3 (>= 1.0.1), mlr3pipelines (>= 0.6.0), torch (>= 0.16.2), R (>= 3.5.0)

**Imports** backports, cli, checkmate (>= 2.2.0), data.table, lgr, methods, mlr3misc (>= 0.14.0), paradox (>= 1.0.0), R6, withr

**Suggests** callr, curl, future, ggplot2, igraph, jsonlite, knitr, mlr3tuning (>= 1.0.0), progress, rmarkdown, rpart, viridis, visNetwork, testthat (>= 3.0.0), tibble, tfevents, torchvision (>= 0.6.0), waldo

**Config/testthat.edition** 3

**NeedsCompilation** no

**ByteCompile** yes

**Encoding** UTF-8

**RoxygenNote** 7.3.3

**Collate** 'CallbackSet.R' 'aaa.R' 'TorchCallback.R'  
'CallbackSetCheckpoint.R' 'CallbackSetEarlyStopping.R'  
'CallbackSetHistory.R' 'CallbackSetLRScheduler.R'  
'CallbackSetProgress.R' 'CallbackSetTB.R'  
'CallbackSetUnfreeze.R' 'ContextTorch.R' 'DataBackendLazy.R'  
'utils.R' 'DataDescriptor.R' 'LearnerFTTransformer.R'  
'LearnerTorch.R' 'LearnerTorchFeatureless.R'

```

'LearnerTorchImage.R' 'LearnerTorchMLP.R' 'task_dataset.R'
'shape.R' 'PipeOpTorchIngress.R' 'LearnerTorchModel.R'
'LearnerTorchModule.R' 'LearnerTorchTabResNet.R'
'LearnerTorchVision.R' 'ModelDescriptor.R' 'PipeOpModule.R'
'PipeOpTorch.R' 'PipeOpTaskPreprocTorch.R'
'PipeOpTorchActivation.R' 'PipeOpTorchAdaptiveAvgPool.R'
'PipeOpTorchAvgPool.R' 'PipeOpTorchBatchNorm.R'
'PipeOpTorchBlock.R' 'PipeOpTorchCallbacks.R'
'PipeOpTorchConv.R' 'PipeOpTorchConvTranspose.R'
'PipeOpTorchDropout.R' 'PipeOpTorchFTCLS.R'
'PipeOpTorchFTTransformerBlock.R' 'PipeOpTorchFn.R'
'PipeOpTorchHead.R' 'PipeOpTorchIdentity.R'
'PipeOpTorchLayerNorm.R' 'PipeOpTorchLinear.R' 'TorchLoss.R'
'PipeOpTorchLoss.R' 'PipeOpTorchMaxPool.R' 'PipeOpTorchMerge.R'
'PipeOpTorchModel.R' 'PipeOpTorchOptimizer.R'
'PipeOpTorchReshape.R' 'PipeOpTorchSoftmax.R'
'PipeOpTorchTokenizer.R' 'Select.R' 'TaskClassif_cifar.R'
'TaskClassif_lazy_iris.R' 'TaskClassif_melanoma.R'
'TaskClassif_mnist.R' 'TaskClassif_tiny_imagenet.R'
'TorchDescriptor.R' 'TorchOptimizer.R' 'bibentries.R' 'cache.R'
'lazy_tensor.R' 'learner_torch_methods.R' 'materialize.R'
'merge_graphs.R' 'multi_tensor_dataset.R' 'nn.R' 'nn_graph.R'
'paramset_torchlearner.R' 'preprocess.R' 'rd_info.R'
'with_torch_settings.R' 'zzz.R'

```

**Author** Sebastian Fischer [cre, aut] (ORCID:

[<https://orcid.org/0000-0002-9609-3197>](https://orcid.org/0000-0002-9609-3197)),

Bernd Bischl [ctb] (ORCID: [<https://orcid.org/0000-0001-6002-6980>](https://orcid.org/0000-0001-6002-6980)),

Lukas Burk [ctb] (ORCID: [<https://orcid.org/0000-0001-7528-3795>](https://orcid.org/0000-0001-7528-3795)),

Martin Binder [aut],

Florian Pfisterer [ctb] (ORCID:

[<https://orcid.org/0000-0001-8867-762X>](https://orcid.org/0000-0001-8867-762X)),

Carson Zhang [ctb]

**Maintainer** Sebastian Fischer <sebf.fischer@gmail.com>

**Repository** CRAN

**Date/Publication** 2026-01-31 09:10:02 UTC

## Contents

|                    |    |
|--------------------|----|
| mlr3torch-package  | 6  |
| assert_lazy_tensor | 7  |
| as_data_descriptor | 8  |
| as_lazy_tensor     | 9  |
| as_lr_scheduler    | 10 |
| as_torch_callback  | 10 |
| as_torch_callbacks | 11 |
| as_torch_loss      | 12 |
| as_torch_optimizer | 12 |

|                                                           |    |
|-----------------------------------------------------------|----|
| auto_device . . . . .                                     | 13 |
| batchgetter_categ . . . . .                               | 13 |
| batchgetter_num . . . . .                                 | 14 |
| callback_set . . . . .                                    | 14 |
| cross_entropy . . . . .                                   | 16 |
| DataDescriptor . . . . .                                  | 17 |
| infer_shapes . . . . .                                    | 19 |
| ingress_categ . . . . .                                   | 20 |
| ingress_ltnsr . . . . .                                   | 21 |
| ingress_num . . . . .                                     | 21 |
| is_lazy_tensor . . . . .                                  | 22 |
| lazy_shape . . . . .                                      | 22 |
| lazy_tensor . . . . .                                     | 23 |
| materialize . . . . .                                     | 23 |
| mlr3torch_callbacks . . . . .                             | 25 |
| mlr3torch_losses . . . . .                                | 25 |
| mlr3torch_optimizers . . . . .                            | 26 |
| mlr_backends_lazy . . . . .                               | 27 |
| mlr_callback_set . . . . .                                | 30 |
| mlr_callback_set.checkpoint . . . . .                     | 33 |
| mlr_callback_set.history . . . . .                        | 34 |
| mlr_callback_set.lr_scheduler . . . . .                   | 36 |
| mlr_callback_set.lr_scheduler_one_cycle . . . . .         | 37 |
| mlr_callback_set.lr_scheduler_reduce_on_plateau . . . . . | 38 |
| mlr_callback_set.progress . . . . .                       | 39 |
| mlr_callback_set.tb . . . . .                             | 41 |
| mlr_callback_set.unfreeze . . . . .                       | 42 |
| mlr_context_torch . . . . .                               | 43 |
| mlr_learners.ft_transformer . . . . .                     | 46 |
| mlr_learners.mlp . . . . .                                | 49 |
| mlr_learners.module . . . . .                             | 51 |
| mlr_learners.tab_resnet . . . . .                         | 54 |
| mlr_learners.torchvision . . . . .                        | 56 |
| mlr_learners.torch_featureless . . . . .                  | 58 |
| mlr_learners_torch . . . . .                              | 60 |
| mlr_learners_torch_image . . . . .                        | 68 |
| mlr_learners_torch_model . . . . .                        | 70 |
| mlr_pipeops_augment_center_crop . . . . .                 | 72 |
| mlr_pipeops_augment_color_jitter . . . . .                | 73 |
| mlr_pipeops_augment_crop . . . . .                        | 74 |
| mlr_pipeops_augment_hflip . . . . .                       | 74 |
| mlr_pipeops_augment_random_affine . . . . .               | 75 |
| mlr_pipeops_augment_random_choice . . . . .               | 76 |
| mlr_pipeops_augment_random_crop . . . . .                 | 76 |
| mlr_pipeops_augment_random_horizontal_flip . . . . .      | 77 |
| mlr_pipeops_augment_random_order . . . . .                | 78 |
| mlr_pipeops_augment_random_resized_crop . . . . .         | 78 |
| mlr_pipeops_augment_random_vertical_flip . . . . .        | 79 |

|                                               |     |
|-----------------------------------------------|-----|
| mlr_pipeops_augment_resized_crop . . . . .    | 80  |
| mlr_pipeops_augment_rotate . . . . .          | 80  |
| mlr_pipeops_augment_vflip . . . . .           | 81  |
| mlr_pipeops_module . . . . .                  | 82  |
| mlr_pipeops_nn_adaptive_avg_pool1d . . . . .  | 85  |
| mlr_pipeops_nn_adaptive_avg_pool2d . . . . .  | 87  |
| mlr_pipeops_nn_adaptive_avg_pool3d . . . . .  | 88  |
| mlr_pipeops_nn_avg_pool1d . . . . .           | 90  |
| mlr_pipeops_nn_avg_pool2d . . . . .           | 92  |
| mlr_pipeops_nn_avg_pool3d . . . . .           | 94  |
| mlr_pipeops_nn_batch_norm1d . . . . .         | 96  |
| mlr_pipeops_nn_batch_norm2d . . . . .         | 98  |
| mlr_pipeops_nn_batch_norm3d . . . . .         | 100 |
| mlr_pipeops_nn_block . . . . .                | 102 |
| mlr_pipeops_nn_celu . . . . .                 | 105 |
| mlr_pipeops_nn_conv1d . . . . .               | 107 |
| mlr_pipeops_nn_conv2d . . . . .               | 109 |
| mlr_pipeops_nn_conv3d . . . . .               | 111 |
| mlr_pipeops_nn_conv_transpose1d . . . . .     | 113 |
| mlr_pipeops_nn_conv_transpose2d . . . . .     | 115 |
| mlr_pipeops_nn_conv_transpose3d . . . . .     | 117 |
| mlr_pipeops_nn_dropout . . . . .              | 120 |
| mlr_pipeops_nn_elu . . . . .                  | 121 |
| mlr_pipeops_nn_flatten . . . . .              | 123 |
| mlr_pipeops_nn_fn . . . . .                   | 125 |
| mlr_pipeops_nn_ft_cls . . . . .               | 127 |
| mlr_pipeops_nn_ft_transformer_block . . . . . | 128 |
| mlr_pipeops_nn_gelu . . . . .                 | 130 |
| mlr_pipeops_nn_gelu . . . . .                 | 132 |
| mlr_pipeops_nn_glu . . . . .                  | 134 |
| mlr_pipeops_nn_hardshrink . . . . .           | 135 |
| mlr_pipeops_nn_hardsigmoid . . . . .          | 137 |
| mlr_pipeops_nn_hardtanh . . . . .             | 139 |
| mlr_pipeops_nn_head . . . . .                 | 141 |
| mlr_pipeops_nn_identity . . . . .             | 143 |
| mlr_pipeops_nn_layer_norm . . . . .           | 144 |
| mlr_pipeops_nn_leaky_relu . . . . .           | 146 |
| mlr_pipeops_nn_linear . . . . .               | 148 |
| mlr_pipeops_nn_log_sigmoid . . . . .          | 150 |
| mlr_pipeops_nn_max_pool1d . . . . .           | 152 |
| mlr_pipeops_nn_max_pool2d . . . . .           | 154 |
| mlr_pipeops_nn_max_pool3d . . . . .           | 156 |
| mlr_pipeops_nn_merge . . . . .                | 158 |
| mlr_pipeops_nn_merge_cat . . . . .            | 160 |
| mlr_pipeops_nn_merge_prod . . . . .           | 162 |
| mlr_pipeops_nn_merge_sum . . . . .            | 164 |
| mlr_pipeops_nn_prelu . . . . .                | 166 |
| mlr_pipeops_nn_reglu . . . . .                | 168 |

|                                               |     |
|-----------------------------------------------|-----|
| mlr_pipeops_nn_relu . . . . .                 | 170 |
| mlr_pipeops_nn_relu6 . . . . .                | 172 |
| mlr_pipeops_nn_reshape . . . . .              | 174 |
| mlr_pipeops_nn_rrelu . . . . .                | 175 |
| mlr_pipeops_nn_selu . . . . .                 | 177 |
| mlr_pipeops_nn_sigmoid . . . . .              | 179 |
| mlr_pipeops_nn_softmax . . . . .              | 181 |
| mlr_pipeops_nn_softplus . . . . .             | 183 |
| mlr_pipeops_nn_softshrink . . . . .           | 184 |
| mlr_pipeops_nn_softsign . . . . .             | 186 |
| mlr_pipeops_nn_squeeze . . . . .              | 188 |
| mlr_pipeops_nn_tanh . . . . .                 | 190 |
| mlr_pipeops_nn_tanhshrink . . . . .           | 192 |
| mlr_pipeops_nn_threshold . . . . .            | 193 |
| mlr_pipeops_nn_tokenizer_categ . . . . .      | 195 |
| mlr_pipeops_nn_tokenizer_num . . . . .        | 197 |
| mlr_pipeops_nn_unsqueeze . . . . .            | 199 |
| mlr_pipeops_preproc_torch . . . . .           | 201 |
| mlr_pipeops_torch . . . . .                   | 206 |
| mlr_pipeops_torch_callbacks . . . . .         | 212 |
| mlr_pipeops_torch_ingress . . . . .           | 214 |
| mlr_pipeops_torch_ingress_categ . . . . .     | 216 |
| mlr_pipeops_torch_ingress_ltnsr . . . . .     | 218 |
| mlr_pipeops_torch_ingress_num . . . . .       | 221 |
| mlr_pipeops_torch_loss . . . . .              | 222 |
| mlr_pipeops_torch_model . . . . .             | 224 |
| mlr_pipeops_torch_model_classif . . . . .     | 228 |
| mlr_pipeops_torch_model_regr . . . . .        | 230 |
| mlr_pipeops_torch_optimizer . . . . .         | 232 |
| mlr_pipeops_trafo_adjust_brightness . . . . . | 233 |
| mlr_pipeops_trafo_adjust_gamma . . . . .      | 234 |
| mlr_pipeops_trafo_adjust_hue . . . . .        | 235 |
| mlr_pipeops_trafo_adjust_saturation . . . . . | 235 |
| mlr_pipeops_trafo_grayscale . . . . .         | 236 |
| mlr_pipeops_trafo_nop . . . . .               | 236 |
| mlr_pipeops_trafo_normalize . . . . .         | 237 |
| mlr_pipeops_trafo_pad . . . . .               | 237 |
| mlr_pipeops_trafo_reshape . . . . .           | 238 |
| mlr_pipeops_trafo_resize . . . . .            | 238 |
| mlr_pipeops_trafo_rgb_to_grayscale . . . . .  | 239 |
| mlr_tasks_cifar . . . . .                     | 240 |
| mlr_tasks_lazy_iris . . . . .                 | 241 |
| mlr_tasks_melanoma . . . . .                  | 242 |
| mlr_tasks_mnist . . . . .                     | 243 |
| mlr_tasks_tiny_imagenet . . . . .             | 244 |
| ModelDescriptor . . . . .                     | 245 |
| model_descriptor_to_learner . . . . .         | 246 |
| model_descriptor_to_module . . . . .          | 247 |

|                         |     |
|-------------------------|-----|
| model_descriptor_union  | 248 |
| nn                      | 249 |
| nn_ft_cls               | 249 |
| nn_ft_transformer_block | 250 |
| nn_gelu                 | 252 |
| nn_graph                | 253 |
| nn_merge_cat            | 254 |
| nn_merge_prod           | 254 |
| nn_merge_sum            | 255 |
| nn_reglu                | 255 |
| nn_reshape              | 256 |
| nn_squeeze              | 256 |
| nn_tokenizer_categ      | 257 |
| nn_tokenizer_num        | 257 |
| nn_unsqueeze            | 258 |
| output_dim_for          | 258 |
| pipeop_preproc_torch    | 259 |
| Select                  | 260 |
| task_dataset            | 261 |
| TorchCallback           | 262 |
| TorchDescriptor         | 265 |
| TorchIngressToken       | 267 |
| TorchLoss               | 268 |
| TorchOptimizer          | 271 |
| torch_callback          | 273 |
| t_clbk                  | 276 |
| t_loss                  | 277 |
| t_opt                   | 278 |

|              |            |
|--------------|------------|
| <b>Index</b> | <b>280</b> |
|--------------|------------|

## Description

Deep Learning library that extends the mlr3 framework by building upon the 'torch' package. It allows to conveniently build, train, and evaluate deep learning models without having to worry about low level details. Custom architectures can be created using the graph language defined in 'mlr3pipelines'.

## Options

- `mlr3torch.cache`: Whether to cache the downloaded data (TRUE) or not (FALSE, default). This can also be set to a specific folder on the file system to be used as the cache directory.

## Author(s)

**Maintainer:** Sebastian Fischer <[sebf.fischer@gmail.com](mailto:sebf.fischer@gmail.com)> ([ORCID](#))

Authors:

- Martin Binder <[mlr.developer@mb706.com](mailto:mlr.developer@mb706.com)>

Other contributors:

- Bernd Bischl <[bernd\\_bischl@gmx.net](mailto:bernd_bischl@gmx.net)> ([ORCID](#)) [contributor]
- Lukas Burk <[github@quantenbrot.de](mailto:github@quantenbrot.de)> ([ORCID](#)) [contributor]
- Florian Pfisterer <[pfistererf@googlemail.com](mailto:pfistererf@googlemail.com)> ([ORCID](#)) [contributor]
- Carson Zhang <[carsonzhang4@gmail.com](mailto:carsonzhang4@gmail.com)> [contributor]

## See Also

Useful links:

- <https://mlr3torch.mlr-org.com/>
- <https://github.com/mlr-org/mlr3torch/>
- Report bugs at <https://github.com/mlr-org/mlr3torch/issues>

---

`assert_lazy_tensor`      *Assert Lazy Tensor*

---

## Description

Asserts whether something is a lazy tensor.

## Usage

```
assert_lazy_tensor(x)
```

## Arguments

|                |                  |
|----------------|------------------|
| <code>x</code> | (any)            |
|                | Object to check. |

---

|                    |                                   |
|--------------------|-----------------------------------|
| as_data_descriptor | <i>Convert to Data Descriptor</i> |
|--------------------|-----------------------------------|

---

## Description

Converts the input to a [DataDescriptor](#).

## Usage

```
as_data_descriptor(x, dataset_shapes, ...)
```

## Arguments

|                |                                                                                                                                                                                                                              |
|----------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| x              | (any)                                                                                                                                                                                                                        |
|                | Object to convert.                                                                                                                                                                                                           |
| dataset_shapes | (named list() of (integer() or NULL))                                                                                                                                                                                        |
|                | The shapes of the output. Names are the elements of the list returned by the dataset. If the shape is not NULL (unknown, e.g. for images of different sizes) the first dimension must be NA to indicate the batch dimension. |
| ...            | (any)                                                                                                                                                                                                                        |
|                | Further arguments passed to the <a href="#">DataDescriptor</a> constructor.                                                                                                                                                  |

## Examples

```
ds = dataset("example",
  initialize = function() self$iris = iris[, -5],
  .getitem = function(i) list(x = torch_tensor(as.numeric(self$iris[i, ]))),
  .length = function() nrow(self$iris)
)()
as_data_descriptor(ds, list(x = c(NA, 4L)))

# if the dataset has a .getbatch method, the shapes are inferred
ds2 = dataset("example",
  initialize = function() self$iris = iris[, -5],
  .getbatch = function(i) list(x = torch_tensor(as.matrix(self$iris[i, ]))),
  .length = function() nrow(self$iris)
)()
as_data_descriptor(ds2)
```

---

|                |                               |
|----------------|-------------------------------|
| as_lazy_tensor | <i>Convert to Lazy Tensor</i> |
|----------------|-------------------------------|

---

## Description

Convert a object to a [lazy\\_tensor](#).

## Usage

```
as_lazy_tensor(x, ...)

## S3 method for class 'dataset'
as_lazy_tensor(x, dataset_shapes = NULL, ids = NULL, ...)
```

## Arguments

|                |                                                                                                                                                                                                                                                                       |
|----------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| x              | (any)<br>Object to convert to a <a href="#">lazy_tensor</a>                                                                                                                                                                                                           |
| ...            | (any)<br>Additional arguments passed to the method.                                                                                                                                                                                                                   |
| dataset_shapes | (named list() of (integer() or NULL))<br>The shapes of the output. Names are the elements of the list returned by the dataset. If the shape is not NULL (unknown, e.g. for images of different sizes) the first dimension must be NA to indicate the batch dimension. |
| ids            | (integer())<br>Which ids to include in the lazy tensor.                                                                                                                                                                                                               |

## Examples

```
iris_ds = dataset("iris",
  initialize = function() {
    self$iris = iris[, -5]
  },
  .getbatch = function(i) {
    list(x = torch_tensor(as.matrix(self$iris[i, ])))
  },
  .length = function() nrow(self$iris)
)()
# no need to specify the dataset shapes as they can be inferred from the .getbatch method
# only first 5 observations
as_lazy_tensor(iris_ds, ids = 1:5)
# all observations
head(as_lazy_tensor(iris_ds))

iris_ds2 = dataset("iris",
  initialize = function() self$iris = iris[, -5],
  .getitem = function(i) list(x = torch_tensor(as.numeric(self$iris[i, ]))),
  .length = function() nrow(self$iris)
```

```

)()
# if .getitem is implemented we cannot infer the shapes as they might vary,
# so we have to annotate them explicitly
as_lazy_tensor(iris_ds2, dataset_shapes = list(x = c(NA, 4L)))[1:5]

# Convert a matrix
lt = as_lazy_tensor(matrix(rnorm(100), nrow = 20))
materialize(lt[1:5], rbind = TRUE)

```

## as\_lr\_scheduler

*Convert to CallbackSetLRScheduler***Description**

Convert a torch scheduler generator to a CallbackSetLRScheduler.

**Usage**

```
as_lr_scheduler(x, step_on_epoch)
```

**Arguments**

|               |                                                                                   |
|---------------|-----------------------------------------------------------------------------------|
| x             | (function)                                                                        |
|               | The torch scheduler generator defined using <code>torch:::lr_scheduler()</code> . |
| step_on_epoch | (logical(1))                                                                      |
|               | Whether the scheduler steps after every epoch                                     |

## as\_torch\_callback

*Convert to a TorchCallback***Description**

Converts an object to a [TorchCallback](#).

**Usage**

```
as_torch_callback(x, clone = FALSE, ...)
```

**Arguments**

|       |                               |
|-------|-------------------------------|
| x     | (any)                         |
|       | Object to be converted.       |
| clone | (logical(1))                  |
|       | Whether to make a deep clone. |
| ...   | (any)                         |
|       | Additional arguments          |

**Value**

[TorchCallback](#).

**See Also**

Other Callback: [TorchCallback](#), [as\\_torch\\_callbacks\(\)](#), [callback\\_set\(\)](#), [mlr3torch\\_callbacks](#), [mlr\\_callback\\_set](#), [mlr\\_callback\\_set.checkpoint](#), [mlr\\_callback\\_set.progress](#), [mlr\\_callback\\_set.tb](#), [mlr\\_callback\\_set.unfreeze](#), [mlr\\_context\\_torch](#), [t\\_clbk\(\)](#), [torch\\_callback\(\)](#)

---

[as\\_torch\\_callbacks](#)

*Convert to a list of Torch Callbacks*

---

**Description**

Converts an object to a list of [TorchCallback](#).

**Usage**

```
as_torch_callbacks(x, clone, ...)
```

**Arguments**

|       |                                 |
|-------|---------------------------------|
| x     | (any)                           |
|       | Object to convert.              |
| clone | (logical(1))                    |
|       | Whether to create a deep clone. |
| ...   | (any)                           |
|       | Additional arguments.           |

**Value**

`list()` of [TorchCallbacks](#)

**See Also**

Other Callback: [TorchCallback](#), [as\\_torch\\_callback\(\)](#), [callback\\_set\(\)](#), [mlr3torch\\_callbacks](#), [mlr\\_callback\\_set](#), [mlr\\_callback\\_set.checkpoint](#), [mlr\\_callback\\_set.progress](#), [mlr\\_callback\\_set.tb](#), [mlr\\_callback\\_set.unfreeze](#), [mlr\\_context\\_torch](#), [t\\_clbk\(\)](#), [torch\\_callback\(\)](#)

Other Torch Descriptor: [TorchCallback](#), [TorchDescriptor](#), [TorchLoss](#), [TorchOptimizer](#), [as\\_torch\\_loss\(\)](#), [as\\_torch\\_optimizer\(\)](#), [mlr3torch\\_losses](#), [mlr3torch\\_optimizers](#), [t\\_clbk\(\)](#), [t\\_loss\(\)](#), [t\\_opt\(\)](#)

---

|               |                             |
|---------------|-----------------------------|
| as_torch_loss | <i>Convert to TorchLoss</i> |
|---------------|-----------------------------|

---

## Description

Converts an object to a [TorchLoss](#).

## Usage

```
as_torch_loss(x, clone = FALSE, ...)
```

## Arguments

|       |              |                                                                                                                                                       |
|-------|--------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|
| x     | (any)        |                                                                                                                                                       |
|       |              | Object to convert to a <a href="#">TorchLoss</a> .                                                                                                    |
| clone | (logical(1)) |                                                                                                                                                       |
|       |              | Whether to make a deep clone.                                                                                                                         |
| ...   | (any)        |                                                                                                                                                       |
|       |              | Additional arguments. Currently used to pass additional constructor arguments to <a href="#">TorchLoss</a> for objects of type <code>nn_loss</code> . |

## Value

[TorchLoss](#).

## See Also

Other Torch Descriptor: [TorchCallback](#), [TorchDescriptor](#), [TorchLoss](#), [TorchOptimizer](#), [as\\_torch\\_callbacks\(\)](#), [as\\_torch\\_optimizer\(\)](#), [mlr3torch\\_losses](#), [mlr3torch\\_optimizers](#), [t\\_clbk\(\)](#), [t\\_loss\(\)](#), [t\\_opt\(\)](#)

---

|                    |                                  |
|--------------------|----------------------------------|
| as_torch_optimizer | <i>Convert to TorchOptimizer</i> |
|--------------------|----------------------------------|

---

## Description

Converts an object to a [TorchOptimizer](#).

## Usage

```
as_torch_optimizer(x, clone = FALSE, ...)
```

**Arguments**

|       |              |                                                                                                                                                                              |
|-------|--------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| x     | (any)        |                                                                                                                                                                              |
|       |              | Object to convert to a <a href="#">TorchOptimizer</a> .                                                                                                                      |
| clone | (logical(1)) |                                                                                                                                                                              |
|       |              | Whether to make a deep clone. Default is FALSE.                                                                                                                              |
| ...   | (any)        |                                                                                                                                                                              |
|       |              | Additional arguments. Currently used to pass additional constructor arguments to <a href="#">TorchOptimizer</a> for objects of type <code>torch_optimizer_generator</code> . |

**Value**

[TorchOptimizer](#)

**See Also**

Other Torch Descriptor: [TorchCallback](#), [TorchDescriptor](#), [TorchLoss](#), [TorchOptimizer](#), [as\\_torch\\_callbacks\(\)](#), [as\\_torch\\_loss\(\)](#), [mlr3torch\\_losses](#), [mlr3torch\\_optimizers](#), [t\\_clbk\(\)](#), [t\\_loss\(\)](#), [t\\_opt\(\)](#)

auto\_device

*Auto Device*

**Description**

First tries cuda, then cpu.

**Usage**

`auto_device(device = NULL)`

**Arguments**

|        |                |                                             |
|--------|----------------|---------------------------------------------|
| device | (character(1)) |                                             |
|        |                | The device. If not NULL, is returned as is. |

batchgetter\_categ

*Batchgetter for Categorical data*

**Description**

Converts a data frame of categorical data into a long tensor by converting the data to integers. No input checks are performed.

**Usage**

`batchgetter_categ(data, ...)`

**Arguments**

|      |                                         |
|------|-----------------------------------------|
| data | (data.table)                            |
|      | data.table to be converted to a tensor. |
| ...  | (any)                                   |
|      | Unused.                                 |

|                 |                                     |
|-----------------|-------------------------------------|
| batchgetter_num | <i>Batchgetter for Numeric Data</i> |
|-----------------|-------------------------------------|

**Description**

Converts a data frame of numeric data into a float tensor by calling `as.matrix()`. No input checks are performed

**Usage**

```
batchgetter_num(data, ...)
```

**Arguments**

|      |                                         |
|------|-----------------------------------------|
| data | (data.table())                          |
|      | data.table to be converted to a tensor. |
| ...  | (any)                                   |
|      | Unused.                                 |

|              |                                            |
|--------------|--------------------------------------------|
| callback_set | <i>Create a Set of Callbacks for Torch</i> |
|--------------|--------------------------------------------|

**Description**

Creates an R6ClassGenerator inheriting from [CallbackSet](#). Additionally performs checks such as that the stages are not accidentally misspelled. To create a [TorchCallback](#) use [torch\\_callback\(\)](#).

In order for the resulting class to be cloneable, the private method `$deep_clone()` must be provided.

**Usage**

```
callback_set(
  classname,
  on_begin = NULL,
  on_end = NULL,
  on_exit = NULL,
  on_epoch_begin = NULL,
  on_before_valid = NULL,
```

```

    on_epoch_end = NULL,
    on_batch_begin = NULL,
    on_batch_end = NULL,
    on_after_backward = NULL,
    on_batch_valid_begin = NULL,
    on_batch_valid_end = NULL,
    on_valid_end = NULL,
    state_dict = NULL,
    load_state_dict = NULL,
    initialize = NULL,
    public = NULL,
    private = NULL,
    active = NULL,
    parent_env = parent.frame(),
    inherit = CallbackSet,
    lock_objects = FALSE
)

```

## Arguments

|                                                                 |                                                                                                                                                                                  |
|-----------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| classname                                                       | (character(1))                                                                                                                                                                   |
|                                                                 | The class name.                                                                                                                                                                  |
| on_begin, on_end, on_epoch_begin, on_before_valid,              |                                                                                                                                                                                  |
| on_epoch_end, on_batch_begin, on_batch_end, on_after_backward,  |                                                                                                                                                                                  |
| on_batch_valid_begin, on_batch_valid_end, on_valid_end, on_exit |                                                                                                                                                                                  |
|                                                                 | (function)                                                                                                                                                                       |
|                                                                 | Function to execute at the given stage, see section <i>Stages</i> .                                                                                                              |
| state_dict                                                      | (function())                                                                                                                                                                     |
|                                                                 | The function that retrieves the state dict from the callback. This is what will be available in the learner after training.                                                      |
| load_state_dict                                                 | (function(state_dict))                                                                                                                                                           |
|                                                                 | Function that loads a callback state.                                                                                                                                            |
| initialize                                                      | (function())                                                                                                                                                                     |
|                                                                 | The initialization method of the callback.                                                                                                                                       |
| public, private, active                                         | (list())                                                                                                                                                                         |
|                                                                 | Additional public, private, and active fields to add to the callback.                                                                                                            |
| parent_env                                                      | (environment())                                                                                                                                                                  |
|                                                                 | The parent environment for the <a href="#">R6Class</a> .                                                                                                                         |
| inherit                                                         | (R6ClassGenerator)                                                                                                                                                               |
|                                                                 | From which class to inherit. This class must either be <a href="#">CallbackSet</a> (default) or inherit from it.                                                                 |
| lock_objects                                                    | (logical(1))                                                                                                                                                                     |
|                                                                 | Whether to lock the objects of the resulting <a href="#">R6Class</a> . If FALSE (default), values can be freely assigned to self without declaring them in the class definition. |

**Value**`CallbackSet`**See Also**

Other Callback: `TorchCallback`, `as_torch_callback()`, `as_torch_callbacks()`, `mlr3torch_callbacks`, `mlr_callback_set`, `mlr_callback_set.checkpoint`, `mlr_callback_set.progress`, `mlr_callback_set.tb`, `mlr_callback_set.unfreeze`, `mlr_context_torch`, `t_clbk()`, `torch_callback()`

---

`cross_entropy`*Cross Entropy Loss*

---

**Description**

The `cross_entropy` loss function selects the multi-class (`nn_cross_entropy_loss`) or binary (`nn_bce_with_logits_loss`) cross entropy loss based on the number of classes. Because of this, there is a slight reparameterization of the loss arguments, see *Parameters*.

**Parameters**

- `class_weight:: torch_tensor`  
The class weights. For multi-class problems, this must be a `torch_tensor` of length `num_classes` (and is passed as argument `weight` to `nn_cross_entropy_loss`). For binary problems, this must be a scalar (and is passed as argument `pos_weight` to `nn_bce_with_logits_loss`).
- `ignore_index:: integer(1)`  
Index of the class which to ignore and which does not contribute to the gradient. This is only available for multi-class loss.
- `reduction :: character(1)`  
The reduction to apply. Is either "mean" or "sum" and passed as argument `reduction` to either loss function. The default is "mean".

**Examples**

```
loss = t_loss("cross_entropy")
# multi-class
multi_ce = loss$generate(tsk("iris"))
multi_ce

# binary
binary_ce = loss$generate(tsk("sonar"))
binary_ce
```

---

DataDescriptor

---

*Data Descriptor*

---

## Description

A data descriptor is a rather internal data structure used in the `lazy_tensor` data type. In essence it is an annotated `torch::dataset` and a preprocessing graph (consisting mostly of `PipeOpModule` operators). The additional meta data (e.g. pointer, shapes) allows to preprocess `lazy_tensors` in an `mlr3pipelines::Graph` just like any (non-lazy) data types. The preprocessing is applied when `materialize()` is called on the `lazy_tensor`.

To create a data descriptor, you can also use the `as_data_descriptor()` function.

## Details

While it would be more natural to define this as an S3 class, we opted for an R6 class to avoid the usual trouble of serializing S3 objects. If each row contained a DataDescriptor as an S3 class, this would copy the object when serializing.

## Public fields

`dataset` (`torch::dataset`)  
The dataset.

`graph` (`Graph`)  
The preprocessing graph.

`dataset_shapes` (named list() of (integer() or NULL))  
The shapes of the output.

`input_map` (character())  
The input map from the dataset to the preprocessing graph.

`pointer` (character(2))  
The output pointer.

`pointer_shape` (integer() | NULL)  
The shape of the output indicated by pointer.

`dataset_hash` (character(1))  
Hash for the wrapped dataset.

`hash` (character(1))  
Hash for the data descriptor.

`graph_input` (character())  
The input channels of the preprocessing graph (cached to save time).

`pointer_shape_predict` (integer() or NULL)  
Internal use only.

## Methods

### Public methods:

- `DataDescriptor$new()`
- `DataDescriptor$print()`
- `DataDescriptor$clone()`

**Method** `new()`: Creates a new instance of this `R6` class.

*Usage:*

```
DataDescriptor$new(
  dataset,
  dataset_shapes = NULL,
  graph = NULL,
  input_map = NULL,
  pointer = NULL,
  pointer_shape = NULL,
  pointer_shape_predict = NULL,
  clone_graph = TRUE
)
```

*Arguments:*

`dataset` (`torch::dataset`)

The torch dataset. It should return a named `list()` of `torch_tensor` objects.

`dataset_shapes` (named `list()` of (`integer()` or `NULL`))

The shapes of the output. Names are the elements of the list returned by the dataset. If the shape is not `NULL` (unknown, e.g. for images of different sizes) the first dimension must be `NA` to indicate the batch dimension.

`graph` (`Graph`)

The preprocessing graph. If left `NULL`, no preprocessing is applied to the data and `input_map`, `pointer`, `pointer_shape`, and `pointer_shape_predict` are inferred in case the dataset returns only one element.

`input_map` (`character()`)

Character vector that must have the same length as the input of the graph. Specifies how the data from the dataset is fed into the preprocessing graph.

`pointer` (`character(2) | NULL`)

Points to an output channel within `graph`: Element 1 is the PipeOp's id and element 2 is that PipeOp's output channel.

`pointer_shape` (`integer() | NULL`)

Shape of the output indicated by `pointer`.

`pointer_shape_predict` (`integer() or NULL`)

Internal use only. Used in a `Graph` to anticipate possible mismatches between train and predict shapes.

`clone_graph` (`logical(1)`)

Whether to clone the preprocessing graph.

**Method** `print()`: Prints the object

*Usage:*

```
  DataDescriptor$print(...)
```

*Arguments:*

... (any)  
Unused

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

```
  DataDescriptor$clone(deep = FALSE)
```

*Arguments:*

deep Whether to make a deep clone.

## See Also

`ModelDescriptor`, `lazy_tensor`

## Examples

```
# Create a dataset
ds = dataset(
  initialize = function() self$x = torch_randn(10, 3, 3),
  .getitem = function(i) list(x = self$x[i, ]),
  .length = function() nrow(self$x)
)()
dd = DataDescriptor$new(ds, list(x = c(NA, 3, 3)))
dd
# is the same as using the converter:
as_data_descriptor(ds, list(x = c(NA, 3, 3)))
```

`infer_shapes`

*Infer Shapes*

## Description

Infer the shapes of the output of a function based on the shapes of the input. This is done as follows:

1. All NAs are replaced with values 1, 2, 3.
2. Three tensors are generated for the three shapes of step 1.
3. The function is called on these three tensors and the shapes are calculated.
4. If:
  - the number of dimensions varies, an error is thrown.
  - the number of dimensions is the same, values are set to NA if the dimension is varying between the three tensors and otherwise set to the unique value.

## Usage

```
infer_shapes(shapes_in, param_vals, output_names, fn, rowwise, id)
```

**Arguments**

|              |                                              |
|--------------|----------------------------------------------|
| shapes_in    | (list())                                     |
|              | A list of shapes of the input tensors.       |
| param_vals   | (list())                                     |
|              | A list of named parameters for the function. |
| output_names | (character())                                |
|              | The names of the output tensors.             |
| fn           | (function())                                 |
|              | The function to infer the shapes for.        |
| rowwise      | (logical(1))                                 |
|              | Whether the function is rowwise.             |
| id           | (character(1))                               |
|              | The id of the PipeOp (for error messages).   |

**Value**

|                                         |
|-----------------------------------------|
| (list())                                |
| A list of shapes of the output tensors. |

ingress\_categ

*Ingress Token for Categorical Features***Description**

Represents an entry point representing a tensor containing all categorical (factor(), ordered(), logical()) features of a task.

**Usage**

```
ingress_categ(shape = NULL)
```

**Arguments**

|       |                                                                                |
|-------|--------------------------------------------------------------------------------|
| shape | (integer() or NULL)                                                            |
|       | Shape that batchgetter will produce. Batch-dimension should be included as NA. |

**Value**

[TorchIngressToken](#)

---

|               |                                              |
|---------------|----------------------------------------------|
| ingress_ltnsr | <i>Ingress Token for Lazy Tensor Feature</i> |
|---------------|----------------------------------------------|

---

### Description

Represents an entry point representing a tensor containing a single lazy tensor feature.

### Usage

```
ingress_ltnsr(feature_name = NULL, shape = NULL)
```

### Arguments

|              |                                                                                |
|--------------|--------------------------------------------------------------------------------|
| feature_name | (character(1))                                                                 |
|              | Which lazy tensor feature to select if there is more than one.                 |
| shape        | (integer() or NULL)                                                            |
|              | Shape that batchgetter will produce. Batch-dimension should be included as NA. |

### Value

[TorchIngressToken](#)

---

|             |                                           |
|-------------|-------------------------------------------|
| ingress_num | <i>Ingress Token for Numeric Features</i> |
|-------------|-------------------------------------------|

---

### Description

Represents an entry point representing a tensor containing all numeric (integer() and double()) features of a task.

### Usage

```
ingress_num(shape = NULL)
```

### Arguments

|       |                                                                                |
|-------|--------------------------------------------------------------------------------|
| shape | (integer() or NULL)                                                            |
|       | Shape that batchgetter will produce. Batch-dimension should be included as NA. |

### Value

[TorchIngressToken](#)

---

|                |                              |
|----------------|------------------------------|
| is_lazy_tensor | <i>Check for lazy tensor</i> |
|----------------|------------------------------|

---

## Description

Checks whether an object is a lazy tensor.

## Usage

```
is_lazy_tensor(x)
```

## Arguments

|   |                  |
|---|------------------|
| x | (any)            |
|   | Object to check. |

---

|            |                             |
|------------|-----------------------------|
| lazy_shape | <i>Shape of Lazy Tensor</i> |
|------------|-----------------------------|

---

## Description

Shape of a lazy tensor. Might be `NULL` if the shapes is not known or varying between rows. Batch dimension is always `NA`.

## Usage

```
lazy_shape(x)
```

## Arguments

|   |                                 |
|---|---------------------------------|
| x | ( <a href="#">lazy_tensor</a> ) |
|   | Lazy tensor.                    |

## Value

(`integer()` or `NULL`)

## Examples

```
lt = as_lazy_tensor(1:10)
lazy_shape(lt)
lt = as_lazy_tensor(matrix(1:10, nrow = 2))
lazy_shape(lt)
```

---

|             |                             |
|-------------|-----------------------------|
| lazy_tensor | <i>Create a lazy tensor</i> |
|-------------|-----------------------------|

---

## Description

Create a lazy tensor.

## Usage

```
lazy_tensor(data_descriptor = NULL, ids = NULL)
```

## Arguments

|                 |                                                                        |
|-----------------|------------------------------------------------------------------------|
| data_descriptor | ( <a href="#">DataDescriptor</a> or NULL)                              |
|                 | The data descriptor or NULL for a lazy tensor of length 0.             |
| ids             | ( <a href="#">integer()</a> )                                          |
|                 | The elements of the data_descriptor to be included in the lazy tensor. |

## Examples

```
ds = dataset("example",
  initialize = function() self$iris = iris[, -5],
  .getitem = function(i) list(x = torch_tensor(as.numeric(self$iris[i, ]))),
  .length = function() nrow(self$iris)
)()
dd = as_data_descriptor(ds, list(x = c(NA, 4L)))
lt = as_lazy_tensor(dd)
```

---

|             |                                        |
|-------------|----------------------------------------|
| materialize | <i>Materialize Lazy Tensor Columns</i> |
|-------------|----------------------------------------|

---

## Description

This will materialize a `lazy_tensor()` or a `data.frame()` / `list()` containing – among other things – `lazy_tensor()` columns. I.e. the data described in the underlying `DataDescriptor`s is loaded for the indices in the `lazy_tensor()`, is preprocessed and then put unto the specified device. Because not all elements in a lazy tensor must have the same shape, a list of tensors is returned by default. If all elements have the same shape, these tensors can also be rbinded into a single tensor (parameter `rbind`).

## Usage

```
materialize(x, device = "cpu", rbind = FALSE, ...)
## S3 method for class 'list'
materialize(x, device = "cpu", rbind = FALSE, cache = "auto", ...)
```

## Arguments

|        |                                                                                                                                                                                                                        |
|--------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| x      | (any)                                                                                                                                                                                                                  |
|        | The object to materialize. Either a <code>lazy_tensor</code> or a <code>list()</code> / <code>data.frame()</code> containing <code>lazy_tensor</code> columns.                                                         |
| device | (character(1))                                                                                                                                                                                                         |
|        | The torch device.                                                                                                                                                                                                      |
| rbind  | (logical(1))                                                                                                                                                                                                           |
|        | Whether to rbind the lazy tensor columns (TRUE) or return them as a list of tensors (FALSE). In the second case, there is no batch dimension.                                                                          |
| ...    | (any)                                                                                                                                                                                                                  |
|        | Additional arguments.                                                                                                                                                                                                  |
| cache  | (character(1) or <code>environment()</code> or NULL)                                                                                                                                                                   |
|        | Optional cache for (intermediate) materialization results. Per default, caching will be enabled when the same dataset or data descriptor (with different output pointer) is used for more than one lazy tensor column. |

## Details

Materializing a lazy tensor consists of:

1. Loading the data from the internal dataset of the `DataDescriptor`.
2. Processing these batches in the preprocessing `Graphs`.
3. Returning the result of the `PipeOp` pointed to by the `DataDescriptor` (pointer).

With multiple `lazy_tensor` columns we can benefit from caching because: a) Output(s) from the dataset might be input to multiple graphs. b) Different lazy tensors might be outputs from the same graph.

For this reason it is possible to provide a cache environment. The hash key for a) is the hash of the indices and the dataset. The hash key for b) is the hash of the indices, dataset and preprocessing graph.

## Value

(`list()` of `lazy_tensors` or a `lazy_tensor`)

## Examples

```
lt1 = as_lazy_tensor(torch_randn(10, 3))
materialize(lt1, rbind = TRUE)
materialize(lt1, rbind = FALSE)
lt2 = as_lazy_tensor(torch_randn(10, 4))
d = data.table::data.table(lt1 = lt1, lt2 = lt2)
materialize(d, rbind = TRUE)
materialize(d, rbind = FALSE)
```

---

**mlr3torch\_callbacks** *Dictionary of Torch Callbacks*

---

**Description**

A [mlr3misc::Dictionary](#) of torch callbacks. Use [t\\_clbk\(\)](#) to conveniently retrieve callbacks. Can be converted to a [data.table](#) using [as.data.table](#).

**Usage**

```
mlr3torch_callbacks
```

**Format**

An object of class [DictionaryMlr3torchCallbacks](#) (inherits from [Dictionary](#), [R6](#)) of length 12.

**See Also**

Other Callback: [TorchCallback](#), [as\\_torch\\_callback\(\)](#), [as\\_torch\\_callbacks\(\)](#), [callback\\_set\(\)](#), [mlr\\_callback\\_set](#), [mlr\\_callback\\_set.checkpoint](#), [mlr\\_callback\\_set.progress](#), [mlr\\_callback\\_set.tb](#), [mlr\\_callback\\_set.unfreeze](#), [mlr\\_context\\_torch](#), [t\\_clbk\(\)](#), [torch\\_callback\(\)](#)

Other Dictionary: [mlr3torch\\_losses](#), [mlr3torch\\_optimizers](#), [t\\_opt\(\)](#)

**Examples**

```
mlr3torch_callbacks$get("checkpoint")
# is the same as
t_clbk("checkpoint")
# convert to a data.table
as.data.table(mlr3torch_callbacks)
```

---

**mlr3torch\_losses** *Loss Functions*

---

**Description**

Dictionary of torch loss descriptors. See [t\\_loss\(\)](#) for conveniently retrieving a loss function. Can be converted to a [data.table](#) using [as.data.table](#).

**Usage**

```
mlr3torch_losses
```

**Format**

An object of class [DictionaryMlr3torchLosses](#) (inherits from [Dictionary](#), [R6](#)) of length 12.

## Available Loss Functions

`cross_entropy`, `l1`, `mse`

## See Also

Other Torch Descriptor: `TorchCallback`, `TorchDescriptor`, `TorchLoss`, `TorchOptimizer`, `as_torch_callbacks()`, `as_torch_loss()`, `as_torch_optimizer()`, `mlr3torch_optimizers`, `t_clbk()`, `t_loss()`, `t_opt()`

Other Dictionary: `mlr3torch_callbacks`, `mlr3torch_losses`, `t_opt()`

## Examples

```
mlr3torch_losses$get("mse")
# is equivalent to
t_loss("mse")
# convert to a data.table
as.data.table(mlr3torch_losses)
```

`mlr3torch_optimizers` *Optimizers*

## Description

Dictionary of torch optimizers. Use `t_opt` for conveniently retrieving optimizers. Can be converted to a `data.table` using `as.data.table`.

## Usage

`mlr3torch_optimizers`

## Format

An object of class `DictionaryMlr3torchOptimizers` (inherits from `Dictionary`, `R6`) of length 12.

## Available Optimizers

`adagrad`, `adam`, `adamw`, `rmsprop`, `sgd`

## See Also

Other Torch Descriptor: `TorchCallback`, `TorchDescriptor`, `TorchLoss`, `TorchOptimizer`, `as_torch_callbacks()`, `as_torch_loss()`, `as_torch_optimizer()`, `mlr3torch_losses`, `t_clbk()`, `t_loss()`, `t_opt()`

Other Dictionary: `mlr3torch_callbacks`, `mlr3torch_losses`, `t_opt()`

## Examples

```
mlr3torch_optimizers$get("adam")
# is equivalent to
t_opt("adam")
# convert to a data.table
as.data.table(mlr3torch_optimizers)
```

---

|                   |                          |
|-------------------|--------------------------|
| mlr_backends_lazy | <i>Lazy Data Backend</i> |
|-------------------|--------------------------|

---

## Description

This lazy data backend wraps a constructor that lazily creates another backend, e.g. by downloading (and caching) some data from the internet. This backend should be used, when some metadata of the backend is known in advance and should be accessible before downloading the actual data. When the backend is first constructed, it is verified that the provided metadata was correct, otherwise an informative error message is thrown. After the construction of the lazily constructed backend, calls like `$data()`, `$missings()`, `$distinct()`, or `$hash()` are redirected to it.

Information that is available before the backend is constructed is:

- `nrow` - The number of rows (set as the length of the `rownames`).
- `ncol` - The number of columns (provided via the `id` column of `col_info`).
- `colnames` - The column names.
- `rownames` - The row names.
- `col_info` - The column information, which can be obtained via [mlr3::col\\_info\(\)](#).

Beware that accessing the backend's hash also constructs the backend.

Note that while in most cases the data contains `lazy_tensor` columns, this is not necessary and the naming of this class has nothing to do with the `lazy_tensor` data type.

### Important

When the constructor generates `factor()` variables it is important that the ordering of the levels in data corresponds to the ordering of the levels in the `col_info` argument.

## Super class

[mlr3::DataBackend](#) -> DataBackendLazy

## Active bindings

`backend` (`DataBackend`)

The wrapped backend that is lazily constructed when first accessed.

`nrow` (`integer(1)`)

Number of rows (observations).

```

ncol (integer(1))
  Number of columns (variables), including the primary key column.

rownames (integer())
  Returns vector of all distinct row identifiers, i.e. the contents of the primary key column.

colnames (character())
  Returns vector of all column names, including the primary key column.

is_constructed (logical(1))
  Whether the backend has already been constructed.

```

## Methods

### Public methods:

- `DataBackendLazy$new()`
- `DataBackendLazy$data()`
- `DataBackendLazy$head()`
- `DataBackendLazy$distinct()`
- `DataBackendLazy$missings()`
- `DataBackendLazy$print()`

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

```
DataBackendLazy$new(backend, rownames, col_info, primary_key)
```

*Arguments:*

`constructor (function)`

A function with argument `backend` (the lazy backend), whose return value must be the actual backend. This function is called the first time the field `$backend` is accessed.

`rownames (integer())`

The row names. Must be a permutation of the rownames of the lazily constructed backend.

`col_info (data.table::data.table())`

A `data.table` with columns `id`, `type` and `levels` containing the column `id`, `type` and `levels`.

Note that the levels must be provided in the correct order.

`primary_key (character(1))`

Name of the primary key column.

**Method** `data()`: Returns a slice of the data in the specified format. The rows must be addressed as vector of primary key values, columns must be referred to via column names. Queries for rows with no matching row id and queries for columns with no matching column name are silently ignored. Rows are guaranteed to be returned in the same order as `rows`, columns may be returned in an arbitrary order. Duplicated row ids result in duplicated rows, duplicated column names lead to an exception.

Accessing the data triggers the construction of the backend.

*Usage:*

```
DataBackendLazy$data(rows, cols)
```

*Arguments:*

```

rows (integer())
  Row indices.
cols (character())
  Column names.

```

**Method** `head()`: Retrieve the first n rows. This triggers the construction of the backend.

*Usage:*

```
DataBackendLazy$head(n = 6L)
```

*Arguments:*

```

n (integer(1))
  Number of rows.

```

*Returns:* `data.table::data.table()` of the first n rows.

**Method** `distinct()`: Returns a named list of vectors of distinct values for each column specified. If `na_rm` is TRUE, missing values are removed from the returned vectors of distinct values. Non-existing rows and columns are silently ignored.

This triggers the construction of the backend.

*Usage:*

```
DataBackendLazy$distinct(rows, cols, na_rm = TRUE)
```

*Arguments:*

```

rows (integer())
  Row indices.
cols (character())
  Column names.
na_rm (logical(1))
  Whether to remove NAs or not.

```

*Returns:* Named list() of distinct values.

**Method** `missings()`: Returns the number of missing values per column in the specified slice of data. Non-existing rows and columns are silently ignored.

This triggers the construction of the backend.

*Usage:*

```
DataBackendLazy$missings(rows, cols)
```

*Arguments:*

```

rows (integer())
  Row indices.
cols (character())
  Column names.

```

*Returns:* Total of missing values per column (named `numeric()`).

**Method** `print()`: Printer.

*Usage:*

```
DataBackendLazy$print()
```

## Examples

```

# We first define a backend constructor
constructor = function(backend) {
  cat("Data is constructed!\n")
  DataBackendDataTable$new(
    data.table(x = rnorm(10), y = rnorm(10), row_id = 1:10),
    primary_key = "row_id"
  )
}

# to wrap this backend constructor in a lazy backend, we need to provide the correct metadata for it
column_info = data.table(
  id = c("x", "y", "row_id"),
  type = c("numeric", "numeric", "integer"),
  levels = list(NULL, NULL, NULL)
)
backend_lazy = DataBackendLazy$new(
  constructor = constructor,
  rownames = 1:10,
  col_info = column_info,
  primary_key = "row_id"
)

# Note that the constructor is not called for the calls below
# as they can be read from the metadata
backend_lazy$nrow
backend_lazy$rownames
backend_lazy$ncol
backend_lazy$colnames
col_info(backend_lazy)

# Only now the backend is constructed
backend_lazy$data(1, "x")
# Is the same as:
backend_lazy$backend$data(1, "x")

```

---

`mlr_callback_set`      *Base Class for Callbacks*

---

## Description

Base class from which callbacks should inherit (see section *Inheriting*). A callback set is a collection of functions that are executed at different stages of the training loop. They can be used to gain more control over the training process of a neural network without having to write everything from scratch.

When used a in torch learner, the `CallbackSet` is wrapped in a `TorchCallback`. The latters parameter set represents the arguments of the `CallbackSet`'s `$initialize()` method.

## Inheriting

For each available stage (see section *Stages*) a public method `$on_<stage>()` can be defined. The evaluation context (a [ContextTorch](#)) can be accessed via `self$ctx`, which contains the current state of the training loop. This context is assigned at the beginning of the training loop and removed afterwards. Different stages of a callback can communicate with each other by assigning values to `$self`.

*State*: To be able to store information in the `$model` slot of a [LearnerTorch](#), callbacks support a state API. You can overload the `$state_dict()` public method to define what will be stored in `learner$model$callbacks$<id>` after training finishes. This then also requires to implement a `$load_state_dict(state_dict)` method that defines how to load a previously saved callback state into a different callback. Note that the `$state_dict()` should not include the parameter values that were used to initialize the callback.

For creating custom callbacks, the function `torch_callback()` is recommended, which creates a `CallbackSet` and then wraps it in a [TorchCallback](#). To create a `CallbackSet` the convenience function `callback_set()` can be used. These functions perform checks such as that the stages are not accidentally misspelled.

## Stages

- `begin` :: Run before the training loop begins.
- `epoch_begin` :: Run he beginning of each epoch.
- `batch_begin` :: Run before the forward call.
- `after_backward` :: Run after the backward call.
- `batch_end` :: Run after the optimizer step.
- `batch_valid_begin` :: Run before the forward call in the validation loop.
- `batch_valid_end` :: Run after the forward call in the validation loop.
- `valid_end` :: Run at the end of validation.
- `epoch_end` :: Run at the end of each epoch.
- `end` :: Run after last epoch.
- `exit` :: Run at last, using `on.exit()`.

## Terminate Training

If training is to be stopped, it is possible to set the field `$terminate` of [ContextTorch](#). At the end of every epoch this field is checked and if it is TRUE, training stops. This can for example be used to implement custom early stopping.

## Public fields

`ctx` ([ContextTorch](#) or `NULL`)

The evaluation context for the callback. This field should always be `NULL` except during the `$train()` call of the torch learner.

## Active bindings

`stages` (character())  
The active stages of this callback set.

## Methods

### Public methods:

- `CallbackSet$print()`
- `CallbackSet$state_dict()`
- `CallbackSet$load_state_dict()`
- `CallbackSet$clone()`

**Method** `print()`: Prints the object.

*Usage:*

`CallbackSet$print(...)`

*Arguments:*

`...` (any)  
Currently unused.

**Method** `state_dict()`: Returns information that is kept in the the `LearnerTorch`'s state after training. This information should be loadable into the callback using `$load_state_dict()` to be able to continue training. This returns NULL by default.

*Usage:*

`CallbackSet$state_dict()`

**Method** `load_state_dict()`: Loads the state dict into the callback to continue training.

*Usage:*

`CallbackSet$load_state_dict(state_dict)`

*Arguments:*

`state_dict` (any)  
The state dict as retrieved via `$state_dict()`.

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

`CallbackSet$clone(deep = FALSE)`

*Arguments:*

`deep` Whether to make a deep clone.

## See Also

Other Callback: `TorchCallback`, `as_torch_callback()`, `as_torch_callbacks()`, `callback_set()`, `mlr3torch_callbacks`, `mlr_callback_set.checkpoint`, `mlr_callback_set.progress`, `mlr_callback_set.tb`, `mlr_callback_set.unfreeze`, `mlr_context_torch`, `t_clbk()`, `torch_callback()`

---

`mlr_callback_set.checkpoint`  
*Checkpoint Callback*

---

## Description

Saves the optimizer and network states during training. The final network and optimizer are always stored.

## Details

Saving the learner itself in the callback with a trained model is impossible, as the model slot is set *after* the last callback step is executed.

## Super class

`mlr3torch::CallbackSet` -> `CallbackSetCheckpoint`

## Methods

### Public methods:

- `CallbackSetCheckpoint$new()`
- `CallbackSetCheckpoint$on_epoch_end()`
- `CallbackSetCheckpoint$on_batch_end()`
- `CallbackSetCheckpoint$on_exit()`
- `CallbackSetCheckpoint$clone()`

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

`CallbackSetCheckpoint$new(path, freq, freq_type = "epoch")`

*Arguments:*

`path` (`character(1)`)

The path to a folder where the models are saved.

`freq` (`integer(1)`)

The frequency how often the model is saved. Frequency is either per step or epoch, which can be configured through the `freq_type` parameter.

`freq_type` (`character(1)`)

Can be either "epoch" (default) or "step".

**Method** `on_epoch_end()`: Saves the network and optimizer state dict. Does nothing if `freq_type` or `freq` are not met.

*Usage:*

`CallbackSetCheckpoint$on_epoch_end()`

**Method** `on_batch_end()`: Saves the selected objects defined in `save`. Does nothing if `freq_type` or `freq` are not met.

*Usage:*

```
CallbackSetCheckpoint$on_batch_end()
```

**Method** `on_exit()`: Saves the learner.

*Usage:*

```
CallbackSetCheckpoint$on_exit()
```

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

```
CallbackSetCheckpoint$clone(deep = FALSE)
```

*Arguments:*

`deep` Whether to make a deep clone.

## See Also

Other Callback: [TorchCallback](#), [as\\_torch\\_callback\(\)](#), [as\\_torch\\_callbacks\(\)](#), [callback\\_set\(\)](#), [mlr3torch\\_callbacks](#), [mlr\\_callback\\_set](#), [mlr\\_callback\\_set.progress](#), [mlr\\_callback\\_set.tb](#), [mlr\\_callback\\_set.unfreeze](#), [mlr\\_context\\_torch](#), [t\\_clbk\(\)](#), [torch\\_callback\(\)](#)

## Examples

```
cb = t_clbk("checkpoint", freq = 1)
task = tsk("iris")

pth = tempfile()
learner = lrn("classif.mlp", epochs = 3, batch_size = 1, callbacks = cb)
learner$param_set$set_values(cb.checkpoint.path = pth)

learner$train(task)

list.files(pth)
```

---

### mlr\_callback\_set.history

*History Callback*

---

## Description

Saves the training and validation history during training. The history is saved as a data.table where the validation measures are prefixed with "valid." and the training measures are prefixed with "train.".

## Super class

[mlr3torch::CallbackSet](#) -> [CallbackSetHistory](#)

## Methods

### Public methods:

- `CallbackSetHistory$on_begin()`
- `CallbackSetHistory$state_dict()`
- `CallbackSetHistory$load_state_dict()`
- `CallbackSetHistory$on_before_valid()`
- `CallbackSetHistory$on_epoch_end()`
- `CallbackSetHistory$clone()`

**Method** `on_begin()`: Initializes lists where the train and validation metrics are stored.

*Usage:*

```
CallbackSetHistory$on_begin()
```

**Method** `state_dict()`: Converts the lists to data.tables.

*Usage:*

```
CallbackSetHistory$state_dict()
```

**Method** `load_state_dict()`: Sets the field `$train` and `$valid` to those contained in the state dict.

*Usage:*

```
CallbackSetHistory$load_state_dict(state_dict)
```

*Arguments:*

`state_dict (callback_state_history)`

The state dict as retrieved via `$state_dict()`.

**Method** `on_before_valid()`: Add the latest training scores to the history.

*Usage:*

```
CallbackSetHistory$on_before_valid()
```

**Method** `on_epoch_end()`: Add the latest validation scores to the history.

*Usage:*

```
CallbackSetHistory$on_epoch_end()
```

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

```
CallbackSetHistory$clone(deep = FALSE)
```

*Arguments:*

`deep` Whether to make a deep clone.

## Examples

```
cb = t_clbk("history")
task = tsk("iris")

learner = lrn("classif.mlp", epochs = 3, batch_size = 1,
  callbacks = t_clbk("history"), validate = 0.3)
learner$param_set$set_values(
  measures_train = msrs(c("classif.acc", "classif.ce")),
  measures_valid = msr("classif.ce")
)
learner$train(task)

print(learner$model$callbacks$history)
```

---

**mlr\_callback\_set.lr\_scheduler**  
*Learning Rate Scheduling Callback*

---

## Description

Changes the learning rate based on the schedule specified by a `torch:::lr_scheduler`.

As of this writing, the following are available:

- `torch:::lr_cosine_annealing()`
- `torch:::lr_lambda()`
- `torch:::lr_multiplicative()`
- `torch:::lr_one_cycle()` (where the default values for `epochs` and `steps_per_epoch` are the number of training epochs and the number of batches per epoch)
- `torch:::lr_reduce_on_plateau()`
- `torch:::lr_step()`
- Custom schedulers defined with `torch:::lr_scheduler()`.

## Super class

`mlr3torch::CallbackSet` -> `CallbackSetLRScheduler`

## Public fields

`scheduler_fn (lr_scheduler_generator)`  
 The `torch` function that creates a learning rate scheduler

`scheduler (LRScheduler)`  
 The learning rate scheduler wrapped by this callback

## Methods

### Public methods:

- `CallbackSetLRScheduler$new()`
- `CallbackSetLRScheduler$on_begin()`
- `CallbackSetLRScheduler$clone()`

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

```
CallbackSetLRScheduler$new(.scheduler, step_on_epoch, ...)
```

*Arguments:*

`.scheduler` (`lr_scheduler_generator`)  
The torch scheduler generator (e.g. `torch::lr_step`).

`step_on_epoch` (`logical(1)`)  
Whether the scheduler steps after every epoch (otherwise every batch).

`...` (any)  
The scheduler-specific initialization arguments.

**Method** `on_begin()`: Creates the scheduler using the optimizer from the context

*Usage:*

```
CallbackSetLRScheduler$on_begin()
```

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

```
CallbackSetLRScheduler$clone(deep = FALSE)
```

*Arguments:*

`deep` Whether to make a deep clone.

`mlr_callback_set.lr_scheduler_one_cycle`  
*OneCycle Learning Rate Scheduling Callback*

## Description

Changes the learning rate based on the 1cycle learning rate policy.

Wraps `torch::lr_one_cycle()`, where the default values for `epochs` and `steps_per_epoch` are the number of training epochs and the number of batches per epoch.

## Super classes

`mlr3torch::CallbackSet` -> `mlr3torch::CallbackSetLRScheduler` -> `CallbackSetLRSchedulerOneCycle`

## Methods

### Public methods:

- `CallbackSetLRSchedulerOneCycle$new()`
- `CallbackSetLRSchedulerOneCycle$on_begin()`
- `CallbackSetLRSchedulerOneCycle$clone()`

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

`CallbackSetLRSchedulerOneCycle$new(...)`

*Arguments:*

... (any)

The scheduler-specific initialization arguments.

**Method** `on_begin()`: Creates the scheduler using the optimizer from the context

*Usage:*

`CallbackSetLRSchedulerOneCycle$on_begin()`

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

`CallbackSetLRSchedulerOneCycle$clone(deep = FALSE)`

*Arguments:*

deep Whether to make a deep clone.

`mlr_callback_set.lr_scheduler_reduce_on_plateau`

*Reduce On Plateau Learning Rate Scheduler*

## Description

Reduces the learning rate when the first validation metric stops improving for patience epochs.

Wraps `torch::lr_reduce_on_plateau()`

## Super classes

`mlr3torch::CallbackSet -> mlr3torch::CallbackSetLRScheduler -> CallbackSetLRSchedulerReduceOnPlateau`

## Methods

### Public methods:

- `CallbackSetLRSchedulerReduceOnPlateau$new()`
- `CallbackSetLRSchedulerReduceOnPlateau$clone()`

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

```
CallbackSetLRSchedulerReduceOnPlateau$new(...)
```

*Arguments:*

... (any)

The scheduler-specific initialization arguments.

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

```
CallbackSetLRSchedulerReduceOnPlateau$clone(deep = FALSE)
```

*Arguments:*

deep Whether to make a deep clone.

---

**mlr\_callback\_set.progress**  
*Progress Callback*

---

## Description

Prints a progress bar and the metrics for training and validation.

## Super class

`mlr3torch::CallbackSet` -> `CallbackSetProgress`

## Methods

### Public methods:

- `CallbackSetProgress$new()`
- `CallbackSetProgress$on_epoch_begin()`
- `CallbackSetProgress$on_batch_end()`
- `CallbackSetProgress$on_before_valid()`
- `CallbackSetProgress$on_batch_valid_end()`
- `CallbackSetProgress$on_epoch_end()`
- `CallbackSetProgress$on_end()`
- `CallbackSetProgress$clone()`

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

```
CallbackSetProgress$new(digits = 2)
```

*Arguments:*

`digits` `integer(1)`

The number of digits to print for the measures.

**Method** `on_epoch_begin()`: Initializes the progress bar for training.

*Usage:*

`CallbackSetProgress$on_epoch_begin()`

**Method** `on_batch_end()`: Increments the training progress bar.

*Usage:*

`CallbackSetProgress$on_batch_end()`

**Method** `on_before_valid()`: Creates the progress bar for validation.

*Usage:*

`CallbackSetProgress$on_before_valid()`

**Method** `on_batch_valid_end()`: Increments the validation progress bar.

*Usage:*

`CallbackSetProgress$on_batch_valid_end()`

**Method** `on_epoch_end()`: Prints a summary of the training and validation process.

*Usage:*

`CallbackSetProgress$on_epoch_end()`

**Method** `on_end()`: Prints the time at the end of training.

*Usage:*

`CallbackSetProgress$on_end()`

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

`CallbackSetProgress$clone(deep = FALSE)`

*Arguments:*

`deep` Whether to make a deep clone.

## See Also

Other Callback: [TorchCallback](#), [as\\_torch\\_callback\(\)](#), [as\\_torch\\_callbacks\(\)](#), [callback\\_set\(\)](#), [mlr3torch\\_callbacks](#), [mlr\\_callback\\_set](#), [mlr\\_callback\\_set.checkpoint](#), [mlr\\_callback\\_set.tb](#), [mlr\\_callback\\_set.unfreeze](#), [mlr\\_context\\_torch](#), [t\\_clbk\(\)](#), [torch\\_callback\(\)](#)

## Examples

```
task = tsk("iris")

learner = lrn("classif.mlp", epochs = 5, batch_size = 1,
  callbacks = t_clbk("progress"), validate = 0.3)
learner$param_set$set_values(
  measures_train = msrs(c("classif.acc", "classif.ce")),
  measures_valid = msr("classif.ce")
)
learner$train(task)
```

---

**mlr\_callback\_set.tb** *TensorBoard Logging Callback*

---

**Description**

Logs training loss, training measures, and validation measures as events. To view them, use TensorBoard with `tensorflow::tensorflow()` (requires `tensorflow`) or the CLI.

**Details**

Logs events at most every epoch.

**Super class**

`mlr3torch::CallbackSet` -> `CallbackSetTB`

**Methods****Public methods:**

- `CallbackSetTB$new()`
- `CallbackSetTB$on_epoch_end()`
- `CallbackSetTB$clone()`

**Method** `new()`: Creates a new instance of this `R6` class.

*Usage:*

`CallbackSetTB$new(path, log_train_loss)`

*Arguments:*

`path` (`character(1)`)

The path to a folder where the events are logged. Point TensorBoard to this folder to view them.

`log_train_loss` (`logical(1)`)

Whether we log the training loss.

**Method** `on_epoch_end()`: Logs the training loss, training measures, and validation measures as TensorBoard events.

*Usage:*

`CallbackSetTB$on_epoch_end()`

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

`CallbackSetTB$clone(deep = FALSE)`

*Arguments:*

`deep` Whether to make a deep clone.

**See Also**

Other Callback: [TorchCallback](#), [as\\_torch\\_callback\(\)](#), [as\\_torch\\_callbacks\(\)](#), [callback\\_set\(\)](#), [mlr3torch\\_callbacks](#), [mlr\\_callback\\_set](#), [mlr\\_callback\\_set.checkpoint](#), [mlr\\_callback\\_set.progress](#), [mlr\\_callback\\_set.unfreeze](#), [mlr\\_context\\_torch](#), [t\\_clbk\(\)](#), [torch\\_callback\(\)](#)

---

**mlr\_callback\_set.unfreeze**

*Unfreezing Weights Callback*

---

**Description**

Unfreeze some weights (parameters of the network) after some number of steps or epochs.

**Super class**

[mlr3torch::CallbackSet](#) -> [CallbackSetUnfreeze](#)

**Methods****Public methods:**

- [CallbackSetUnfreeze\\$new\(\)](#)
- [CallbackSetUnfreeze\\$on\\_begin\(\)](#)
- [CallbackSetUnfreeze\\$on\\_epoch\\_begin\(\)](#)
- [CallbackSetUnfreeze\\$on\\_batch\\_begin\(\)](#)
- [CallbackSetUnfreeze\\$clone\(\)](#)

**Method** [new\(\)](#): Creates a new instance of this [R6](#) class.

*Usage:*

`CallbackSetUnfreeze$new(starting_weights, unfreeze)`

*Arguments:*

`starting_weights` (Select)

A Select denoting the weights that are trainable from the start.

`unfreeze` (data.table)

A data.table with a column `weights` (a list column of Selects) and a column `epoch` or `batch`. The selector indicates which parameters to unfreeze, while the `epoch` or `batch` column indicates when to do so.

**Method** [on\\_begin\(\)](#): Sets the starting weights

*Usage:*

`CallbackSetUnfreeze$on_begin()`

**Method** [on\\_epoch\\_begin\(\)](#): Unfreezes weights if the training is at the correct epoch

*Usage:*

`CallbackSetUnfreeze$on_epoch_begin()`

**Method** `on_batch_begin()`: Unfreezes weights if the training is at the correct batch

*Usage:*

`CallbackSetUnfreeze$on_batch_begin()`

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

`CallbackSetUnfreeze$clone(deep = FALSE)`

*Arguments:*

`deep` Whether to make a deep clone.

## See Also

Other Callback: `TorchCallback`, `as_torch_callback()`, `as_torch_callbacks()`, `callback_set()`, `mlr3torch_callbacks`, `mlr_callback_set`, `mlr_callback_set.checkpoint`, `mlr_callback_set.progress`, `mlr_callback_set.tb`, `mlr_context_torch`, `t_clbk()`, `torch_callback()`

## Examples

```
task = tsk("iris")
cb = t_clbk("unfreeze")
mlp = lrn("classif.mlp", callbacks = cb,
  cb.unfreeze.starting_weights = select_invert(
    select_name(c("0.weight", "3.weight", "6.weight", "6.bias"))
  ),
  cb.unfreeze.unfreeze = data.table(
    epoch = c(2, 5),
    weights = list(select_name("0.weight"), select_name(c("3.weight", "6.weight"))))
  ),
  epochs = 6, batch_size = 150, neurons = c(1, 1, 1)
)
mlp$train(task)
```

## Description

Context for training a torch learner. This is the - mostly read-only - information callbacks have access to through the argument `ctx`. For more information on callbacks, see [CallbackSet](#).

## Public fields

learner ([Learner](#))  
The torch learner.

task\_train ([Task](#))  
The training task.

task\_valid ([Task](#) or NULL)  
The validation task.

loader\_train ([torch::dataloader](#))  
The data loader for training.

loader\_valid ([torch::dataloader](#))  
The data loader for validation.

measures\_train (list() of [Measures](#))  
Measures used for training.

measures\_valid (list() of [Measures](#))  
Measures used for validation.

network ([torch::nn\\_module](#))  
The torch network.

optimizer ([torch::optimizer](#))  
The optimizer.

loss\_fn ([torch::nn\\_module](#))  
The loss function.

total\_epochs (integer(1))  
The total number of epochs the learner is trained for.

last\_scores\_train (named list() or NULL)  
The scores from the last training batch. Names are the ids of the training measures. If [LearnerTorch](#) sets eval\_freq different from 1, this is NULL in all epochs that don't evaluate the model.

last\_scores\_valid (list())  
The scores from the last validation batch. Names are the ids of the validation measures. If [LearnerTorch](#) sets eval\_freq different from 1, this is NULL in all epochs that don't evaluate the model.

last\_loss (numeric(1))  
The loss from the last trainings batch.

y\_hat (torch\_tensor)  
The model's prediction for the current batch.

epoch (integer(1))  
The current epoch.

step (integer(1))  
The current iteration.

prediction\_encoder (function())  
The learner's prediction encoder.

batch (named list() of torch\_tensors)  
The current batch.

```

terminate (logical(1))
  If this field is set to TRUE at the end of an epoch, training stops.
device (torch::torch_device)
  The device.

```

## Methods

### Public methods:

- [ContextTorch\\$new\(\)](#)
- [ContextTorch\\$clone\(\)](#)

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

```
ContextTorch$new(
  learner,
  task_train,
  task_valid = NULL,
  loader_train,
  loader_valid = NULL,
  measures_train = NULL,
  measures_valid = NULL,
  network,
  optimizer,
  loss_fn,
  total_epochs,
  prediction_encoder,
  eval_freq = 1L,
  device
)
```

*Arguments:*

`learner` ([Learner](#))  
 The torch learner.

`task_train` ([Task](#))  
 The training task.

`task_valid` ([Task](#) or `NULL`)  
 The validation task.

`loader_train` ([torch::dataloader](#))  
 The data loader for training.

`loader_valid` ([torch::dataloader](#) or `NULL`)  
 The data loader for validation.

`measures_train` (`list()` of [Measures](#) or `NULL`)  
 Measures used for training. Default is `NULL`.

`measures_valid` (`list()` of [Measures](#) or `NULL`)  
 Measures used for validation.

`network` ([torch::nn\\_module](#))  
 The torch network.

```

optimizer (torch::optimizer)
  The optimizer.

loss_fn (torch::nn::Module)
  The loss function.

total_epochs (integer(1))
  The total number of epochs the learner is trained for.

prediction_encoder (function())
  The learner's prediction encoder. See section Inheriting of LearnerTorch.

eval_freq (integer(1))
  The evaluation frequency.

device (character(1))
  The device.

```

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

```
ContextTorch$clone(deep = FALSE)
```

*Arguments:*

`deep` Whether to make a deep clone.

## See Also

Other Callback: [TorchCallback](#), [as\\_torch\\_callback\(\)](#), [as\\_torch\\_callbacks\(\)](#), [callback\\_set\(\)](#), [mlr3torch\\_callbacks](#), [mlr\\_callback\\_set](#), [mlr\\_callback\\_set.checkpoint](#), [mlr\\_callback\\_set.progress](#), [mlr\\_callback\\_set.tb](#), [mlr\\_callback\\_set.unfreeze](#), [t\\_clbk\(\)](#), [torch\\_callback\(\)](#)

---

`mlr_learners.ft_transformer`  
*FT-Transformer*

---

## Description

Feature-Tokenizer Transformer for tabular data that can either work on [lazy\\_tensor](#) inputs or on standard tabular features.

Some differences from the paper implementation: no attention compression, no option to have prenormalization in the first layer.

If training is unstable, consider a combination of standardizing features (e.g. using `po("scale")`), using an adaptive optimizer (e.g. Adam), reducing the learning rate, and using a learning rate scheduler (see [CallbackSetLRScheduler](#) for options).

## Dictionary

This [Learner](#) can be instantiated using the sugar function `lrn()`:

```

lrn("classif.ft_transformer", ...)
lrn("regr.ft_transformer", ...)

```

## Properties

- Supported task types: 'classif', 'regr'
- Predict Types:
  - classif: 'response', 'prob'
  - regr: 'response'
- Feature Types: "logical", "integer", "numeric", "factor", "ordered", "lazy\_tensor"
- Required Packages: **mlr3**, **mlr3torch**, **torch**

## Parameters

Parameters from [LearnerTorch](#) and [PipeOpTorchFTTransformerBlock](#), as well as:

- `n_blocks` :: `integer(1)`  
The number of transformer blocks.
- `d_token` :: `integer(1)`  
The dimension of the embedding.
- `cardinalities` :: `integer(1)`  
The number of categories for each categorical feature. This only needs to be specified when working with `lazy_tensor` inputs.
- `init_token` :: `character(1)`  
The initialization method for the embedding weights. Either "uniform" or "normal". "Uniform" by default.
- `ingress_tokens` :: named `list()` or `NULL`  
A list of `TorchIngressTokens`. Only required when using lazy tensor features. The names are either "num.input" or "categ.input", and the values are lazy tensor ingress tokens constructed by, e.g. `ingress_ltnsr(<num_feat_name>)`.

## Super classes

[mlr3::Learner](#) -> [mlr3torch::LearnerTorch](#) -> [LearnerTorchFTTransformer](#)

## Methods

### Public methods:

- `LearnerTorchFTTransformer$new()`
- `LearnerTorchFTTransformer$clone()`

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

```
LearnerTorchFTTransformer$new(
  task_type,
  optimizer = NULL,
  loss = NULL,
  callbacks = list()
)
```

*Arguments:*

**task\_type** (character(1))  
 The task type, either "classif" or "regr".

**optimizer** ([TorchOptimizer](#))  
 The optimizer to use for training. Per default, *adam* is used.

**loss** ([TorchLoss](#))  
 The loss used to train the network. Per default, *mse* is used for regression and *cross\_entropy* for classification.

**callbacks** (list() of [TorchCallbacks](#))  
 The callbacks. Must have unique ids.

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

```
LearnerTorchFTTransformer$clone(deep = FALSE)
```

*Arguments:*

**deep** Whether to make a deep clone.

## References

Gorishniy Y, Rubachev I, Khrulkov V, Babenko A (2021). “Revisiting Deep Learning for Tabular Data.” *arXiv*, **2106.11959**.

## See Also

Other Learner: [mlr\\_learners.mlp](#), [mlr\\_learners.module](#), [mlr\\_learners.tab\\_resnet](#), [mlr\\_learners.torch\\_feature](#), [mlr\\_learners\\_torch](#), [mlr\\_learners\\_torch\\_image](#), [mlr\\_learners\\_torch\\_model](#)

## Examples

```
# Define the Learner and set parameter values
learner = lrn("classif.ft_transformer")
learner$param_set$set_values(
  epochs = 1, batch_size = 16, device = "cpu",
  n_blocks = 2, d_token = 32, ffn_d_hidden_multiplier = 4/3
)

# Define a Task
task = tsk("iris")

# Create train and test set
ids = partition(task)

# Train the learner on the training ids
learner$train(task, row_ids = ids$train)

# Make predictions for the test rows
predictions = learner$predict(task, row_ids = ids$test)

# Score the predictions
```

```
predictions$score()
```

---

|                               |                               |
|-------------------------------|-------------------------------|
| <code>mlr_learners.mlp</code> | <i>Multi Layer Perceptron</i> |
|-------------------------------|-------------------------------|

---

## Description

Fully connected feed forward network with dropout after each activation function. The features can either be a single `lazy_tensor` or one or more numeric columns (but not both).

## Dictionary

This `Learner` can be instantiated using the sugar function `lrn()`:

```
lrn("classif.mlp", ...)
lrn("regr.mlp", ...)
```

## Properties

- Supported task types: 'classif', 'regr'
- Predict Types:
  - classif: 'response', 'prob'
  - regr: 'response'
- Feature Types: "integer", "numeric", "lazy\_tensor"
- Required Packages: **mlr3**, **mlr3torch**, **torch**

## Parameters

Parameters from `LearnerTorch`, as well as:

- `activation` :: `[nn_module]`  
The activation function. Is initialized to `nn_relu`.
- `activation_args` :: named `list()`  
A named list with initialization arguments for the activation function. This is initialized to an empty list.
- `neurons` :: `integer()`  
The number of neurons per hidden layer. By default there is no hidden layer. Setting this to `c(10, 20)` would have the first hidden layer with 10 neurons and the second with 20.
- `n_layers` :: `integer()`  
The number of layers. This parameter must only be set when `neurons` has length 1.
- `p` :: `numeric(1)`  
The dropout probability. Is initialized to 0.5.
- `shape` :: `integer()` or `NULL`  
The input shape of length 2, e.g. `c(NA, 5)`. Only needs to be present when there is a lazy tensor input with unknown shape (`NULL`). Otherwise the input shape is inferred from the number of numeric features.

## Super classes

`mlr3::Learner` -> `mlr3torch::LearnerTorch` -> `LearnerTorchMLP`

## Methods

### Public methods:

- `LearnerTorchMLP$new()`
- `LearnerTorchMLP$clone()`

**Method** `new()`: Creates a new instance of this `R6` class.

*Usage:*

```
LearnerTorchMLP$new(
  task_type,
  optimizer = NULL,
  loss = NULL,
  callbacks = list()
)
```

*Arguments:*

`task_type` (character(1))

The task type, either "classif" or "regr".

`optimizer` (`TorchOptimizer`)

The optimizer to use for training. Per default, `adam` is used.

`loss` (`TorchLoss`)

The loss used to train the network. Per default, `mse` is used for regression and `cross_entropy` for classification.

`callbacks` (list() of `TorchCallbacks`)

The callbacks. Must have unique ids.

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

```
LearnerTorchMLP$clone(deep = FALSE)
```

*Arguments:*

`deep` Whether to make a deep clone.

## References

Gorishniy Y, Rubachev I, Khrulkov V, Babenko A (2021). “Revisiting Deep Learning for Tabular Data.” *arXiv*, **2106.11959**.

## See Also

Other Learner: `mlr_learners.ft_transformer`, `mlr_learners.module`, `mlr_learners.tab_resnet`,  
`mlr_learners.torch_featureless`, `mlr_learners_torch`, `mlr_learners_torch_image`, `mlr_learners_torch_model`

## Examples

```

# Define the Learner and set parameter values
learner = lrn("classif.mlp")
learner$param_set$set_values(
  epochs = 1, batch_size = 16, device = "cpu",
  neurons = 10
)

# Define a Task
task = tsk("iris")

# Create train and test set
ids = partition(task)

# Train the learner on the training ids
learner$train(task, row_ids = ids$train)

# Make predictions for the test rows
predictions = learner$predict(task, row_ids = ids$test)

# Score the predictions
predictions$score()

```

---

mlr\_learners.module    *Learner Torch Module*

---

## Description

Create a torch learner from a torch module.

## Dictionary

This [Learner](#) can be instantiated using the sugar function [lrn\(\)](#):

```
lrn("classif.module", ...)
lrn("regr.module", ...)
```

## Properties

- Supported task types: 'classif', 'regr'
- Predict Types:
  - classif: 'response', 'prob'
  - regr: 'response'
- Feature Types: "logical", "integer", "numeric", "character", "factor", "ordered", "POSIXct", "Date", "lazy\_tensor"
- Required Packages: **mlr3**, **mlr3torch**, **torch**

## Super classes

[mlr3::Learner](#) -> [mlr3torch::LearnerTorch](#) -> [LearnerTorchModule](#)

## Methods

### Public methods:

- [LearnerTorchModule\\$new\(\)](#)
- [LearnerTorchModule\\$clone\(\)](#)

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

```
LearnerTorchModule$new(
  module_generator = NULL,
  param_set = NULL,
  ingress_tokens = NULL,
  task_type,
  properties = NULL,
  optimizer = NULL,
  loss = NULL,
  callbacks = list(),
  packages = character(0),
  feature_types = NULL,
  predict_types = NULL
)
```

*Arguments:*

`module_generator` (function or `nn_module_generator`)

A `nn_module_generator` or function returning an `nn_module`. Both must take as argument the task for which to construct the network. Other arguments to its initialize method can be provided as parameters.

`param_set` (NULL or [ParamSet](#))

If provided, contains the parameters for the `module_generator`. If NULL, parameters will be inferred from the `module_generator`.

`ingress_tokens` (list of [TorchIngressToken](#)())

A list with ingress tokens that defines how the dataset will be defined. The names must correspond to the arguments of the network's forward method. For numeric, categorical, and lazy tensor features, you can use `ingress_num()`, `ingress_categ()`, and `ingress_ltnsr()` to create them.

`task_type` (character(1))

The task type, either "classif" or "regr".

`task_type` (character(1))

The task type.

`properties` (NULL or character())

The properties of the learner. Defaults to all available properties for the given task type.

`optimizer` ([TorchOptimizer](#))

The optimizer to use for training. Per default, `adam` is used.

```

loss (TorchLoss)
  The loss used to train the network. Per default, mse is used for regression and cross_entropy for classification.

callbacks (list() of TorchCallbacks)
  The callbacks. Must have unique ids.

packages (character())
  The R packages this object depends on.

feature_types (NULL or character())
  The feature types. Defaults to all available feature types.

predict_types (character())
  The predict types. See mlr\_reflections\$learner\_predict\_types for available values.

```

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

```
LearnerTorchModule$clone(deep = FALSE)
```

*Arguments:*

```
deep Whether to make a deep clone.
```

## See Also

Other Learner: [mlr\\_learners.ft\\_transformer](#), [mlr\\_learners.mlp](#), [mlr\\_learners.tab\\_resnet](#), [mlr\\_learners.torch\\_featureless](#), [mlr\\_learners\\_torch](#), [mlr\\_learners\\_torch\\_image](#), [mlr\\_learners\\_torch\\_model](#)

Other Learner: [mlr\\_learners.ft\\_transformer](#), [mlr\\_learners.mlp](#), [mlr\\_learners.tab\\_resnet](#), [mlr\\_learners.torch\\_featureless](#), [mlr\\_learners\\_torch](#), [mlr\\_learners\\_torch\\_image](#), [mlr\\_learners\\_torch\\_model](#)

## Examples

```

nn_one_layer = nn_module("nn_one_layer",
  initialize = function(task, size_hidden) {
    self$first = nn_linear(task$n_features, size_hidden)
    self$second = nn_linear(size_hidden, output_dim_for(task))
  },
  # argument x corresponds to the ingress token x
  forward = function(x) {
    x = self$first(x)
    x = nnf_relu(x)
    self$second(x)
  }
)
learner = lrn("classif.module",
  module_generator = nn_one_layer,
  ingress_tokens = list(x = ingress_num()),
  epochs = 10,
  size_hidden = 20,
  batch_size = 16
)
task = tsk("iris")
learner$train(task)
learner$network

```

---

**mlr\_learners.tab\_resnet**  
*Tabular ResNet*

---

## Description

Tabular resnet.

## Dictionary

This [Learner](#) can be instantiated using the sugar function [lrn\(\)](#):

```
lrn("classif.tab_resnet", ...)
lrn("regr.tab_resnet", ...)
```

## Properties

- Supported task types: 'classif', 'regr'
- Predict Types:
  - classif: 'response', 'prob'
  - regr: 'response'
- Feature Types: "integer", "numeric", "lazy\_tensor"
- Required Packages: **mlr3**, **mlr3torch**, **torch**

## Parameters

Parameters from [LearnerTorch](#), as well as:

- **n\_blocks** :: `integer(1)`  
 The number of blocks.
- **d\_block** :: `integer(1)`  
 The input and output dimension of a block.
- **d\_hidden** :: `integer(1)`  
 The latent dimension of a block.
- **d\_hidden\_multiplier** :: `numeric(1)`  
 Alternative way to specify the latent dimension as `d_block * d_hidden_multiplier`.
- **dropout1** :: `numeric(1)`  
 First dropout ratio.
- **dropout2** :: `numeric(1)`  
 Second dropout ratio.
- **shape** :: `integer()` or `NULL`  
 Shape of the input tensor. Only needs to be provided if the input is a lazy tensor with unknown shape.

## Super classes

[mlr3::Learner](#) -> [mlr3torch::LearnerTorch](#) -> LearnerTorchTabResNet

## Methods

### Public methods:

- [LearnerTorchTabResNet\\$new\(\)](#)
- [LearnerTorchTabResNet\\$clone\(\)](#)

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

```
LearnerTorchTabResNet$new(
  task_type,
  optimizer = NULL,
  loss = NULL,
  callbacks = list()
)
```

*Arguments:*

`task_type` (character(1))

The task type, either "classif" or "regr".

`optimizer` ([TorchOptimizer](#))

The optimizer to use for training. Per default, *adam* is used.

`loss` ([TorchLoss](#))

The loss used to train the network. Per default, *mse* is used for regression and *cross\_entropy* for classification.

`callbacks` (list() of [TorchCallbacks](#))

The callbacks. Must have unique ids.

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

```
LearnerTorchTabResNet$clone(deep = FALSE)
```

*Arguments:*

`deep` Whether to make a deep clone.

## References

Gorishniy Y, Rubachev I, Khrulkov V, Babenko A (2021). “Revisiting Deep Learning for Tabular Data.” *arXiv*, **2106.11959**.

## See Also

Other Learner: [mlr\\_learners.ft\\_transformer](#), [mlr\\_learners.mlp](#), [mlr\\_learners.module](#), [mlr\\_learners.torch\\_fea](#), [mlr\\_learners\\_torch](#), [mlr\\_learners\\_torch\\_image](#), [mlr\\_learners\\_torch\\_model](#)

## Examples

```

# Define the Learner and set parameter values
learner = lrn("classif.tab_resnet")
learner$param_set$set_values(
  epochs = 1, batch_size = 16, device = "cpu",
  n_blocks = 2, d_block = 10, d_hidden = 20, dropout1 = 0.3, dropout2 = 0.3
)

# Define a Task
task = tsk("iris")

# Create train and test set
ids = partition(task)

# Train the learner on the training ids
learner$train(task, row_ids = ids$train)

# Make predictions for the test rows
predictions = learner$predict(task, row_ids = ids$test)

# Score the predictions
predictions$score()

```

---

mlr\_learners.torchvision

*AlexNet Image Classifier*

---

## Description

Classic image classification networks from torchvision.

## Parameters

Parameters from [LearnerTorchImage](#) and

- `pretrained` :: `logical(1)`  
Whether to use the pretrained model. The final linear layer will be replaced with a new `nn_linear` with the number of classes inferred from the [Task](#).

## Properties

- Supported task types: `"classif"`
- Predict Types: `"response"` and `"prob"`
- Feature Types: `"lazy_tensor"`
- Required packages: `"mlr3torch"`, `"torch"`, `"torchvision"`

## Super classes

`mlr3::Learner` -> `mlr3torch::LearnerTorch` -> `mlr3torch::LearnerTorchImage` -> `LearnerTorchVision`

## Methods

### Public methods:

- `LearnerTorchVision$new()`
- `LearnerTorchVision$clone()`

**Method** `new()`: Creates a new instance of this `R6` class.

*Usage:*

```
LearnerTorchVision$new(
  name,
  module_generator,
  label,
  optimizer = NULL,
  loss = NULL,
  callbacks = list(),
  jittable = FALSE
)
```

*Arguments:*

`name` (character(1))

The name of the network.

`module_generator` (function(pretrained, num\_classes))

Function that generates the network.

`label` (character(1))

The label of the network.

`optimizer` (`TorchOptimizer`)

The optimizer to use for training. Per default, `adam` is used.

`loss` (`TorchLoss`)

The loss used to train the network. Per default, `mse` is used for regression and `cross_entropy` for classification.

`callbacks` (list() of `TorchCallbacks`)

The callbacks. Must have unique ids.

`jittable` (logical(1))

Whether to use jitting.

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

```
LearnerTorchVision$clone(deep = FALSE)
```

*Arguments:*

`deep` Whether to make a deep clone.

## References

Krizhevsky, Alex, Sutskever, Ilya, Hinton, E. G (2017). “Imagenet classification with deep convolutional neural networks.” *Communications of the ACM*, **60**(6), 84–90. Sandler, Mark, Howard, Andrew, Zhu, Menglong, Zhmoginov, Andrey, Chen, Liang-Chieh (2018). “Mobilenetv2: Inverted residuals and linear bottlenecks.” In *Proceedings of the IEEE conference on computer vision and pattern recognition*, 4510–4520. He, Kaiming, Zhang, Xiangyu, Ren, Shaoqing, Sun, Jian (2016). “Deep residual learning for image recognition.” In *Proceedings of the IEEE conference on computer vision and pattern recognition*, 770–778. Simonyan, Karen, Zisserman, Andrew (2014). “Very deep convolutional networks for large-scale image recognition.” *arXiv preprint arXiv:1409.1556*.

---

**mlr\_learners.torch\_featureless**  
*Featureless Torch Learner*

---

## Description

Featureless torch learner. Output is a constant weight that is learned during training. For classification, this should (asymptotically) result in a majority class prediction when using the standard cross-entropy loss. For regression, this should result in the median for L1 loss and in the mean for L2 loss.

## Dictionary

This [Learner](#) can be instantiated using the sugar function [lrn\(\)](#):

```
lrn("classif.torch_featureless", ...)
lrn("regr.torch_featureless", ...)
```

## Properties

- Supported task types: 'classif', 'regr'
- Predict Types:
  - classif: 'response', 'prob'
  - regr: 'response'
- Feature Types: "logical", "integer", "numeric", "character", "factor", "ordered", "POSIXct", "Date", "lazy\_tensor"
- Required Packages: [mlr3](#), [mlr3torch](#), [torch](#)

## Parameters

Only those from [LearnerTorch](#).

## Super classes

```
mlr3::Learner -> mlr3torch::LearnerTorch -> LearnerTorchFeatureless
```

## Methods

### Public methods:

- `LearnerTorchFeatureless$new()`
- `LearnerTorchFeatureless$clone()`

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

```
LearnerTorchFeatureless$new(
  task_type,
  optimizer = NULL,
  loss = NULL,
  callbacks = list()
)
```

*Arguments:*

`task_type` (character(1))

The task type, either "classif" or "regr".

`optimizer` ([TorchOptimizer](#))

The optimizer to use for training. Per default, *adam* is used.

`loss` ([TorchLoss](#))

The loss used to train the network. Per default, *mse* is used for regression and *cross\_entropy* for classification.

`callbacks` (list() of [TorchCallbacks](#))

The callbacks. Must have unique ids.

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

```
LearnerTorchFeatureless$clone(deep = FALSE)
```

*Arguments:*

`deep` Whether to make a deep clone.

## See Also

Other Learner: [mlr\\_learners.ft\\_transformer](#), [mlr\\_learners.mlp](#), [mlr\\_learners.module](#), [mlr\\_learners.tab\\_resnet](#), [mlr\\_learners\\_torch](#), [mlr\\_learners\\_torch\\_image](#), [mlr\\_learners\\_torch\\_model](#)

## Examples

```
# Define the Learner and set parameter values
learner = lrn("classif.torch_featureless")
learner$param_set$set_values(
  epochs = 1, batch_size = 16, device = "cpu"
)

# Define a Task
task = tsk("iris")
```

```

# Create train and test set
ids = partition(task)

# Train the learner on the training ids
learner$train(task, row_ids = ids$train)

# Make predictions for the test rows
predictions = learner$predict(task, row_ids = ids$test)

# Score the predictions
predictions$score()

```

---

mlr\_learners\_torch      *Base Class for Torch Learners*

---

## Description

This base class provides the basic functionality for training and prediction of a neural network. All torch learners should inherit from this class.

## Validation

To specify the validation data, you can set the `$validate` field of the Learner, which can be set to:

- `NULL`: no validation
- `ratio`: only proportion  $1 - \text{ratio}$  of the task is used for training and `ratio` is used for validation.
- "test" means that the "test" task of a resampling is used and is not possible when calling `$train()` manually.
- "predefined": This will use the predefined `$internal_valid_task` of a [mlr3::Task](#).

This validation data can also be used for early stopping, see the description of the Learner's parameters.

## Saving a Learner

In order to save a LearnerTorch for later usage, it is necessary to call the `$marshal()` method on the Learner before writing it to disk, as the object will otherwise not be saved correctly. After loading a marshaled LearnerTorch into R again, you then need to call `$unmarshal()` to transform it into a useable state.

## Early Stopping and Internal Tuning

In order to prevent overfitting, the `LearnerTorch` class allows to use early stopping via the `patience` and `min_delta` parameters, see the Learner's parameters. When tuning a `LearnerTorch` it is also possible to combine the explicit tuning via `mlr3tuning` and the `LearnerTorch`'s internal tuning of the epochs via early stopping. To do so, you just need to include `epochs = to_tune(upper = <upper>, internal = TRUE)` in the search space, where `<upper>` is the maximally allowed number of epochs, and configure the early stopping.

## Network Head and Target Encoding

Torch learners are expected to have the following output:

- binary classification: `(batch_size, 1)`, representing the logits for the positive class.
- multiclass classification: `(batch_size, n_classes)`, representing the logits for all classes.
- regression: `(batch_size, 1)` representing the response prediction.

Furthermore, the target encoding is expected to be as follows:

- regression: The numeric target variable of a `TaskRegr` is encoded as a `torch_float` with shape `c(batch_size, 1)`.
- binary classification: The factor target variable of a `TaskClassif` is encoded as a `torch_float` with shape `(batch_size, 1)` where the positive class (`Task$positive`, which is also ensured to be the first factor level) is `1` and the negative class is `0`.
- multi-class classification: The factor target variable of a `TaskClassif` is a label-encoded `torch_long` with shape `(batch_size)` where the label-encoding goes from `1` to `n_classes`.

## Important Runtime Considerations

There are a few hyperparameters settings that can have a considerable impact on the runtime of the learner. These include:

- `device`: Use a GPU if possible.
- `num_threads`: Set this to the number of CPU cores available if training on CPU.
- `tensor_dataset`: Set this to `TRUE` (or "device" if on a GPU) if the dataset fits into memory.
- `batch_size`: Especially for very small models, choose a larger batch size.

Also, see the *Early Stopping and Internal Tuning* section for how to terminate training early.

## Model

The Model is a list of class "`learner_torch_model`" with the following elements:

- `network` :: The trained `network`.
- `optimizer` :: The `$state_dict()` `optimizer` used to train the network.
- `loss_fn` :: The `$state_dict()` of the `loss` used to train the network.
- `callbacks` :: The `callbacks` used to train the network.
- `seed` :: The seed that was / is used for training and prediction.
- `epochs` :: How many epochs the model was trained for (early stopping).
- `task_col_info` :: A `data.table()` containing information about the train-task.

## Parameters

### General:

The parameters of the optimizer, loss and callbacks, prefixed with "opt.", "loss." and "cb.<callback id>." respectively, as well as:

- **epochs** :: `integer(1)`  
The number of epochs.
- **device** :: `character(1)`  
The device. One of "auto", "cpu", or "cuda" or other values defined in `mlr_reflections$torch$devices`. The value is initialized to "auto", which will select "cuda" if possible, then try "mps" and otherwise fall back to "cpu".
- **num\_threads** :: `integer(1)`  
The number of threads for intraop parallelization (if device is "cpu"). This value is initialized to 1.
- **num\_interop\_threads** :: `integer(1)`  
The number of threads for intraop and interop parallelization (if device is "cpu"). This value is initialized to 1. Note that this can only be set once during a session and changing the value within an R session will raise a warning.
- **seed** :: `integer(1)` or "random" or `NULL`  
The torch seed that is used during training and prediction. This value is initialized to "random", which means that a random seed will be sampled at the beginning of the training phase. This seed (either set or randomly sampled) is available via `$model$seed` after training and used during prediction. Note that by setting the seed during the training phase this will mean that by default (i.e. when seed is "random"), clones of the learner will use a different seed. If set to `NULL`, no seeding will be done.
- **tensor\_dataset** :: `logical(1) | "device"`  
Whether to load all batches at once at the beginning of training and stack them. This is initialized to `FALSE`. If set to "device", the device of the tensors will be set to the value of `device`, which can avoid unnecessary moving of tensors between devices. When your dataset fits into memory this will make the loading of batches faster. Note that this should not be set for datasets that contain `lazy_tensors` with random data augmentation, as this augmentation will only be applied once at the beginning of training.

### Evaluation:

- **measures\_train** :: `Measure` or `list()` of `Measures`  
Measures to be evaluated during training.
- **measures\_valid** :: `Measure` or `list()` of `Measures`  
Measures to be evaluated during validation.
- **eval\_freq** :: `integer(1)`  
How often the train / validation predictions are evaluated using `measures_train/measures_valid`. This is initialized to 1. Note that the final model is always evaluated.

### Early Stopping:

- **patience** :: `integer(1)`  
This activates early stopping using the validation scores. If the performance of a model does

not improve for patience evaluation steps, training is ended. Note that the final model is stored in the learner, not the best model. This is initialized to 0, which means no early stopping. The first entry from `measures_valid` is used as the metric. This also requires to specify the `$validate` field of the Learner, as well as `measures_valid`. If this is set, the epoch after which no improvement was observed, can be accessed via the `$internal_tuned_values` field of the learner.

- `min_delta` :: `double(1)`  
The minimum improvement threshold for early stopping. Is initialized to 0.

#### Dataloader:

- `batch_size` :: `integer(1)`  
The batch size (required).
- `shuffle` :: `logical(1)`  
Whether to shuffle the instances in the dataset. This is initialized to TRUE, which differs from the default (FALSE).
- `sampler` :: `torch::sampler`  
Object that defines how the dataloader draw samples.
- `batch_sampler` :: `torch::sampler`  
Object that defines how the dataloader draws batches.
- `num_workers` :: `integer(1)`  
The number of workers for data loading (batches are loaded in parallel). The default is 0, which means that data will be loaded in the main process.
- `collate_fn` :: `function`  
How to merge a list of samples to form a batch.
- `pin_memory` :: `logical(1)`  
Whether the dataloader copies tensors into CUDA pinned memory before returning them.
- `drop_last` :: `logical(1)`  
Whether to drop the last training batch in each epoch during training. Default is FALSE.
- `timeout` :: `numeric(1)`  
The timeout value for collecting a batch from workers. Negative values mean no timeout and the default is -1.
- `worker_init_fn` :: `function(id)`  
A function that receives the worker id (in `[1, num_workers]`) and is executed after seeding on the worker but before data loading.
- `worker_globals` :: `list() | character()`  
When loading data in parallel, this allows to export globals to the workers. If this is a character vector, the objects in the global environment with those names are copied to the workers.
- `worker_packages` :: `character()`  
Which packages to load on the workers.

Also see `torch::dataloader` for more information.

## Inheriting

There are no separate classes for classification and regression to inherit from. Instead, the `task_type` must be specified as a construction argument. Currently, only classification and regression are supported.

When inheriting from this class, one should overload the following methods:

- `.network(task, param_vals)`

`(Task, list())->nn_module`

Construct a `torch::nn_module` object for the given task and parameter values, i.e. the neural network that is trained by the learner. Note that a specific output shape is expected from the returned network, see section *Network Head and Target Encoding*. You can use `output_dim_for()` to obtain the correct output dimension for a given task.

- `.ingress_tokens(task, param_vals)`

`(Task, list())-> named list() with TorchIngressTokens`

Create the `TorchIngressTokens` that are passed to the `task_dataset` constructor. The number of ingress tokens must correspond to the number of input parameters of the network. If there is more than one input, the names must correspond to the inputs of the network. See `ingress_num`, `ingress_categ`, and `ingress_ltnsr` on how to easily create the correct tokens. For more flexibility, you can also directly implement the `.dataset(task, param_vals)` method, see below.

- `.dataset(task, param_vals)`

`(Task, list())-> torch::dataset`

Create the dataset for the task. Don't implement this if the `.ingress_tokens()` method is defined. The dataset must return a named list where:

- `x` is a list of torch tensors that are the input to the network. For networks with more than one input, the names must correspond to the inputs of the network.
- `y` is the target tensor.
- `.index` are the indices of the batch (`integer()` or a `torch_int()`).

For information on the expected target encoding of `y`, see section *Network Head and Target Encoding*. Moreover, one needs to pay attention respect the row ids of the provided task. It is recommended to rely on `task_dataset` for creating the `dataset`.

It is also possible to overwrite the private `.dataloader()` method. This must respect the dataloader parameters from the `ParamSet`.

- `.dataloader(dataset, param_vals)`

`(Task, list())-> torch::dataloader`

Create a dataloader from the task. Needs to respect at least `batch_size` and `shuffle` (otherwise predictions will be incorrectly ordered).

To change the predict types, it is possible to overwrite the method below:

- `.encode_prediction(predict_tensor, task)`

`(torch_tensor, Task) -> list()`

Take in the raw predictions from `self$network` (`predict_tensor`) and encode them into a format that can be converted to valid `mlr3` predictions using `mlr3::as_prediction_data()`. This method must take `self$predict_type` into account.

While it is possible to add parameters by specifying the `param_set` construction argument, it is currently not possible to remove existing parameters, i.e. those listed in section *Parameters*. None of the parameters provided in `param_set` can have an id that starts with "loss.", "opt.", or "cb.", as these are preserved for the dynamically constructed parameters of the optimizer, the loss function, and the callbacks.

To perform additional input checks on the task, the private `.check_train_task(task, param_vals)` and `.check_predict_task(task, param_vals)` can be overwritten. These should return TRUE if the input task is valid and otherwise a string with an error message.

For learners that have other construction arguments that should change the hash of a learner, it is required to implement the private `$.additional_phash_input()`.

## Super class

`mlr3::Learner` -> `LearnerTorch`

### Active bindings

`validate` How to construct the internal validation data. This parameter can be either NULL, a ratio in \$(0, 1]\$, "test", or "predefined".

`loss` (`TorchLoss`)  
 The torch loss.

`optimizer` (`TorchOptimizer`)  
 The torch optimizer.

`callbacks` (list() of `TorchCallbacks`)  
 List of torch callbacks. The ids will be set as the names.

`internal_valid_scores` Retrieves the internal validation scores as a named list(). Specify the `$validate` field and the `measures_valid` parameter to configure this. Returns NULL if learner is not trained yet.

`internal_tuned_values` When early stopping is active, this returns a named list with the early-stopped epochs, otherwise an empty list is returned. Returns NULL if learner is not trained yet.

`marshaled` (logical(1))  
 Whether the learner is marshaled.

`network` (`nn_module()`)  
 Shortcut for `learner$model$network`.

`param_set` (`ParamSet`)  
 The parameter set

`hash` (character(1))  
 Hash (unique identifier) for this object.

`phash` (character(1))  
 Hash (unique identifier) for this partial object, excluding some components which are varied systematically during tuning (parameter values).

## Methods

### Public methods:

- `LearnerTorch$new()`
- `LearnerTorch$format()`
- `LearnerTorch$print()`
- `LearnerTorch$marshal()`
- `LearnerTorch$unmarshal()`
- `LearnerTorch$dataset()`
- `LearnerTorch$clone()`

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

```
LearnerTorch$new(
  id,
  task_type,
  param_set,
  properties = character(),
  man,
  label,
  feature_types,
  optimizer = NULL,
  loss = NULL,
  packages = character(),
  predict_types = NULL,
  callbacks = list(),
  jittable = FALSE
)
```

*Arguments:*

`id` (character(1))

The id for of the new object.

`task_type` (character(1))

The task type.

`param_set` ([ParamSet](#) or `alist()`)

Either a parameter set, or an `alist()` containing different values of `self`, e.g. `alist(private$.param_set1, private$.param_set2)`, from which a [ParamSet](#) collection should be created.

`properties` (character())

The properties of the object. See [mlr\\_reflections\\$learner\\_properties](#) for available values.

`man` (character(1))

String in the format `[pkg]::[topic]` pointing to a manual page for this object. The referenced help package can be opened via method `$help()`.

`label` (character(1))

Label for the new instance.

`feature_types` (character())

The feature types. See [mlr\\_reflections\\$task\\_feature\\_types](#) for available values, Additionally, "lazy\_tensor" is supported.

**optimizer** (NULL or `TorchOptimizer`)  
 The optimizer to use for training. Defaults to adam.

**loss** (NULL or `TorchLoss`)  
 The loss to use for training. Defaults to MSE for regression and cross entropy for classification.

**packages** (character())  
 The R packages this object depends on.

**predict\_types** (character())  
 The predict types. See `mlr_reflections$learner_predict_types` for available values. For regression, the default is "response". For classification, this defaults to "response" and "prob". To deviate from the defaults, it is necessary to overwrite the private `$.encode_prediction()` method, see section *Inheriting*.

**callbacks** (list() of `TorchCallbacks`)  
 The callbacks to use for training. Defaults to an empty list(), i.e. no callbacks.

**jittable** (logical(1))  
 Whether the model can be jit-traced. Default is FALSE.

**Method** `format()`: Helper for print outputs.

*Usage:*

`LearnerTorch$format(...)`

*Arguments:*

... (ignored).

**Method** `print()`: Prints the object.

*Usage:*

`LearnerTorch$print(...)`

*Arguments:*

... (any)

Currently unused.

**Method** `marshal()`: Marshal the learner.

*Usage:*

`LearnerTorch$marshal(...)`

*Arguments:*

... (any)

Additional parameters.

*Returns:* self

**Method** `unmarshal()`: Unmarshal the learner.

*Usage:*

`LearnerTorch$unmarshal(...)`

*Arguments:*

... (any)

Additional parameters.

*Returns:* self

**Method** dataset(): Create the dataset for a task.

*Usage:*

```
LearnerTorch$dataset(task)
```

*Arguments:*

task [Task](#)

The task

*Returns:* [dataset](#)

**Method** clone(): The objects of this class are cloneable with this method.

*Usage:*

```
LearnerTorch$clone(deep = FALSE)
```

*Arguments:*

deep Whether to make a deep clone.

## See Also

Other Learner: [mlr\\_learners.ft\\_transformer](#), [mlr\\_learners.mlp](#), [mlr\\_learners.module](#), [mlr\\_learners.tab\\_resnet](#), [mlr\\_learners.torch\\_featureless](#), [mlr\\_learners\\_torch\\_image](#), [mlr\\_learners\\_torch\\_model](#)

---

[mlr\\_learners\\_torch\\_image](#)

*Image Learner*

---

## Description

Base Class for Image Learners. The features are assumed to be a single [lazy\\_tensor](#) column in RGB format.

## Parameters

Parameters include those inherited from [LearnerTorch](#) and the `param_set` construction argument.

## Super classes

[mlr3::Learner](#) -> [mlr3torch::LearnerTorch](#) -> [LearnerTorchImage](#)

## Methods

### Public methods:

- `LearnerTorchImage$new()`
- `LearnerTorchImage$clone()`

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

```
LearnerTorchImage$new(
  id,
  task_type,
  param_set = ps(),
  label,
  optimizer = NULL,
  loss = NULL,
  callbacks = list(),
  packages,
  man,
  properties = NULL,
  predict_types = NULL,
  jittable = FALSE
)
```

*Arguments:*

`id` (character(1))  
 The id for of the new object.

`task_type` (character(1))  
 The task type.

`param_set` ([ParamSet](#))  
 The parameter set.

`label` (character(1))  
 Label for the new instance.

`optimizer` ([TorchOptimizer](#))  
 The torch optimizer.

`loss` ([TorchLoss](#))  
 The loss to use for training.

`callbacks` (list() of [TorchCallbacks](#))  
 The callbacks used during training. Must have unique ids. They are executed in the order in which they are provided

`packages` (character())  
 The R packages this object depends on.

`man` (character(1))  
 String in the format `[pkg]::[topic]` pointing to a manual page for this object. The referenced help package can be opened via method `$help()`.

`properties` (character())  
 The properties of the object. See `mlr_reflections$learner_properties` for available values.

```

predict_types (character())
  The predict types. See mlr\_reflections\$learner\_predict\_types for available values.
jittable (logical(1))
  Whether the model can be jit-traced.

```

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

```
LearnerTorchImage$clone(deep = FALSE)
```

*Arguments:*

```
deep Whether to make a deep clone.
```

## See Also

Other Learner: [mlr\\_learners.ft\\_transformer](#), [mlr\\_learners.mlp](#), [mlr\\_learners.module](#), [mlr\\_learners.tab\\_resnet](#), [mlr\\_learners.torch\\_featureless](#), [mlr\\_learners\\_torch](#), [mlr\\_learners\\_torch\\_model](#)

[mlr\\_learners\\_torch\\_model](#)

*Learner Torch Model*

## Description

Create a torch learner from an instantiated [nn\\_module\(\)](#). For classification, the output of the network must be the scores (before the softmax).

## Parameters

See [LearnerTorch](#)

## Super classes

[mlr3::Learner](#) -> [mlr3torch::LearnerTorch](#) -> [LearnerTorchModel](#)

## Active bindings

`ingress_tokens` (named list() with `TorchIngressToken` or `NULL`)  
 The ingress tokens. Must be non-NULL when calling `$train()`.

## Methods

### Public methods:

- [LearnerTorchModel\\$new\(\)](#)
- [LearnerTorchModel\\$clone\(\)](#)

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

```
LearnerTorchModel$new(
  network = NULL,
  ingress_tokens = NULL,
  task_type,
  properties = NULL,
  optimizer = NULL,
  loss = NULL,
  callbacks = list(),
  packages = character(0),
  feature_types = NULL
)
Arguments:
network (nn\_module)
  An instantiated nn\_module. Is not cloned during construction. For classification, outputs must be the scores (before the softmax).
ingress_tokens (list of TorchIngressToken\(\))
  A list with ingress tokens that defines how the dataloader will be defined.
task_type (character(1))
  The task type.
properties (NULL or character())
  The properties of the learner. Defaults to all available properties for the given task type.
optimizer (TorchOptimizer)
  The torch optimizer.
loss (TorchLoss)
  The loss to use for training.
callbacks (list() of TorchCallbacks)
  The callbacks used during training. Must have unique ids. They are executed in the order in which they are provided.
packages (character())
  The R packages this object depends on.
feature_types (NULL or character())
  The feature types. Defaults to all available feature types.
```

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

```
LearnerTorchModel$clone(deep = FALSE)
```

*Arguments:*

deep Whether to make a deep clone.

## See Also

Other Learner: [mlr\\_learners.ft\\_transformer](#), [mlr\\_learners.mlp](#), [mlr\\_learners.module](#), [mlr\\_learners.tab\\_resnet](#), [mlr\\_learners.torch\\_featureless](#), [mlr\\_learners\\_torch](#), [mlr\\_learners\\_torch\\_image](#)

Other Graph Network: [ModelDescriptor\(\)](#), [TorchIngressToken\(\)](#), [mlr\\_pipeops\\_module](#), [mlr\\_pipeops\\_torch](#), [mlr\\_pipeops\\_torch\\_ingress](#), [mlr\\_pipeops\\_torch\\_ingress\\_categ](#), [mlr\\_pipeops\\_torch\\_ingress\\_ltnsr](#), [mlr\\_pipeops\\_torch\\_ingress\\_num](#), [model\\_descriptor\\_to\\_learner\(\)](#), [model\\_descriptor\\_to\\_module\(\)](#), [model\\_descriptor\\_union\(\)](#), [nn\\_graph\(\)](#)

## Examples

```
# We show the learner using a classification task

# The iris task has 4 features and 3 classes
network = nn_linear(4, 3)
task = tsk("iris")

# This defines the dataloader.
# It loads all 4 features, which are also numeric.
# The shape is (NA, 4) because the batch dimension is generally NA
ingress_tokens = list(
  input = TorchIngressToken(task$feature_names, batchgetter_num, c(NA, 4))
)

# Creating the learner and setting required parameters
learner = lrn("classif.torch_model",
  network = network,
  ingress_tokens = ingress_tokens,
  batch_size = 16,
  epochs = 1,
  device = "cpu"
)

# A simple train-predict
ids = partition(task)
learner$train(task, ids$train)
learner$predict(task, ids$test)
```

---

**mlr\_pipeops\_augment\_center\_crop**  
*Center Crop Augmentation*

---

## Description

Calls [torchvision::transform\\_center\\_crop](#), see there for more information on the parameters. The preprocessing is applied to each element of a batch individually.

## Format

[R6Class](#) inheriting from [PipeOpTaskPreprocTorch](#).

## Construction

```
po("augment_center_crop")
```

## Parameters

| Id             | Type      | Default        | Levels               |
|----------------|-----------|----------------|----------------------|
| size           | untyped   | -              |                      |
| stages         | character | -              | train, predict, both |
| affect_columns | untyped   | selector_all() |                      |

---

**mlr\_pipeops\_augment\_color\_jitter**  
*Color Jitter Augmentation*

---

## Description

Calls `torchvision::transform_color_jitter`, see there for more information on the parameters. The preprocessing is applied to each element of a batch individually.

## Format

`R6Class` inheriting from `PipeOpTaskPreprocTorch`.

## Construction

```
po("augment_color_jitter")
```

## Parameters

| Id             | Type      | Default        | Levels               | Range         |
|----------------|-----------|----------------|----------------------|---------------|
| brightness     | numeric   | 0              |                      | $[0, \infty)$ |
| contrast       | numeric   | 0              |                      | $[0, \infty)$ |
| saturation     | numeric   | 0              |                      | $[0, \infty)$ |
| hue            | numeric   | 0              |                      | $[0, \infty)$ |
| stages         | character | -              | train, predict, both | -             |
| affect_columns | untyped   | selector_all() |                      | -             |

---

**mlr\_pipeops\_augment\_crop***Crop Augmentation*

---

**Description**

Calls `torchvision::transform_crop`, see there for more information on the parameters. The preprocessing is applied to each element of a batch individually.

**Format**

`R6Class` inheriting from `PipeOpTaskPreprocTorch`.

**Construction**

```
po("augment_crop")
```

**Parameters**

| Id             | Type      | Default        | Levels               | Range               |
|----------------|-----------|----------------|----------------------|---------------------|
| top            | integer   | -              |                      | $(-\infty, \infty)$ |
| left           | integer   | -              |                      | $(-\infty, \infty)$ |
| height         | integer   | -              |                      | $(-\infty, \infty)$ |
| width          | integer   | -              |                      | $(-\infty, \infty)$ |
| stages         | character | -              | train, predict, both | -                   |
| affect_columns | untyped   | selector_all() |                      | -                   |

---

**mlr\_pipeops\_augment\_hflip***Horizontal Flip Augmentation*

---

**Description**

Calls `torchvision::transform_hflip`, see there for more information on the parameters. The preprocessing is applied to each element of a batch individually.

**Format**

`R6Class` inheriting from `PipeOpTaskPreprocTorch`.

## Construction

```
po("augment_random_affine")
```

## Parameters

| Id             | Type      | Default        | Levels               |
|----------------|-----------|----------------|----------------------|
| stages         | character | -              | train, predict, both |
| affect_columns | untyped   | selector_all() |                      |

---

**mlr\_pipeops\_augment\_random\_affine**  
*Random Affine Augmentation*

---

## Description

Calls `torchvision::transform_random_affine`, see there for more information on the parameters. The preprocessing is applied to each element of a batch individually.

## Format

`R6Class` inheriting from `PipeOpTaskPreprocTorch`.

## Construction

```
po("augment_random_affine")
```

## Parameters

| Id             | Type      | Default        | Levels               | Range               |
|----------------|-----------|----------------|----------------------|---------------------|
| degrees        | untyped   | -              |                      | -                   |
| translate      | untyped   | NULL           |                      | -                   |
| scale          | untyped   | NULL           |                      | -                   |
| resample       | integer   | 0              |                      | $(-\infty, \infty)$ |
| fillcolor      | untyped   | 0              |                      | -                   |
| stages         | character | -              | train, predict, both | -                   |
| affect_columns | untyped   | selector_all() |                      | -                   |

---

**mlr\_pipeops\_augment\_random\_choice**  
*Random Choice Augmentation*

---

### Description

Calls `torchvision::transform_random_choice`, see there for more information on the parameters. The preprocessing is applied to each element of a batch individually.

### Format

`R6Class` inheriting from `PipeOpTaskPreprocTorch`.

### Construction

```
po("augment_random_choice")
```

### Parameters

| Id             | Type      | Default        | Levels               |
|----------------|-----------|----------------|----------------------|
| transforms     | untyped   | -              |                      |
| stages         | character | -              | train, predict, both |
| affect_columns | untyped   | selector_all() |                      |

---

**mlr\_pipeops\_augment\_random\_crop**  
*Random Crop Augmentation*

---

### Description

Calls `torchvision::transform_random_crop`, see there for more information on the parameters. The preprocessing is applied to each element of a batch individually.

### Format

`R6Class` inheriting from `PipeOpTaskPreprocTorch`.

### Construction

```
po("augment_random_crop")
```

## Parameters

| Id             | Type      | Default        | Levels                             |
|----------------|-----------|----------------|------------------------------------|
| size           | untyped   | -              |                                    |
| padding        | untyped   | NULL           |                                    |
| pad_if_needed  | logical   | FALSE          | TRUE, FALSE                        |
| fill           | untyped   | 0L             |                                    |
| padding_mode   | character | constant       | constant, edge, reflect, symmetric |
| stages         | character | -              | train, predict, both               |
| affect_columns | untyped   | selector_all() |                                    |

---

**mlr\_pipeops\_augment\_random\_horizontal\_flip**  
*Random Horizontal Flip Augmentation*

---

## Description

Calls `torchvision::transform_random_horizontal_flip`, see there for more information on the parameters. The preprocessing is applied to each element of a batch individually.

## Format

`R6Class` inheriting from `PipeOpTaskPreprocTorch`.

## Construction

```
po("augment_random_horizontal_flip")
```

## Parameters

| Id             | Type      | Default        | Levels               | Range  |
|----------------|-----------|----------------|----------------------|--------|
| p              | numeric   | 0.5            |                      | [0, 1] |
| stages         | character | -              | train, predict, both | -      |
| affect_columns | untyped   | selector_all() |                      | -      |

---

**mlr\_pipeops\_augment\_random\_order**  
*Random Order Augmentation*

---

### Description

Calls [torchvision::transform\\_random\\_order](#), see there for more information on the parameters. The preprocessing is applied to each element of a batch individually.

### Format

[R6Class](#) inheriting from [PipeOpTaskPreprocTorch](#).

### Construction

```
po("augment_random_order")
```

### Parameters

| Id             | Type      | Default        | Levels               |
|----------------|-----------|----------------|----------------------|
| transforms     | untyped   | -              |                      |
| stages         | character | -              | train, predict, both |
| affect_columns | untyped   | selector_all() |                      |

---

**mlr\_pipeops\_augment\_random\_resized\_crop**  
*Random Resized Crop Augmentation*

---

### Description

Calls [torchvision::transform\\_random\\_resized\\_crop](#), see there for more information on the parameters. The preprocessing is applied to each element of a batch individually.

### Format

[R6Class](#) inheriting from [PipeOpTaskPreprocTorch](#).

### Construction

```
po("augment_random_resized_crop")
```

## Parameters

| Id             | Type      | Default        | Levels               | Range  |
|----------------|-----------|----------------|----------------------|--------|
| size           | untyped   | -              |                      | -      |
| scale          | untyped   | c(0.08, 1)     |                      | -      |
| ratio          | untyped   | c(3/4, 4/3)    |                      | -      |
| interpolation  | integer   | 2              |                      | [0, 3] |
| stages         | character | -              | train, predict, both | -      |
| affect_columns | untyped   | selector_all() |                      | -      |

---

**mlr\_pipeops\_augment\_random\_vertical\_flip**  
*Random Vertical Flip Augmentation*

---

## Description

Calls `torchvision::transform_random_vertical_flip`, see there for more information on the parameters. The preprocessing is applied to each element of a batch individually.

## Format

`R6Class` inheriting from `PipeOpTaskPreprocTorch`.

## Construction

```
po("augment_random_vertical_flip")
```

## Parameters

| Id             | Type      | Default        | Levels               | Range  |
|----------------|-----------|----------------|----------------------|--------|
| p              | numeric   | 0.5            |                      | [0, 1] |
| stages         | character | -              | train, predict, both | -      |
| affect_columns | untyped   | selector_all() |                      | -      |

---

**mlr\_pipeops\_augment\_resized\_crop**  
*Resized Crop Augmentation*

---

### Description

Calls `torchvision::transform_resized_crop`, see there for more information on the parameters. The preprocessing is applied to each element of a batch individually.

### Format

`R6Class` inheriting from `PipeOpTaskPreprocTorch`.

### Construction

```
po("augment_resized_crop")
```

### Parameters

| Id             | Type      | Default        | Levels               | Range               |
|----------------|-----------|----------------|----------------------|---------------------|
| top            | integer   | -              |                      | $(-\infty, \infty)$ |
| left           | integer   | -              |                      | $(-\infty, \infty)$ |
| height         | integer   | -              |                      | $(-\infty, \infty)$ |
| width          | integer   | -              |                      | $(-\infty, \infty)$ |
| size           | untyped   | -              |                      | -                   |
| interpolation  | integer   | 2              |                      | [0, 3]              |
| stages         | character | -              | train, predict, both | -                   |
| affect_columns | untyped   | selector_all() |                      | -                   |

---

**mlr\_pipeops\_augment\_rotate**  
*Rotate Augmentation*

---

### Description

Calls `torchvision::transform_rotate`, see there for more information on the parameters. The preprocessing is applied to each element of a batch individually.

### Format

`R6Class` inheriting from `PipeOpTaskPreprocTorch`.

## Construction

```
po("augment_rotate")
```

## Parameters

| Id             | Type      | Default        | Levels               | Range                 |
|----------------|-----------|----------------|----------------------|-----------------------|
| angle          | untyped   | -              |                      | -                     |
| resample       | integer   | 0              |                      | ( $-\infty, \infty$ ) |
| expand         | logical   | FALSE          | TRUE, FALSE          | -                     |
| center         | untyped   | NULL           |                      | -                     |
| fill           | untyped   | NULL           |                      | -                     |
| stages         | character | -              | train, predict, both | -                     |
| affect_columns | untyped   | selector_all() |                      | -                     |

---

## mlr\_pipeops\_augment\_vflip

*Vertical Flip Augmentation*

---

## Description

Calls `torchvision::transform_vflip`, see there for more information on the parameters. The preprocessing is applied to each element of a batch individually.

## Format

`R6Class` inheriting from `PipeOpTaskPreprocTorch`.

## Construction

```
po("augment_vflip")
```

## Parameters

| Id             | Type      | Default        | Levels               |
|----------------|-----------|----------------|----------------------|
| stages         | character | -              | train, predict, both |
| affect_columns | untyped   | selector_all() |                      |

---

mlr\_pipeops\_module      *Class for Torch Module Wrappers*

---

## Description

PipeOpModule wraps an [nn\\_module](#) or function that is being called during the `train` phase of this [mlr3pipelines::PipeOp](#). By doing so, this allows to assemble PipeOpModules in a computational [mlr3pipelines::Graph](#) that represents either a neural network or a preprocessing graph of a [lazy\\_tensor](#). In most cases it is easier to create such a network by creating a graph that generates this graph.

In most cases it is easier to create such a network by creating a structurally related graph consisting of nodes of class [PipeOpTorchIngress](#) and [PipeOpTorch](#). This graph will then generate the graph consisting of PipeOpModules as part of the [ModelDescriptor](#).

## Input and Output Channels

The number and names of the input and output channels can be set during construction. They input and output "torch\_tensor" during training, and NULL during prediction as the prediction phase currently serves no meaningful purpose.

## State

The state is the value calculated by the public method `shapes_out()`.

## Parameters

No parameters.

## Internals

During training, the wrapped [nn\\_module](#) / function is called with the provided inputs in the order in which the channels are defined. Arguments are **not** matched by name.

## Super class

[mlr3pipelines::PipeOp](#) -> PipeOpModule

## Public fields

`module (nn_module)`

The torch module that is called during the training phase.

## Methods

### Public methods:

- `PipeOpModule$new()`
- `PipeOpModule$clone()`

**Method** `new()`: Creates a new instance of this `R6` class.

*Usage:*

```
PipeOpModule$new(
  id = "module",
  module = nn_identity(),
  inname = "input",
  outname = "output",
  param_vals = list(),
  packages = character(0)
)
```

*Arguments:*

`id` (character(1))

The id for of the new object.

`module` (`nn_module` or `function()`)

The torch module or function that is being wrapped.

`inname` (character())

The names of the input channels.

`outname` (character())

The names of the output channels. If this parameter has length 1, the parameter `module` must return a `tensor`. Otherwise it must return a `list()` of tensors of corresponding length.

`param_vals` (named `list()`)

Parameter values to be set after construction.

`packages` (character())

The R packages this object depends on.

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

```
PipeOpModule$clone(deep = FALSE)
```

*Arguments:*

`deep` Whether to make a deep clone.

## See Also

Other Graph Network: `ModelDescriptor()`, `TorchIngressToken()`, `mlr_learners_torch_model`, `mlr_pipeops_torch`, `mlr_pipeops_torch_ingress`, `mlr_pipeops_torch_ingress_categ`, `mlr_pipeops_torch_ingress_num`, `model_descriptor_to_learner()`, `model_descriptor_to_module()`, `model_descriptor_union()`, `nn_graph()`

Other PipeOp: `mlr_pipeops_torch_callbacks`, `mlr_pipeops_torch_optimizer`

## Examples

```

## creating an PipeOpModule manually

# one input and output channel
po_module = po("module",
  id = "linear",
  module = torch::nn_linear(10, 20),
  inname = "input",
  outname = "output"
)
x = torch::torch_rndn(16, 10)
# This calls the forward function of the wrapped module.
y = po_module$train(list(input = x))
str(y)

# multiple input and output channels
nn_custom = torch::nn_module("nn_custom",
  initialize = function(in_features, out_features) {
    self$lin1 = torch::nn_linear(in_features, out_features)
    self$lin2 = torch::nn_linear(in_features, out_features)
  },
  forward = function(x, z) {
    list(out1 = self$lin1(x), out2 = torch::nnf_relu(self$lin2(z)))
  }
)

module = nn_custom(3, 2)
po_module = po("module",
  id = "custom",
  module = module,
  inname = c("x", "z"),
  outname = c("out1", "out2")
)
x = torch::torch_rndn(1, 3)
z = torch::torch_rndn(1, 3)
out = po_module$train(list(x = x, z = z))
str(out)

# How such a PipeOpModule is usually generated
graph = po("torch_ingress_num") %>>% po("nn_linear", out_features = 10L)
result = graph$train(tsk("iris"))
# The PipeOpTorchLinear generates a PipeOpModule and adds it to a new (module) graph
result[[1]]$graph
linear_module = result[[1L]]$graph$pipeops$nn_linear
linear_module
formalArgs(linear_module$module)
linear_module$input$name

# Constructing a PipeOpModule using a simple function
po_add1 = po("module",
  id = "add_one",
  module = function(x) x + 1
)

```

```

)
input = list(torch_tensor(1))
po_add1$train(input)$output

```

---

**mlr\_pipeops\_nn\_adaptive\_avg\_pool1d**  
*1D Adaptive Average Pooling*

---

## Description

Applies a 1D adaptive average pooling over an input signal composed of several input planes.

### nn\_module

Calls [nn\\_adaptive\\_avg\\_pool1d\(\)](#) during training.

### Parameters

- `output_size` :: `integer(1)`  
The target output size. A single number.

### Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

### State

The state is the value calculated by the public method `$shapes_out()`.

### Super classes

```

mlr3pipelines::PipeOp -> mlr3torch::PipeOpTorch -> mlr3torch::PipeOpTorchAdaptiveAvgPool
-> PipeOpTorchAdaptiveAvgPool1D

```

### Methods

#### Public methods:

- [PipeOpTorchAdaptiveAvgPool1D\\$new\(\)](#)
- [PipeOpTorchAdaptiveAvgPool1D\\$clone\(\)](#)

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

```

PipeOpTorchAdaptiveAvgPool1D$new(
  id = "nn_adaptive_avg_pool1d",
  param_vals = list()
)

```

*Arguments:*

`id` (character(1))  
 Identifier of the resulting object.  
`param_vals` (list())  
 List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

`PipeOpTorchAdaptiveAvgPool1D$clone(deep = FALSE)`

*Arguments:*

`deep` Whether to make a deep clone.

## See Also

Other PipeOps: [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm2d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm3d](#), [mlr\\_pipeops\\_nn\\_block](#), [mlr\\_pipeops\\_nn\\_celu](#), [mlr\\_pipeops\\_nn\\_conv1d](#), [mlr\\_pipeops\\_nn\\_conv2d](#), [mlr\\_pipeops\\_nn\\_conv3d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose1d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose2d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose3d](#), [mlr\\_pipeops\\_nn\\_dropout](#), [mlr\\_pipeops\\_nn\\_elu](#), [mlr\\_pipeops\\_nn\\_flatten](#), [mlr\\_pipeops\\_nn\\_ft\\_cls](#), [mlr\\_pipeops\\_nn\\_ft\\_transformer\\_block](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_glu](#), [mlr\\_pipeops\\_nn\\_hardshrink](#), [mlr\\_pipeops\\_nn\\_hardsigmoid](#), [mlr\\_pipeops\\_nn\\_hardtanh](#), [mlr\\_pipeops\\_nn\\_head](#), [mlr\\_pipeops\\_nn\\_identity](#), [mlr\\_pipeops\\_nn\\_layer\\_norm](#), [mlr\\_pipeops\\_nn\\_leaky\\_relu](#), [mlr\\_pipeops\\_nn\\_linear](#), [mlr\\_pipeops\\_nn\\_log\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_max\\_pool1d](#), [mlr\\_pipeops\\_nn\\_max\\_pool2d](#), [mlr\\_pipeops\\_nn\\_max\\_pool3d](#), [mlr\\_pipeops\\_nn\\_merge](#), [mlr\\_pipeops\\_nn\\_merge\\_cat](#), [mlr\\_pipeops\\_nn\\_merge\\_prod](#), [mlr\\_pipeops\\_nn\\_merge\\_sum](#), [mlr\\_pipeops\\_nn\\_prelu](#), [mlr\\_pipeops\\_nn\\_reglu](#), [mlr\\_pipeops\\_nn\\_relu](#), [mlr\\_pipeops\\_nn\\_relu6](#), [mlr\\_pipeops\\_nn\\_reshape](#), [mlr\\_pipeops\\_nn\\_rrelu](#), [mlr\\_pipeops\\_nn\\_selu](#), [mlr\\_pipeops\\_nn\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_softmax](#), [mlr\\_pipeops\\_nn\\_softplus](#), [mlr\\_pipeops\\_nn\\_softshrink](#), [mlr\\_pipeops\\_nn\\_softsign](#), [mlr\\_pipeops\\_nn\\_squeeze](#), [mlr\\_pipeops\\_nn\\_tanh](#), [mlr\\_pipeops\\_nn\\_tanhshrink](#), [mlr\\_pipeops\\_nn\\_threshold](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_cat](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_num](#), [mlr\\_pipeops\\_nn\\_unsqueeze](#), [mlr\\_pipeops\\_torch\\_ingress](#), [mlr\\_pipeops\\_torch\\_ingress\\_categ](#), [mlr\\_pipeops\\_torch\\_ingress\\_ltnsr](#), [mlr\\_pipeops\\_torch\\_ingress\\_num](#), [mlr\\_pipeops\\_torch\\_loss](#), [mlr\\_pipeops\\_torch\\_model](#), [mlr\\_pipeops\\_torch\\_model\\_classif](#), [mlr\\_pipeops\\_torch\\_model\\_regr](#)

## Examples

```
# Construct the PipeOp
pipeop = po("nn_adaptive_avg_pool1d")
pipeop
# The available parameters
pipeop$param_set
```

---

**mlr\_pipeops\_nn\_adaptive\_avg\_pool2d**  
*2D Adaptive Average Pooling*

---

## Description

Applies a 2D adaptive average pooling over an input signal composed of several input planes.

### nn\_module

Calls [nn\\_adaptive\\_avg\\_pool2d\(\)](#) during training.

### Parameters

- `output_size :: integer()`  
 The target output size. Can be a single number or a vector.

### Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

### State

The state is the value calculated by the public method `$shapes_out()`.

### Super classes

`mlr3pipelines::PipeOp -> mlr3torch::PipeOpTorch -> mlr3torch::PipeOpTorchAdaptiveAvgPool -> PipeOpTorchAdaptiveAvgPool2D`

### Methods

#### Public methods:

- [PipeOpTorchAdaptiveAvgPool2D\\$new\(\)](#)
- [PipeOpTorchAdaptiveAvgPool2D\\$clone\(\)](#)

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

```
PipeOpTorchAdaptiveAvgPool2D$new(
  id = "nn_adaptive_avg_pool2d",
  param_vals = list()
)
```

*Arguments:*

`id (character(1))`  
 Identifier of the resulting object.

```
param_vals (list())
  List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.
```

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

```
PipeOpTorchAdaptiveAvgPool2D$clone(deep = FALSE)
```

*Arguments:*

`deep` Whether to make a deep clone.

## See Also

Other PipeOps: [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm2d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm3d](#), [mlr\\_pipeops\\_nn\\_block](#), [mlr\\_pipeops\\_nn\\_celu](#), [mlr\\_pipeops\\_nn\\_conv1d](#), [mlr\\_pipeops\\_nn\\_conv2d](#), [mlr\\_pipeops\\_nn\\_conv3d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose1d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose2d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose3d](#), [mlr\\_pipeops\\_nn\\_dropout](#), [mlr\\_pipeops\\_nn\\_elu](#), [mlr\\_pipeops\\_nn\\_flatten](#), [mlr\\_pipeops\\_nn\\_ft\\_cls](#), [mlr\\_pipeops\\_nn\\_ft\\_transformer\\_block](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_glu](#), [mlr\\_pipeops\\_nn\\_hardshrink](#), [mlr\\_pipeops\\_nn\\_hardsigmoid](#), [mlr\\_pipeops\\_nn\\_hardtanh](#), [mlr\\_pipeops\\_nn\\_head](#), [mlr\\_pipeops\\_nn\\_identity](#), [mlr\\_pipeops\\_nn\\_layer\\_norm](#), [mlr\\_pipeops\\_nn\\_leaky\\_relu](#), [mlr\\_pipeops\\_nn\\_linear](#), [mlr\\_pipeops\\_nn\\_log\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_max\\_pool1d](#), [mlr\\_pipeops\\_nn\\_max\\_pool2d](#), [mlr\\_pipeops\\_nn\\_max\\_pool3d](#), [mlr\\_pipeops\\_nn\\_merge](#), [mlr\\_pipeops\\_nn\\_merge\\_cat](#), [mlr\\_pipeops\\_nn\\_merge\\_prod](#), [mlr\\_pipeops\\_nn\\_merge\\_sum](#), [mlr\\_pipeops\\_nn\\_prelu](#), [mlr\\_pipeops\\_nn\\_relu](#), [mlr\\_pipeops\\_nn\\_relu](#), [mlr\\_pipeops\\_nn\\_relu6](#), [mlr\\_pipeops\\_nn\\_reshape](#), [mlr\\_pipeops\\_nn\\_rrelu](#), [mlr\\_pipeops\\_nn\\_selu](#), [mlr\\_pipeops\\_nn\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_softmax](#), [mlr\\_pipeops\\_nn\\_softplus](#), [mlr\\_pipeops\\_nn\\_softshrink](#), [mlr\\_pipeops\\_nn\\_softsign](#), [mlr\\_pipeops\\_nn\\_squeeze](#), [mlr\\_pipeops\\_nn\\_tanh](#), [mlr\\_pipeops\\_nn\\_tanhshrink](#), [mlr\\_pipeops\\_nn\\_threshold](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_cate](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_num](#), [mlr\\_pipeops\\_nn\\_unsqueeze](#), [mlr\\_pipeops\\_torch\\_ingress](#), [mlr\\_pipeops\\_torch\\_ingress\\_categ](#), [mlr\\_pipeops\\_torch\\_ingress\\_ltnsr](#), [mlr\\_pipeops\\_torch\\_ingress\\_num](#), [mlr\\_pipeops\\_torch\\_loss](#), [mlr\\_pipeops\\_torch\\_model](#), [mlr\\_pipeops\\_torch\\_model\\_classif](#), [mlr\\_pipeops\\_torch\\_model\\_regr](#)

## Examples

```
# Construct the PipeOp
pipeop = po("nn_adaptive_avg_pool2d")
pipeop
# The available parameters
pipeop$param_set
```

---

**mlr\_pipeops\_nn\_adaptive\_avg\_pool3d**  
3D Adaptive Average Pooling

---

## Description

Applies a 3D adaptive average pooling over an input signal composed of several input planes.

### nn\_module

Calls [nn\\_adaptive\\_avg\\_pool3d\(\)](#) during training.

### Parameters

- `output_size :: integer()`  
The target output size. Can be a single number or a vector.

### Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

### State

The state is the value calculated by the public method `$shapes_out()`.

### Super classes

```
mlr3pipelines::PipeOp -> mlr3torch::PipeOpTorch -> mlr3torch::PipeOpTorchAdaptiveAvgPool
-> PipeOpTorchAdaptiveAvgPool3D
```

### Methods

#### Public methods:

- [PipeOpTorchAdaptiveAvgPool3D\\$new\(\)](#)
- [PipeOpTorchAdaptiveAvgPool3D\\$clone\(\)](#)

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

```
PipeOpTorchAdaptiveAvgPool3D$new(
  id = "nn_adaptive_avg_pool3d",
  param_vals = list()
)
```

*Arguments:*

`id` (character(1))  
Identifier of the resulting object.  
`param_vals` (list())  
List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

```
PipeOpTorchAdaptiveAvgPool3D$clone(deep = FALSE)
```

*Arguments:*

`deep` Whether to make a deep clone.

**See Also**

Other PipeOps: [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm2d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm3d](#), [mlr\\_pipeops\\_nn\\_block](#), [mlr\\_pipeops\\_nn\\_celu](#), [mlr\\_pipeops\\_nn\\_conv1d](#), [mlr\\_pipeops\\_nn\\_conv2d](#), [mlr\\_pipeops\\_nn\\_conv3d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose1d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose2d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose3d](#), [mlr\\_pipeops\\_nn\\_dropout](#), [mlr\\_pipeops\\_nn\\_elu](#), [mlr\\_pipeops\\_nn\\_flatten](#), [mlr\\_pipeops\\_nn\\_ft\\_cls](#), [mlr\\_pipeops\\_nn\\_ft\\_transformer\\_block](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_glu](#), [mlr\\_pipeops\\_nn\\_hardshrink](#), [mlr\\_pipeops\\_nn\\_hardsigmoid](#), [mlr\\_pipeops\\_nn\\_hardtanh](#), [mlr\\_pipeops\\_nn\\_head](#), [mlr\\_pipeops\\_nn\\_identity](#), [mlr\\_pipeops\\_nn\\_layer\\_norm](#), [mlr\\_pipeops\\_nn\\_leaky\\_relu](#), [mlr\\_pipeops\\_nn\\_linear](#), [mlr\\_pipeops\\_nn\\_log\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_max\\_pool1d](#), [mlr\\_pipeops\\_nn\\_max\\_pool2d](#), [mlr\\_pipeops\\_nn\\_max\\_pool3d](#), [mlr\\_pipeops\\_nn\\_merge](#), [mlr\\_pipeops\\_nn\\_merge\\_cat](#), [mlr\\_pipeops\\_nn\\_merge\\_prod](#), [mlr\\_pipeops\\_nn\\_merge\\_sum](#), [mlr\\_pipeops\\_nn\\_prelu](#), [mlr\\_pipeops\\_nn\\_relu](#), [mlr\\_pipeops\\_nn\\_relu](#), [mlr\\_pipeops\\_nn\\_relu6](#), [mlr\\_pipeops\\_nn\\_reshape](#), [mlr\\_pipeops\\_nn\\_rrelu](#), [mlr\\_pipeops\\_nn\\_selu](#), [mlr\\_pipeops\\_nn\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_softmax](#), [mlr\\_pipeops\\_nn\\_softplus](#), [mlr\\_pipeops\\_nn\\_softshrink](#), [mlr\\_pipeops\\_nn\\_softsign](#), [mlr\\_pipeops\\_nn\\_squeeze](#), [mlr\\_pipeops\\_nn\\_tanh](#), [mlr\\_pipeops\\_nn\\_tanhshrink](#), [mlr\\_pipeops\\_nn\\_threshold](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_cat](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_num](#), [mlr\\_pipeops\\_nn\\_unsqueeze](#), [mlr\\_pipeops\\_torch\\_ingress](#), [mlr\\_pipeops\\_torch\\_ingress\\_categ](#), [mlr\\_pipeops\\_torch\\_ingress\\_ltnsr](#), [mlr\\_pipeops\\_torch\\_ingress\\_num](#), [mlr\\_pipeops\\_torch\\_loss](#), [mlr\\_pipeops\\_torch\\_model](#), [mlr\\_pipeops\\_torch\\_model\\_classif](#), [mlr\\_pipeops\\_torch\\_model\\_regr](#)

**Examples**

```
# Construct the PipeOp
pipeop = po("nn_adaptive_avg_pool3d")
pipeop
# The available parameters
pipeop$param_set
```

---

**mlr\_pipeops\_nn\_avg\_pool1d**  
*ID Average Pooling*

---

**Description**

Applies a 1D average pooling over an input signal composed of several input planes.

**nn\_module**

Calls [nn\\_avg\\_pool1d\(\)](#) during training.

**Parameters**

- `kernel_size` :: `(integer())`  
The size of the window. Can be a single number or a vector.

- `stride :: integer()`  
The stride of the window. Can be a single number or a vector. Default: `kernel_size`.
- `padding :: integer()`  
Implicit zero paddings on both sides of the input. Can be a single number or a vector. Default: 0.
- `ceil_mode :: integer()`  
When TRUE, will use ceil instead of floor to compute the output shape. Default: FALSE.
- `count_include_pad :: logical(1)`  
When TRUE, will include the zero-padding in the averaging calculation. Default: TRUE.
- `divisor_override :: logical(1)`  
If specified, it will be used as divisor, otherwise size of the pooling region will be used. Default: NULL. Only available for dimension greater than 1.

## Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

## State

The state is the value calculated by the public method `$shapes_out()`.

## Super classes

`mlr3pipelines::PipeOp -> mlr3torch::PipeOpTorch -> mlr3torch::PipeOpTorchAvgPool -> PipeOpTorchAvgPool1D`

## Methods

### Public methods:

- `PipeOpTorchAvgPool1D$new()`
- `PipeOpTorchAvgPool1D$clone()`

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

`PipeOpTorchAvgPool1D$new(id = "nn_avg_pool1d", param_vals = list())`

*Arguments:*

`id (character(1))`

Identifier of the resulting object.

`param_vals (list())`

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

`PipeOpTorchAvgPool1D$clone(deep = FALSE)`

*Arguments:*

`deep` Whether to make a deep clone.

## See Also

Other PipeOps: [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm1d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm2d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm3d](#), [mlr\\_pipeops\\_nn\\_block](#), [mlr\\_pipeops\\_nn\\_celu](#), [mlr\\_pipeops\\_nn\\_conv1d](#), [mlr\\_pipeops\\_nn\\_conv2d](#), [mlr\\_pipeops\\_nn\\_conv3d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose1d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose2d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose3d](#), [mlr\\_pipeops\\_nn\\_dropout](#), [mlr\\_pipeops\\_nn\\_elu](#), [mlr\\_pipeops\\_nn\\_flatten](#), [mlr\\_pipeops\\_nn\\_ft\\_cls](#), [mlr\\_pipeops\\_nn\\_ft\\_transformer\\_block](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_glu](#), [mlr\\_pipeops\\_nn\\_hardshrink](#), [mlr\\_pipeops\\_nn\\_hardsigmoid](#), [mlr\\_pipeops\\_nn\\_hardtanh](#), [mlr\\_pipeops\\_nn\\_head](#), [mlr\\_pipeops\\_nn\\_identity](#), [mlr\\_pipeops\\_nn\\_layer\\_norm](#), [mlr\\_pipeops\\_nn\\_leaky\\_relu](#), [mlr\\_pipeops\\_nn\\_linear](#), [mlr\\_pipeops\\_nn\\_log\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_max\\_pool1d](#), [mlr\\_pipeops\\_nn\\_max\\_pool2d](#), [mlr\\_pipeops\\_nn\\_max\\_pool3d](#), [mlr\\_pipeops\\_nn\\_merge](#), [mlr\\_pipeops\\_nn\\_merge\\_cat](#), [mlr\\_pipeops\\_nn\\_merge\\_prod](#), [mlr\\_pipeops\\_nn\\_merge\\_sum](#), [mlr\\_pipeops\\_nn\\_prelu](#), [mlr\\_pipeops\\_nn\\_reglu](#), [mlr\\_pipeops\\_nn\\_relu](#), [mlr\\_pipeops\\_nn\\_relu6](#), [mlr\\_pipeops\\_nn\\_reshape](#), [mlr\\_pipeops\\_nn\\_rrelu](#), [mlr\\_pipeops\\_nn\\_selu](#), [mlr\\_pipeops\\_nn\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_softmax](#), [mlr\\_pipeops\\_nn\\_softplus](#), [mlr\\_pipeops\\_nn\\_softshrink](#), [mlr\\_pipeops\\_nn\\_softsign](#), [mlr\\_pipeops\\_nn\\_squeeze](#), [mlr\\_pipeops\\_nn\\_tanh](#), [mlr\\_pipeops\\_nn\\_tanhshrink](#), [mlr\\_pipeops\\_nn\\_threshold](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_categ](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_num](#), [mlr\\_pipeops\\_nn\\_unsqueeze](#), [mlr\\_pipeops\\_torch\\_ingress](#), [mlr\\_pipeops\\_torch\\_ingress\\_categ](#), [mlr\\_pipeops\\_torch\\_ingress\\_ltnsr](#), [mlr\\_pipeops\\_torch\\_ingress\\_num](#), [mlr\\_pipeops\\_torch\\_loss](#), [mlr\\_pipeops\\_torch\\_model](#), [mlr\\_pipeops\\_torch\\_model\\_classif](#), [mlr\\_pipeops\\_torch\\_model\\_regr](#)

## Examples

```
# Construct the PipeOp
pipeop = po("nn_avg_pool1d")
pipeop
# The available parameters
pipeop$param_set
```

---

**mlr\_pipeops\_nn\_avg\_pool2d**  
*2D Average Pooling*

---

## Description

Applies 2D average-pooling operation in  $kH * kW$  regions by step size  $sH * sW$  steps. The number of output features is equal to the number of input planes.

### nn\_module

Calls [nn\\_avg\\_pool2d\(\)](#) during training.

### Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

## State

The state is the value calculated by the public method `$shapes_out()`.

## Parameters

- `kernel_size` :: `(integer())`  
The size of the window. Can be a single number or a vector.
- `stride` :: `integer()`  
The stride of the window. Can be a single number or a vector. Default: `kernel_size`.
- `padding` :: `integer()`  
Implicit zero paddings on both sides of the input. Can be a single number or a vector. Default: 0.
- `ceil_mode` :: `integer()`  
When TRUE, will use ceil instead of floor to compute the output shape. Default: FALSE.
- `count_include_pad` :: `logical(1)`  
When TRUE, will include the zero-padding in the averaging calculation. Default: TRUE.
- `divisor_override` :: `logical(1)`  
If specified, it will be used as divisor, otherwise size of the pooling region will be used. Default: NULL. Only available for dimension greater than 1.

## Super classes

```
mlr3pipelines::PipeOp -> mlr3torch::PipeOpTorch -> mlr3torch::PipeOpTorchAvgPool -> PipeOpTorchAvgPool2D
```

## Methods

### Public methods:

- `PipeOpTorchAvgPool2D$new()`
- `PipeOpTorchAvgPool2D$clone()`

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

```
PipeOpTorchAvgPool2D$new(id = "nn_avg_pool2d", param_vals = list())
```

*Arguments:*

`id` (`character(1)`)

Identifier of the resulting object.

`param_vals` (`list()`)

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

```
PipeOpTorchAvgPool2D$clone(deep = FALSE)
```

*Arguments:*

`deep` Whether to make a deep clone.

## See Also

Other PipeOps: [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm1d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm2d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm3d](#), [mlr\\_pipeops\\_nn\\_block](#), [mlr\\_pipeops\\_nn\\_celu](#), [mlr\\_pipeops\\_nn\\_conv1d](#), [mlr\\_pipeops\\_nn\\_conv2d](#), [mlr\\_pipeops\\_nn\\_conv3d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose1d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose2d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose3d](#), [mlr\\_pipeops\\_nn\\_dropout](#), [mlr\\_pipeops\\_nn\\_elu](#), [mlr\\_pipeops\\_nn\\_flatten](#), [mlr\\_pipeops\\_nn\\_ft\\_cls](#), [mlr\\_pipeops\\_nn\\_ft\\_transformer\\_block](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_glu](#), [mlr\\_pipeops\\_nn\\_hardshrink](#), [mlr\\_pipeops\\_nn\\_hardsigmoid](#), [mlr\\_pipeops\\_nn\\_hardtanh](#), [mlr\\_pipeops\\_nn\\_head](#), [mlr\\_pipeops\\_nn\\_identity](#), [mlr\\_pipeops\\_nn\\_layer\\_norm](#), [mlr\\_pipeops\\_nn\\_leaky\\_relu](#), [mlr\\_pipeops\\_nn\\_linear](#), [mlr\\_pipeops\\_nn\\_log\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_max\\_pool1d](#), [mlr\\_pipeops\\_nn\\_max\\_pool2d](#), [mlr\\_pipeops\\_nn\\_max\\_pool3d](#), [mlr\\_pipeops\\_nn\\_merge](#), [mlr\\_pipeops\\_nn\\_merge\\_cat](#), [mlr\\_pipeops\\_nn\\_merge\\_prod](#), [mlr\\_pipeops\\_nn\\_merge\\_sum](#), [mlr\\_pipeops\\_nn\\_prelu](#), [mlr\\_pipeops\\_nn\\_reglu](#), [mlr\\_pipeops\\_nn\\_relu](#), [mlr\\_pipeops\\_nn\\_relu6](#), [mlr\\_pipeops\\_nn\\_reshape](#), [mlr\\_pipeops\\_nn\\_rrelu](#), [mlr\\_pipeops\\_nn\\_selu](#), [mlr\\_pipeops\\_nn\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_softmax](#), [mlr\\_pipeops\\_nn\\_softplus](#), [mlr\\_pipeops\\_nn\\_softshrink](#), [mlr\\_pipeops\\_nn\\_softsign](#), [mlr\\_pipeops\\_nn\\_squeeze](#), [mlr\\_pipeops\\_nn\\_tanh](#), [mlr\\_pipeops\\_nn\\_tanhshrink](#), [mlr\\_pipeops\\_nn\\_threshold](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_categ](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_num](#), [mlr\\_pipeops\\_nn\\_unsqueeze](#), [mlr\\_pipeops\\_torch\\_ingress](#), [mlr\\_pipeops\\_torch\\_ingress\\_categ](#), [mlr\\_pipeops\\_torch\\_ingress\\_ltnsr](#), [mlr\\_pipeops\\_torch\\_ingress\\_num](#), [mlr\\_pipeops\\_torch\\_loss](#), [mlr\\_pipeops\\_torch\\_model](#), [mlr\\_pipeops\\_torch\\_model\\_classif](#), [mlr\\_pipeops\\_torch\\_model\\_regr](#)

## Examples

```
# Construct the PipeOp
pipeop = po("nn_avg_pool2d")
pipeop
# The available parameters
pipeop$param_set
```

---

**mlr\_pipeops\_nn\_avg\_pool3d**  
*3D Average Pooling*

---

## Description

Applies 3D average-pooling operation in  $kT * kH * kW$  regions by step size  $sT * sH * sW$  steps. The number of output features is equal to  $\lfloor \frac{\text{input planes}}{sT} \rfloor$ .

## Internals

Calls [nn\\_avg\\_pool3d\(\)](#) during training.

## Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

## State

The state is the value calculated by the public method `$shapes_out()`.

## Parameters

- `kernel_size` :: `(integer())`  
The size of the window. Can be a single number or a vector.
- `stride` :: `integer()`  
The stride of the window. Can be a single number or a vector. Default: `kernel_size`.
- `padding` :: `integer()`  
Implicit zero paddings on both sides of the input. Can be a single number or a vector. Default: 0.
- `ceil_mode` :: `integer()`  
When TRUE, will use ceil instead of floor to compute the output shape. Default: FALSE.
- `count_include_pad` :: `logical(1)`  
When TRUE, will include the zero-padding in the averaging calculation. Default: TRUE.
- `divisor_override` :: `logical(1)`  
If specified, it will be used as divisor, otherwise size of the pooling region will be used. Default: NULL. Only available for dimension greater than 1.

## Super classes

```
mlr3pipelines::PipeOp -> mlr3torch::PipeOpTorch -> mlr3torch::PipeOpTorchAvgPool -> PipeOpTorchAvgPool3D
```

## Methods

### Public methods:

- `PipeOpTorchAvgPool3D$new()`
- `PipeOpTorchAvgPool3D$clone()`

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

```
PipeOpTorchAvgPool3D$new(id = "nn_avg_pool3d", param_vals = list())
```

*Arguments:*

`id` (`character(1)`)

Identifier of the resulting object.

`param_vals` (`list()`)

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

```
PipeOpTorchAvgPool3D$clone(deep = FALSE)
```

*Arguments:*

`deep` Whether to make a deep clone.

## See Also

Other PipeOps: [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm1d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm2d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm3d](#), [mlr\\_pipeops\\_nn\\_block](#), [mlr\\_pipeops\\_nn\\_celu](#), [mlr\\_pipeops\\_nn\\_conv1d](#), [mlr\\_pipeops\\_nn\\_conv2d](#), [mlr\\_pipeops\\_nn\\_conv3d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose1d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose2d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose3d](#), [mlr\\_pipeops\\_nn\\_dropout](#), [mlr\\_pipeops\\_nn\\_elu](#), [mlr\\_pipeops\\_nn\\_flatten](#), [mlr\\_pipeops\\_nn\\_ft\\_cls](#), [mlr\\_pipeops\\_nn\\_ft\\_transformer\\_block](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_glu](#), [mlr\\_pipeops\\_nn\\_hardshrink](#), [mlr\\_pipeops\\_nn\\_hardsigmoid](#), [mlr\\_pipeops\\_nn\\_hardtanh](#), [mlr\\_pipeops\\_nn\\_head](#), [mlr\\_pipeops\\_nn\\_identity](#), [mlr\\_pipeops\\_nn\\_layer\\_norm](#), [mlr\\_pipeops\\_nn\\_leaky\\_relu](#), [mlr\\_pipeops\\_nn\\_linear](#), [mlr\\_pipeops\\_nn\\_log\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_max\\_pool1d](#), [mlr\\_pipeops\\_nn\\_max\\_pool2d](#), [mlr\\_pipeops\\_nn\\_max\\_pool3d](#), [mlr\\_pipeops\\_nn\\_merge](#), [mlr\\_pipeops\\_nn\\_merge\\_cat](#), [mlr\\_pipeops\\_nn\\_merge\\_prod](#), [mlr\\_pipeops\\_nn\\_merge\\_sum](#), [mlr\\_pipeops\\_nn\\_prelu](#), [mlr\\_pipeops\\_nn\\_reglu](#), [mlr\\_pipeops\\_nn\\_relu](#), [mlr\\_pipeops\\_nn\\_relu6](#), [mlr\\_pipeops\\_nn\\_reshape](#), [mlr\\_pipeops\\_nn\\_rrelu](#), [mlr\\_pipeops\\_nn\\_selu](#), [mlr\\_pipeops\\_nn\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_softmax](#), [mlr\\_pipeops\\_nn\\_softplus](#), [mlr\\_pipeops\\_nn\\_softshrink](#), [mlr\\_pipeops\\_nn\\_softsign](#), [mlr\\_pipeops\\_nn\\_squeeze](#), [mlr\\_pipeops\\_nn\\_tanh](#), [mlr\\_pipeops\\_nn\\_tanhshrink](#), [mlr\\_pipeops\\_nn\\_threshold](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_categ](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_num](#), [mlr\\_pipeops\\_nn\\_unsqueeze](#), [mlr\\_pipeops\\_torch\\_ingress](#), [mlr\\_pipeops\\_torch\\_ingress\\_categ](#), [mlr\\_pipeops\\_torch\\_ingress\\_ltnsr](#), [mlr\\_pipeops\\_torch\\_ingress\\_num](#), [mlr\\_pipeops\\_torch\\_loss](#), [mlr\\_pipeops\\_torch\\_model](#), [mlr\\_pipeops\\_torch\\_model\\_classif](#), [mlr\\_pipeops\\_torch\\_model\\_regr](#)

## Examples

```
# Construct the PipeOp
pipeop = po("nn_avg_pool3d")
pipeop
# The available parameters
pipeop$param_set
```

---

**mlr\_pipeops\_nn\_batch\_norm1d**  
*ID Batch Normalization*

---

## Description

Applies Batch Normalization for each channel across a batch of data.

### nn\_module

Calls [torch::nn\\_batch\\_norm1d\(\)](#). The parameter num\_features is inferred as the second dimension of the input shape.

## Parameters

- `eps` :: `numeric(1)`  
A value added to the denominator for numerical stability. Default: 1e-5.
- `momentum` :: `numeric(1)`  
The value used for the `running_mean` and `running_var` computation. Can be set to `NULL` for cumulative moving average (i.e. simple average). Default: 0.1
- `affine` :: `logical(1)`  
a boolean value that when set to `TRUE`, this module has learnable affine parameters. Default: `TRUE`
- `track_running_stats` :: `logical(1)`  
a boolean value that when set to `TRUE`, this module tracks the running mean and variance, and when set to `FALSE`, this module does not track such statistics and always uses batch statistics in both training and eval modes. Default: `TRUE`

## Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

## State

The state is the value calculated by the public method `$shapes_out()`.

## Super classes

`mlr3pipelines::PipeOp -> mlr3torch::PipeOpTorch -> mlr3torch::PipeOpTorchBatchNorm -> PipeOpTorchBatchNorm1D`

## Methods

### Public methods:

- [PipeOpTorchBatchNorm1D\\$new\(\)](#)
- [PipeOpTorchBatchNorm1D\\$clone\(\)](#)

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

`PipeOpTorchBatchNorm1D$new(id = "nn_batch_norm1d", param_vals = list())`

*Arguments:*

`id` (`character(1)`)

Identifier of the resulting object.

`param_vals` (`list()`)

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

```
PipeOpTorchBatchNorm1D$clone(deep = FALSE)
```

*Arguments:*

deep Whether to make a deep clone.

## See Also

Other PipeOps: [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm2d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm3d](#), [mlr\\_pipeops\\_nn\\_block](#), [mlr\\_pipeops\\_nn\\_celu](#), [mlr\\_pipeops\\_nn\\_conv1d](#), [mlr\\_pipeops\\_nn\\_conv2d](#), [mlr\\_pipeops\\_nn\\_conv3d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose1d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose2d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose3d](#), [mlr\\_pipeops\\_nn\\_dropout](#), [mlr\\_pipeops\\_nn\\_elu](#), [mlr\\_pipeops\\_nn\\_flatten](#), [mlr\\_pipeops\\_nn\\_ft\\_cls](#), [mlr\\_pipeops\\_nn\\_ft\\_transformer\\_block](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_glu](#), [mlr\\_pipeops\\_nn\\_hardshrink](#), [mlr\\_pipeops\\_nn\\_hardsigmoid](#), [mlr\\_pipeops\\_nn\\_hardtanh](#), [mlr\\_pipeops\\_nn\\_head](#), [mlr\\_pipeops\\_nn\\_identity](#), [mlr\\_pipeops\\_nn\\_layer\\_norm](#), [mlr\\_pipeops\\_nn\\_leaky\\_relu](#), [mlr\\_pipeops\\_nn\\_linear](#), [mlr\\_pipeops\\_nn\\_log\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_max\\_pool1d](#), [mlr\\_pipeops\\_nn\\_max\\_pool2d](#), [mlr\\_pipeops\\_nn\\_max\\_pool3d](#), [mlr\\_pipeops\\_nn\\_merge](#), [mlr\\_pipeops\\_nn\\_merge\\_cat](#), [mlr\\_pipeops\\_nn\\_merge\\_prod](#), [mlr\\_pipeops\\_nn\\_merge\\_sum](#), [mlr\\_pipeops\\_nn\\_prelu](#), [mlr\\_pipeops\\_nn\\_reglu](#), [mlr\\_pipeops\\_nn\\_relu](#), [mlr\\_pipeops\\_nn\\_relu6](#), [mlr\\_pipeops\\_nn\\_reshape](#), [mlr\\_pipeops\\_nn\\_rrelu](#), [mlr\\_pipeops\\_nn\\_selu](#), [mlr\\_pipeops\\_nn\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_softmax](#), [mlr\\_pipeops\\_nn\\_softplus](#), [mlr\\_pipeops\\_nn\\_softshrink](#), [mlr\\_pipeops\\_nn\\_softsign](#), [mlr\\_pipeops\\_nn\\_squeeze](#), [mlr\\_pipeops\\_nn\\_tanh](#), [mlr\\_pipeops\\_nn\\_tanhshrink](#), [mlr\\_pipeops\\_nn\\_threshold](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_categ](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_num](#), [mlr\\_pipeops\\_nn\\_unsqueeze](#), [mlr\\_pipeops\\_torch\\_ingress](#), [mlr\\_pipeops\\_torch\\_ingress\\_categ](#), [mlr\\_pipeops\\_torch\\_ingress\\_ltnsr](#), [mlr\\_pipeops\\_torch\\_ingress\\_num](#), [mlr\\_pipeops\\_torch\\_loss](#), [mlr\\_pipeops\\_torch\\_model](#), [mlr\\_pipeops\\_torch\\_model\\_classif](#), [mlr\\_pipeops\\_torch\\_model\\_regr](#)

## Examples

```
# Construct the PipeOp
pipeop = po("nn_batch_norm1d")
pipeop
# The available parameters
pipeop$param_set
```

---

mlr\_pipeops\_nn\_batch\_norm2d  
2D Batch Normalization

---

## Description

Applies Batch Normalization for each channel across a batch of data.

### nn\_module

Calls [torch::nn\\_batch\\_norm2d\(\)](#). The parameter num\_features is inferred as the second dimension of the input shape.

## Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

## State

The state is the value calculated by the public method `$shapes_out()`.

## Parameters

- `eps :: numeric(1)`  
A value added to the denominator for numerical stability. Default: 1e-5.
- `momentum :: numeric(1)`  
The value used for the `running_mean` and `running_var` computation. Can be set to `NULL` for cumulative moving average (i.e. simple average). Default: 0.1
- `affine :: logical(1)`  
a boolean value that when set to `TRUE`, this module has learnable affine parameters. Default: `TRUE`
- `track_running_stats :: logical(1)`  
a boolean value that when set to `TRUE`, this module tracks the running mean and variance, and when set to `FALSE`, this module does not track such statistics and always uses batch statistics in both training and eval modes. Default: `TRUE`

## Super classes

```
mlr3pipelines::PipeOp -> mlr3torch::PipeOpTorch -> mlr3torch::PipeOpTorchBatchNorm
-> PipeOpTorchBatchNorm2D
```

## Methods

### Public methods:

- [PipeOpTorchBatchNorm2D\\$new\(\)](#)
- [PipeOpTorchBatchNorm2D\\$clone\(\)](#)

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

```
PipeOpTorchBatchNorm2D$new(id = "nn_batch_norm2d", param_vals = list())
```

*Arguments:*

`id` (`character(1)`)

Identifier of the resulting object.

`param_vals` (`list()`)

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

```
PipeOpTorchBatchNorm2D$clone(deep = FALSE)
```

*Arguments:*

deep Whether to make a deep clone.

## See Also

Other PipeOps: [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm1d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm3d](#), [mlr\\_pipeops\\_nn\\_block](#), [mlr\\_pipeops\\_nn\\_celu](#), [mlr\\_pipeops\\_nn\\_conv1d](#), [mlr\\_pipeops\\_nn\\_conv2d](#), [mlr\\_pipeops\\_nn\\_conv3d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose1d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose2d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose3d](#), [mlr\\_pipeops\\_nn\\_dropout](#), [mlr\\_pipeops\\_nn\\_elu](#), [mlr\\_pipeops\\_nn\\_flatten](#), [mlr\\_pipeops\\_nn\\_ft\\_cls](#), [mlr\\_pipeops\\_nn\\_ft\\_transformer\\_block](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_glu](#), [mlr\\_pipeops\\_nn\\_hardshrink](#), [mlr\\_pipeops\\_nn\\_hardsigmoid](#), [mlr\\_pipeops\\_nn\\_hardtanh](#), [mlr\\_pipeops\\_nn\\_head](#), [mlr\\_pipeops\\_nn\\_identity](#), [mlr\\_pipeops\\_nn\\_layer\\_norm](#), [mlr\\_pipeops\\_nn\\_leaky\\_relu](#), [mlr\\_pipeops\\_nn\\_linear](#), [mlr\\_pipeops\\_nn\\_log\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_max\\_pool1d](#), [mlr\\_pipeops\\_nn\\_max\\_pool2d](#), [mlr\\_pipeops\\_nn\\_max\\_pool3d](#), [mlr\\_pipeops\\_nn\\_merge](#), [mlr\\_pipeops\\_nn\\_merge\\_cat](#), [mlr\\_pipeops\\_nn\\_merge\\_prod](#), [mlr\\_pipeops\\_nn\\_merge\\_sum](#), [mlr\\_pipeops\\_nn\\_prelu](#), [mlr\\_pipeops\\_nn\\_reglu](#), [mlr\\_pipeops\\_nn\\_relu](#), [mlr\\_pipeops\\_nn\\_relu6](#), [mlr\\_pipeops\\_nn\\_reshape](#), [mlr\\_pipeops\\_nn\\_rrelu](#), [mlr\\_pipeops\\_nn\\_selu](#), [mlr\\_pipeops\\_nn\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_softmax](#), [mlr\\_pipeops\\_nn\\_softplus](#), [mlr\\_pipeops\\_nn\\_softshrink](#), [mlr\\_pipeops\\_nn\\_softsign](#), [mlr\\_pipeops\\_nn\\_squeeze](#), [mlr\\_pipeops\\_nn\\_tanh](#), [mlr\\_pipeops\\_nn\\_tanhshrink](#), [mlr\\_pipeops\\_nn\\_threshold](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_categ](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_num](#), [mlr\\_pipeops\\_nn\\_unsqueeze](#), [mlr\\_pipeops\\_torch\\_ingress](#), [mlr\\_pipeops\\_torch\\_ingress\\_categ](#), [mlr\\_pipeops\\_torch\\_ingress\\_ltnsr](#), [mlr\\_pipeops\\_torch\\_ingress\\_num](#), [mlr\\_pipeops\\_torch\\_loss](#), [mlr\\_pipeops\\_torch\\_model](#), [mlr\\_pipeops\\_torch\\_model\\_classif](#), [mlr\\_pipeops\\_torch\\_model\\_regr](#)

## Examples

```
# Construct the PipeOp
pipeop = po("nn_batch_norm2d")
pipeop
# The available parameters
pipeop$param_set
```

---

**mlr\_pipeops\_nn\_batch\_norm3d**  
*3D Batch Normalization*

---

## Description

Applies Batch Normalization for each channel across a batch of data.

### nn\_module

Calls [torch::nn\\_batch\\_norm3d\(\)](#). The parameter num\_features is inferred as the second dimension of the input shape.

## Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

## State

The state is the value calculated by the public method `$shapes_out()`.

## Parameters

- `eps :: numeric(1)`  
A value added to the denominator for numerical stability. Default: 1e-5.
- `momentum :: numeric(1)`  
The value used for the `running_mean` and `running_var` computation. Can be set to `NULL` for cumulative moving average (i.e. simple average). Default: 0.1
- `affine :: logical(1)`  
a boolean value that when set to `TRUE`, this module has learnable affine parameters. Default: `TRUE`
- `track_running_stats :: logical(1)`  
a boolean value that when set to `TRUE`, this module tracks the running mean and variance, and when set to `FALSE`, this module does not track such statistics and always uses batch statistics in both training and eval modes. Default: `TRUE`

## Super classes

```
mlr3pipelines::PipeOp -> mlr3torch::PipeOpTorch -> mlr3torch::PipeOpTorchBatchNorm
-> PipeOpTorchBatchNorm3D
```

## Methods

### Public methods:

- [PipeOpTorchBatchNorm3D\\$new\(\)](#)
- [PipeOpTorchBatchNorm3D\\$clone\(\)](#)

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

```
PipeOpTorchBatchNorm3D$new(id = "nn_batch_norm3d", param_vals = list())
```

*Arguments:*

`id` (`character(1)`)

Identifier of the resulting object.

`param_vals` (`list()`)

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

```
PipeOpTorchBatchNorm3D$clone(deep = FALSE)
```

*Arguments:*

deep Whether to make a deep clone.

## See Also

Other PipeOps: [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm1d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm2d](#), [mlr\\_pipeops\\_nn\\_block](#), [mlr\\_pipeops\\_nn\\_celu](#), [mlr\\_pipeops\\_nn\\_conv1d](#), [mlr\\_pipeops\\_nn\\_conv2d](#), [mlr\\_pipeops\\_nn\\_conv3d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose1d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose2d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose3d](#), [mlr\\_pipeops\\_nn\\_dropout](#), [mlr\\_pipeops\\_nn\\_elu](#), [mlr\\_pipeops\\_nn\\_flatten](#), [mlr\\_pipeops\\_nn\\_ft\\_cls](#), [mlr\\_pipeops\\_nn\\_ft\\_transformer\\_block](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_glu](#), [mlr\\_pipeops\\_nn\\_hardshrink](#), [mlr\\_pipeops\\_nn\\_hardsigmoid](#), [mlr\\_pipeops\\_nn\\_hardtanh](#), [mlr\\_pipeops\\_nn\\_head](#), [mlr\\_pipeops\\_nn\\_identity](#), [mlr\\_pipeops\\_nn\\_layer\\_norm](#), [mlr\\_pipeops\\_nn\\_leaky\\_relu](#), [mlr\\_pipeops\\_nn\\_linear](#), [mlr\\_pipeops\\_nn\\_log\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_max\\_pool1d](#), [mlr\\_pipeops\\_nn\\_max\\_pool2d](#), [mlr\\_pipeops\\_nn\\_max\\_pool3d](#), [mlr\\_pipeops\\_nn\\_merge](#), [mlr\\_pipeops\\_nn\\_merge\\_cat](#), [mlr\\_pipeops\\_nn\\_merge\\_prod](#), [mlr\\_pipeops\\_nn\\_merge\\_sum](#), [mlr\\_pipeops\\_nn\\_prelu](#), [mlr\\_pipeops\\_nn\\_reglu](#), [mlr\\_pipeops\\_nn\\_relu](#), [mlr\\_pipeops\\_nn\\_relu6](#), [mlr\\_pipeops\\_nn\\_reshape](#), [mlr\\_pipeops\\_nn\\_rrelu](#), [mlr\\_pipeops\\_nn\\_selu](#), [mlr\\_pipeops\\_nn\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_softmax](#), [mlr\\_pipeops\\_nn\\_softplus](#), [mlr\\_pipeops\\_nn\\_softshrink](#), [mlr\\_pipeops\\_nn\\_softsign](#), [mlr\\_pipeops\\_nn\\_squeeze](#), [mlr\\_pipeops\\_nn\\_tanh](#), [mlr\\_pipeops\\_nn\\_tanhshrink](#), [mlr\\_pipeops\\_nn\\_threshold](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_categ](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_num](#), [mlr\\_pipeops\\_nn\\_unsqueeze](#), [mlr\\_pipeops\\_torch\\_ingress](#), [mlr\\_pipeops\\_torch\\_ingress\\_categ](#), [mlr\\_pipeops\\_torch\\_ingress\\_ltnsr](#), [mlr\\_pipeops\\_torch\\_ingress\\_num](#), [mlr\\_pipeops\\_torch\\_loss](#), [mlr\\_pipeops\\_torch\\_model](#), [mlr\\_pipeops\\_torch\\_model\\_classif](#), [mlr\\_pipeops\\_torch\\_model\\_regr](#)

## Examples

```
# Construct the PipeOp
pipeop = po("nn_batch_norm3d")
pipeop
# The available parameters
pipeop$param_set
```

---

**mlr\_pipeops\_nn\_block** *Block Repetition*

---

## Description

Repeat a block `n_blocks` times by concatenating it with itself (via `%>>%`).

## Naming

For the generated module graph, the IDs of the modules are generated by prefixing the IDs of the `n_blocks` layers with the ID of the `PipeOpTorchBlock` and postfixing them with `__<layer>`.

## Parameters

The parameters available for the provided block, as well as

- `n_blocks` :: `integer(1)`  
How often to repeat the block.
- `trafo` :: `function(i, param_vals, param_set) -> list()`  
A function that allows to transform the parameters values of each layer (block). Here,
  - `i` :: `integer(1)`  
is the index of the layer, ranging from 1 to `n_blocks`.
  - `param_vals` :: `named list()`  
are the parameter values of the layer `i`.
  - `param_set` :: `ParamSet`  
is the parameter set of the whole `PipeOpTorchBlock`.

The function must return the modified parameter values for the given layer. This, e.g., allows for special behavior of the first or last layer.

## Input and Output Channels

The PipeOp sets its input and output channels to those from the block (Graph) it received during construction.

## State

The state is the value calculated by the public method `$shapes_out()`.

## Super classes

`mlr3pipelines::PipeOp -> mlr3torch::PipeOpTorch -> PipeOpTorchBlock`

## Active bindings

`block` (`Graph`)

The neural network segment that is repeated by this PipeOp.

## Methods

### Public methods:

- `PipeOpTorchBlock$new()`
- `PipeOpTorchBlock$clone()`

**Method** `new()`: Creates a new instance of this `R6` class.

*Usage:*

`PipeOpTorchBlock$new(block, id = "nn_block", param_vals = list())`

*Arguments:*

`block` (`Graph`)

A graph consisting primarily of `PipeOpTorch` objects that is to be repeated.

```

  id (character(1))
    The id for of the new object.
  param_vals (named list())
    Parameter values to be set after construction.

```

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

```
PipeOpTorchBlock$clone(deep = FALSE)
```

*Arguments:*

```
deep Whether to make a deep clone.
```

## See Also

Other PipeOps: [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm1d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm2d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm3d](#), [mlr\\_pipeops\\_nn\\_celu](#), [mlr\\_pipeops\\_nn\\_conv1d](#), [mlr\\_pipeops\\_nn\\_conv2d](#), [mlr\\_pipeops\\_nn\\_conv3d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose1d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose2d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose3d](#), [mlr\\_pipeops\\_nn\\_dropout](#), [mlr\\_pipeops\\_nn\\_elu](#), [mlr\\_pipeops\\_nn\\_flatten](#), [mlr\\_pipeops\\_nn\\_ft\\_cls](#), [mlr\\_pipeops\\_nn\\_ft\\_transformer\\_block](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_glu](#), [mlr\\_pipeops\\_nn\\_hardshrink](#), [mlr\\_pipeops\\_nn\\_hardsigmoid](#), [mlr\\_pipeops\\_nn\\_hardtanh](#), [mlr\\_pipeops\\_nn\\_head](#), [mlr\\_pipeops\\_nn\\_identity](#), [mlr\\_pipeops\\_nn\\_layer\\_norm](#), [mlr\\_pipeops\\_nn\\_leaky\\_relu](#), [mlr\\_pipeops\\_nn\\_linear](#), [mlr\\_pipeops\\_nn\\_log\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_max\\_pool1d](#), [mlr\\_pipeops\\_nn\\_max\\_pool2d](#), [mlr\\_pipeops\\_nn\\_max\\_pool3d](#), [mlr\\_pipeops\\_nn\\_merge](#), [mlr\\_pipeops\\_nn\\_merge\\_cat](#), [mlr\\_pipeops\\_nn\\_merge\\_prod](#), [mlr\\_pipeops\\_nn\\_merge\\_sum](#), [mlr\\_pipeops\\_nn\\_prelu](#), [mlr\\_pipeops\\_nn\\_reglu](#), [mlr\\_pipeops\\_nn\\_relu](#), [mlr\\_pipeops\\_nn\\_relu6](#), [mlr\\_pipeops\\_nn\\_reshape](#), [mlr\\_pipeops\\_nn\\_rrelu](#), [mlr\\_pipeops\\_nn\\_selu](#), [mlr\\_pipeops\\_nn\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_softmax](#), [mlr\\_pipeops\\_nn\\_softplus](#), [mlr\\_pipeops\\_nn\\_softshrink](#), [mlr\\_pipeops\\_nn\\_softsign](#), [mlr\\_pipeops\\_nn\\_squeeze](#), [mlr\\_pipeops\\_nn\\_tanh](#), [mlr\\_pipeops\\_nn\\_tanhshrink](#), [mlr\\_pipeops\\_nn\\_threshold](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_categ](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_num](#), [mlr\\_pipeops\\_nn\\_unsqueeze](#), [mlr\\_pipeops\\_torch\\_ingress](#), [mlr\\_pipeops\\_torch\\_ingress\\_categ](#), [mlr\\_pipeops\\_torch\\_ingress\\_ltnsr](#), [mlr\\_pipeops\\_torch\\_ingress\\_num](#), [mlr\\_pipeops\\_torch\\_loss](#), [mlr\\_pipeops\\_torch\\_model](#), [mlr\\_pipeops\\_torch\\_model\\_classif](#), [mlr\\_pipeops\\_torch\\_model\\_regr](#)

## Examples

```

# repeat a simple linear layer with ReLU activation 3 times, but set the bias for the last
# layer to `FALSE`
block = nn("linear") %>>% nn("relu")

blocks = nn("block", block,
  linear.out_features = 10L, linear.bias = TRUE, n_blocks = 3,
  trafo = function(i, param_vals, param_set) {
    if (i == param_set$get_values()$n_blocks) {
      param_vals$linear.bias = FALSE
    }
    param_vals
  })
graph = po("torch_ingress_num") %>>%

```

```

blocks %>>%
  nn("head")
md = graph$train(tsk("iris"))[[1L]]
network = model_descriptor_to_module(md)
network

```

---

`mlr_pipeops_nn_celu`    *CELU Activation Function*

---

## Description

Applies element-wise,  $CELU(x) = \max(0, x) + \min(0, \alpha * (\exp(x\alpha) - 1))$ .

### `nn_module`

Calls `torch::nn_celu()` when trained.

### Parameters

- `alpha` :: `numeric(1)`  
The alpha value for the ELU formulation. Default: 1.0
- `inplace` :: `logical(1)`  
Whether to do the operation in-place. Default: FALSE.

### Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

### State

The state is the value calculated by the public method `$shapes_out()`.

### Super classes

`mlr3pipelines::PipeOp` -> `mlr3torch::PipeOpTorch` -> `PipeOpTorchCELU`

### Methods

#### Public methods:

- `PipeOpTorchCELU$new()`
- `PipeOpTorchCELU$clone()`

**Method** `new()`: Creates a new instance of this `R6` class.

*Usage:*

`PipeOpTorchCELU$new(id = "nn_celu", param_vals = list())`

*Arguments:*

`id` (character(1))  
 Identifier of the resulting object.  
`param_vals` (list())  
 List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

```
PipeOpTorchCELU$clone(deep = FALSE)
```

*Arguments:*

`deep` Whether to make a deep clone.

## See Also

Other PipeOps: [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm1d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm2d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm3d](#), [mlr\\_pipeops\\_nn\\_block](#), [mlr\\_pipeops\\_nn\\_conv1d](#), [mlr\\_pipeops\\_nn\\_conv2d](#), [mlr\\_pipeops\\_nn\\_conv3d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose1d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose2d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose3d](#), [mlr\\_pipeops\\_nn\\_dropout](#), [mlr\\_pipeops\\_nn\\_elu](#), [mlr\\_pipeops\\_nn\\_flatten](#), [mlr\\_pipeops\\_nn\\_ft\\_cls](#), [mlr\\_pipeops\\_nn\\_ft\\_transformer\\_block](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_glu](#), [mlr\\_pipeops\\_nn\\_hardshrink](#), [mlr\\_pipeops\\_nn\\_hardsigmoid](#), [mlr\\_pipeops\\_nn\\_hardtanh](#), [mlr\\_pipeops\\_nn\\_head](#), [mlr\\_pipeops\\_nn\\_identity](#), [mlr\\_pipeops\\_nn\\_layer\\_norm](#), [mlr\\_pipeops\\_nn\\_leaky\\_relu](#), [mlr\\_pipeops\\_nn\\_linear](#), [mlr\\_pipeops\\_nn\\_log\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_max\\_pool1d](#), [mlr\\_pipeops\\_nn\\_max\\_pool2d](#), [mlr\\_pipeops\\_nn\\_max\\_pool3d](#), [mlr\\_pipeops\\_nn\\_merge](#), [mlr\\_pipeops\\_nn\\_merge\\_cat](#), [mlr\\_pipeops\\_nn\\_merge\\_prod](#), [mlr\\_pipeops\\_nn\\_merge\\_sum](#), [mlr\\_pipeops\\_nn\\_prelu](#), [mlr\\_pipeops\\_nn\\_reglu](#), [mlr\\_pipeops\\_nn\\_relu](#), [mlr\\_pipeops\\_nn\\_relu6](#), [mlr\\_pipeops\\_nn\\_reshape](#), [mlr\\_pipeops\\_nn\\_rrelu](#), [mlr\\_pipeops\\_nn\\_selu](#), [mlr\\_pipeops\\_nn\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_softmax](#), [mlr\\_pipeops\\_nn\\_softplus](#), [mlr\\_pipeops\\_nn\\_softshrink](#), [mlr\\_pipeops\\_nn\\_softsign](#), [mlr\\_pipeops\\_nn\\_squeeze](#), [mlr\\_pipeops\\_nn\\_tanh](#), [mlr\\_pipeops\\_nn\\_tanhshrink](#), [mlr\\_pipeops\\_nn\\_threshold](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_categ](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_num](#), [mlr\\_pipeops\\_nn\\_unsqueeze](#), [mlr\\_pipeops\\_torch\\_ingress](#), [mlr\\_pipeops\\_torch\\_ingress\\_categ](#), [mlr\\_pipeops\\_torch\\_ingress\\_ltnsr](#), [mlr\\_pipeops\\_torch\\_ingress\\_num](#), [mlr\\_pipeops\\_torch\\_loss](#), [mlr\\_pipeops\\_torch\\_model](#), [mlr\\_pipeops\\_torch\\_model\\_classif](#), [mlr\\_pipeops\\_torch\\_model\\_regr](#)

## Examples

```
# Construct the PipeOp
pipeop = po("nn_celu")
pipeop
# The available parameters
pipeop$param_set
```

---

**mlr\_pipeops\_nn\_conv1d** *ID Convolution*

---

## Description

Applies a 1D convolution over an input signal composed of several input planes.

### nn\_module

Calls `torch::nn_conv1d()` when trained. The parameter `in_channels` is inferred from the second dimension of the input tensor.

### Parameters

- `out_channels` :: `integer(1)`  
Number of channels produced by the convolution.
- `kernel_size` :: `integer()`  
Size of the convolving kernel.
- `stride` :: `integer()`  
Stride of the convolution. The default is 1.
- `padding` :: `integer()`  
 $dilation * (kernel\_size - 1) - padding$  zero-padding will be added to both sides of the input. Default: 0.
- `groups` :: `integer()`  
Number of blocked connections from input channels to output channels. Default: 1
- `bias` :: `logical(1)`  
If TRUE, adds a learnable bias to the output. Default: TRUE.
- `dilation` :: `integer()`  
Spacing between kernel elements. Default: 1.
- `padding_mode` :: `character(1)`  
The padding mode. One of "zeros", "reflect", "replicate", or "circular". Default is "zeros".

### Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

### State

The state is the value calculated by the public method `$shapes_out()`.

### Super classes

`mlr3pipelines::PipeOp` -> `mlr3torch::PipeOpTorch` -> `mlr3torch::PipeOpTorchConv` -> `PipeOpTorchConv1D`

## Methods

### Public methods:

- `PipeOpTorchConv1D$new()`
- `PipeOpTorchConv1D$clone()`

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

```
PipeOpTorchConv1D$new(id = "nn_conv1d", param_vals = list())
```

*Arguments:*

`id` (character(1))

Identifier of the resulting object.

`param_vals` (list())

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

```
PipeOpTorchConv1D$clone(deep = FALSE)
```

*Arguments:*

`deep` Whether to make a deep clone.

## See Also

Other PipeOps: [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm1d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm2d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm3d](#), [mlr\\_pipeops\\_nn\\_block](#), [mlr\\_pipeops\\_nn\\_celu](#), [mlr\\_pipeops\\_nn\\_conv2d](#), [mlr\\_pipeops\\_nn\\_conv3d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose1d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose2d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose3d](#), [mlr\\_pipeops\\_nn\\_dropout](#), [mlr\\_pipeops\\_nn\\_elu](#), [mlr\\_pipeops\\_nn\\_flatten](#), [mlr\\_pipeops\\_nn\\_ft\\_cls](#), [mlr\\_pipeops\\_nn\\_ft\\_transformer\\_block](#), [mlr\\_pipeops\\_nn\\_geglu](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_glu](#), [mlr\\_pipeops\\_nn\\_hardshrink](#), [mlr\\_pipeops\\_nn\\_hardsigmoid](#), [mlr\\_pipeops\\_nn\\_hardtanh](#), [mlr\\_pipeops\\_nn\\_head](#), [mlr\\_pipeops\\_nn\\_identity](#), [mlr\\_pipeops\\_nn\\_layer\\_norm](#), [mlr\\_pipeops\\_nn\\_leaky\\_relu](#), [mlr\\_pipeops\\_nn\\_linear](#), [mlr\\_pipeops\\_nn\\_log\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_max\\_pool1d](#), [mlr\\_pipeops\\_nn\\_max\\_pool2d](#), [mlr\\_pipeops\\_nn\\_max\\_pool3d](#), [mlr\\_pipeops\\_nn\\_merge](#), [mlr\\_pipeops\\_nn\\_merge\\_cat](#), [mlr\\_pipeops\\_nn\\_merge\\_prod](#), [mlr\\_pipeops\\_nn\\_merge\\_sum](#), [mlr\\_pipeops\\_nn\\_prelu](#), [mlr\\_pipeops\\_nn\\_reglu](#), [mlr\\_pipeops\\_nn\\_relu](#), [mlr\\_pipeops\\_nn\\_relu6](#), [mlr\\_pipeops\\_nn\\_reshape](#), [mlr\\_pipeops\\_nn\\_rrelu](#), [mlr\\_pipeops\\_nn\\_selu](#), [mlr\\_pipeops\\_nn\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_softmax](#), [mlr\\_pipeops\\_nn\\_softplus](#), [mlr\\_pipeops\\_nn\\_softshrink](#), [mlr\\_pipeops\\_nn\\_softsign](#), [mlr\\_pipeops\\_nn\\_squeeze](#), [mlr\\_pipeops\\_nn\\_tanh](#), [mlr\\_pipeops\\_nn\\_tanhshrink](#), [mlr\\_pipeops\\_nn\\_threshold](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_categ](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_num](#), [mlr\\_pipeops\\_nn\\_unsqueeze](#), [mlr\\_pipeops\\_torch\\_ingress](#), [mlr\\_pipeops\\_torch\\_ingress\\_categ](#), [mlr\\_pipeops\\_torch\\_ingress\\_ltnsr](#), [mlr\\_pipeops\\_torch\\_ingress\\_num](#), [mlr\\_pipeops\\_torch\\_loss](#), [mlr\\_pipeops\\_torch\\_model](#), [mlr\\_pipeops\\_torch\\_model\\_classif](#), [mlr\\_pipeops\\_torch\\_model\\_regr](#)

## Examples

```
# Construct the PipeOp
pipeop = po("nn_conv1d", kernel_size = 10, out_channels = 1)
pipeop
# The available parameters
pipeop$param_set
```

---

mlr\_pipeops\_nn\_conv2d *2D Convolution*

---

## Description

Applies a 2D convolution over an input image composed of several input planes.

### nn\_module

Calls [torch::nn\\_conv2d\(\)](#) when trained. The parameter `in_channels` is inferred from the second dimension of the input tensor.

### Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

### State

The state is the value calculated by the public method `$shapes_out()`.

### Parameters

- `out_channels` :: `integer(1)`  
Number of channels produced by the convolution.
- `kernel_size` :: `integer()`  
Size of the convolving kernel.
- `stride` :: `integer()`  
Stride of the convolution. The default is 1.
- `padding` :: `integer()`  
 $dilation * (kernel\_size - 1) - padding$  zero-padding will be added to both sides of the input. Default: 0.
- `groups` :: `integer()`  
Number of blocked connections from input channels to output channels. Default: 1
- `bias` :: `logical(1)`  
If TRUE, adds a learnable bias to the output. Default: TRUE.
- `dilation` :: `integer()`  
Spacing between kernel elements. Default: 1.

- `padding_mode` :: `character(1)`  
The padding mode. One of "zeros", "reflect", "replicate", or "circular". Default is "zeros".

## Super classes

`mlr3pipelines::PipeOp -> mlr3torch::PipeOpTorch -> mlr3torch::PipeOpTorchConv -> PipeOpTorchConv2D`

## Methods

### Public methods:

- `PipeOpTorchConv2D$new()`
- `PipeOpTorchConv2D$clone()`

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

`PipeOpTorchConv2D$new(id = "nn_conv2d", param_vals = list())`

*Arguments:*

`id` (`character(1)`)

Identifier of the resulting object.

`param_vals` (`list()`)

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

`PipeOpTorchConv2D$clone(deep = FALSE)`

*Arguments:*

`deep` Whether to make a deep clone.

## See Also

Other PipeOps: `mlr_pipeops_nn_adaptive_avg_pool1d`, `mlr_pipeops_nn_adaptive_avg_pool2d`, `mlr_pipeops_nn_adaptive_avg_pool3d`, `mlr_pipeops_nn_avg_pool1d`, `mlr_pipeops_nn_avg_pool2d`, `mlr_pipeops_nn_avg_pool3d`, `mlr_pipeops_nn_batch_norm1d`, `mlr_pipeops_nn_batch_norm2d`, `mlr_pipeops_nn_batch_norm3d`, `mlr_pipeops_nn_block`, `mlr_pipeops_nn_celu`, `mlr_pipeops_nn_conv1d`, `mlr_pipeops_nn_conv3d`, `mlr_pipeops_nn_conv_transpose1d`, `mlr_pipeops_nn_conv_transpose2d`, `mlr_pipeops_nn_conv_transpose3d`, `mlr_pipeops_nn_dropout`, `mlr_pipeops_nn_elu`, `mlr_pipeops_nn_flatten`, `mlr_pipeops_nn_ft_cls`, `mlr_pipeops_nn_ft_transformer_block`, `mlr_pipeops_nn_gelu`, `mlr_pipeops_nn_gelu`, `mlr_pipeops_nn_glu`, `mlr_pipeops_nn_hardshrink`, `mlr_pipeops_nn_hardsigmoid`, `mlr_pipeops_nn_hardtanh`, `mlr_pipeops_nn_head`, `mlr_pipeops_nn_identity`, `mlr_pipeops_nn_layer_norm`, `mlr_pipeops_nn_leaky_relu`, `mlr_pipeops_nn_linear`, `mlr_pipeops_nn_log_sigmoid`, `mlr_pipeops_nn_max_pool1d`, `mlr_pipeops_nn_max_pool2d`, `mlr_pipeops_nn_max_pool3d`, `mlr_pipeops_nn_merge`, `mlr_pipeops_nn_merge_cat`, `mlr_pipeops_nn_merge_prod`, `mlr_pipeops_nn_merge_sum`, `mlr_pipeops_nn_prelu`, `mlr_pipeops_nn_relu`, `mlr_pipeops_nn_relu6`, `mlr_pipeops_nn_reshape`, `mlr_pipeops_nn_rrelu`, `mlr_pipeops_nn_selu`, `mlr_pipeops_nn_sigmoid`, `mlr_pipeops_nn_softmax`, `mlr_pipeops_nn_softplus`, `mlr_pipeops_nn_softshrink`, `mlr_pipeops_nn_softsign`, `mlr_pipeops_nn_squeeze`, `mlr_pipeops_nn_tanh`,

```
mlr_pipeops_nn_tanhshrink, mlr_pipeops_nn_threshold, mlr_pipeops_nn_tokenizer_categ,
mlr_pipeops_nn_tokenizer_num, mlr_pipeops_nn_unsqueeze, mlr_pipeops_torch_ingress,
mlr_pipeops_torch_ingress_categ, mlr_pipeops_torch_ingress_ltnsr, mlr_pipeops_torch_ingress_num,
mlr_pipeops_torch_loss, mlr_pipeops_torch_model, mlr_pipeops_torch_model_classif,
mlr_pipeops_torch_model_regr
```

## Examples

```
# Construct the PipeOp
pipeop = po("nn_conv2d", kernel_size = 10, out_channels = 1)
pipeop
# The available parameters
pipeop$param_set
```

---

mlr\_pipeops\_nn\_conv3d *3D Convolution*

---

## Description

Applies a 3D convolution over an input image composed of several input planes.

### nn\_module

Calls `torch::nn_conv3d()` when trained. The parameter `in_channels` is inferred from the second dimension of the input tensor.

### Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

### State

The state is the value calculated by the public method `$shapes_out()`.

### Parameters

- `out_channels :: integer(1)`  
Number of channels produced by the convolution.
- `kernel_size :: integer()`  
Size of the convolving kernel.
- `stride :: integer()`  
Stride of the convolution. The default is 1.
- `padding :: integer()`  
`dilation * (kernel_size - 1) - padding` zero-padding will be added to both sides of the input. Default: 0.

- `groups :: integer()`  
Number of blocked connections from input channels to output channels. Default: 1
- `bias :: logical(1)`  
If TRUE, adds a learnable bias to the output. Default: TRUE.
- `dilation :: integer()`  
Spacing between kernel elements. Default: 1.
- `padding_mode :: character(1)`  
The padding mode. One of "zeros", "reflect", "replicate", or "circular". Default is "zeros".

## Super classes

`mlr3pipelines::PipeOp -> mlr3torch::PipeOpTorch -> mlr3torch::PipeOpTorchConv -> PipeOpTorchConv3D`

## Methods

### Public methods:

- `PipeOpTorchConv3D$new()`
- `PipeOpTorchConv3D$clone()`

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

`PipeOpTorchConv3D$new(id = "nn_conv3d", param_vals = list())`

*Arguments:*

`id (character(1))`

Identifier of the resulting object.

`param_vals (list())`

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

`PipeOpTorchConv3D$clone(deep = FALSE)`

*Arguments:*

`deep` Whether to make a deep clone.

## See Also

Other PipeOps: `mlr_pipeops_nn_adaptive_avg_pool1d`, `mlr_pipeops_nn_adaptive_avg_pool2d`, `mlr_pipeops_nn_adaptive_avg_pool3d`, `mlr_pipeops_nn_avg_pool1d`, `mlr_pipeops_nn_avg_pool2d`, `mlr_pipeops_nn_avg_pool3d`, `mlr_pipeops_nn_batch_norm1d`, `mlr_pipeops_nn_batch_norm2d`, `mlr_pipeops_nn_batch_norm3d`, `mlr_pipeops_nn_block`, `mlr_pipeops_nn_celu`, `mlr_pipeops_nn_conv1d`, `mlr_pipeops_nn_conv2d`, `mlr_pipeops_nn_conv_transpose1d`, `mlr_pipeops_nn_conv_transpose2d`, `mlr_pipeops_nn_conv_transpose3d`, `mlr_pipeops_nn_dropout`, `mlr_pipeops_nn_elu`, `mlr_pipeops_nn_flatten`, `mlr_pipeops_nn_ft_cls`, `mlr_pipeops_nn_ft_transformer_block`, `mlr_pipeops_nn_gelu`, `mlr_pipeops_nn_glu`, `mlr_pipeops_nn_hardshrink`, `mlr_pipeops_nn_hardsigmoid`,

```
mlr_pipeops_nn_hardtanh, mlr_pipeops_nn_head, mlr_pipeops_nn_identity, mlr_pipeops_nn_layer_norm,
mlr_pipeops_nn_leaky_relu, mlr_pipeops_nn_linear, mlr_pipeops_nn_log_sigmoid, mlr_pipeops_nn_max_pool1d,
mlr_pipeops_nn_max_pool2d, mlr_pipeops_nn_max_pool3d, mlr_pipeops_nn_merge, mlr_pipeops_nn_merge_cat,
mlr_pipeops_nn_merge_prod, mlr_pipeops_nn_merge_sum, mlr_pipeops_nn_prelu, mlr_pipeops_nn_reglu,
mlr_pipeops_nn_relu, mlr_pipeops_nn_relu6, mlr_pipeops_nn_reshape, mlr_pipeops_nn_rrelu,
mlr_pipeops_nn_selu, mlr_pipeops_nn_sigmoid, mlr_pipeops_nn_softmax, mlr_pipeops_nn_softplus,
mlr_pipeops_nn_softshrink, mlr_pipeops_nn_softsign, mlr_pipeops_nn_squeeze, mlr_pipeops_nn_tanh,
mlr_pipeops_nn_tanhshrink, mlr_pipeops_nn_threshold, mlr_pipeops_nn_tokenizer_categ,
mlr_pipeops_nn_tokenizer_num, mlr_pipeops_nn_unsqueeze, mlr_pipeops_torch_ingress,
mlr_pipeops_torch_ingress_categ, mlr_pipeops_torch_ingress_ltnsr, mlr_pipeops_torch_ingress_num,
mlr_pipeops_torch_loss, mlr_pipeops_torch_model, mlr_pipeops_torch_model_classif,
mlr_pipeops_torch_model_regr
```

## Examples

```
# Construct the PipeOp
pipeop = po("nn_conv3d", kernel_size = 10, out_channels = 1)
pipeop
# The available parameters
pipeop$param_set
```

---

### mlr\_pipeops\_nn\_conv\_transpose1d

*Transpose 1D Convolution*

---

## Description

Applies a 1D transposed convolution operator over an input signal composed of several input planes, sometimes also called "deconvolution".

### nn\_module

Calls [nn\\_conv\\_transpose1d](#). The parameter `in_channels` is inferred as the second dimension of the input tensor.

### Parameters

- `out_channels` :: `integer(1)`  
Number of output channels produced by the convolution.
- `kernel_size` :: `integer()`  
Size of the convolving kernel.
- `stride` :: `integer()`  
Stride of the convolution. Default: 1.
- `padding` :: `integer()\cr dilation * (kernel_size - 1) - padding`  
zero-padding will be added to both sides of the input. Default: 0.

- `output_padding ::integer()`  
Additional size added to one side of the output shape. Default: 0.
- `groups :: integer()`  
Number of blocked connections from input channels to output channels. Default: 1
- `bias :: logical(1)`  
If True, adds a learnable bias to the output. Default: TRUE.
- `dilation :: integer()`  
Spacing between kernel elements. Default: 1.
- `padding_mode :: character(1)`  
The padding mode. One of "zeros", "reflect", "replicate", or "circular". Default is "zeros".

## State

The state is the value calculated by the public method `$shapes_out()`.

## Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

## Super classes

```
mlr3pipelines::PipeOp -> mlr3torch::PipeOpTorch -> mlr3torch::PipeOpTorchConvTranspose
-> PipeOpTorchConvTranspose1D
```

## Methods

### Public methods:

- [PipeOpTorchConvTranspose1D\\$new\(\)](#)
- [PipeOpTorchConvTranspose1D\\$clone\(\)](#)

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

```
PipeOpTorchConvTranspose1D$new(id = "nn_conv_transpose1d", param_vals = list())
```

*Arguments:*

`id (character(1))`

Identifier of the resulting object.

`param_vals (list())`

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

```
PipeOpTorchConvTranspose1D$clone(deep = FALSE)
```

*Arguments:*

`deep` Whether to make a deep clone.

## See Also

Other PipeOps: [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm1d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm2d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm3d](#), [mlr\\_pipeops\\_nn\\_block](#), [mlr\\_pipeops\\_nn\\_celu](#), [mlr\\_pipeops\\_nn\\_conv1d](#), [mlr\\_pipeops\\_nn\\_conv2d](#), [mlr\\_pipeops\\_nn\\_conv3d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose2d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose3d](#), [mlr\\_pipeops\\_nn\\_dropout](#), [mlr\\_pipeops\\_nn\\_elu](#), [mlr\\_pipeops\\_nn\\_flatten](#), [mlr\\_pipeops\\_nn\\_ft\\_cls](#), [mlr\\_pipeops\\_nn\\_ft\\_transformer\\_block](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_hardsigmoid](#), [mlr\\_pipeops\\_nn\\_hardtanh](#), [mlr\\_pipeops\\_nn\\_head](#), [mlr\\_pipeops\\_nn\\_identity](#), [mlr\\_pipeops\\_nn\\_layer\\_norm](#), [mlr\\_pipeops\\_nn\\_leaky\\_relu](#), [mlr\\_pipeops\\_nn\\_linear](#), [mlr\\_pipeops\\_nn\\_log\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_max\\_pool1d](#), [mlr\\_pipeops\\_nn\\_max\\_pool2d](#), [mlr\\_pipeops\\_nn\\_max\\_pool3d](#), [mlr\\_pipeops\\_nn\\_merge](#), [mlr\\_pipeops\\_nn\\_merge\\_cat](#), [mlr\\_pipeops\\_nn\\_merge\\_prod](#), [mlr\\_pipeops\\_nn\\_merge\\_sum](#), [mlr\\_pipeops\\_nn\\_prelu](#), [mlr\\_pipeops\\_nn\\_relu](#), [mlr\\_pipeops\\_nn\\_relu](#), [mlr\\_pipeops\\_nn\\_relu6](#), [mlr\\_pipeops\\_nn\\_reshape](#), [mlr\\_pipeops\\_nn\\_rrelu](#), [mlr\\_pipeops\\_nn\\_selu](#), [mlr\\_pipeops\\_nn\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_softmax](#), [mlr\\_pipeops\\_nn\\_softplus](#), [mlr\\_pipeops\\_nn\\_softshrink](#), [mlr\\_pipeops\\_nn\\_softsign](#), [mlr\\_pipeops\\_nn\\_squeeze](#), [mlr\\_pipeops\\_nn\\_tanh](#), [mlr\\_pipeops\\_nn\\_tanhshrink](#), [mlr\\_pipeops\\_nn\\_threshold](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_categ](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_num](#), [mlr\\_pipeops\\_nn\\_unsqueeze](#), [mlr\\_pipeops\\_torch\\_ingress](#), [mlr\\_pipeops\\_torch\\_ingress\\_categ](#), [mlr\\_pipeops\\_torch\\_ingress\\_ltnsr](#), [mlr\\_pipeops\\_torch\\_ingress\\_num](#), [mlr\\_pipeops\\_torch\\_loss](#), [mlr\\_pipeops\\_torch\\_model](#), [mlr\\_pipeops\\_torch\\_model\\_classif](#), [mlr\\_pipeops\\_torch\\_model\\_regr](#)

## Examples

```
# Construct the PipeOp
pipeop = po("nn_conv_transpose1d", kernel_size = 3, out_channels = 2)
pipeop
# The available parameters
pipeop$param_set
```

---

**mlr\_pipeops\_nn\_conv\_transpose2d**  
*Transpose 2D Convolution*

---

## Description

Applies a 2D transposed convolution operator over an input image composed of several input planes, sometimes also called "deconvolution".

### nn\_module

Calls [nn\\_conv\\_transpose2d](#). The parameter `in_channels` is inferred as the second dimension of the input tensor.

### Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

## State

The state is the value calculated by the public method `$shapes_out()`.

## Parameters

- `out_channels :: integer(1)`  
Number of output channels produced by the convolution.
- `kernel_size :: integer()`  
Size of the convolving kernel.
- `stride :: integer()`  
Stride of the convolution. Default: 1.
- `padding :: integer()\cr dilation * (kernel_size - 1) - padding` zero-padding will be added to both sides of the input. Default: 0.
- `output_padding :: integer()`  
Additional size added to one side of the output shape. Default: 0.
- `groups :: integer()`  
Number of blocked connections from input channels to output channels. Default: 1
- `bias :: logical(1)`  
If True, adds a learnable bias to the output. Default: TRUE.
- `dilation :: integer()`  
Spacing between kernel elements. Default: 1.
- `padding_mode :: character(1)`  
The padding mode. One of "zeros", "reflect", "replicate", or "circular". Default is "zeros".

## Super classes

```
mlr3pipelines::PipeOp -> mlr3torch::PipeOpTorch -> mlr3torch::PipeOpTorchConvTranspose
-> PipeOpTorchConvTranspose2D
```

## Methods

### Public methods:

- `PipeOpTorchConvTranspose2D$new()`
- `PipeOpTorchConvTranspose2D$clone()`

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

```
PipeOpTorchConvTranspose2D$new(id = "nn_conv_transpose2d", param_vals = list())
```

*Arguments:*

`id (character(1))`

Identifier of the resulting object.

`param_vals (list())`

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

```
PipeOpTorchConvTranspose2D$clone(deep = FALSE)
```

*Arguments:*

`deep` Whether to make a deep clone.

## See Also

Other PipeOps: [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm1d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm2d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm3d](#), [mlr\\_pipeops\\_nn\\_block](#), [mlr\\_pipeops\\_nn\\_celu](#), [mlr\\_pipeops\\_nn\\_conv1d](#), [mlr\\_pipeops\\_nn\\_conv2d](#), [mlr\\_pipeops\\_nn\\_conv3d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose1d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose3d](#), [mlr\\_pipeops\\_nn\\_dropout](#), [mlr\\_pipeops\\_nn\\_elu](#), [mlr\\_pipeops\\_nn\\_flatten](#), [mlr\\_pipeops\\_nn\\_ft\\_cls](#), [mlr\\_pipeops\\_nn\\_ft\\_transformer\\_block](#), [mlr\\_pipeops\\_nn\\_geglu](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_glu](#), [mlr\\_pipeops\\_nn\\_hardshrink](#), [mlr\\_pipeops\\_nn\\_hardsigmoid](#), [mlr\\_pipeops\\_nn\\_hardtanh](#), [mlr\\_pipeops\\_nn\\_head](#), [mlr\\_pipeops\\_nn\\_identity](#), [mlr\\_pipeops\\_nn\\_layer\\_norm](#), [mlr\\_pipeops\\_nn\\_leaky\\_relu](#), [mlr\\_pipeops\\_nn\\_linear](#), [mlr\\_pipeops\\_nn\\_log\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_max\\_pool1d](#), [mlr\\_pipeops\\_nn\\_max\\_pool2d](#), [mlr\\_pipeops\\_nn\\_max\\_pool3d](#), [mlr\\_pipeops\\_nn\\_merge](#), [mlr\\_pipeops\\_nn\\_merge\\_cat](#), [mlr\\_pipeops\\_nn\\_merge\\_prod](#), [mlr\\_pipeops\\_nn\\_merge\\_sum](#), [mlr\\_pipeops\\_nn\\_prelu](#), [mlr\\_pipeops\\_nn\\_reglu](#), [mlr\\_pipeops\\_nn\\_relu](#), [mlr\\_pipeops\\_nn\\_relu6](#), [mlr\\_pipeops\\_nn\\_reshape](#), [mlr\\_pipeops\\_nn\\_rrelu](#), [mlr\\_pipeops\\_nn\\_selu](#), [mlr\\_pipeops\\_nn\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_softmax](#), [mlr\\_pipeops\\_nn\\_softplus](#), [mlr\\_pipeops\\_nn\\_softshrink](#), [mlr\\_pipeops\\_nn\\_softsign](#), [mlr\\_pipeops\\_nn\\_squeeze](#), [mlr\\_pipeops\\_nn\\_tanh](#), [mlr\\_pipeops\\_nn\\_tanhshrink](#), [mlr\\_pipeops\\_nn\\_threshold](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_categ](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_num](#), [mlr\\_pipeops\\_nn\\_unsqueeze](#), [mlr\\_pipeops\\_torch\\_ingress](#), [mlr\\_pipeops\\_torch\\_ingress\\_categ](#), [mlr\\_pipeops\\_torch\\_ingress\\_ltnsr](#), [mlr\\_pipeops\\_torch\\_ingress\\_num](#), [mlr\\_pipeops\\_torch\\_loss](#), [mlr\\_pipeops\\_torch\\_model](#), [mlr\\_pipeops\\_torch\\_model\\_classif](#), [mlr\\_pipeops\\_torch\\_model\\_regr](#)

## Examples

```
# Construct the PipeOp
pipeop = po("nn_conv_transpose2d", kernel_size = 3, out_channels = 2)
pipeop
# The available parameters
pipeop$param_set
```

---

**mlr\_pipeops\_nn\_conv\_transpose3d**  
*Transpose 3D Convolution*

---

## Description

Applies a 3D transposed convolution operator over an input image composed of several input planes, sometimes also called "deconvolution"

### nn\_module

Calls [nn\\_conv\\_transpose3d](#). The parameter `in_channels` is inferred as the second dimension of the input tensor.

### Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

### State

The state is the value calculated by the public method `$shapes_out()`.

### Parameters

- `out_channels :: integer(1)`  
Number of output channels produced by the convolution.
- `kernel_size :: integer()`  
Size of the convolving kernel.
- `stride :: integer()`  
Stride of the convolution. Default: 1.
- `padding :: integer()\cr dilation * (kernel_size - 1) - padding`` zero-padding will be added to both sides of the input. Default: 0.
- `output_padding :: integer()`  
Additional size added to one side of the output shape. Default: 0.
- `groups :: integer()`  
Number of blocked connections from input channels to output channels. Default: 1
- `bias :: logical(1)`  
If True, adds a learnable bias to the output. Default: TRUE.
- `dilation :: integer()`  
Spacing between kernel elements. Default: 1.
- `padding_mode :: character(1)`  
The padding mode. One of "zeros", "reflect", "replicate", or "circular". Default is "zeros".

### Super classes

```
mlr3pipelines::PipeOp -> mlr3torch::PipeOpTorch -> mlr3torch::PipeOpTorchConvTranspose
-> PipeOpTorchConvTranspose3D
```

### Methods

#### Public methods:

- [PipeOpTorchConvTranspose3D\\$new\(\)](#)
- [PipeOpTorchConvTranspose3D\\$clone\(\)](#)

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

```
PipeOpTorchConvTranspose3D$new(id = "nn_conv_transpose3d", param_vals = list())
```

*Arguments:*

**id** (character(1))

Identifier of the resulting object.

**param\_vals** (list())

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

```
PipeOpTorchConvTranspose3D$clone(deep = FALSE)
```

*Arguments:*

**deep** Whether to make a deep clone.

## See Also

Other PipeOps: [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm1d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm2d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm3d](#), [mlr\\_pipeops\\_nn\\_block](#), [mlr\\_pipeops\\_nn\\_celu](#), [mlr\\_pipeops\\_nn\\_conv1d](#), [mlr\\_pipeops\\_nn\\_conv2d](#), [mlr\\_pipeops\\_nn\\_conv3d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose1d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose3d](#), [mlr\\_pipeops\\_nn\\_dropout](#), [mlr\\_pipeops\\_nn\\_elu](#), [mlr\\_pipeops\\_nn\\_flatten](#), [mlr\\_pipeops\\_nn\\_ft\\_cls](#), [mlr\\_pipeops\\_nn\\_ft\\_transformer\\_block](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_hardshrink](#), [mlr\\_pipeops\\_nn\\_hardsigmoid](#), [mlr\\_pipeops\\_nn\\_hardtanh](#), [mlr\\_pipeops\\_nn\\_head](#), [mlr\\_pipeops\\_nn\\_identity](#), [mlr\\_pipeops\\_nn\\_layer\\_norm](#), [mlr\\_pipeops\\_nn\\_leaky\\_relu](#), [mlr\\_pipeops\\_nn\\_linear](#), [mlr\\_pipeops\\_nn\\_log\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_max\\_pool1d](#), [mlr\\_pipeops\\_nn\\_max\\_pool2d](#), [mlr\\_pipeops\\_nn\\_max\\_pool3d](#), [mlr\\_pipeops\\_nn\\_merge](#), [mlr\\_pipeops\\_nn\\_merge\\_cat](#), [mlr\\_pipeops\\_nn\\_merge\\_prod](#), [mlr\\_pipeops\\_nn\\_merge\\_sum](#), [mlr\\_pipeops\\_nn\\_prelu](#), [mlr\\_pipeops\\_nn\\_relu](#), [mlr\\_pipeops\\_nn\\_relu](#), [mlr\\_pipeops\\_nn\\_relu6](#), [mlr\\_pipeops\\_nn\\_reshape](#), [mlr\\_pipeops\\_nn\\_rrelu](#), [mlr\\_pipeops\\_nn\\_selu](#), [mlr\\_pipeops\\_nn\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_softmax](#), [mlr\\_pipeops\\_nn\\_softplus](#), [mlr\\_pipeops\\_nn\\_softshrink](#), [mlr\\_pipeops\\_nn\\_softsign](#), [mlr\\_pipeops\\_nn\\_squeeze](#), [mlr\\_pipeops\\_nn\\_tanh](#), [mlr\\_pipeops\\_nn\\_tanhshrink](#), [mlr\\_pipeops\\_nn\\_threshold](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_categ](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_num](#), [mlr\\_pipeops\\_nn\\_unsqueeze](#), [mlr\\_pipeops\\_torch\\_ingress](#), [mlr\\_pipeops\\_torch\\_ingress\\_categ](#), [mlr\\_pipeops\\_torch\\_ingress\\_ltnsr](#), [mlr\\_pipeops\\_torch\\_ingress\\_num](#), [mlr\\_pipeops\\_torch\\_loss](#), [mlr\\_pipeops\\_torch\\_model](#), [mlr\\_pipeops\\_torch\\_model\\_classif](#), [mlr\\_pipeops\\_torch\\_model\\_regr](#)

## Examples

```
# Construct the PipeOp
pipeop = po("nn_conv_transpose3d", kernel_size = 3, out_channels = 2)
pipeop
# The available parameters
pipeop$param_set
```

---

**mlr\_pipeops\_nn\_dropout**  
*Dropout*

---

## Description

During training, randomly zeroes some of the elements of the input tensor with probability  $p$  using samples from a Bernoulli distribution.

### nn\_module

Calls [torch::nn\\_dropout\(\)](#) when trained.

### Parameters

- $p :: \text{numeric}(1)$   
 Probability of an element to be zeroed. Default: 0.5.
- $\text{inplace} :: \text{logical}(1)$   
 If set to TRUE, will do this operation in-place. Default: FALSE.

### Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

### State

The state is the value calculated by the public method `$shapes_out()`.

### Super classes

[mlr3pipelines::PipeOp](#) -> [mlr3torch::PipeOpTorch](#) -> PipeOpTorchDropout

### Methods

#### Public methods:

- [PipeOpTorchDropout\\$new\(\)](#)
- [PipeOpTorchDropout\\$clone\(\)](#)

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

`PipeOpTorchDropout$new(id = "nn_dropout", param_vals = list())`

*Arguments:*

- `id (character(1))`  
 Identifier of the resulting object.

```
param_vals (list())
```

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

```
PipeOpTorchDropout$clone(deep = FALSE)
```

*Arguments:*

`deep` Whether to make a deep clone.

## See Also

Other PipeOps: [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm1d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm2d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm3d](#), [mlr\\_pipeops\\_nn\\_block](#), [mlr\\_pipeops\\_nn\\_celu](#), [mlr\\_pipeops\\_nn\\_conv1d](#), [mlr\\_pipeops\\_nn\\_conv2d](#), [mlr\\_pipeops\\_nn\\_conv3d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose1d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose3d](#), [mlr\\_pipeops\\_nn\\_elu](#), [mlr\\_pipeops\\_nn\\_flatten](#), [mlr\\_pipeops\\_nn\\_ft\\_cls](#), [mlr\\_pipeops\\_nn\\_ft\\_transformer\\_block](#), [mlr\\_pipeops\\_nn\\_geglu](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_glu](#), [mlr\\_pipeops\\_nn\\_hardshrink](#), [mlr\\_pipeops\\_nn\\_hardsigmoid](#), [mlr\\_pipeops\\_nn\\_hardtanh](#), [mlr\\_pipeops\\_nn\\_head](#), [mlr\\_pipeops\\_nn\\_identity](#), [mlr\\_pipeops\\_nn\\_layer\\_norm](#), [mlr\\_pipeops\\_nn\\_leaky\\_relu](#), [mlr\\_pipeops\\_nn\\_linear](#), [mlr\\_pipeops\\_nn\\_log\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_max\\_pool1d](#), [mlr\\_pipeops\\_nn\\_max\\_pool2d](#), [mlr\\_pipeops\\_nn\\_max\\_pool3d](#), [mlr\\_pipeops\\_nn\\_merge](#), [mlr\\_pipeops\\_nn\\_merge\\_cat](#), [mlr\\_pipeops\\_nn\\_merge\\_prod](#), [mlr\\_pipeops\\_nn\\_merge\\_sum](#), [mlr\\_pipeops\\_nn\\_prelu](#), [mlr\\_pipeops\\_nn\\_reglu](#), [mlr\\_pipeops\\_nn\\_relu](#), [mlr\\_pipeops\\_nn\\_relu6](#), [mlr\\_pipeops\\_nn\\_reshape](#), [mlr\\_pipeops\\_nn\\_rrelu](#), [mlr\\_pipeops\\_nn\\_selu](#), [mlr\\_pipeops\\_nn\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_softmax](#), [mlr\\_pipeops\\_nn\\_softplus](#), [mlr\\_pipeops\\_nn\\_softshrink](#), [mlr\\_pipeops\\_nn\\_softsign](#), [mlr\\_pipeops\\_nn\\_squeeze](#), [mlr\\_pipeops\\_nn\\_tanh](#), [mlr\\_pipeops\\_nn\\_tanhshrink](#), [mlr\\_pipeops\\_nn\\_threshold](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_categ](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_num](#), [mlr\\_pipeops\\_nn\\_unsqueeze](#), [mlr\\_pipeops\\_torch\\_ingress](#), [mlr\\_pipeops\\_torch\\_ingress\\_categ](#), [mlr\\_pipeops\\_torch\\_ingress\\_ltnsr](#), [mlr\\_pipeops\\_torch\\_ingress\\_num](#), [mlr\\_pipeops\\_torch\\_loss](#), [mlr\\_pipeops\\_torch\\_model](#), [mlr\\_pipeops\\_torch\\_model\\_classif](#), [mlr\\_pipeops\\_torch\\_model\\_regr](#)

## Examples

```
# Construct the PipeOp
pipeop = po("nn_dropout")
pipeop
# The available parameters
pipeop$param_set
```

## Description

Applies element-wise,

$$ELU(x) = \max(0, x) + \min(0, \alpha * (\exp(x) - 1))$$

## nn\_module

Calls `torch::nn_elu()` when trained.

## Parameters

- `alpha` :: `numeric(1)`  
The alpha value for the ELU formulation. Default: 1.0
- `inplace` :: `logical(1)`  
Whether to do the operation in-place. Default: FALSE.

## Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

## State

The state is the value calculated by the public method `$shapes_out()`.

## Super classes

`mlr3pipelines::PipeOp` -> `mlr3torch::PipeOpTorch` -> `PipeOpTorchELU`

## Methods

### Public methods:

- `PipeOpTorchELU$new()`
- `PipeOpTorchELU$clone()`

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

`PipeOpTorchELU$new(id = "nn_elu", param_vals = list())`

*Arguments:*

`id` (`character(1)`)

Identifier of the resulting object.

`param_vals` (`list()`)

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

```
PipeOpTorchELU$clone(deep = FALSE)
```

*Arguments:*

deep Whether to make a deep clone.

## See Also

Other PipeOps: [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm1d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm2d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm3d](#), [mlr\\_pipeops\\_nn\\_block](#), [mlr\\_pipeops\\_nn\\_celu](#), [mlr\\_pipeops\\_nn\\_conv1d](#), [mlr\\_pipeops\\_nn\\_conv2d](#), [mlr\\_pipeops\\_nn\\_conv3d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose1d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose3d](#), [mlr\\_pipeops\\_nn\\_dropout](#), [mlr\\_pipeops\\_nn\\_flatten](#), [mlr\\_pipeops\\_nn\\_ft\\_cls](#), [mlr\\_pipeops\\_nn\\_ft\\_transformer\\_block](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_hardsigmoid](#), [mlr\\_pipeops\\_nn\\_hardsigmoid](#), [mlr\\_pipeops\\_nn\\_hardtanh](#), [mlr\\_pipeops\\_nn\\_head](#), [mlr\\_pipeops\\_nn\\_identity](#), [mlr\\_pipeops\\_nn\\_layer\\_norm](#), [mlr\\_pipeops\\_nn\\_leaky\\_relu](#), [mlr\\_pipeops\\_nn\\_linear](#), [mlr\\_pipeops\\_nn\\_log\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_max\\_pool1d](#), [mlr\\_pipeops\\_nn\\_max\\_pool2d](#), [mlr\\_pipeops\\_nn\\_max\\_pool3d](#), [mlr\\_pipeops\\_nn\\_merge](#), [mlr\\_pipeops\\_nn\\_merge\\_cat](#), [mlr\\_pipeops\\_nn\\_merge\\_prod](#), [mlr\\_pipeops\\_nn\\_merge\\_sum](#), [mlr\\_pipeops\\_nn\\_prelu](#), [mlr\\_pipeops\\_nn\\_relu](#), [mlr\\_pipeops\\_nn\\_relu](#), [mlr\\_pipeops\\_nn\\_relu6](#), [mlr\\_pipeops\\_nn\\_reshape](#), [mlr\\_pipeops\\_nn\\_rrelu](#), [mlr\\_pipeops\\_nn\\_selu](#), [mlr\\_pipeops\\_nn\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_softmax](#), [mlr\\_pipeops\\_nn\\_softplus](#), [mlr\\_pipeops\\_nn\\_softshrink](#), [mlr\\_pipeops\\_nn\\_softsign](#), [mlr\\_pipeops\\_nn\\_squeeze](#), [mlr\\_pipeops\\_nn\\_tanh](#), [mlr\\_pipeops\\_nn\\_tanhshrink](#), [mlr\\_pipeops\\_nn\\_threshold](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_categ](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_num](#), [mlr\\_pipeops\\_nn\\_unsqueeze](#), [mlr\\_pipeops\\_torch\\_ingress](#), [mlr\\_pipeops\\_torch\\_ingress\\_categ](#), [mlr\\_pipeops\\_torch\\_ingress\\_ltnsr](#), [mlr\\_pipeops\\_torch\\_ingress\\_num](#), [mlr\\_pipeops\\_torch\\_loss](#), [mlr\\_pipeops\\_torch\\_model](#), [mlr\\_pipeops\\_torch\\_model\\_classif](#), [mlr\\_pipeops\\_torch\\_model\\_regr](#)

## Examples

```
# Construct the PipeOp
pipeop = po("nn_elu")
pipeop
# The available parameters
pipeop$param_set
```

---

### mlr\_pipeops\_nn\_flatten

*Flattens a Tensor*

---

## Description

For use with [nn\\_sequential](#).

### nn\_module

Calls [torch::nn\\_flatten\(\)](#) when trained.

## Parameters

`start_dim` :: `integer(1)`

At which dimension to start flattening. Default is 2. `end_dim` :: `integer(1)`

At which dimension to stop flattening. Default is -1.

## Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

## State

The state is the value calculated by the public method `$shapes_out()`.

## Super classes

[mlr3pipelines::PipeOp](#) -> [mlr3torch::PipeOpTorch](#) -> `PipeOpTorchFlatten`

## Methods

### Public methods:

- [PipeOpTorchFlatten\\$new\(\)](#)
- [PipeOpTorchFlatten\\$clone\(\)](#)

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

`PipeOpTorchFlatten$new(id = "nn_flatten", param_vals = list())`

*Arguments:*

`id` (`character(1)`)

Identifier of the resulting object.

`param_vals` (`list()`)

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

`PipeOpTorchFlatten$clone(deep = FALSE)`

*Arguments:*

`deep` Whether to make a deep clone.

## See Also

Other PipeOps: [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm1d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm2d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm3d](#), [mlr\\_pipeops\\_nn\\_block](#), [mlr\\_pipeops\\_nn\\_celu](#), [mlr\\_pipeops\\_nn\\_conv1d](#), [mlr\\_pipeops\\_nn\\_conv2d](#), [mlr\\_pipeops\\_nn\\_conv3d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose1d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose2d](#)

```
mlr_pipeops_nn_conv_transpose3d,mlr_pipeops_nn_dropout,mlr_pipeops_nn_elu,mlr_pipeops_nn_ft_cls,
mlr_pipeops_nn_ft_transformer_block,mlr_pipeops_nn_gelu,mlr_pipeops_nn_gelu,mlr_pipeops_nn_glu,
mlr_pipeops_nn_hardshrink,mlr_pipeops_nn_hardsigmoid,mlr_pipeops_nn_hardtanh,mlr_pipeops_nn_head,
mlr_pipeops_nn_identity,mlr_pipeops_nn_layer_norm,mlr_pipeops_nn_leaky_relu,mlr_pipeops_nn_linear,
mlr_pipeops_nn_log_sigmoid,mlr_pipeops_nn_max_pool1d,mlr_pipeops_nn_max_pool2d,
mlr_pipeops_nn_max_pool3d,mlr_pipeops_nn_merge,mlr_pipeops_nn_merge_cat,mlr_pipeops_nn_merge_prod,
mlr_pipeops_nn_merge_sum,mlr_pipeops_nn_prelu,mlr_pipeops_nn_relu,mlr_pipeops_nn_relu,
mlr_pipeops_nn_relu6,mlr_pipeops_nn_reshape,mlr_pipeops_nn_rrelu,mlr_pipeops_nn_selu,
mlr_pipeops_nn_sigmoid,mlr_pipeops_nn_softmax,mlr_pipeops_nn_softplus,mlr_pipeops_nn_softshrink,
mlr_pipeops_nn_softsign,mlr_pipeops_nn_squeeze,mlr_pipeops_nn_tanh,mlr_pipeops_nn_tanhshrink,
mlr_pipeops_nn_threshold,mlr_pipeops_nn_tokenizer_categ,mlr_pipeops_nn_tokenizer_num,
mlr_pipeops_nn_unsqueeze,mlr_pipeops_torch_ingress,mlr_pipeops_torch_ingress_categ,
mlr_pipeops_torch_ingress_ltnsr,mlr_pipeops_torch_ingress_num,mlr_pipeops_torch_loss,
mlr_pipeops_torch_model,mlr_pipeops_torch_model_classif,mlr_pipeops_torch_model_regr
```

## Examples

```
# Construct the PipeOp
pipeop = po("nn_flatten")
pipeop
# The available parameters
pipeop$param_set
```

---

|                   |                        |
|-------------------|------------------------|
| mlr_pipeops_nn_fn | <i>Custom Function</i> |
|-------------------|------------------------|

---

## Description

Applies a user-supplied function to a tensor.

## Parameters

By default, these are inferred as all but the first arguments of the function `fn`. It is also possible to specify these more explicitly via the `param_set` constructor argument.

## Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

## Super classes

`mlr3pipelines::PipeOp` -> `mlr3torch::PipeOpTorch` -> `PipeOpTorchFn`

## Methods

### Public methods:

- [PipeOpTorchFn\\$new\(\)](#)
- [PipeOpTorchFn\\$clone\(\)](#)

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

```
PipeOpTorchFn$new(
  fn,
  id = "nn_fn",
  param_vals = list(),
  param_set = NULL,
  shapes_out = NULL
)
```

*Arguments:*

`fn` (function)

The function to be applied. Takes a torch tensor as first argument and returns a torch tensor.

`id` (character(1))

Identifier of the resulting object.

`param_vals` (list())

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

`param_set` ([ParamSet](#) or NULL)

A ParamSet wrapping the arguments to `fn`. If omitted, then the ParamSet for this PipeOp will be inferred from the function signature.

`shapes_out` (function or NULL)

A function that computes the output shapes of the `fn`. See [PipeOpTorch](#)'s `.shapes_out()` method for details on the parameters, and [PipeOpTaskPreprocTorch](#) for details on how the shapes are inferred when this parameter is NULL.

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

```
PipeOpTorchFn$clone(deep = FALSE)
```

*Arguments:*

`deep` Whether to make a deep clone.

## Examples

```
custom_fn = function(x, a) x / a
obj = po("nn_fn", fn = custom_fn, a = 2)
obj$param_set

graph = po("torch_ingress_ltnsr") %>>% obj

task = tsk("lazy_iris")$filter(1)
```

```

tnsr = materialize(task$data()$x)[[1]]

md_trained = graph$train(task)
trained = md_trained[[1]]$graph$train(tnsr)

trained[[1]]

custom_fn(tnsr, a = 2)

```

---

**mlr\_pipeops\_nn\_ft\_cls** *CLS Token for FT-Transformer*

---

## Description

Concatenates a CLS token to the input as the last feature. The input shape is expected to be (batch, n\_features, d\_token) and the output shape is (batch, n\_features + 1, d\_token). This is used in the [LearnerTorchFTTransformer](#).

### nn\_module

Calls [nn\\_ft\\_cls\(\)](#) when trained.

### State

The state is the value calculated by the public method `$shapes_out()`.

### Super classes

[mlr3pipelines::PipeOp](#) -> [mlr3torch::PipeOpTorch](#) -> [PipeOpTorchFTCLS](#)

### Methods

#### Public methods:

- [PipeOpTorchFTCLS\\$new\(\)](#)
- [PipeOpTorchFTCLS\\$clone\(\)](#)

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

`PipeOpTorchFTCLS$new(id = "nn_ft_cls", param_vals = list())`

*Arguments:*

`id` (`character(1)`)

Identifier of the resulting object.

`param_vals` (`list()`)

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

```
PipeOpTorchFTCLS$clone(deep = FALSE)
```

*Arguments:*

`deep` Whether to make a deep clone.

## See Also

Other PipeOps: [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm1d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm2d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm3d](#), [mlr\\_pipeops\\_nn\\_block](#), [mlr\\_pipeops\\_nn\\_celu](#), [mlr\\_pipeops\\_nn\\_conv1d](#), [mlr\\_pipeops\\_nn\\_conv2d](#), [mlr\\_pipeops\\_nn\\_conv3d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose1d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose3d](#), [mlr\\_pipeops\\_nn\\_dropout](#), [mlr\\_pipeops\\_nn\\_elu](#), [mlr\\_pipeops\\_nn\\_flatten](#), [mlr\\_pipeops\\_nn\\_ft\\_transformer\\_block](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_glu](#), [mlr\\_pipeops\\_nn\\_hardshrink](#), [mlr\\_pipeops\\_nn\\_hardsigmoid](#), [mlr\\_pipeops\\_nn\\_hardtanh](#), [mlr\\_pipeops\\_nn\\_head](#), [mlr\\_pipeops\\_nn\\_identity](#), [mlr\\_pipeops\\_nn\\_layer\\_norm](#), [mlr\\_pipeops\\_nn\\_leaky\\_relu](#), [mlr\\_pipeops\\_nn\\_linear](#), [mlr\\_pipeops\\_nn\\_log\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_max\\_pool1d](#), [mlr\\_pipeops\\_nn\\_max\\_pool2d](#), [mlr\\_pipeops\\_nn\\_max\\_pool3d](#), [mlr\\_pipeops\\_nn\\_merge](#), [mlr\\_pipeops\\_nn\\_merge\\_cat](#), [mlr\\_pipeops\\_nn\\_merge\\_prod](#), [mlr\\_pipeops\\_nn\\_merge\\_sum](#), [mlr\\_pipeops\\_nn\\_prelu](#), [mlr\\_pipeops\\_nn\\_relu](#), [mlr\\_pipeops\\_nn\\_relu](#), [mlr\\_pipeops\\_nn\\_relu6](#), [mlr\\_pipeops\\_nn\\_reshape](#), [mlr\\_pipeops\\_nn\\_rrelu](#), [mlr\\_pipeops\\_nn\\_selu](#), [mlr\\_pipeops\\_nn\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_softmax](#), [mlr\\_pipeops\\_nn\\_softplus](#), [mlr\\_pipeops\\_nn\\_softshrink](#), [mlr\\_pipeops\\_nn\\_softsign](#), [mlr\\_pipeops\\_nn\\_squeeze](#), [mlr\\_pipeops\\_nn\\_tanh](#), [mlr\\_pipeops\\_nn\\_tanhshrink](#), [mlr\\_pipeops\\_nn\\_threshold](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_categ](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_num](#), [mlr\\_pipeops\\_nn\\_unsqueeze](#), [mlr\\_pipeops\\_torch\\_ingress](#), [mlr\\_pipeops\\_torch\\_ingress\\_categ](#), [mlr\\_pipeops\\_torch\\_ingress\\_ltnsr](#), [mlr\\_pipeops\\_torch\\_ingress\\_num](#), [mlr\\_pipeops\\_torch\\_loss](#), [mlr\\_pipeops\\_torch\\_model](#), [mlr\\_pipeops\\_torch\\_model\\_classif](#), [mlr\\_pipeops\\_torch\\_model\\_regr](#)

## Examples

```
# Construct the PipeOp
pipeop = po("nn_ft_cls")
pipeop
# The available parameters
pipeop$param_set
```

---

### mlr\_pipeops\_nn\_ft\_transformer\_block

*Single Transformer Block for the FT-Transformer*

---

## Description

A transformer block consisting of a multi-head self-attention mechanism followed by a feed-forward network.

This is used in [LearnerTorchFTTransformer](#).

**nn\_module**

Calls [nn\\_ft\\_transformer\\_block\(\)](#) when trained.

**State**

The state is the value calculated by the public method `$shapes_out()`.

**Super classes**

`mlr3pipelines::PipeOp -> mlr3torch::PipeOpTorch -> PipeOpTorchFTTransformerBlock`

**Methods****Public methods:**

- [PipeOpTorchFTTransformerBlock\\$new\(\)](#)
- [PipeOpTorchFTTransformerBlock\\$clone\(\)](#)

**Method** `new()`: Create a new instance of this [R6](#) class.

*Usage:*

```
PipeOpTorchFTTransformerBlock$new(
  id = "nn_ft_transformer_block",
  param_vals = list()
)
```

*Arguments:*

`id` (character(1))

Identifier of the resulting object.

`param_vals` (list())

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

```
PipeOpTorchFTTransformerBlock$clone(deep = FALSE)
```

*Arguments:*

`deep` Whether to make a deep clone.

**See Also**

Other PipeOps: [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm1d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm2d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm3d](#), [mlr\\_pipeops\\_nn\\_block](#), [mlr\\_pipeops\\_nn\\_celu](#), [mlr\\_pipeops\\_nn\\_conv1d](#), [mlr\\_pipeops\\_nn\\_conv2d](#), [mlr\\_pipeops\\_nn\\_conv3d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose1d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose3d](#), [mlr\\_pipeops\\_nn\\_dropout](#), [mlr\\_pipeops\\_nn\\_elu](#), [mlr\\_pipeops\\_nn\\_flatten](#), [mlr\\_pipeops\\_nn\\_ft\\_cls](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_glu](#), [mlr\\_pipeops\\_nn\\_hardshrink](#), [mlr\\_pipeops\\_nn\\_hardsigmoid](#), [mlr\\_pipeops\\_nn\\_hardtanh](#), [mlr\\_pipeops\\_nn\\_head](#),

```
mlr_pipeops_nn_identity, mlr_pipeops_nn_layer_norm, mlr_pipeops_nn_leaky_relu, mlr_pipeops_nn_linear,
mlr_pipeops_nn_log_sigmoid, mlr_pipeops_nn_max_pool1d, mlr_pipeops_nn_max_pool2d,
mlr_pipeops_nn_max_pool3d, mlr_pipeops_nn_merge, mlr_pipeops_nn_merge_cat, mlr_pipeops_nn_merge_prod,
mlr_pipeops_nn_merge_sum, mlr_pipeops_nn_prelu, mlr_pipeops_nn_reglu, mlr_pipeops_nn_relu,
mlr_pipeops_nn_relu6, mlr_pipeops_nn_reshape, mlr_pipeops_nn_rrelu, mlr_pipeops_nn_selu,
mlr_pipeops_nn_sigmoid, mlr_pipeops_nn_softmax, mlr_pipeops_nn_softplus, mlr_pipeops_nn_softshrink,
mlr_pipeops_nn_softsign, mlr_pipeops_nn_squeeze, mlr_pipeops_nn_tanh, mlr_pipeops_nn_tanhshrink,
mlr_pipeops_nn_threshold, mlr_pipeops_nn_tokenizer_categ, mlr_pipeops_nn_tokenizer_num,
mlr_pipeops_nn_unsqueeze, mlr_pipeops_torch_ingress, mlr_pipeops_torch_ingress_categ,
mlr_pipeops_torch_ingress_ltnsr, mlr_pipeops_torch_ingress_num, mlr_pipeops_torch_loss,
mlr_pipeops_torch_model, mlr_pipeops_torch_model_classif, mlr_pipeops_torch_model_regr
```

## Examples

```
# Construct the PipeOp
pipeop = po("nn_ft_transformer_block")
pipeop
# The available parameters
pipeop$param_set
```

---

mlr\_pipeops\_nn\_gelu    *GeGLU Activation Function*

---

## Description

Gaussian Error Linear Unit Gated Linear Unit (GeGLU) activation function, see [nn\\_gelu](#) for details.

## Parameters

No parameters.

## Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

## State

The state is the value calculated by the public method `$shapes_out()`.

## Super classes

`mlr3pipelines::PipeOp` -> `mlr3torch::PipeOpTorch` -> `PipeOpTorchGeGLU`

## Methods

### Public methods:

- `PipeOpTorchGeGLU$new()`
- `PipeOpTorchGeGLU$clone()`

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

```
PipeOpTorchGeGLU$new(id = "nn_geglu", param_vals = list())
```

*Arguments:*

`id` (character(1))

Identifier of the resulting object.

`param_vals` (list())

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

```
PipeOpTorchGeGLU$clone(deep = FALSE)
```

*Arguments:*

`deep` Whether to make a deep clone.

## See Also

Other PipeOps: [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm1d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm2d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm3d](#), [mlr\\_pipeops\\_nn\\_block](#), [mlr\\_pipeops\\_nn\\_celu](#), [mlr\\_pipeops\\_nn\\_conv1d](#), [mlr\\_pipeops\\_nn\\_conv2d](#), [mlr\\_pipeops\\_nn\\_conv3d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose1d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose3d](#), [mlr\\_pipeops\\_nn\\_dropout](#), [mlr\\_pipeops\\_nn\\_elu](#), [mlr\\_pipeops\\_nn\\_flatten](#), [mlr\\_pipeops\\_nn\\_ft\\_cls](#), [mlr\\_pipeops\\_nn\\_ft\\_transformer\\_block](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_glu](#), [mlr\\_pipeops\\_nn\\_hardshrink](#), [mlr\\_pipeops\\_nn\\_hardsigmoid](#), [mlr\\_pipeops\\_nn\\_hardtanh](#), [mlr\\_pipeops\\_nn\\_head](#), [mlr\\_pipeops\\_nn\\_identity](#), [mlr\\_pipeops\\_nn\\_layer\\_norm](#), [mlr\\_pipeops\\_nn\\_leaky\\_relu](#), [mlr\\_pipeops\\_nn\\_linear](#), [mlr\\_pipeops\\_nn\\_log\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_max\\_pool1d](#), [mlr\\_pipeops\\_nn\\_max\\_pool2d](#), [mlr\\_pipeops\\_nn\\_max\\_pool3d](#), [mlr\\_pipeops\\_nn\\_merge](#), [mlr\\_pipeops\\_nn\\_merge\\_cat](#), [mlr\\_pipeops\\_nn\\_merge\\_prod](#), [mlr\\_pipeops\\_nn\\_merge\\_sum](#), [mlr\\_pipeops\\_nn\\_prelu](#), [mlr\\_pipeops\\_nn\\_relu](#), [mlr\\_pipeops\\_nn\\_relu6](#), [mlr\\_pipeops\\_nn\\_reshape](#), [mlr\\_pipeops\\_nn\\_rrelu](#), [mlr\\_pipeops\\_nn\\_selu](#), [mlr\\_pipeops\\_nn\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_softmax](#), [mlr\\_pipeops\\_nn\\_softplus](#), [mlr\\_pipeops\\_nn\\_softshrink](#), [mlr\\_pipeops\\_nn\\_softsign](#), [mlr\\_pipeops\\_nn\\_squeeze](#), [mlr\\_pipeops\\_nn\\_tanh](#), [mlr\\_pipeops\\_nn\\_tanhshrink](#), [mlr\\_pipeops\\_nn\\_threshold](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_categ](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_num](#), [mlr\\_pipeops\\_nn\\_unsqueeze](#), [mlr\\_pipeops\\_torch\\_ingress](#), [mlr\\_pipeops\\_torch\\_ingress\\_categ](#), [mlr\\_pipeops\\_torch\\_ingress\\_ltnsr](#), [mlr\\_pipeops\\_torch\\_ingress\\_num](#), [mlr\\_pipeops\\_torch\\_loss](#), [mlr\\_pipeops\\_torch\\_model](#), [mlr\\_pipeops\\_torch\\_model\\_classif](#), [mlr\\_pipeops\\_torch\\_model\\_regr](#)

## Examples

```
# Construct the PipeOp
pipeop = po("nn_gelu")
pipeop
# The available parameters
pipeop$param_set
```

---

mlr\_pipeops\_nn\_gelu     *GELU Activation Function*

---

## Description

Gelu

### nn\_module

Calls [torch::nn\\_gelu\(\)](#) when trained.

### Parameters

- `approximate :: character(1)`  
Whether to use an approximation algorithm. Default is "none".

### Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

### State

The state is the value calculated by the public method `$shapes_out()`.

### Super classes

[mlr3pipelines::PipeOp](#) -> [mlr3torch::PipeOpTorch](#) -> PipeOpTorchGELU

### Methods

#### Public methods:

- [PipeOpTorchGELU\\$new\(\)](#)
- [PipeOpTorchGELU\\$clone\(\)](#)

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

`PipeOpTorchGELU$new(id = "nn_gelu", param_vals = list())`

*Arguments:*

```

  id (character(1))
    Identifier of the resulting object.
  param_vals (list())
    List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

```

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

```
PipeOpTorchGELU$clone(deep = FALSE)
```

*Arguments:*

`deep` Whether to make a deep clone.

## See Also

Other PipeOps: [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm1d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm2d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm3d](#), [mlr\\_pipeops\\_nn\\_block](#), [mlr\\_pipeops\\_nn\\_celu](#), [mlr\\_pipeops\\_nn\\_conv1d](#), [mlr\\_pipeops\\_nn\\_conv2d](#), [mlr\\_pipeops\\_nn\\_conv3d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose1d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose3d](#), [mlr\\_pipeops\\_nn\\_dropout](#), [mlr\\_pipeops\\_nn\\_elu](#), [mlr\\_pipeops\\_nn\\_flatten](#), [mlr\\_pipeops\\_nn\\_ft\\_cls](#), [mlr\\_pipeops\\_nn\\_ft\\_transformer\\_block](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_glu](#), [mlr\\_pipeops\\_nn\\_hardshrink](#), [mlr\\_pipeops\\_nn\\_hardsigmoid](#), [mlr\\_pipeops\\_nn\\_hardtanh](#), [mlr\\_pipeops\\_nn\\_head](#), [mlr\\_pipeops\\_nn\\_identity](#), [mlr\\_pipeops\\_nn\\_layer\\_norm](#), [mlr\\_pipeops\\_nn\\_leaky\\_relu](#), [mlr\\_pipeops\\_nn\\_linear](#), [mlr\\_pipeops\\_nn\\_log\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_max\\_pool1d](#), [mlr\\_pipeops\\_nn\\_max\\_pool2d](#), [mlr\\_pipeops\\_nn\\_max\\_pool3d](#), [mlr\\_pipeops\\_nn\\_merge](#), [mlr\\_pipeops\\_nn\\_merge\\_cat](#), [mlr\\_pipeops\\_nn\\_merge\\_prod](#), [mlr\\_pipeops\\_nn\\_merge\\_sum](#), [mlr\\_pipeops\\_nn\\_prelu](#), [mlr\\_pipeops\\_nn\\_relu](#), [mlr\\_pipeops\\_nn\\_relu6](#), [mlr\\_pipeops\\_nn\\_reshape](#), [mlr\\_pipeops\\_nn\\_rrelu](#), [mlr\\_pipeops\\_nn\\_selu](#), [mlr\\_pipeops\\_nn\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_softmax](#), [mlr\\_pipeops\\_nn\\_softplus](#), [mlr\\_pipeops\\_nn\\_softshrink](#), [mlr\\_pipeops\\_nn\\_softsign](#), [mlr\\_pipeops\\_nn\\_squeeze](#), [mlr\\_pipeops\\_nn\\_tanh](#), [mlr\\_pipeops\\_nn\\_tanhshrink](#), [mlr\\_pipeops\\_nn\\_threshold](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_categ](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_num](#), [mlr\\_pipeops\\_nn\\_unsqueeze](#), [mlr\\_pipeops\\_torch\\_ingress](#), [mlr\\_pipeops\\_torch\\_ingress\\_categ](#), [mlr\\_pipeops\\_torch\\_ingress\\_ltnsr](#), [mlr\\_pipeops\\_torch\\_ingress\\_num](#), [mlr\\_pipeops\\_torch\\_loss](#), [mlr\\_pipeops\\_torch\\_model](#), [mlr\\_pipeops\\_torch\\_model\\_classif](#), [mlr\\_pipeops\\_torch\\_model\\_regr](#)

## Examples

```

# Construct the PipeOp
pipeop = po("nn_gelu")
pipeop
# The available parameters
pipeop$param_set

```

---

 mlr\_pipeops\_nn\_glu      *GLU Activation Function*


---

## Description

The gated linear unit. Computes:

### nn\_module

Calls `torch::nn_glu()` when trained.

### Parameters

- `dim :: integer(1)`  
Dimension on which to split the input. Default: -1

### Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

### State

The state is the value calculated by the public method `$shapes_out()`.

### Super classes

`mlr3pipelines::PipeOp` -> `mlr3torch::PipeOpTorch` -> `PipeOpTorchGLU`

### Methods

#### Public methods:

- `PipeOpTorchGLU$new()`
- `PipeOpTorchGLU$clone()`

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

`PipeOpTorchGLU$new(id = "nn_glu", param_vals = list())`

*Arguments:*

`id (character(1))`

Identifier of the resulting object.

`param_vals (list())`

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

```
PipeOpTorchGLU$clone(deep = FALSE)
```

*Arguments:*

deep Whether to make a deep clone.

## See Also

Other PipeOps: [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm1d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm2d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm3d](#), [mlr\\_pipeops\\_nn\\_block](#), [mlr\\_pipeops\\_nn\\_celu](#), [mlr\\_pipeops\\_nn\\_conv1d](#), [mlr\\_pipeops\\_nn\\_conv2d](#), [mlr\\_pipeops\\_nn\\_conv3d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose1d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose3d](#), [mlr\\_pipeops\\_nn\\_dropout](#), [mlr\\_pipeops\\_nn\\_elu](#), [mlr\\_pipeops\\_nn\\_flatten](#), [mlr\\_pipeops\\_nn\\_ft\\_cls](#), [mlr\\_pipeops\\_nn\\_ft\\_transformer\\_block](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_hardshrink](#), [mlr\\_pipeops\\_nn\\_hardsigmoid](#), [mlr\\_pipeops\\_nn\\_hardtanh](#), [mlr\\_pipeops\\_nn\\_head](#), [mlr\\_pipeops\\_nn\\_identity](#), [mlr\\_pipeops\\_nn\\_layer\\_norm](#), [mlr\\_pipeops\\_nn\\_leaky\\_relu](#), [mlr\\_pipeops\\_nn\\_linear](#), [mlr\\_pipeops\\_nn\\_log\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_max\\_pool1d](#), [mlr\\_pipeops\\_nn\\_max\\_pool2d](#), [mlr\\_pipeops\\_nn\\_max\\_pool3d](#), [mlr\\_pipeops\\_nn\\_merge](#), [mlr\\_pipeops\\_nn\\_merge\\_cat](#), [mlr\\_pipeops\\_nn\\_merge\\_prod](#), [mlr\\_pipeops\\_nn\\_merge\\_sum](#), [mlr\\_pipeops\\_nn\\_prelu](#), [mlr\\_pipeops\\_nn\\_reglu](#), [mlr\\_pipeops\\_nn\\_relu](#), [mlr\\_pipeops\\_nn\\_relu6](#), [mlr\\_pipeops\\_nn\\_reshape](#), [mlr\\_pipeops\\_nn\\_rrelu](#), [mlr\\_pipeops\\_nn\\_selu](#), [mlr\\_pipeops\\_nn\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_softmax](#), [mlr\\_pipeops\\_nn\\_softplus](#), [mlr\\_pipeops\\_nn\\_softshrink](#), [mlr\\_pipeops\\_nn\\_softsign](#), [mlr\\_pipeops\\_nn\\_squeeze](#), [mlr\\_pipeops\\_nn\\_tanh](#), [mlr\\_pipeops\\_nn\\_tanhshrink](#), [mlr\\_pipeops\\_nn\\_threshold](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_categ](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_num](#), [mlr\\_pipeops\\_nn\\_unsqueeze](#), [mlr\\_pipeops\\_torch\\_ingress](#), [mlr\\_pipeops\\_torch\\_ingress\\_categ](#), [mlr\\_pipeops\\_torch\\_ingress\\_ltnsr](#), [mlr\\_pipeops\\_torch\\_ingress\\_num](#), [mlr\\_pipeops\\_torch\\_loss](#), [mlr\\_pipeops\\_torch\\_model](#), [mlr\\_pipeops\\_torch\\_model\\_classif](#), [mlr\\_pipeops\\_torch\\_model\\_regr](#)

## Examples

```
# Construct the PipeOp
pipeop = po("nn_glu")
pipeop
# The available parameters
pipeop$param_set
```

---

**mlr\_pipeops\_nn\_hardshrink**

*Hard Shrink Activation Function*

---

## Description

Applies the hard shrinkage function element-wise

### nn\_module

Calls [torch::nn\\_hardshrink\(\)](#) when trained.

## Parameters

- `lambda :: numeric(1)`

The lambda value for the Hardshrink formulation formulation. Default 0.5.

## Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

## State

The state is the value calculated by the public method `$shapes_out()`.

## Super classes

`mlr3pipelines::PipeOp -> mlr3torch::PipeOpTorch -> PipeOpTorchHardShrink`

## Methods

### Public methods:

- [PipeOpTorchHardShrink\\$new\(\)](#)
- [PipeOpTorchHardShrink\\$clone\(\)](#)

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

`PipeOpTorchHardShrink$new(id = "nn_hardshrink", param_vals = list())`

*Arguments:*

`id (character(1))`

Identifier of the resulting object.

`param_vals (list())`

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

`PipeOpTorchHardShrink$clone(deep = FALSE)`

*Arguments:*

`deep` Whether to make a deep clone.

## See Also

Other PipeOps: [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm1d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm2d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm3d](#), [mlr\\_pipeops\\_nn\\_block](#), [mlr\\_pipeops\\_nn\\_celu](#), [mlr\\_pipeops\\_nn\\_conv1d](#), [mlr\\_pipeops\\_nn\\_conv2d](#), [mlr\\_pipeops\\_nn\\_conv3d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose1d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose3d](#), [mlr\\_pipeops\\_nn\\_dropout](#), [mlr\\_pipeops\\_nn\\_elu](#), [mlr\\_pipeops\\_nn\\_flatten](#),

```
mlr_pipeops_nn_ft_cls, mlr_pipeops_nn_ft_transformer_block, mlr_pipeops_nn_gelu,
mlr_pipeops_nn_gelu, mlr_pipeops_nn_glu, mlr_pipeops_nn_hardsigmoid, mlr_pipeops_nn_hardtanh,
mlr_pipeops_nn_head, mlr_pipeops_nn_identity, mlr_pipeops_nn_layer_norm, mlr_pipeops_nn_leaky_relu,
mlr_pipeops_nn_linear, mlr_pipeops_nn_log_sigmoid, mlr_pipeops_nn_max_pool1d, mlr_pipeops_nn_max_pool2d,
mlr_pipeops_nn_max_pool3d, mlr_pipeops_nn_merge, mlr_pipeops_nn_merge_cat, mlr_pipeops_nn_merge_prod,
mlr_pipeops_nn_merge_sum, mlr_pipeops_nn_prelu, mlr_pipeops_nn_reglu, mlr_pipeops_nn_relu,
mlr_pipeops_nn_relu6, mlr_pipeops_nn_reshape, mlr_pipeops_nn_rrelu, mlr_pipeops_nn_selu,
mlr_pipeops_nn_sigmoid, mlr_pipeops_nn_softmax, mlr_pipeops_nn_softplus, mlr_pipeops_nn_softshrink,
mlr_pipeops_nn_softsign, mlr_pipeops_nn_squeeze, mlr_pipeops_nn_tanh, mlr_pipeops_nn_tanhshrink,
mlr_pipeops_nn_threshold, mlr_pipeops_nn_tokenizer_categ, mlr_pipeops_nn_tokenizer_num,
mlr_pipeops_nn_unsqueeze, mlr_pipeops_torch_ingress, mlr_pipeops_torch_ingress_categ,
mlr_pipeops_torch_ingress_ltnsr, mlr_pipeops_torch_ingress_num, mlr_pipeops_torch_loss,
mlr_pipeops_torch_model, mlr_pipeops_torch_model_classif, mlr_pipeops_torch_model_regr
```

## Examples

```
# Construct the PipeOp
pipeop = po("nn_hardshrink")
pipeop
# The available parameters
pipeop$param_set
```

---

mlr\_pipeops\_nn\_hardsigmoid

*Hard Sigmoid Activation Function*

---

## Description

Applies the element-wise function  $\text{Hardsigmoid}(x) = \frac{\text{ReLU6}(x+3)}{6}$

### nn\_module

Calls `torch::nn_hardsigmoid()` when trained.

### Parameters

No parameters.

### Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

### State

The state is the value calculated by the public method `$shapes_out()`.

## Super classes

[mlr3pipelines::PipeOp](#) -> [mlr3torch::PipeOpTorch](#) -> PipeOpTorchHardSigmoid

## Methods

### Public methods:

- [PipeOpTorchHardSigmoid\\$new\(\)](#)
- [PipeOpTorchHardSigmoid\\$clone\(\)](#)

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

`PipeOpTorchHardSigmoid$new(id = "nn_hardsigmoid", param_vals = list())`

*Arguments:*

`id` (character(1))

Identifier of the resulting object.

`param_vals` (list())

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

`PipeOpTorchHardSigmoid$clone(deep = FALSE)`

*Arguments:*

`deep` Whether to make a deep clone.

## See Also

Other PipeOps: [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm1d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm2d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm3d](#), [mlr\\_pipeops\\_nn\\_block](#), [mlr\\_pipeops\\_nn\\_celu](#), [mlr\\_pipeops\\_nn\\_conv1d](#), [mlr\\_pipeops\\_nn\\_conv2d](#), [mlr\\_pipeops\\_nn\\_conv3d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose1d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose3d](#), [mlr\\_pipeops\\_nn\\_dropout](#), [mlr\\_pipeops\\_nn\\_elu](#), [mlr\\_pipeops\\_nn\\_flatten](#), [mlr\\_pipeops\\_nn\\_ft\\_cls](#), [mlr\\_pipeops\\_nn\\_ft\\_transformer\\_block](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_hardshrink](#), [mlr\\_pipeops\\_nn\\_hardtanh](#), [mlr\\_pipeops\\_nn\\_head](#), [mlr\\_pipeops\\_nn\\_identity](#), [mlr\\_pipeops\\_nn\\_layer\\_norm](#), [mlr\\_pipeops\\_nn\\_leaky\\_relu](#), [mlr\\_pipeops\\_nn\\_linear](#), [mlr\\_pipeops\\_nn\\_log\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_max\\_pool1d](#), [mlr\\_pipeops\\_nn\\_max\\_pool2d](#), [mlr\\_pipeops\\_nn\\_max\\_pool3d](#), [mlr\\_pipeops\\_nn\\_merge](#), [mlr\\_pipeops\\_nn\\_merge\\_cat](#), [mlr\\_pipeops\\_nn\\_merge\\_prod](#), [mlr\\_pipeops\\_nn\\_merge\\_sum](#), [mlr\\_pipeops\\_nn\\_prelu](#), [mlr\\_pipeops\\_nn\\_reglu](#), [mlr\\_pipeops\\_nn\\_relu](#), [mlr\\_pipeops\\_nn\\_relu6](#), [mlr\\_pipeops\\_nn\\_reshape](#), [mlr\\_pipeops\\_nn\\_rrelu](#), [mlr\\_pipeops\\_nn\\_selu](#), [mlr\\_pipeops\\_nn\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_softmax](#), [mlr\\_pipeops\\_nn\\_softplus](#), [mlr\\_pipeops\\_nn\\_softshrink](#), [mlr\\_pipeops\\_nn\\_softsign](#), [mlr\\_pipeops\\_nn\\_squeeze](#), [mlr\\_pipeops\\_nn\\_tanh](#), [mlr\\_pipeops\\_nn\\_tanhshrink](#), [mlr\\_pipeops\\_nn\\_threshold](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_categ](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_num](#), [mlr\\_pipeops\\_nn\\_unsqueeze](#), [mlr\\_pipeops\\_torch\\_ingress](#), [mlr\\_pipeops\\_torch\\_ingress\\_categ](#), [mlr\\_pipeops\\_torch\\_ingress\\_ltnsr](#), [mlr\\_pipeops\\_torch\\_ingress\\_num](#), [mlr\\_pipeops\\_torch\\_loss](#), [mlr\\_pipeops\\_torch\\_model](#), [mlr\\_pipeops\\_torch\\_model\\_classif](#), [mlr\\_pipeops\\_torch\\_model\\_regr](#)

## Examples

```
# Construct the PipeOp
pipeop = po("nn_hardsigmoid")
pipeop
# The available parameters
pipeop$param_set
```

---

### mlr\_pipeops\_nn\_hardtanh

*Hard Tanh Activation Function*

---

## Description

Applies the HardTanh function element-wise.

### nn\_module

Calls `torch::nnhardtanh()` when trained.

### Parameters

- `min_val` :: `numeric(1)`  
Minimum value of the linear region range. Default: -1.
- `max_val` :: `numeric(1)`  
Maximum value of the linear region range. Default: 1.
- `inplace` :: `logical(1)`  
Can optionally do the operation in-place. Default: FALSE.

### State

The state is the value calculated by the public method `$shapes_out()`.

### Super classes

`mlr3pipelines::PipeOp` -> `mlr3torch::PipeOpTorch` -> `PipeOpTorchHardTanh`

### Methods

#### Public methods:

- `PipeOpTorchHardTanh$new()`
- `PipeOpTorchHardTanh$clone()`

**Method** `new()`: Creates a new instance of this `R6` class.

*Usage:*

`PipeOpTorchHardTanh$new(id = "nn_hardtanh", param_vals = list())`

*Arguments:*

`id` (character(1))  
 Identifier of the resulting object.  
`param_vals` (list())  
 List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

```
PipeOpTorchHardTanh$clone(deep = FALSE)
```

*Arguments:*

`deep` Whether to make a deep clone.

## See Also

Other PipeOps: [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm1d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm2d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm3d](#), [mlr\\_pipeops\\_nn\\_block](#), [mlr\\_pipeops\\_nn\\_celu](#), [mlr\\_pipeops\\_nn\\_conv1d](#), [mlr\\_pipeops\\_nn\\_conv2d](#), [mlr\\_pipeops\\_nn\\_conv3d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose1d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose3d](#), [mlr\\_pipeops\\_nn\\_dropout](#), [mlr\\_pipeops\\_nn\\_elu](#), [mlr\\_pipeops\\_nn\\_flatten](#), [mlr\\_pipeops\\_nn\\_ft\\_cls](#), [mlr\\_pipeops\\_nn\\_ft\\_transformer\\_block](#), [mlr\\_pipeops\\_nn\\_geglu](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_glu](#), [mlr\\_pipeops\\_nn\\_hardshrink](#), [mlr\\_pipeops\\_nn\\_hardsigmoid](#), [mlr\\_pipeops\\_nn\\_head](#), [mlr\\_pipeops\\_nn\\_identity](#), [mlr\\_pipeops\\_nn\\_layer\\_norm](#), [mlr\\_pipeops\\_nn\\_leaky\\_relu](#), [mlr\\_pipeops\\_nn\\_linear](#), [mlr\\_pipeops\\_nn\\_log\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_max\\_pool1d](#), [mlr\\_pipeops\\_nn\\_max\\_pool2d](#), [mlr\\_pipeops\\_nn\\_max\\_pool3d](#), [mlr\\_pipeops\\_nn\\_merge](#), [mlr\\_pipeops\\_nn\\_merge\\_cat](#), [mlr\\_pipeops\\_nn\\_merge\\_prod](#), [mlr\\_pipeops\\_nn\\_merge\\_sum](#), [mlr\\_pipeops\\_nn\\_prelu](#), [mlr\\_pipeops\\_nn\\_reglu](#), [mlr\\_pipeops\\_nn\\_relu](#), [mlr\\_pipeops\\_nn\\_relu6](#), [mlr\\_pipeops\\_nn\\_reshape](#), [mlr\\_pipeops\\_nn\\_rrelu](#), [mlr\\_pipeops\\_nn\\_selu](#), [mlr\\_pipeops\\_nn\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_softmax](#), [mlr\\_pipeops\\_nn\\_softplus](#), [mlr\\_pipeops\\_nn\\_softshrink](#), [mlr\\_pipeops\\_nn\\_softsign](#), [mlr\\_pipeops\\_nn\\_squeeze](#), [mlr\\_pipeops\\_nn\\_tanh](#), [mlr\\_pipeops\\_nn\\_tanhshrink](#), [mlr\\_pipeops\\_nn\\_threshold](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_categ](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_num](#), [mlr\\_pipeops\\_nn\\_unsqueeze](#), [mlr\\_pipeops\\_torch\\_ingress](#), [mlr\\_pipeops\\_torch\\_ingress\\_categ](#), [mlr\\_pipeops\\_torch\\_ingress\\_ltnsr](#), [mlr\\_pipeops\\_torch\\_ingress\\_num](#), [mlr\\_pipeops\\_torch\\_loss](#), [mlr\\_pipeops\\_torch\\_model](#), [mlr\\_pipeops\\_torch\\_model\\_classif](#), [mlr\\_pipeops\\_torch\\_model\\_regr](#)

## Examples

```
# Construct the PipeOp
pipeop = po("nn_hardtanh")
pipeop
# The available parameters
pipeop$param_set
```

---

mlr\_pipeops\_nn\_head     *Output Head*

---

## Description

Output head for classification and regression.

## Details

When the method `$shapes_out()` does not have access to the task, it returns `c(NA, NA)`. When this [PipeOp](#) is trained however, the model descriptor has the correct output shape.

### **nn\_module**

Calls [torch::nn\\_linear\(\)](#) with the input and output features inferred from the input shape / task. For

- binary classification, the output dimension is 1.
- multiclass classification, the output dimension is the number of classes.
- regression, the output dimension is 1.

## Parameters

- `bias :: logical(1)`  
Whether to use a bias. Default is TRUE.

## Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

## State

The state is the value calculated by the public method `$shapes_out()`.

## Super classes

[mlr3pipelines::PipeOp](#) -> [mlr3torch::PipeOpTorch](#) -> [PipeOpTorchHead](#)

## Methods

### Public methods:

- [PipeOpTorchHead\\$new\(\)](#)
- [PipeOpTorchHead\\$clone\(\)](#)

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

```
PipeOpTorchHead$new(id = "nn_head", param_vals = list())
```

*Arguments:*

`id` (character(1))

Identifier of the resulting object.

`param_vals` (list())

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

```
PipeOpTorchHead$clone(deep = FALSE)
```

*Arguments:*

`deep` Whether to make a deep clone.

## See Also

Other PipeOps: [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm1d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm2d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm3d](#), [mlr\\_pipeops\\_nn\\_block](#), [mlr\\_pipeops\\_nn\\_celu](#), [mlr\\_pipeops\\_nn\\_conv1d](#), [mlr\\_pipeops\\_nn\\_conv2d](#), [mlr\\_pipeops\\_nn\\_conv3d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose1d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose3d](#), [mlr\\_pipeops\\_nn\\_dropout](#), [mlr\\_pipeops\\_nn\\_elu](#), [mlr\\_pipeops\\_nn\\_flatten](#), [mlr\\_pipeops\\_nn\\_ft\\_cls](#), [mlr\\_pipeops\\_nn\\_ft\\_transformer\\_block](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_glu](#), [mlr\\_pipeops\\_nn\\_hardshrink](#), [mlr\\_pipeops\\_nn\\_hardsigmoid](#), [mlr\\_pipeops\\_nn\\_hardtanh](#), [mlr\\_pipeops\\_nn\\_identity](#), [mlr\\_pipeops\\_nn\\_layer\\_norm](#), [mlr\\_pipeops\\_nn\\_leaky\\_relu](#), [mlr\\_pipeops\\_nn\\_linear](#), [mlr\\_pipeops\\_nn\\_log\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_max\\_pool1d](#), [mlr\\_pipeops\\_nn\\_max\\_pool2d](#), [mlr\\_pipeops\\_nn\\_max\\_pool3d](#), [mlr\\_pipeops\\_nn\\_merge](#), [mlr\\_pipeops\\_nn\\_merge\\_cat](#), [mlr\\_pipeops\\_nn\\_merge\\_prod](#), [mlr\\_pipeops\\_nn\\_merge\\_sum](#), [mlr\\_pipeops\\_nn\\_prelu](#), [mlr\\_pipeops\\_nn\\_relu](#), [mlr\\_pipeops\\_nn\\_relu](#), [mlr\\_pipeops\\_nn\\_relu6](#), [mlr\\_pipeops\\_nn\\_reshape](#), [mlr\\_pipeops\\_nn\\_rrelu](#), [mlr\\_pipeops\\_nn\\_selu](#), [mlr\\_pipeops\\_nn\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_softmax](#), [mlr\\_pipeops\\_nn\\_softplus](#), [mlr\\_pipeops\\_nn\\_softshrink](#), [mlr\\_pipeops\\_nn\\_softsign](#), [mlr\\_pipeops\\_nn\\_squeeze](#), [mlr\\_pipeops\\_nn\\_tanh](#), [mlr\\_pipeops\\_nn\\_tanhshrink](#), [mlr\\_pipeops\\_nn\\_threshold](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_categ](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_num](#), [mlr\\_pipeops\\_nn\\_unsqueeze](#), [mlr\\_pipeops\\_torch\\_ingress](#), [mlr\\_pipeops\\_torch\\_ingress\\_categ](#), [mlr\\_pipeops\\_torch\\_ingress\\_ltnsr](#), [mlr\\_pipeops\\_torch\\_ingress\\_num](#), [mlr\\_pipeops\\_torch\\_loss](#), [mlr\\_pipeops\\_torch\\_model](#), [mlr\\_pipeops\\_torch\\_model\\_classif](#), [mlr\\_pipeops\\_torch\\_model\\_regr](#)

## Examples

```
# Construct the PipeOp
pipeop = po("nn_head")
pipeop
# The available parameters
pipeop$param_set
```

---

**mlr\_pipeops\_nn\_identity**  
*Identity Layer*

---

## Description

A placeholder identity operator that is argument-insensitive.

### nn\_module

Calls `torch::nn_identity()` when trained, which passes the input unchanged to the output.

### Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

### State

The state is the value calculated by the public method `$shapes_out()`.

### Super classes

`mlr3pipelines::PipeOp -> mlr3torch::PipeOpTorch -> PipeOpTorchIdentity`

### Methods

#### Public methods:

- `PipeOpTorchIdentity$new()`
- `PipeOpTorchIdentity$clone()`

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

`PipeOpTorchIdentity$new(id = "nn_identity", param_vals = list())`

*Arguments:*

`id` (character(1))

Identifier of the resulting object.

`param_vals` (list())

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

`PipeOpTorchIdentity$clone(deep = FALSE)`

*Arguments:*

`deep` Whether to make a deep clone.

**See Also**

Other PipeOps: [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm1d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm2d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm3d](#), [mlr\\_pipeops\\_nn\\_block](#), [mlr\\_pipeops\\_nn\\_celu](#), [mlr\\_pipeops\\_nn\\_conv1d](#), [mlr\\_pipeops\\_nn\\_conv2d](#), [mlr\\_pipeops\\_nn\\_conv3d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose1d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose3d](#), [mlr\\_pipeops\\_nn\\_dropout](#), [mlr\\_pipeops\\_nn\\_elu](#), [mlr\\_pipeops\\_nn\\_flatten](#), [mlr\\_pipeops\\_nn\\_ft\\_cls](#), [mlr\\_pipeops\\_nn\\_ft\\_transformer\\_block](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_glu](#), [mlr\\_pipeops\\_nn\\_hardshrink](#), [mlr\\_pipeops\\_nn\\_hardsigmoid](#), [mlr\\_pipeops\\_nn\\_hardtanh](#), [mlr\\_pipeops\\_nn\\_head](#), [mlr\\_pipeops\\_nn\\_layer\\_norm](#), [mlr\\_pipeops\\_nn\\_leaky\\_relu](#), [mlr\\_pipeops\\_nn\\_linear](#), [mlr\\_pipeops\\_nn\\_log\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_max\\_pool1d](#), [mlr\\_pipeops\\_nn\\_max\\_pool2d](#), [mlr\\_pipeops\\_nn\\_max\\_pool3d](#), [mlr\\_pipeops\\_nn\\_merge](#), [mlr\\_pipeops\\_nn\\_merge\\_cat](#), [mlr\\_pipeops\\_nn\\_merge\\_prod](#), [mlr\\_pipeops\\_nn\\_merge\\_sum](#), [mlr\\_pipeops\\_nn\\_prelu](#), [mlr\\_pipeops\\_nn\\_reglu](#), [mlr\\_pipeops\\_nn\\_relu](#), [mlr\\_pipeops\\_nn\\_relu6](#), [mlr\\_pipeops\\_nn\\_reshape](#), [mlr\\_pipeops\\_nn\\_rrelu](#), [mlr\\_pipeops\\_nn\\_selu](#), [mlr\\_pipeops\\_nn\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_softmax](#), [mlr\\_pipeops\\_nn\\_softplus](#), [mlr\\_pipeops\\_nn\\_softshrink](#), [mlr\\_pipeops\\_nn\\_softsign](#), [mlr\\_pipeops\\_nn\\_squeeze](#), [mlr\\_pipeops\\_nn\\_tanh](#), [mlr\\_pipeops\\_nn\\_tanhshrink](#), [mlr\\_pipeops\\_nn\\_threshold](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_categ](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_num](#), [mlr\\_pipeops\\_nn\\_unsqueeze](#), [mlr\\_pipeops\\_torch\\_ingress](#), [mlr\\_pipeops\\_torch\\_ingress\\_categ](#), [mlr\\_pipeops\\_torch\\_ingress\\_ltnsr](#), [mlr\\_pipeops\\_torch\\_ingress\\_num](#), [mlr\\_pipeops\\_torch\\_loss](#), [mlr\\_pipeops\\_torch\\_model](#), [mlr\\_pipeops\\_torch\\_model\\_classif](#), [mlr\\_pipeops\\_torch\\_model\\_regr](#)

**Examples**

```
# Construct the PipeOp
pipeop = po("nn_identity")
pipeop
# The available parameters
pipeop$param_set
```

---

**mlr\_pipeops\_nn\_layer\_norm**  
*Layer Normalization*

---

**Description**

Applies Layer Normalization for last certain number of dimensions.

**nn\_module**

Calls `torch::nn_layer_norm()` when trained. The parameter `normalized_shape` is inferred as the dimensions of the last `dims` dimensions of the input shape.

**Parameters**

- `dims :: integer(1)`  
The number of dimensions over which will be normalized (starting from the last dimension).

- `elementwise_affine` :: `logical(1)`  
Whether to learn affine-linear parameters initialized to 1 for weights and to 0 for biases. The default is TRUE.
- `eps` :: `numeric(1)`  
A value added to the denominator for numerical stability.

## State

The state is the value calculated by the public method `$shapes_out()`.

## Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

## Super classes

[mlr3pipelines::PipeOp](#) -> [mlr3torch::PipeOpTorch](#) -> `PipeOpTorchLayerNorm`

## Methods

### Public methods:

- [PipeOpTorchLayerNorm\\$new\(\)](#)
- [PipeOpTorchLayerNorm\\$clone\(\)](#)

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

`PipeOpTorchLayerNorm$new(id = "nn_layer_norm", param_vals = list())`

*Arguments:*

`id` (`character(1)`)

Identifier of the resulting object.

`param_vals` (`list()`)

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

`PipeOpTorchLayerNorm$clone(deep = FALSE)`

*Arguments:*

`deep` Whether to make a deep clone.

**See Also**

Other PipeOps: [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm1d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm2d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm3d](#), [mlr\\_pipeops\\_nn\\_block](#), [mlr\\_pipeops\\_nn\\_celu](#), [mlr\\_pipeops\\_nn\\_conv1d](#), [mlr\\_pipeops\\_nn\\_conv2d](#), [mlr\\_pipeops\\_nn\\_conv3d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose1d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose3d](#), [mlr\\_pipeops\\_nn\\_dropout](#), [mlr\\_pipeops\\_nn\\_elu](#), [mlr\\_pipeops\\_nn\\_flatten](#), [mlr\\_pipeops\\_nn\\_ft\\_cls](#), [mlr\\_pipeops\\_nn\\_ft\\_transformer\\_block](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_glu](#), [mlr\\_pipeops\\_nn\\_hardshrink](#), [mlr\\_pipeops\\_nn\\_hardsigmoid](#), [mlr\\_pipeops\\_nn\\_hardtanh](#), [mlr\\_pipeops\\_nn\\_head](#), [mlr\\_pipeops\\_nn\\_identity](#), [mlr\\_pipeops\\_nn\\_leaky\\_relu](#), [mlr\\_pipeops\\_nn\\_linear](#), [mlr\\_pipeops\\_nn\\_log\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_max\\_pool1d](#), [mlr\\_pipeops\\_nn\\_max\\_pool2d](#), [mlr\\_pipeops\\_nn\\_max\\_pool3d](#), [mlr\\_pipeops\\_nn\\_merge](#), [mlr\\_pipeops\\_nn\\_merge\\_cat](#), [mlr\\_pipeops\\_nn\\_merge\\_prod](#), [mlr\\_pipeops\\_nn\\_merge\\_sum](#), [mlr\\_pipeops\\_nn\\_prelu](#), [mlr\\_pipeops\\_nn\\_relu](#), [mlr\\_pipeops\\_nn\\_relu6](#), [mlr\\_pipeops\\_nn\\_reshape](#), [mlr\\_pipeops\\_nn\\_rrelu](#), [mlr\\_pipeops\\_nn\\_selu](#), [mlr\\_pipeops\\_nn\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_softmax](#), [mlr\\_pipeops\\_nn\\_softplus](#), [mlr\\_pipeops\\_nn\\_softshrink](#), [mlr\\_pipeops\\_nn\\_softsign](#), [mlr\\_pipeops\\_nn\\_squeeze](#), [mlr\\_pipeops\\_nn\\_tanh](#), [mlr\\_pipeops\\_nn\\_tanhshrink](#), [mlr\\_pipeops\\_nn\\_threshold](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_categ](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_num](#), [mlr\\_pipeops\\_nn\\_unsqueeze](#), [mlr\\_pipeops\\_torch\\_ingress](#), [mlr\\_pipeops\\_torch\\_ingress\\_categ](#), [mlr\\_pipeops\\_torch\\_ingress\\_ltnsr](#), [mlr\\_pipeops\\_torch\\_ingress\\_num](#), [mlr\\_pipeops\\_torch\\_loss](#), [mlr\\_pipeops\\_torch\\_model](#), [mlr\\_pipeops\\_torch\\_model\\_classif](#), [mlr\\_pipeops\\_torch\\_model\\_regr](#)

**Examples**

```
# Construct the PipeOp
pipeop = po("nn_layer_norm", dims = 1)
pipeop
# The available parameters
pipeop$param_set
```

---

**mlr\_pipeops\_nn\_leaky\_relu***Leaky ReLU Activation Function*

---

**Description**

Applies element-wise,  $\text{LeakyReLU}(x) = \max(0, x) + \text{negative\_slope} * \min(0, x)$

**nn\_module**

Calls `torch::nn_leaky_relu()` when trained.

**Parameters**

- `negative_slope` :: `numeric(1)`  
Controls the angle of the negative slope. Default: 1e-2.
- `inplace` :: `logical(1)`  
Can optionally do the operation in-place. Default: FALSE.

## Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

## State

The state is the value calculated by the public method `$shapes_out()`.

## Super classes

`mlr3pipelines::PipeOp -> mlr3torch::PipeOpTorch -> PipeOpTorchLeakyReLU`

## Methods

### Public methods:

- `PipeOpTorchLeakyReLU$new()`
- `PipeOpTorchLeakyReLU$clone()`

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

`PipeOpTorchLeakyReLU$new(id = "nn_leaky_relu", param_vals = list())`

*Arguments:*

`id` (character(1))

Identifier of the resulting object.

`param_vals` (list())

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

`PipeOpTorchLeakyReLU$clone(deep = FALSE)`

*Arguments:*

`deep` Whether to make a deep clone.

## See Also

Other PipeOps: `mlr_pipeops_nn_adaptive_avg_pool1d`, `mlr_pipeops_nn_adaptive_avg_pool2d`, `mlr_pipeops_nn_adaptive_avg_pool3d`, `mlr_pipeops_nn_avg_pool1d`, `mlr_pipeops_nn_avg_pool2d`, `mlr_pipeops_nn_avg_pool3d`, `mlr_pipeops_nn_batch_norm1d`, `mlr_pipeops_nn_batch_norm2d`, `mlr_pipeops_nn_batch_norm3d`, `mlr_pipeops_nn_block`, `mlr_pipeops_nn_celu`, `mlr_pipeops_nn_conv1d`, `mlr_pipeops_nn_conv2d`, `mlr_pipeops_nn_conv3d`, `mlr_pipeops_nn_conv_transpose1d`, `mlr_pipeops_nn_conv_transpose3d`, `mlr_pipeops_nn_dropout`, `mlr_pipeops_nn_elu`, `mlr_pipeops_nn_flatten`, `mlr_pipeops_nn_ft_cls`, `mlr_pipeops_nn_ft_transformer_block`, `mlr_pipeops_nn_gelu`, `mlr_pipeops_nn_gelu`, `mlr_pipeops_nn_glu`, `mlr_pipeops_nn_hardshrink`, `mlr_pipeops_nn_hardsigmoid`, `mlr_pipeops_nn_hardtanh`, `mlr_pipeops_nn_head`, `mlr_pipeops_nn_identity`, `mlr_pipeops_nn_layer_norm`, `mlr_pipeops_nn_linear`, `mlr_pipeops_nn_log_sigmoid`, `mlr_pipeops_nn_max_pool1d`, `mlr_pipeops_nn_max_pool2d`

```
mlr_pipeops_nn_max_pool3d, mlr_pipeops_nn_merge, mlr_pipeops_nn_merge_cat, mlr_pipeops_nn_merge_prod,
mlr_pipeops_nn_merge_sum, mlr_pipeops_nn_prelu, mlr_pipeops_nn_reglu, mlr_pipeops_nn_relu,
mlr_pipeops_nn_relu6, mlr_pipeops_nn_reshape, mlr_pipeops_nn_rrelu, mlr_pipeops_nn_selu,
mlr_pipeops_nn_sigmoid, mlr_pipeops_nn_softmax, mlr_pipeops_nn_softplus, mlr_pipeops_nn_softshrink,
mlr_pipeops_nn_softsign, mlr_pipeops_nn_squeeze, mlr_pipeops_nn_tanh, mlr_pipeops_nn_tanhshrink,
mlr_pipeops_nn_threshold, mlr_pipeops_nn_tokenizer_categ, mlr_pipeops_nn_tokenizer_num,
mlr_pipeops_nn_unsqueeze, mlr_pipeops_torch_ingress, mlr_pipeops_torch_ingress_categ,
mlr_pipeops_torch_ingress_ltnsr, mlr_pipeops_torch_ingress_num, mlr_pipeops_torch_loss,
mlr_pipeops_torch_model, mlr_pipeops_torch_model_classif, mlr_pipeops_torch_model_regr
```

## Examples

```
# Construct the PipeOp
pipeop = po("nn_leaky_relu")
pipeop
# The available parameters
pipeop$param_set
```

---

mlr\_pipeops\_nn\_linear *Linear Layer*

---

## Description

Applies a linear transformation to the incoming data:  $y = xA^T + b$ .

### nn\_module

Calls `torch::nn_linear()` when trained where the parameter `in_features` is inferred as the second to last dimension of the input tensor.

### Parameters

- `out_features` :: `integer(1)`  
The output features of the linear layer.
- `bias` :: `logical(1)`  
Whether to use a bias. Default is TRUE.

### Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

### State

The state is the value calculated by the public method `$shapes_out()`.

## Super classes

[mlr3pipelines::PipeOp](#) -> [mlr3torch::PipeOpTorch](#) -> [PipeOpTorchLinear](#)

## Methods

### Public methods:

- [PipeOpTorchLinear\\$new\(\)](#)
- [PipeOpTorchLinear\\$clone\(\)](#)

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

`PipeOpTorchLinear$new(id = "nn_linear", param_vals = list())`

*Arguments:*

`id` (character(1))

Identifier of the resulting object.

`param_vals` (list())

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

`PipeOpTorchLinear$clone(deep = FALSE)`

*Arguments:*

`deep` Whether to make a deep clone.

## See Also

Other PipeOps: [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm1d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm2d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm3d](#), [mlr\\_pipeops\\_nn\\_block](#), [mlr\\_pipeops\\_nn\\_celu](#), [mlr\\_pipeops\\_nn\\_conv1d](#), [mlr\\_pipeops\\_nn\\_conv2d](#), [mlr\\_pipeops\\_nn\\_conv3d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose1d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose3d](#), [mlr\\_pipeops\\_nn\\_dropout](#), [mlr\\_pipeops\\_nn\\_elu](#), [mlr\\_pipeops\\_nn\\_flatten](#), [mlr\\_pipeops\\_nn\\_ft\\_cls](#), [mlr\\_pipeops\\_nn\\_ft\\_transformer\\_block](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_glu](#), [mlr\\_pipeops\\_nn\\_hardshrink](#), [mlr\\_pipeops\\_nn\\_hardsigmoid](#), [mlr\\_pipeops\\_nn\\_hardtanh](#), [mlr\\_pipeops\\_nn\\_head](#), [mlr\\_pipeops\\_nn\\_identity](#), [mlr\\_pipeops\\_nn\\_layer\\_norm](#), [mlr\\_pipeops\\_nn\\_leaky\\_relu](#), [mlr\\_pipeops\\_nn\\_log\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_max\\_pool1d](#), [mlr\\_pipeops\\_nn\\_max\\_pool2d](#), [mlr\\_pipeops\\_nn\\_max\\_pool3d](#), [mlr\\_pipeops\\_nn\\_merge](#), [mlr\\_pipeops\\_nn\\_merge\\_cat](#), [mlr\\_pipeops\\_nn\\_merge\\_prod](#), [mlr\\_pipeops\\_nn\\_merge\\_sum](#), [mlr\\_pipeops\\_nn\\_prelu](#), [mlr\\_pipeops\\_nn\\_reglu](#), [mlr\\_pipeops\\_nn\\_relu](#), [mlr\\_pipeops\\_nn\\_relu6](#), [mlr\\_pipeops\\_nn\\_reshape](#), [mlr\\_pipeops\\_nn\\_rrelu](#), [mlr\\_pipeops\\_nn\\_selu](#), [mlr\\_pipeops\\_nn\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_softmax](#), [mlr\\_pipeops\\_nn\\_softplus](#), [mlr\\_pipeops\\_nn\\_softshrink](#), [mlr\\_pipeops\\_nn\\_softsign](#), [mlr\\_pipeops\\_nn\\_squeeze](#), [mlr\\_pipeops\\_nn\\_tanh](#), [mlr\\_pipeops\\_nn\\_tanhshrink](#), [mlr\\_pipeops\\_nn\\_threshold](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_categ](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_num](#), [mlr\\_pipeops\\_nn\\_unsqueeze](#), [mlr\\_pipeops\\_torch\\_ingress](#), [mlr\\_pipeops\\_torch\\_ingress\\_categ](#), [mlr\\_pipeops\\_torch\\_ingress\\_ltnsr](#), [mlr\\_pipeops\\_torch\\_ingress\\_num](#), [mlr\\_pipeops\\_torch\\_loss](#), [mlr\\_pipeops\\_torch\\_model](#), [mlr\\_pipeops\\_torch\\_model\\_classif](#), [mlr\\_pipeops\\_torch\\_model\\_regr](#)

## Examples

```
# Construct the PipeOp
pipeop = po("nn_linear", out_features = 10)
pipeop
# The available parameters
pipeop$param_set
```

---

### mlr\_pipeops\_nn\_log\_sigmoid

*Log Sigmoid Activation Function*

---

## Description

Applies element-wise  $\text{LogSigmoid}(x_i) = \log\left(\frac{1}{1+\exp(-x_i)}\right)$

### nn\_module

Calls `torch::nn_log_sigmoid()` when trained.

### Parameters

No parameters.

### Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

### State

The state is the value calculated by the public method `$shapes_out()`.

### Super classes

`mlr3pipelines::PipeOp -> mlr3torch::PipeOpTorch -> PipeOpTorchLogSigmoid`

### Methods

#### Public methods:

- `PipeOpTorchLogSigmoid$new()`
- `PipeOpTorchLogSigmoid$clone()`

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

`PipeOpTorchLogSigmoid$new(id = "nn_log_sigmoid", param_vals = list())`

*Arguments:*

```

  id (character(1))
    Identifier of the resulting object.
  param_vals (list())
    List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

```

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

```
PipeOpTorchLogSigmoid$clone(deep = FALSE)
```

*Arguments:*

`deep` Whether to make a deep clone.

## See Also

Other PipeOps: [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm1d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm2d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm3d](#), [mlr\\_pipeops\\_nn\\_block](#), [mlr\\_pipeops\\_nn\\_celu](#), [mlr\\_pipeops\\_nn\\_conv1d](#), [mlr\\_pipeops\\_nn\\_conv2d](#), [mlr\\_pipeops\\_nn\\_conv3d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose1d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose3d](#), [mlr\\_pipeops\\_nn\\_dropout](#), [mlr\\_pipeops\\_nn\\_elu](#), [mlr\\_pipeops\\_nn\\_flatten](#), [mlr\\_pipeops\\_nn\\_ft\\_cls](#), [mlr\\_pipeops\\_nn\\_ft\\_transformer\\_block](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_glu](#), [mlr\\_pipeops\\_nn\\_hardshrink](#), [mlr\\_pipeops\\_nn\\_hardsigmoid](#), [mlr\\_pipeops\\_nn\\_hardtanh](#), [mlr\\_pipeops\\_nn\\_head](#), [mlr\\_pipeops\\_nn\\_identity](#), [mlr\\_pipeops\\_nn\\_layer\\_norm](#), [mlr\\_pipeops\\_nn\\_leaky\\_relu](#), [mlr\\_pipeops\\_nn\\_linear](#), [mlr\\_pipeops\\_nn\\_max\\_pool1d](#), [mlr\\_pipeops\\_nn\\_max\\_pool2d](#), [mlr\\_pipeops\\_nn\\_max\\_pool3d](#), [mlr\\_pipeops\\_nn\\_merge](#), [mlr\\_pipeops\\_nn\\_merge\\_cat](#), [mlr\\_pipeops\\_nn\\_merge\\_prod](#), [mlr\\_pipeops\\_nn\\_merge\\_sum](#), [mlr\\_pipeops\\_nn\\_prelu](#), [mlr\\_pipeops\\_nn\\_relu](#), [mlr\\_pipeops\\_nn\\_relu6](#), [mlr\\_pipeops\\_nn\\_reshape](#), [mlr\\_pipeops\\_nn\\_rrelu](#), [mlr\\_pipeops\\_nn\\_selu](#), [mlr\\_pipeops\\_nn\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_softmax](#), [mlr\\_pipeops\\_nn\\_softplus](#), [mlr\\_pipeops\\_nn\\_softshrink](#), [mlr\\_pipeops\\_nn\\_softsign](#), [mlr\\_pipeops\\_nn\\_squeeze](#), [mlr\\_pipeops\\_nn\\_tanh](#), [mlr\\_pipeops\\_nn\\_tanhshrink](#), [mlr\\_pipeops\\_nn\\_threshold](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_categ](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_num](#), [mlr\\_pipeops\\_nn\\_unsqueeze](#), [mlr\\_pipeops\\_torch\\_ingress](#), [mlr\\_pipeops\\_torch\\_ingress\\_categ](#), [mlr\\_pipeops\\_torch\\_ingress\\_ltnsr](#), [mlr\\_pipeops\\_torch\\_ingress\\_num](#), [mlr\\_pipeops\\_torch\\_loss](#), [mlr\\_pipeops\\_torch\\_model](#), [mlr\\_pipeops\\_torch\\_model\\_classif](#), [mlr\\_pipeops\\_torch\\_model\\_regr](#)

## Examples

```

# Construct the PipeOp
pipeop = po("nn_log_sigmoid")
pipeop
# The available parameters
pipeop$param_set

```

---

**mlr\_pipeops\_nn\_max\_pool1d**  
*1D Max Pooling*

---

## Description

Applies a 1D max pooling over an input signal composed of several input planes.

### nn\_module

Calls `torch::nn_max_pool1d()` during training.

### Parameters

- `kernel_size` :: `integer()`  
The size of the window. Can be single number or a vector.
- `stride` :: `(integer(1))`  
The stride of the window. Can be a single number or a vector. Default: `kernel_size`
- `padding` :: `integer()`  
Implicit zero paddings on both sides of the input. Can be a single number or a tuple (padW). Default: 0
- `dilation` :: `integer()`  
Controls the spacing between the kernel points; also known as the a trous algorithm. Default: 1
- `ceil_mode` :: `logical(1)`  
When True, will use ceil instead of floor to compute the output shape. Default: FALSE

### Input and Output Channels

If `return_indices` is FALSE during construction, there is one input channel 'input' and one output channel 'output'. If `return_indices` is TRUE, there are two output channels 'output' and 'indices'. For an explanation see [PipeOpTorch](#).

### State

The state is the value calculated by the public method `$shapes_out()`.

### Super classes

`mlr3pipelines::PipeOp` -> `mlr3torch::PipeOpTorch` -> `mlr3torch::PipeOpTorchMaxPool` -> `PipeOpTorchMaxPool1D`

## Methods

### Public methods:

- `PipeOpTorchMaxPool1D$new()`
- `PipeOpTorchMaxPool1D$clone()`

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

```
PipeOpTorchMaxPool1D$new(
  id = "nn_max_pool1d",
  return_indices = FALSE,
  param_vals = list()
)
```

*Arguments:*

`id` (character(1))

Identifier of the resulting object.

`return_indices` (logical(1))

Whether to return the indices. If this is TRUE, there are two output channels "output" and "indices".

`param_vals` (list())

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

```
PipeOpTorchMaxPool1D$clone(deep = FALSE)
```

*Arguments:*

`deep` Whether to make a deep clone.

## See Also

Other PipeOps: [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm1d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm2d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm3d](#), [mlr\\_pipeops\\_nn\\_block](#), [mlr\\_pipeops\\_nn\\_celu](#), [mlr\\_pipeops\\_nn\\_conv1d](#), [mlr\\_pipeops\\_nn\\_conv2d](#), [mlr\\_pipeops\\_nn\\_conv3d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose1d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose3d](#), [mlr\\_pipeops\\_nn\\_dropout](#), [mlr\\_pipeops\\_nn\\_elu](#), [mlr\\_pipeops\\_nn\\_flatten](#), [mlr\\_pipeops\\_nn\\_ft\\_cls](#), [mlr\\_pipeops\\_nn\\_ft\\_transformer\\_block](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_glu](#), [mlr\\_pipeops\\_nn\\_hardshrink](#), [mlr\\_pipeops\\_nn\\_hardsigmoid](#), [mlr\\_pipeops\\_nn\\_hardtanh](#), [mlr\\_pipeops\\_nn\\_head](#), [mlr\\_pipeops\\_nn\\_identity](#), [mlr\\_pipeops\\_nn\\_layer\\_norm](#), [mlr\\_pipeops\\_nn\\_leaky\\_relu](#), [mlr\\_pipeops\\_nn\\_linear](#), [mlr\\_pipeops\\_nn\\_log\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_max\\_pool2d](#), [mlr\\_pipeops\\_nn\\_max\\_pool3d](#), [mlr\\_pipeops\\_nn\\_merge](#), [mlr\\_pipeops\\_nn\\_merge\\_cat](#), [mlr\\_pipeops\\_nn\\_merge\\_prod](#), [mlr\\_pipeops\\_nn\\_merge\\_sum](#), [mlr\\_pipeops\\_nn\\_prelu](#), [mlr\\_pipeops\\_nn\\_reglu](#), [mlr\\_pipeops\\_nn\\_relu](#), [mlr\\_pipeops\\_nn\\_relu6](#), [mlr\\_pipeops\\_nn\\_reshape](#), [mlr\\_pipeops\\_nn\\_rrelu](#), [mlr\\_pipeops\\_nn\\_selu](#), [mlr\\_pipeops\\_nn\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_softmax](#), [mlr\\_pipeops\\_nn\\_softplus](#), [mlr\\_pipeops\\_nn\\_softshrink](#), [mlr\\_pipeops\\_nn\\_softsign](#), [mlr\\_pipeops\\_nn\\_squeeze](#), [mlr\\_pipeops\\_nn\\_tanh](#), [mlr\\_pipeops\\_nn\\_tanhshrink](#), [mlr\\_pipeops\\_nn\\_threshold](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_categ](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_num](#),

```
mlr_pipeops_nn_unsqueeze, mlr_pipeops_torch_ingress, mlr_pipeops_torch_ingress_categ,
mlr_pipeops_torch_ingress_ltnsr, mlr_pipeops_torch_ingress_num, mlr_pipeops_torch_loss,
mlr_pipeops_torch_model, mlr_pipeops_torch_model_classif, mlr_pipeops_torch_model_regr
```

## Examples

```
# Construct the PipeOp
pipeop = po("nn_max_pool1d")
pipeop
# The available parameters
pipeop$param_set
```

---

mlr\_pipeops\_nn\_max\_pool2d  
*2D Max Pooling*

---

## Description

Applies a 2D max pooling over an input signal composed of several input planes.

### nn\_module

Calls [torch::nn\\_max\\_pool2d\(\)](#) during training.

### State

The state is the value calculated by the public method `$shapes_out()`.

### Parameters

- `kernel_size :: integer()`  
The size of the window. Can be single number or a vector.
- `stride :: (integer(1))`  
The stride of the window. Can be a single number or a vector. Default: `kernel_size`
- `padding :: integer()`  
Implicit zero paddings on both sides of the input. Can be a single number or a tuple (padW). Default: 0
- `dilation :: integer()`  
Controls the spacing between the kernel points; also known as the a trous algorithm. Default: 1
- `ceil_mode :: logical(1)`  
When True, will use ceil instead of floor to compute the output shape. Default: FALSE

## Input and Output Channels

If `return_indices` is FALSE during construction, there is one input channel 'input' and one output channel 'output'. If `return_indices` is TRUE, there are two output channels 'output' and 'indices'. For an explanation see [PipeOpTorch](#).

## Super classes

```
mlr3pipelines::PipeOp -> mlr3torch::PipeOpTorch -> mlr3torch::PipeOpTorchMaxPool -> PipeOpTorchMaxPool2D
```

## Methods

### Public methods:

- `PipeOpTorchMaxPool2D$new()`
- `PipeOpTorchMaxPool2D$clone()`

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

```
PipeOpTorchMaxPool2D$new(
  id = "nn_max_pool2d",
  return_indices = FALSE,
  param_vals = list()
)
```

*Arguments:*

`id` (character(1))

Identifier of the resulting object.

`return_indices` (logical(1))

Whether to return the indices. If this is TRUE, there are two output channels "output" and "indices".

`param_vals` (list())

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

```
PipeOpTorchMaxPool2D$clone(deep = FALSE)
```

*Arguments:*

`deep` Whether to make a deep clone.

## See Also

Other PipeOps: [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm1d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm2d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm3d](#), [mlr\\_pipeops\\_nn\\_block](#), [mlr\\_pipeops\\_nn\\_celu](#), [mlr\\_pipeops\\_nn\\_conv1d](#), [mlr\\_pipeops\\_nn\\_conv2d](#), [mlr\\_pipeops\\_nn\\_conv3d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose1d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose2d](#)

```
mlr_pipeops_nn_conv_transpose3d, mlr_pipeops_nn_dropout, mlr_pipeops_nn_elu, mlr_pipeops_nn_flatten,
mlr_pipeops_nn_ft_cls, mlr_pipeops_nn_ft_transformer_block, mlr_pipeops_nn_geglu,
mlr_pipeops_nn_gelu, mlr_pipeops_nn_glu, mlr_pipeops_nn_hardshrink, mlr_pipeops_nn_hardsigmoid,
mlr_pipeops_nn_hardtanh, mlr_pipeops_nn_head, mlr_pipeops_nn_identity, mlr_pipeops_nn_layer_norm,
mlr_pipeops_nn_leaky_relu, mlr_pipeops_nn_linear, mlr_pipeops_nn_log_sigmoid, mlr_pipeops_nn_max_pool1d,
mlr_pipeops_nn_max_pool3d, mlr_pipeops_nn_merge, mlr_pipeops_nn_merge_cat, mlr_pipeops_nn_merge_prod,
mlr_pipeops_nn_merge_sum, mlr_pipeops_nn_prelu, mlr_pipeops_nn_reglu, mlr_pipeops_nn_relu,
mlr_pipeops_nn_relu6, mlr_pipeops_nn_reshape, mlr_pipeops_nn_rrelu, mlr_pipeops_nn_selu,
mlr_pipeops_nn_sigmoid, mlr_pipeops_nn_softmax, mlr_pipeops_nn_softplus, mlr_pipeops_nn_softshrink,
mlr_pipeops_nn_softsign, mlr_pipeops_nn_squeeze, mlr_pipeops_nn_tanh, mlr_pipeops_nn_tanhshrink,
mlr_pipeops_nn_threshold, mlr_pipeops_nn_tokenizer_categ, mlr_pipeops_nn_tokenizer_num,
mlr_pipeops_nn_unsqueeze, mlr_pipeops_torch_ingress, mlr_pipeops_torch_ingress_categ,
mlr_pipeops_torch_ingress_ltnsr, mlr_pipeops_torch_ingress_num, mlr_pipeops_torch_loss,
mlr_pipeops_torch_model, mlr_pipeops_torch_model_classif, mlr_pipeops_torch_model_regr
```

## Examples

```
# Construct the PipeOp
pipeop = po("nn_max_pool2d")
pipeop
# The available parameters
pipeop$param_set
```

---

mlr\_pipeops\_nn\_max\_pool3d  
3D Max Pooling

---

## Description

Applies a 3D max pooling over an input signal composed of several input planes.

### nn\_module

Calls `torch::nn_max_pool3d()` during training.

### State

The state is the value calculated by the public method `$shapes_out()`.

### Parameters

- `kernel_size` :: `integer()`  
The size of the window. Can be single number or a vector.
- `stride` :: `(integer(1))`  
The stride of the window. Can be a single number or a vector. Default: `kernel_size`

- `padding :: integer()`  
Implicit zero paddings on both sides of the input. Can be a single number or a tuple (padW). Default: 0
- `dilation :: integer()`  
Controls the spacing between the kernel points; also known as the a trous algorithm. Default: 1
- `ceil_mode :: logical(1)`  
When True, will use ceil instead of floor to compute the output shape. Default: FALSE

## Input and Output Channels

If `return_indices` is FALSE during construction, there is one input channel 'input' and one output channel 'output'. If `return_indices` is TRUE, there are two output channels 'output' and 'indices'. For an explanation see [PipeOpTorch](#).

## Super classes

`mlr3pipelines::PipeOp` -> `mlr3torch::PipeOpTorch` -> `mlr3torch::PipeOpTorchMaxPool` -> `PipeOpTorchMaxPool3D`

## Methods

### Public methods:

- `PipeOpTorchMaxPool3D$new()`
- `PipeOpTorchMaxPool3D$clone()`

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

```
PipeOpTorchMaxPool3D$new(
  id = "nn_max_pool3d",
  return_indices = FALSE,
  param_vals = list()
)
```

*Arguments:*

`id` (character(1))  
Identifier of the resulting object.  
`return_indices` (logical(1))  
Whether to return the indices. If this is TRUE, there are two output channels "output" and "indices".  
`param_vals` (list())  
List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

```
PipeOpTorchMaxPool3D$clone(deep = FALSE)
```

*Arguments:*

`deep` Whether to make a deep clone.

## See Also

Other PipeOps: [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm1d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm2d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm3d](#), [mlr\\_pipeops\\_nn\\_block](#), [mlr\\_pipeops\\_nn\\_celu](#), [mlr\\_pipeops\\_nn\\_conv1d](#), [mlr\\_pipeops\\_nn\\_conv2d](#), [mlr\\_pipeops\\_nn\\_conv3d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose1d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose3d](#), [mlr\\_pipeops\\_nn\\_dropout](#), [mlr\\_pipeops\\_nn\\_elu](#), [mlr\\_pipeops\\_nn\\_flatten](#), [mlr\\_pipeops\\_nn\\_ft\\_cls](#), [mlr\\_pipeops\\_nn\\_ft\\_transformer\\_block](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_glu](#), [mlr\\_pipeops\\_nn\\_hardshrink](#), [mlr\\_pipeops\\_nn\\_hardsigmoid](#), [mlr\\_pipeops\\_nn\\_hardtanh](#), [mlr\\_pipeops\\_nn\\_head](#), [mlr\\_pipeops\\_nn\\_identity](#), [mlr\\_pipeops\\_nn\\_layer\\_norm](#), [mlr\\_pipeops\\_nn\\_leaky\\_relu](#), [mlr\\_pipeops\\_nn\\_linear](#), [mlr\\_pipeops\\_nn\\_log\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_max\\_pool1d](#), [mlr\\_pipeops\\_nn\\_max\\_pool2d](#), [mlr\\_pipeops\\_nn\\_merge](#), [mlr\\_pipeops\\_nn\\_merge\\_cat](#), [mlr\\_pipeops\\_nn\\_merge\\_prod](#), [mlr\\_pipeops\\_nn\\_merge\\_sum](#), [mlr\\_pipeops\\_nn\\_prelu](#), [mlr\\_pipeops\\_nn\\_reglu](#), [mlr\\_pipeops\\_nn\\_relu](#), [mlr\\_pipeops\\_nn\\_relu6](#), [mlr\\_pipeops\\_nn\\_reshape](#), [mlr\\_pipeops\\_nn\\_rrelu](#), [mlr\\_pipeops\\_nn\\_selu](#), [mlr\\_pipeops\\_nn\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_softmax](#), [mlr\\_pipeops\\_nn\\_softplus](#), [mlr\\_pipeops\\_nn\\_softshrink](#), [mlr\\_pipeops\\_nn\\_softsign](#), [mlr\\_pipeops\\_nn\\_squeeze](#), [mlr\\_pipeops\\_nn\\_tanh](#), [mlr\\_pipeops\\_nn\\_tanhshrink](#), [mlr\\_pipeops\\_nn\\_threshold](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_categ](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_num](#), [mlr\\_pipeops\\_nn\\_unsqueeze](#), [mlr\\_pipeops\\_torch\\_ingress](#), [mlr\\_pipeops\\_torch\\_ingress\\_categ](#), [mlr\\_pipeops\\_torch\\_ingress\\_ltnsr](#), [mlr\\_pipeops\\_torch\\_ingress\\_num](#), [mlr\\_pipeops\\_torch\\_loss](#), [mlr\\_pipeops\\_torch\\_model](#), [mlr\\_pipeops\\_torch\\_model\\_classif](#), [mlr\\_pipeops\\_torch\\_model\\_regr](#)

## Examples

```
# Construct the PipeOp
pipeop = po("nn_max_pool3d")
pipeop
# The available parameters
pipeop$param_set
```

---

### mlr\_pipeops\_nn\_merge *Merge Operation*

---

## Description

Base class for merge operations such as addition ([PipeOpTorchMergeSum](#)), multiplication ([PipeOpTorchMergeProd](#)) or concatenation ([PipeOpTorchMergeCat](#)).

## Parameters

See the respective child class.

## State

The state is the value calculated by the public method `shapes_out()`.

## Input and Output Channels

`PipeOpTorchMerges` has either a `vararg` input channel if the constructor argument `innum` is not set, or input channels "input1", ..., "input<innum>". There is one output channel "output". For an explanation see [PipeOpTorch](#).

## Internals

Per default, the `private$.shapes_out()` method outputs the broadcasted tensors. There are two things to be aware:

1. NAs are assumed to batch (this should almost always be the batch size in the first dimension).
2. Tensors are expected to have the same number of dimensions, i.e. missing dimensions are not filled with 1s. The reason is again that the first dimension should be the batch dimension. This `private` method can be overwritten by [PipeOpTorch](#) inheriting from this class.

## Super classes

`mlr3pipelines::PipeOp` -> `mlr3torch::PipeOpTorch` -> `PipeOpTorchMerge`

## Methods

### Public methods:

- `PipeOpTorchMerge$new()`
- `PipeOpTorchMerge$clone()`

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

```
PipeOpTorchMerge$new(
  id,
  module_generator,
  param_set = ps(),
  innum = 0,
  param_vals = list()
)
```

*Arguments:*

`id` (character(1))

Identifier of the resulting object.

`module_generator` (nn\_module\_generator)

The torch module generator.

`param_set` ([ParamSet](#))

The parameter set.

`innum` (integer(1))

The number of inputs. Default is 0 which means there is one `vararg` input channel.

`param_vals` (list())

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

```
PipeOpTorchMerge$clone(deep = FALSE)
```

*Arguments:*

`deep` Whether to make a deep clone.

## See Also

Other PipeOps: [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm1d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm2d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm3d](#), [mlr\\_pipeops\\_nn\\_block](#), [mlr\\_pipeops\\_nn\\_celu](#), [mlr\\_pipeops\\_nn\\_conv1d](#), [mlr\\_pipeops\\_nn\\_conv2d](#), [mlr\\_pipeops\\_nn\\_conv3d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose1d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose3d](#), [mlr\\_pipeops\\_nn\\_dropout](#), [mlr\\_pipeops\\_nn\\_elu](#), [mlr\\_pipeops\\_nn\\_flatten](#), [mlr\\_pipeops\\_nn\\_ft\\_cls](#), [mlr\\_pipeops\\_nn\\_ft\\_transformer\\_block](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_glu](#), [mlr\\_pipeops\\_nn\\_hardshrink](#), [mlr\\_pipeops\\_nn\\_hardsigmoid](#), [mlr\\_pipeops\\_nn\\_hardtanh](#), [mlr\\_pipeops\\_nn\\_head](#), [mlr\\_pipeops\\_nn\\_identity](#), [mlr\\_pipeops\\_nn\\_layer\\_norm](#), [mlr\\_pipeops\\_nn\\_leaky\\_relu](#), [mlr\\_pipeops\\_nn\\_linear](#), [mlr\\_pipeops\\_nn\\_log\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_max\\_pool1d](#), [mlr\\_pipeops\\_nn\\_max\\_pool2d](#), [mlr\\_pipeops\\_nn\\_max\\_pool3d](#), [mlr\\_pipeops\\_nn\\_merge\\_cat](#), [mlr\\_pipeops\\_nn\\_merge\\_pr](#), [mlr\\_pipeops\\_nn\\_merge\\_sum](#), [mlr\\_pipeops\\_nn\\_prelu](#), [mlr\\_pipeops\\_nn\\_reglu](#), [mlr\\_pipeops\\_nn\\_relu](#), [mlr\\_pipeops\\_nn\\_relu6](#), [mlr\\_pipeops\\_nn\\_reshape](#), [mlr\\_pipeops\\_nn\\_rrelu](#), [mlr\\_pipeops\\_nn\\_selu](#), [mlr\\_pipeops\\_nn\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_softmax](#), [mlr\\_pipeops\\_nn\\_softplus](#), [mlr\\_pipeops\\_nn\\_softshrink](#), [mlr\\_pipeops\\_nn\\_softsign](#), [mlr\\_pipeops\\_nn\\_squeeze](#), [mlr\\_pipeops\\_nn\\_tanh](#), [mlr\\_pipeops\\_nn\\_tanhshrink](#), [mlr\\_pipeops\\_nn\\_threshold](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_categ](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_num](#), [mlr\\_pipeops\\_nn\\_unsqueeze](#), [mlr\\_pipeops\\_torch\\_ingress](#), [mlr\\_pipeops\\_torch\\_ingress\\_categ](#), [mlr\\_pipeops\\_torch\\_ingress\\_ltnsr](#), [mlr\\_pipeops\\_torch\\_ingress\\_num](#), [mlr\\_pipeops\\_torch\\_loss](#), [mlr\\_pipeops\\_torch\\_model](#), [mlr\\_pipeops\\_torch\\_model\\_classif](#), [mlr\\_pipeops\\_torch\\_model\\_regr](#)

---

## mlr\_pipeops\_nn\_merge\_cat

*Merge by Concatenation*

---

### Description

Concatenates multiple tensors on a given dimension. No broadcasting rules are applied here, you must reshape the tensors before to have the same shape.

#### nn\_module

Calls [nn\\_merge\\_cat\(\)](#) when trained.

#### Parameters

- `dim :: integer(1)`  
The dimension along which to concatenate the tensors. The default is -1, i.e., the last dimension.

## Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

PipeOpTorchMerges has either a *vararg* input channel if the constructor argument `innum` is not set, or input channels "input1", ..., "input<innum>". There is one output channel "output". For an explanation see [PipeOpTorch](#).

## State

The state is the value calculated by the public method `$shapes_out()`.

## Super classes

`mlr3pipelines::PipeOp -> mlr3torch::PipeOpTorch -> mlr3torch::PipeOpTorchMerge -> PipeOpTorchMergeCat`

## Methods

### Public methods:

- [PipeOpTorchMergeCat\\$new\(\)](#)
- [PipeOpTorchMergeCat\\$speak\(\)](#)
- [PipeOpTorchMergeCat\\$clone\(\)](#)

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

`PipeOpTorchMergeCat$new(id = "nn_merge_cat", innum = 0, param_vals = list())`

*Arguments:*

`id` (character(1))

Identifier of the resulting object.

`innum` (integer(1))

The number of inputs. Default is 0 which means there is one *vararg* input channel.

`param_vals` (list())

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

**Method** `speak()`: What does the cat say?

*Usage:*

`PipeOpTorchMergeCat$speak()`

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

`PipeOpTorchMergeCat$clone(deep = FALSE)`

*Arguments:*

`deep` Whether to make a deep clone.

**See Also**

Other PipeOps: [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm1d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm2d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm3d](#), [mlr\\_pipeops\\_nn\\_block](#), [mlr\\_pipeops\\_nn\\_celu](#), [mlr\\_pipeops\\_nn\\_conv1d](#), [mlr\\_pipeops\\_nn\\_conv2d](#), [mlr\\_pipeops\\_nn\\_conv3d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose1d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose3d](#), [mlr\\_pipeops\\_nn\\_dropout](#), [mlr\\_pipeops\\_nn\\_elu](#), [mlr\\_pipeops\\_nn\\_flatten](#), [mlr\\_pipeops\\_nn\\_ft\\_cls](#), [mlr\\_pipeops\\_nn\\_ft\\_transformer\\_block](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_glu](#), [mlr\\_pipeops\\_nn\\_hardshrink](#), [mlr\\_pipeops\\_nn\\_hardsigmoid](#), [mlr\\_pipeops\\_nn\\_hardtanh](#), [mlr\\_pipeops\\_nn\\_head](#), [mlr\\_pipeops\\_nn\\_identity](#), [mlr\\_pipeops\\_nn\\_layer\\_norm](#), [mlr\\_pipeops\\_nn\\_leaky\\_relu](#), [mlr\\_pipeops\\_nn\\_linear](#), [mlr\\_pipeops\\_nn\\_log\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_max\\_pool1d](#), [mlr\\_pipeops\\_nn\\_max\\_pool2d](#), [mlr\\_pipeops\\_nn\\_max\\_pool3d](#), [mlr\\_pipeops\\_nn\\_merge](#), [mlr\\_pipeops\\_nn\\_merge\\_prod](#), [mlr\\_pipeops\\_nn\\_merge\\_sum](#), [mlr\\_pipeops\\_nn\\_prelu](#), [mlr\\_pipeops\\_nn\\_reglu](#), [mlr\\_pipeops\\_nn\\_relu](#), [mlr\\_pipeops\\_nn\\_relu6](#), [mlr\\_pipeops\\_nn\\_reshape](#), [mlr\\_pipeops\\_nn\\_rrelu](#), [mlr\\_pipeops\\_nn\\_selu](#), [mlr\\_pipeops\\_nn\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_softmax](#), [mlr\\_pipeops\\_nn\\_softplus](#), [mlr\\_pipeops\\_nn\\_softshrink](#), [mlr\\_pipeops\\_nn\\_softsign](#), [mlr\\_pipeops\\_nn\\_squeeze](#), [mlr\\_pipeops\\_nn\\_tanh](#), [mlr\\_pipeops\\_nn\\_tanhshrink](#), [mlr\\_pipeops\\_nn\\_threshold](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_categ](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_num](#), [mlr\\_pipeops\\_nn\\_unsqueeze](#), [mlr\\_pipeops\\_torch\\_ingress](#), [mlr\\_pipeops\\_torch\\_ingress\\_categ](#), [mlr\\_pipeops\\_torch\\_ingress\\_ltnsr](#), [mlr\\_pipeops\\_torch\\_ingress\\_num](#), [mlr\\_pipeops\\_torch\\_loss](#), [mlr\\_pipeops\\_torch\\_model](#), [mlr\\_pipeops\\_torch\\_model\\_classif](#), [mlr\\_pipeops\\_torch\\_model\\_regr](#)

**Examples**

```
# Construct the PipeOp
pipeop = po("nn_merge_cat")
pipeop
# The available parameters
pipeop$param_set
```

---

**mlr\_pipeops\_nn\_merge\_prod**  
*Merge by Product*

---

**Description**

Calculates the product of all input tensors.

**nn\_module**

Calls [nn\\_merge\\_prod\(\)](#) when trained.

**Parameters**

No parameters.

## Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

PipeOpTorchMerges has either a *vararg* input channel if the constructor argument *innum* is not set, or input channels "input1", ..., "input<innum>". There is one output channel "output". For an explanation see [PipeOpTorch](#).

## State

The state is the value calculated by the public method `$shapes_out()`.

## Super classes

```
mlr3pipelines::PipeOp -> mlr3torch::PipeOpTorch -> mlr3torch::PipeOpTorchMerge ->
PipeOpTorchMergeProd
```

## Methods

### Public methods:

- [PipeOpTorchMergeProd\\$new\(\)](#)
- [PipeOpTorchMergeProd\\$clone\(\)](#)

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

```
PipeOpTorchMergeProd$new(id = "nn_merge_prod", innum = 0, param_vals = list())
```

*Arguments:*

`id` (character(1))

Identifier of the resulting object.

`innum` (integer(1))

The number of inputs. Default is 0 which means there is one *vararg* input channel.

`param_vals` (list())

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

```
PipeOpTorchMergeProd$clone(deep = FALSE)
```

*Arguments:*

`deep` Whether to make a deep clone.

## See Also

Other PipeOps: [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm1d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm2d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm3d](#), [mlr\\_pipeops\\_nn\\_block](#), [mlr\\_pipeops\\_nn\\_celu](#), [mlr\\_pipeops\\_nn\\_conv1d](#),

```
mlr_pipeops_nn_conv2d,mlr_pipeops_nn_conv3d,mlr_pipeops_nn_conv_transpose1d,mlr_pipeops_nn_conv_transpose3d,mlr_pipeops_nn_dropout,mlr_pipeops_nn_elu,mlr_pipeops_nn_flatten,mlr_pipeops_nn_ft_cls,mlr_pipeops_nn_ft_transformer_block,mlr_pipeops_nn_gelu,mlr_pipeops_nn_glu,mlr_pipeops_nn_hardshrink,mlr_pipeops_nn_hardsigmoid,mlr_pipeops_nn_hardtanh,mlr_pipeops_nn_head,mlr_pipeops_nn_identity,mlr_pipeops_nn_layer_norm,mlr_pipeops_nn_leaky_relu,mlr_pipeops_nn_linear,mlr_pipeops_nn_log_sigmoid,mlr_pipeops_nn_max_pool1d,mlr_pipeops_nn_max_pool2d,mlr_pipeops_nn_max_pool3d,mlr_pipeops_nn_merge,mlr_pipeops_nn_merge_cat,mlr_pipeops_nn_merge_sum,mlr_pipeops_nn_prelu,mlr_pipeops_nn_reglu,mlr_pipeops_nn_relu,mlr_pipeops_nn_relu6,mlr_pipeops_nn_reshape,mlr_pipeops_nn_rrelu,mlr_pipeops_nn_selu,mlr_pipeops_nn_sigmoid,mlr_pipeops_nn_softmax,mlr_pipeops_nn_softplus,mlr_pipeops_nn_softshrink,mlr_pipeops_nn_softsign,mlr_pipeops_nn_squeeze,mlr_pipeops_nn_tanh,mlr_pipeops_nn_tanhshrink,mlr_pipeops_nn_threshold,mlr_pipeops_nn_tokenizer_categ,mlr_pipeops_nn_tokenizer_num,mlr_pipeops_nn_unsqueeze,mlr_pipeops_torch_ingress,mlr_pipeops_torch_ingress_categ,mlr_pipeops_torch_ingress_ltnsr,mlr_pipeops_torch_ingress_num,mlr_pipeops_torch_loss,mlr_pipeops_torch_model,mlr_pipeops_torch_model_classif,mlr_pipeops_torch_model_regr
```

## Examples

```
# Construct the PipeOp
pipeop = po("nn_merge_prod")
pipeop
# The available parameters
pipeop$param_set
```

---

**mlr\_pipeops\_nn\_merge\_sum**  
*Merge by Summation*

---

## Description

Calculates the sum of all input tensors.

### nn\_module

Calls `nn_merge_sum()` when trained.

### Parameters

No parameters.

### Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

PipeOpTorchMerges has either a `vararg` input channel if the constructor argument `innum` is not set, or input channels "input1", ..., "input<innum>". There is one output channel "output". For an explanation see [PipeOpTorch](#).

## State

The state is the value calculated by the public method `$shapes_out()`.

## Super classes

`mlr3pipelines::PipeOp -> mlr3torch::PipeOpTorch -> mlr3torch::PipeOpTorchMerge -> PipeOpTorchMergeSum`

## Methods

### Public methods:

- `PipeOpTorchMergeSum$new()`
- `PipeOpTorchMergeSum$clone()`

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

`PipeOpTorchMergeSum$new(id = "nn_merge_sum", innum = 0, param_vals = list())`

*Arguments:*

`id` (character(1))

Identifier of the resulting object.

`innum` (integer(1))

The number of inputs. Default is 0 which means there is one *vararg* input channel.

`param_vals` (list())

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

`PipeOpTorchMergeSum$clone(deep = FALSE)`

*Arguments:*

`deep` Whether to make a deep clone.

## See Also

Other PipeOps: `mlr_pipeops_nn_adaptive_avg_pool1d`, `mlr_pipeops_nn_adaptive_avg_pool2d`, `mlr_pipeops_nn_adaptive_avg_pool3d`, `mlr_pipeops_nn_avg_pool1d`, `mlr_pipeops_nn_avg_pool2d`, `mlr_pipeops_nn_avg_pool3d`, `mlr_pipeops_nn_batch_norm1d`, `mlr_pipeops_nn_batch_norm2d`, `mlr_pipeops_nn_batch_norm3d`, `mlr_pipeops_nn_block`, `mlr_pipeops_nn_celu`, `mlr_pipeops_nn_conv1d`, `mlr_pipeops_nn_conv2d`, `mlr_pipeops_nn_conv3d`, `mlr_pipeops_nn_conv_transpose1d`, `mlr_pipeops_nn_conv_transpose3d`, `mlr_pipeops_nn_dropout`, `mlr_pipeops_nn_elu`, `mlr_pipeops_nn_flatten`, `mlr_pipeops_nn_ft_cls`, `mlr_pipeops_nn_ft_transformer_block`, `mlr_pipeops_nn_gelu`, `mlr_pipeops_nn_gelu`, `mlr_pipeops_nn_glu`, `mlr_pipeops_nn_hardshrink`, `mlr_pipeops_nn_hardsigmoid`, `mlr_pipeops_nn_hardtanh`, `mlr_pipeops_nn_head`, `mlr_pipeops_nn_identity`, `mlr_pipeops_nn_layer_norm`, `mlr_pipeops_nn_leaky_relu`, `mlr_pipeops_nn_linear`, `mlr_pipeops_nn_log_sigmoid`, `mlr_pipeops_nn_max_pool1d`, `mlr_pipeops_nn_max_pool2d`, `mlr_pipeops_nn_max_pool3d`, `mlr_pipeops_nn_merge`, `mlr_pipeops_nn_merge_cat`, `mlr_pipeops_nn_merge_prod`, `mlr_pipeops_nn_prelu`, `mlr_pipeops_nn_relu`, `mlr_pipeops_nn_relu`,

mlr\_pipeops\_nn\_relu6, mlr\_pipeops\_nn\_reshape, mlr\_pipeops\_nn\_rrelu, mlr\_pipeops\_nn\_selu, mlr\_pipeops\_nn\_sigmoid, mlr\_pipeops\_nn\_softmax, mlr\_pipeops\_nn\_softplus, mlr\_pipeops\_nn\_softshrink, mlr\_pipeops\_nn\_softsign, mlr\_pipeops\_nn\_squeeze, mlr\_pipeops\_nn\_tanh, mlr\_pipeops\_nn\_tanhshrink, mlr\_pipeops\_nn\_threshold, mlr\_pipeops\_nn\_tokenizer\_categ, mlr\_pipeops\_nn\_tokenizer\_num, mlr\_pipeops\_nn\_unsqueeze, mlr\_pipeops\_torch\_ingress, mlr\_pipeops\_torch\_ingress\_categ, mlr\_pipeops\_torch\_ingress\_ltnsr, mlr\_pipeops\_torch\_ingress\_num, mlr\_pipeops\_torch\_loss, mlr\_pipeops\_torch\_model, mlr\_pipeops\_torch\_model\_classif, mlr\_pipeops\_torch\_model\_regr

Other PipeOps: mlr\_pipeops\_nn\_adaptive\_avg\_pool1d, mlr\_pipeops\_nn\_adaptive\_avg\_pool2d, mlr\_pipeops\_nn\_adaptive\_avg\_pool3d, mlr\_pipeops\_nn\_avg\_pool1d, mlr\_pipeops\_nn\_avg\_pool2d, mlr\_pipeops\_nn\_avg\_pool3d, mlr\_pipeops\_nn\_batch\_norm1d, mlr\_pipeops\_nn\_batch\_norm2d, mlr\_pipeops\_nn\_batch\_norm3d, mlr\_pipeops\_nn\_block, mlr\_pipeops\_nn\_celu, mlr\_pipeops\_nn\_conv1d, mlr\_pipeops\_nn\_conv2d, mlr\_pipeops\_nn\_conv3d, mlr\_pipeops\_nn\_conv\_transpose1d, mlr\_pipeops\_nn\_conv\_transpose2d, mlr\_pipeops\_nn\_conv\_transpose3d, mlr\_pipeops\_nn\_dropout, mlr\_pipeops\_nn\_elu, mlr\_pipeops\_nn\_flatten, mlr\_pipeops\_nn\_ft\_cls, mlr\_pipeops\_nn\_ft\_transformer\_block, mlr\_pipeops\_nn\_gelu, mlr\_pipeops\_nn\_gelu, mlr\_pipeops\_nn\_glu, mlr\_pipeops\_nn\_hardshrink, mlr\_pipeops\_nn\_hardsigmoid, mlr\_pipeops\_nn\_hardtanh, mlr\_pipeops\_nn\_head, mlr\_pipeops\_nn\_identity, mlr\_pipeops\_nn\_layer\_norm, mlr\_pipeops\_nn\_leaky\_relu, mlr\_pipeops\_nn\_linear, mlr\_pipeops\_nn\_log\_sigmoid, mlr\_pipeops\_nn\_max\_pool1d, mlr\_pipeops\_nn\_max\_pool2d, mlr\_pipeops\_nn\_max\_pool3d, mlr\_pipeops\_nn\_merge, mlr\_pipeops\_nn\_merge\_cat, mlr\_pipeops\_nn\_merge\_prod, mlr\_pipeops\_nn\_prelu, mlr\_pipeops\_nn\_relu, mlr\_pipeops\_nn\_relu, mlr\_pipeops\_nn\_relu6, mlr\_pipeops\_nn\_reshape, mlr\_pipeops\_nn\_rrelu, mlr\_pipeops\_nn\_selu, mlr\_pipeops\_nn\_sigmoid, mlr\_pipeops\_nn\_softmax, mlr\_pipeops\_nn\_softplus, mlr\_pipeops\_nn\_softshrink, mlr\_pipeops\_nn\_softsign, mlr\_pipeops\_nn\_squeeze, mlr\_pipeops\_nn\_tanh, mlr\_pipeops\_nn\_tanhshrink, mlr\_pipeops\_nn\_threshold, mlr\_pipeops\_nn\_tokenizer\_categ, mlr\_pipeops\_nn\_tokenizer\_num, mlr\_pipeops\_nn\_unsqueeze, mlr\_pipeops\_torch\_ingress, mlr\_pipeops\_torch\_ingress\_categ, mlr\_pipeops\_torch\_ingress\_ltnsr, mlr\_pipeops\_torch\_ingress\_num, mlr\_pipeops\_torch\_loss, mlr\_pipeops\_torch\_model, mlr\_pipeops\_torch\_model\_classif, mlr\_pipeops\_torch\_model\_regr

## Examples

```
# Construct the PipeOp
pipeop = po("nn_merge_sum")
pipeop
# The available parameters
pipeop$param_set
```

---

mlr\_pipeops\_nn\_prelu *PReLU Activation Function*

---

## Description

Applies element-wise the function  $PReLU(x) = \max(0, x) + weight * \min(0, x)$  where weight is a learnable parameter.

### nn\_module

Calls `torch::nn_prelu()` when trained.

## Parameters

- `num_parameters` :: `integer(1)`: Number of a to learn. Although it takes an int as input, there is only two values are legitimate: 1, or the number of channels at input. Default: 1.
- `init` :: `numeric(1)`  
T The initial value of a. Default: 0.25.

## Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

## State

The state is the value calculated by the public method `$shapes_out()`.

## Super classes

[mlr3pipelines::PipeOp](#) -> [mlr3torch::PipeOpTorch](#) -> `PipeOpTorchPReLU`

## Methods

### Public methods:

- [PipeOpTorchPReLU\\$new\(\)](#)
- [PipeOpTorchPReLU\\$clone\(\)](#)

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

`PipeOpTorchPReLU$new(id = "nn_prelu", param_vals = list())`

*Arguments:*

`id` (`character(1)`)  
Identifier of the resulting object.

`param_vals` (`list()`)  
List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

`PipeOpTorchPReLU$clone(deep = FALSE)`

*Arguments:*

`deep` Whether to make a deep clone.

**See Also**

Other PipeOps: [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm1d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm2d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm3d](#), [mlr\\_pipeops\\_nn\\_block](#), [mlr\\_pipeops\\_nn\\_celu](#), [mlr\\_pipeops\\_nn\\_conv1d](#), [mlr\\_pipeops\\_nn\\_conv2d](#), [mlr\\_pipeops\\_nn\\_conv3d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose1d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose3d](#), [mlr\\_pipeops\\_nn\\_dropout](#), [mlr\\_pipeops\\_nn\\_elu](#), [mlr\\_pipeops\\_nn\\_flatten](#), [mlr\\_pipeops\\_nn\\_ft\\_cls](#), [mlr\\_pipeops\\_nn\\_ft\\_transformer\\_block](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_glu](#), [mlr\\_pipeops\\_nn\\_hardshrink](#), [mlr\\_pipeops\\_nn\\_hardsigmoid](#), [mlr\\_pipeops\\_nn\\_hardtanh](#), [mlr\\_pipeops\\_nn\\_head](#), [mlr\\_pipeops\\_nn\\_identity](#), [mlr\\_pipeops\\_nn\\_layer\\_norm](#), [mlr\\_pipeops\\_nn\\_leaky\\_relu](#), [mlr\\_pipeops\\_nn\\_linear](#), [mlr\\_pipeops\\_nn\\_log\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_max\\_pool1d](#), [mlr\\_pipeops\\_nn\\_max\\_pool2d](#), [mlr\\_pipeops\\_nn\\_max\\_pool3d](#), [mlr\\_pipeops\\_nn\\_merge](#), [mlr\\_pipeops\\_nn\\_merge\\_cat](#), [mlr\\_pipeops\\_nn\\_merge\\_prod](#), [mlr\\_pipeops\\_nn\\_merge\\_sum](#), [mlr\\_pipeops\\_nn\\_reglu](#), [mlr\\_pipeops\\_nn\\_relu](#), [mlr\\_pipeops\\_nn\\_relu6](#), [mlr\\_pipeops\\_nn\\_reshape](#), [mlr\\_pipeops\\_nn\\_rrelu](#), [mlr\\_pipeops\\_nn\\_selu](#), [mlr\\_pipeops\\_nn\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_softmax](#), [mlr\\_pipeops\\_nn\\_softplus](#), [mlr\\_pipeops\\_nn\\_softshrink](#), [mlr\\_pipeops\\_nn\\_softsign](#), [mlr\\_pipeops\\_nn\\_squeeze](#), [mlr\\_pipeops\\_nn\\_tanh](#), [mlr\\_pipeops\\_nn\\_tanhshrink](#), [mlr\\_pipeops\\_nn\\_threshold](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_categ](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_num](#), [mlr\\_pipeops\\_nn\\_unsqueeze](#), [mlr\\_pipeops\\_torch\\_ingress](#), [mlr\\_pipeops\\_torch\\_ingress\\_categ](#), [mlr\\_pipeops\\_torch\\_ingress\\_ltnsr](#), [mlr\\_pipeops\\_torch\\_ingress\\_num](#), [mlr\\_pipeops\\_torch\\_loss](#), [mlr\\_pipeops\\_torch\\_model](#), [mlr\\_pipeops\\_torch\\_model\\_classif](#), [mlr\\_pipeops\\_torch\\_model\\_regr](#)

**Examples**

```
# Construct the PipeOp
pipeop = po("nn_reglu")
pipeop
# The available parameters
pipeop$param_set
```

---

**mlr\_pipeops\_nn\_reglu** *ReGLU Activation Function*

---

**Description**

Rectified Gated Linear Unit (ReGLU) activation function. See [nn\\_reglu](#) for details.

**Parameters**

No parameters.

**Input and Output Channels**

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

## State

The state is the value calculated by the public method `$shapes_out()`.

## Super classes

`mlr3pipelines::PipeOp -> mlr3torch::PipeOpTorch -> PipeOpTorchReGLU`

## Methods

### Public methods:

- `PipeOpTorchReGLU$new()`
- `PipeOpTorchReGLU$clone()`

**Method** `new()`: Creates a new instance of this `R6` class.

*Usage:*

`PipeOpTorchReGLU$new(id = "nn_reglu", param_vals = list())`

*Arguments:*

`id` (character(1))

Identifier of the resulting object.

`param_vals` (list())

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

`PipeOpTorchReGLU$clone(deep = FALSE)`

*Arguments:*

`deep` Whether to make a deep clone.

## See Also

Other PipeOps: `mlr_pipeops_nn_adaptive_avg_pool1d`, `mlr_pipeops_nn_adaptive_avg_pool2d`, `mlr_pipeops_nn_adaptive_avg_pool3d`, `mlr_pipeops_nn_avg_pool1d`, `mlr_pipeops_nn_avg_pool2d`, `mlr_pipeops_nn_avg_pool3d`, `mlr_pipeops_nn_batch_norm1d`, `mlr_pipeops_nn_batch_norm2d`, `mlr_pipeops_nn_batch_norm3d`, `mlr_pipeops_nn_block`, `mlr_pipeops_nn_celu`, `mlr_pipeops_nn_conv1d`, `mlr_pipeops_nn_conv2d`, `mlr_pipeops_nn_conv3d`, `mlr_pipeops_nn_conv_transpose1d`, `mlr_pipeops_nn_conv_transpose3d`, `mlr_pipeops_nn_dropout`, `mlr_pipeops_nn_elu`, `mlr_pipeops_nn_flatten`, `mlr_pipeops_nn_ft_cls`, `mlr_pipeops_nn_ft_transformer_block`, `mlr_pipeops_nn_gelu`, `mlr_pipeops_nn_gelu`, `mlr_pipeops_nn_glu`, `mlr_pipeops_nn_hardshrink`, `mlr_pipeops_nn_hardsigmoid`, `mlr_pipeops_nn_hardtanh`, `mlr_pipeops_nn_head`, `mlr_pipeops_nn_identity`, `mlr_pipeops_nn_layer_norm`, `mlr_pipeops_nn_leaky_relu`, `mlr_pipeops_nn_linear`, `mlr_pipeops_nn_log_sigmoid`, `mlr_pipeops_nn_max_pool1d`, `mlr_pipeops_nn_max_pool2d`, `mlr_pipeops_nn_max_pool3d`, `mlr_pipeops_nn_merge`, `mlr_pipeops_nn_merge_cat`, `mlr_pipeops_nn_merge_prod`, `mlr_pipeops_nn_merge_sum`, `mlr_pipeops_nn_prelu`, `mlr_pipeops_nn_relu`, `mlr_pipeops_nn_relu6`, `mlr_pipeops_nn_reshape`, `mlr_pipeops_nn_rrelu`, `mlr_pipeops_nn_selu`, `mlr_pipeops_nn_sigmoid`, `mlr_pipeops_nn_softmax`, `mlr_pipeops_nn_softplus`, `mlr_pipeops_nn_softshrink`, `mlr_pipeops_nn_softsign`, `mlr_pipeops_nn_squeeze`, `mlr_pipeops_nn_tanh`, `mlr_pipeops_nn_tanhshrink`,

```
mlr_pipeops_nn_threshold,mlr_pipeops_nn_tokenizer_categ,mlr_pipeops_nn_tokenizer_num,
mlr_pipeops_nn_unsqueeze,mlr_pipeops_torch_ingress,mlr_pipeops_torch_ingress_categ,
mlr_pipeops_torch_ingress_ltnsr,mlr_pipeops_torch_ingress_num,mlr_pipeops_torch_loss,
mlr_pipeops_torch_model,mlr_pipeops_torch_model_classif,mlr_pipeops_torch_model_regr
```

## Examples

```
# Construct the PipeOp
pipeop = po("nn_relu")
pipeop
# The available parameters
pipeop$param_set
```

---

mlr\_pipeops\_nn\_relu     *ReLU Activation Function*

---

## Description

Applies the rectified linear unit function element-wise.

### nn\_module

Calls `torch::nn_relu()` when trained.

### Parameters

- `inplace :: logical(1)`  
Whether to do the operation in-place. Default: FALSE.

### Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

### State

The state is the value calculated by the public method `$shapes_out()`.

### Super classes

`mlr3pipelines::PipeOp` -> `mlr3torch::PipeOpTorch` -> `PipeOpTorchReLU`

## Methods

### Public methods:

- `PipeOpTorchReLU$new()`
- `PipeOpTorchReLU$clone()`

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

```
PipeOpTorchReLU$new(id = "nn_relu", param_vals = list())
```

*Arguments:*

`id` (character(1))

Identifier of the resulting object.

`param_vals` (list())

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

```
PipeOpTorchReLU$clone(deep = FALSE)
```

*Arguments:*

`deep` Whether to make a deep clone.

## See Also

Other PipeOps: `mlr_pipeops_nn_adaptive_avg_pool1d`, `mlr_pipeops_nn_adaptive_avg_pool2d`, `mlr_pipeops_nn_adaptive_avg_pool3d`, `mlr_pipeops_nn_avg_pool1d`, `mlr_pipeops_nn_avg_pool2d`, `mlr_pipeops_nn_avg_pool3d`, `mlr_pipeops_nn_batch_norm1d`, `mlr_pipeops_nn_batch_norm2d`, `mlr_pipeops_nn_batch_norm3d`, `mlr_pipeops_nn_block`, `mlr_pipeops_nn_celu`, `mlr_pipeops_nn_conv1d`, `mlr_pipeops_nn_conv2d`, `mlr_pipeops_nn_conv3d`, `mlr_pipeops_nn_conv_transpose1d`, `mlr_pipeops_nn_conv_transpose3d`, `mlr_pipeops_nn_dropout`, `mlr_pipeops_nn_elu`, `mlr_pipeops_nn_flatten`, `mlr_pipeops_nn_ft_cls`, `mlr_pipeops_nn_ft_transformer_block`, `mlr_pipeops_nn_gelu`, `mlr_pipeops_nn_gelu`, `mlr_pipeops_nn_glu`, `mlr_pipeops_nn_hardsigmoid`, `mlr_pipeops_nn_hardtanh`, `mlr_pipeops_nn_head`, `mlr_pipeops_nn_identity`, `mlr_pipeops_nn_layer_norm`, `mlr_pipeops_nn_leaky_relu`, `mlr_pipeops_nn_linear`, `mlr_pipeops_nn_log_sigmoid`, `mlr_pipeops_nn_max_pool1d`, `mlr_pipeops_nn_max_pool2d`, `mlr_pipeops_nn_max_pool3d`, `mlr_pipeops_nn_merge`, `mlr_pipeops_nn_merge_cat`, `mlr_pipeops_nn_merge_prod`, `mlr_pipeops_nn_merge_sum`, `mlr_pipeops_nn_prelu`, `mlr_pipeops_nn_reglu`, `mlr_pipeops_nn_relu6`, `mlr_pipeops_nn_reshape`, `mlr_pipeops_nn_rrelu`, `mlr_pipeops_nn_selu`, `mlr_pipeops_nn_sigmoid`, `mlr_pipeops_nn_softmax`, `mlr_pipeops_nn_softplus`, `mlr_pipeops_nn_softshrink`, `mlr_pipeops_nn_softsign`, `mlr_pipeops_nn_squeeze`, `mlr_pipeops_nn_tanh`, `mlr_pipeops_nn_tanhshrink`, `mlr_pipeops_nn_threshold`, `mlr_pipeops_nn_tokenizer_categ`, `mlr_pipeops_nn_tokenizer_num`, `mlr_pipeops_nn_unsqueeze`, `mlr_pipeops_torch_ingress`, `mlr_pipeops_torch_ingress_categ`, `mlr_pipeops_torch_ingress_ltnsr`, `mlr_pipeops_torch_ingress_num`, `mlr_pipeops_torch_loss`, `mlr_pipeops_torch_model`, `mlr_pipeops_torch_model_classif`, `mlr_pipeops_torch_model_regr`

## Examples

```
# Construct the PipeOp
pipeop = po("nn_relu")
pipeop
# The available parameters
pipeop$param_set
```

---

**mlr\_pipeops\_nn\_relu6** *ReLU6 Activation Function*

---

## Description

Applies the element-wise function  $ReLU6(x) = \min(\max(0, x), 6)$ .

### nn\_module

Calls [torch::nn\\_relu6\(\)](#) when trained.

### Parameters

- `inplace` :: logical(1)  
Whether to do the operation in-place. Default: FALSE.

### Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

### State

The state is the value calculated by the public method `$shapes_out()`.

### Super classes

[mlr3pipelines::PipeOp](#) -> [mlr3torch::PipeOpTorch](#) -> [PipeOpTorchReLU6](#)

### Methods

#### Public methods:

- [PipeOpTorchReLU6\\$new\(\)](#)
- [PipeOpTorchReLU6\\$clone\(\)](#)

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

`PipeOpTorchReLU6$new(id = "nn_relu6", param_vals = list())`

*Arguments:*

```

  id (character(1))
    Identifier of the resulting object.
  param_vals (list())
    List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

```

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

```
PipeOpTorchReLU6$clone(deep = FALSE)
```

*Arguments:*

`deep` Whether to make a deep clone.

## See Also

Other PipeOps: [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm1d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm2d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm3d](#), [mlr\\_pipeops\\_nn\\_block](#), [mlr\\_pipeops\\_nn\\_celu](#), [mlr\\_pipeops\\_nn\\_conv1d](#), [mlr\\_pipeops\\_nn\\_conv2d](#), [mlr\\_pipeops\\_nn\\_conv3d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose1d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose3d](#), [mlr\\_pipeops\\_nn\\_dropout](#), [mlr\\_pipeops\\_nn\\_elu](#), [mlr\\_pipeops\\_nn\\_flatten](#), [mlr\\_pipeops\\_nn\\_ft\\_cls](#), [mlr\\_pipeops\\_nn\\_ft\\_transformer\\_block](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_glu](#), [mlr\\_pipeops\\_nn\\_hardshrink](#), [mlr\\_pipeops\\_nn\\_hardsigmoid](#), [mlr\\_pipeops\\_nn\\_hardtanh](#), [mlr\\_pipeops\\_nn\\_head](#), [mlr\\_pipeops\\_nn\\_identity](#), [mlr\\_pipeops\\_nn\\_layer\\_norm](#), [mlr\\_pipeops\\_nn\\_leaky\\_relu](#), [mlr\\_pipeops\\_nn\\_linear](#), [mlr\\_pipeops\\_nn\\_log\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_max\\_pool1d](#), [mlr\\_pipeops\\_nn\\_max\\_pool2d](#), [mlr\\_pipeops\\_nn\\_max\\_pool3d](#), [mlr\\_pipeops\\_nn\\_merge](#), [mlr\\_pipeops\\_nn\\_merge\\_cat](#), [mlr\\_pipeops\\_nn\\_merge\\_prod](#), [mlr\\_pipeops\\_nn\\_merge\\_sum](#), [mlr\\_pipeops\\_nn\\_prelu](#), [mlr\\_pipeops\\_nn\\_reglu](#), [mlr\\_pipeops\\_nn\\_relu](#), [mlr\\_pipeops\\_nn\\_reshape](#), [mlr\\_pipeops\\_nn\\_rrelu](#), [mlr\\_pipeops\\_nn\\_selu](#), [mlr\\_pipeops\\_nn\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_softmax](#), [mlr\\_pipeops\\_nn\\_softplus](#), [mlr\\_pipeops\\_nn\\_softshrink](#), [mlr\\_pipeops\\_nn\\_softsign](#), [mlr\\_pipeops\\_nn\\_squeeze](#), [mlr\\_pipeops\\_nn\\_tanh](#), [mlr\\_pipeops\\_nn\\_tanhshrink](#), [mlr\\_pipeops\\_nn\\_threshold](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_categ](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_num](#), [mlr\\_pipeops\\_nn\\_unsqueeze](#), [mlr\\_pipeops\\_torch\\_ingress](#), [mlr\\_pipeops\\_torch\\_ingress\\_categ](#), [mlr\\_pipeops\\_torch\\_ingress\\_ltnsr](#), [mlr\\_pipeops\\_torch\\_ingress\\_num](#), [mlr\\_pipeops\\_torch\\_loss](#), [mlr\\_pipeops\\_torch\\_model](#), [mlr\\_pipeops\\_torch\\_model\\_classif](#), [mlr\\_pipeops\\_torch\\_model\\_regr](#)

## Examples

```

# Construct the PipeOp
pipeop = po("nn_relu6")
pipeop
# The available parameters
pipeop$param_set

```

---

**mlr\_pipeops\_nn\_reshape***Reshape a Tensor*

---

**Description**

Reshape a tensor to the given shape.

**nn\_module**

Calls [nn\\_reshape\(\)](#) when trained. This internally calls [torch::torch\\_reshape\(\)](#) with the given shape.

**Parameters**

- `shape :: integer(1)`  
The desired output shape. Unknown dimension (one at most) can either be specified as `-1`.

**Input and Output Channels**

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

**State**

The state is the value calculated by the public method `$shapes_out()`.

**Super classes**

[mlr3pipelines::PipeOp](#) -> [mlr3torch::PipeOpTorch](#) -> [PipeOpTorchReshape](#)

**Methods****Public methods:**

- [PipeOpTorchReshape\\$new\(\)](#)
- [PipeOpTorchReshape\\$clone\(\)](#)

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

`PipeOpTorchReshape$new(id = "nn_reshape", param_vals = list())`

*Arguments:*

`id (character(1))`

Identifier of the resulting object.

`param_vals (list())`

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

```
PipeOpTorchReshape$clone(deep = FALSE)
```

*Arguments:*

`deep` Whether to make a deep clone.

## See Also

Other PipeOps: [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm1d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm2d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm3d](#), [mlr\\_pipeops\\_nn\\_block](#), [mlr\\_pipeops\\_nn\\_celu](#), [mlr\\_pipeops\\_nn\\_conv1d](#), [mlr\\_pipeops\\_nn\\_conv2d](#), [mlr\\_pipeops\\_nn\\_conv3d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose1d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose3d](#), [mlr\\_pipeops\\_nn\\_dropout](#), [mlr\\_pipeops\\_nn\\_elu](#), [mlr\\_pipeops\\_nn\\_flatten](#), [mlr\\_pipeops\\_nn\\_ft\\_cls](#), [mlr\\_pipeops\\_nn\\_ft\\_transformer\\_block](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_glu](#), [mlr\\_pipeops\\_nn\\_hardshrink](#), [mlr\\_pipeops\\_nn\\_hardsigmoid](#), [mlr\\_pipeops\\_nn\\_hardtanh](#), [mlr\\_pipeops\\_nn\\_head](#), [mlr\\_pipeops\\_nn\\_identity](#), [mlr\\_pipeops\\_nn\\_layer\\_norm](#), [mlr\\_pipeops\\_nn\\_leaky\\_relu](#), [mlr\\_pipeops\\_nn\\_linear](#), [mlr\\_pipeops\\_nn\\_log\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_max\\_pool1d](#), [mlr\\_pipeops\\_nn\\_max\\_pool2d](#), [mlr\\_pipeops\\_nn\\_max\\_pool3d](#), [mlr\\_pipeops\\_nn\\_merge](#), [mlr\\_pipeops\\_nn\\_merge\\_cat](#), [mlr\\_pipeops\\_nn\\_merge\\_prod](#), [mlr\\_pipeops\\_nn\\_merge\\_sum](#), [mlr\\_pipeops\\_nn\\_prelu](#), [mlr\\_pipeops\\_nn\\_reglu](#), [mlr\\_pipeops\\_nn\\_relu](#), [mlr\\_pipeops\\_nn\\_relu6](#), [mlr\\_pipeops\\_nn\\_rrelu](#), [mlr\\_pipeops\\_nn\\_selu](#), [mlr\\_pipeops\\_nn\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_softmax](#), [mlr\\_pipeops\\_nn\\_softplus](#), [mlr\\_pipeops\\_nn\\_softshrink](#), [mlr\\_pipeops\\_nn\\_softsign](#), [mlr\\_pipeops\\_nn\\_squeeze](#), [mlr\\_pipeops\\_nn\\_tanh](#), [mlr\\_pipeops\\_nn\\_tanhshrink](#), [mlr\\_pipeops\\_nn\\_threshold](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_categ](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_num](#), [mlr\\_pipeops\\_nn\\_unsqueeze](#), [mlr\\_pipeops\\_torch\\_ingress](#), [mlr\\_pipeops\\_torch\\_ingress\\_categ](#), [mlr\\_pipeops\\_torch\\_ingress\\_ltnsr](#), [mlr\\_pipeops\\_torch\\_ingress\\_num](#), [mlr\\_pipeops\\_torch\\_loss](#), [mlr\\_pipeops\\_torch\\_model](#), [mlr\\_pipeops\\_torch\\_model\\_classif](#), [mlr\\_pipeops\\_torch\\_model\\_regr](#)

## Examples

```
# Construct the PipeOp
pipeop = po("nn_reshape")
pipeop
# The available parameters
pipeop$param_set
```

---

**mlr\_pipeops\_nn\_rrelu** *RReLU Activation Function*

---

## Description

Randomized leaky ReLU.

### nn\_module

Calls `torch::nn_rrelu()` when trained.

## Parameters

- `lower:: numeric(1)`  
Lower bound of the uniform distribution. Default: 1/8.
- `upper:: numeric(1)`  
Upper bound of the uniform distribution. Default: 1/3.
- `inplace :: logical(1)`  
Whether to do the operation in-place. Default: FALSE.

## Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

## State

The state is the value calculated by the public method `$shapes_out()`.

## Super classes

[mlr3pipelines::PipeOp](#) -> [mlr3torch::PipeOpTorch](#) -> PipeOpTorchRReLU

## Methods

### Public methods:

- [PipeOpTorchRReLU\\$new\(\)](#)
- [PipeOpTorchRReLU\\$clone\(\)](#)

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

`PipeOpTorchRReLU$new(id = "nn_rrelu", param_vals = list())`

*Arguments:*

`id (character(1))`

Identifier of the resulting object.

`param_vals (list())`

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

`PipeOpTorchRReLU$clone(deep = FALSE)`

*Arguments:*

`deep` Whether to make a deep clone.

## See Also

Other PipeOps: [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm1d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm2d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm3d](#), [mlr\\_pipeops\\_nn\\_block](#), [mlr\\_pipeops\\_nn\\_celu](#), [mlr\\_pipeops\\_nn\\_conv1d](#), [mlr\\_pipeops\\_nn\\_conv2d](#), [mlr\\_pipeops\\_nn\\_conv3d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose1d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose3d](#), [mlr\\_pipeops\\_nn\\_dropout](#), [mlr\\_pipeops\\_nn\\_elu](#), [mlr\\_pipeops\\_nn\\_flatten](#), [mlr\\_pipeops\\_nn\\_ft\\_cls](#), [mlr\\_pipeops\\_nn\\_ft\\_transformer\\_block](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_glu](#), [mlr\\_pipeops\\_nn\\_hardshrink](#), [mlr\\_pipeops\\_nn\\_hardsigmoid](#), [mlr\\_pipeops\\_nn\\_hardtanh](#), [mlr\\_pipeops\\_nn\\_head](#), [mlr\\_pipeops\\_nn\\_identity](#), [mlr\\_pipeops\\_nn\\_layer\\_norm](#), [mlr\\_pipeops\\_nn\\_leaky\\_relu](#), [mlr\\_pipeops\\_nn\\_linear](#), [mlr\\_pipeops\\_nn\\_log\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_max\\_pool1d](#), [mlr\\_pipeops\\_nn\\_max\\_pool2d](#), [mlr\\_pipeops\\_nn\\_max\\_pool3d](#), [mlr\\_pipeops\\_nn\\_merge](#), [mlr\\_pipeops\\_nn\\_merge\\_cat](#), [mlr\\_pipeops\\_nn\\_merge\\_prod](#), [mlr\\_pipeops\\_nn\\_merge\\_sum](#), [mlr\\_pipeops\\_nn\\_prelu](#), [mlr\\_pipeops\\_nn\\_reglu](#), [mlr\\_pipeops\\_nn\\_relu](#), [mlr\\_pipeops\\_nn\\_relu6](#), [mlr\\_pipeops\\_nn\\_reshape](#), [mlr\\_pipeops\\_nn\\_selu](#), [mlr\\_pipeops\\_nn\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_softmax](#), [mlr\\_pipeops\\_nn\\_softplus](#), [mlr\\_pipeops\\_nn\\_softshrink](#), [mlr\\_pipeops\\_nn\\_softsign](#), [mlr\\_pipeops\\_nn\\_squeeze](#), [mlr\\_pipeops\\_nn\\_tanh](#), [mlr\\_pipeops\\_nn\\_tanhshrink](#), [mlr\\_pipeops\\_nn\\_threshold](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_categ](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_num](#), [mlr\\_pipeops\\_nn\\_unsqueeze](#), [mlr\\_pipeops\\_torch\\_ingress](#), [mlr\\_pipeops\\_torch\\_ingress\\_categ](#), [mlr\\_pipeops\\_torch\\_ingress\\_ltnsr](#), [mlr\\_pipeops\\_torch\\_ingress\\_num](#), [mlr\\_pipeops\\_torch\\_loss](#), [mlr\\_pipeops\\_torch\\_model](#), [mlr\\_pipeops\\_torch\\_model\\_classif](#), [mlr\\_pipeops\\_torch\\_model\\_regr](#)

## Examples

```
# Construct the PipeOp
pipeop = po("nn_rrelu")
pipeop
# The available parameters
pipeop$param_set
```

---

**mlr\_pipeops\_nn\_selu**     *SELU Activation Function*

---

## Description

Applies element-wise,

$$SELU(x) = scale * (\max(0, x) + \min(0, \alpha * (\exp(x) - 1)))$$

, with  $\alpha = 1.6732632423543772848170429916717$  and  $scale = 1.0507009873554804934193349852946$ .

### nn\_module

Calls [torch::nn\\_selu\(\)](#) when trained.

### Parameters

- `inplace :: logical(1)`  
Whether to do the operation in-place. Default: FALSE.

## Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

## State

The state is the value calculated by the public method `$shapes_out()`.

## Super classes

`mlr3pipelines::PipeOp -> mlr3torch::PipeOpTorch -> PipeOpTorchSELU`

## Methods

### Public methods:

- `PipeOpTorchSELU$new()`
- `PipeOpTorchSELU$clone()`

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

`PipeOpTorchSELU$new(id = "nn_selu", param_vals = list())`

*Arguments:*

`id` (character(1))

Identifier of the resulting object.

`param_vals` (list())

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

`PipeOpTorchSELU$clone(deep = FALSE)`

*Arguments:*

`deep` Whether to make a deep clone.

## See Also

Other PipeOps: `mlr_pipeops_nn_adaptive_avg_pool1d`, `mlr_pipeops_nn_adaptive_avg_pool2d`, `mlr_pipeops_nn_adaptive_avg_pool3d`, `mlr_pipeops_nn_avg_pool1d`, `mlr_pipeops_nn_avg_pool2d`, `mlr_pipeops_nn_avg_pool3d`, `mlr_pipeops_nn_batch_norm1d`, `mlr_pipeops_nn_batch_norm2d`, `mlr_pipeops_nn_batch_norm3d`, `mlr_pipeops_nn_block`, `mlr_pipeops_nn_celu`, `mlr_pipeops_nn_conv1d`, `mlr_pipeops_nn_conv2d`, `mlr_pipeops_nn_conv3d`, `mlr_pipeops_nn_conv_transpose1d`, `mlr_pipeops_nn_conv_transpose3d`, `mlr_pipeops_nn_dropout`, `mlr_pipeops_nn_elu`, `mlr_pipeops_nn_flatten`, `mlr_pipeops_nn_ft_cls`, `mlr_pipeops_nn_ft_transformer_block`, `mlr_pipeops_nn_gelu`, `mlr_pipeops_nn_glu`, `mlr_pipeops_nn_hardshrink`, `mlr_pipeops_nn_hardsigmoid`, `mlr_pipeops_nn_hardtanh`, `mlr_pipeops_nn_head`, `mlr_pipeops_nn_identity`, `mlr_pipeops_nn_layer_norm`, `mlr_pipeops_nn_leaky_relu`, `mlr_pipeops_nn_linear`, `mlr_pipeops_nn_log_sigmoid`, `mlr_pipeops_nn_max_pool1d`

```
mlr_pipeops_nn_max_pool2d, mlr_pipeops_nn_max_pool3d, mlr_pipeops_nn_merge, mlr_pipeops_nn_merge_cat,
mlr_pipeops_nn_merge_prod, mlr_pipeops_nn_merge_sum, mlr_pipeops_nn_prelu, mlr_pipeops_nn_reglu,
mlr_pipeops_nn_relu, mlr_pipeops_nn_relu6, mlr_pipeops_nn_reshape, mlr_pipeops_nn_rrelu,
mlr_pipeops_nn_sigmoid, mlr_pipeops_nn_softmax, mlr_pipeops_nn_softplus, mlr_pipeops_nn_softshrink,
mlr_pipeops_nn_softsign, mlr_pipeops_nn_squeeze, mlr_pipeops_nn_tanh, mlr_pipeops_nn_tanhshrink,
mlr_pipeops_nn_threshold, mlr_pipeops_nn_tokenizer_categ, mlr_pipeops_nn_tokenizer_num,
mlr_pipeops_nn_unsqueeze, mlr_pipeops_torch_ingress, mlr_pipeops_torch_ingress_categ,
mlr_pipeops_torch_ingress_ltnsr, mlr_pipeops_torch_ingress_num, mlr_pipeops_torch_loss,
mlr_pipeops_torch_model, mlr_pipeops_torch_model_classif, mlr_pipeops_torch_model_regr
```

## Examples

```
# Construct the PipeOp
pipeop = po("nn_selu")
pipeop
# The available parameters
pipeop$param_set
```

---

**mlr\_pipeops\_nn\_sigmoid**

*Sigmoid Activation Function*

---

## Description

Applies element-wise  $Sigmoid(x_i) = \frac{1}{1+exp(-x_i)}$

### nn\_module

Calls `torch::nn_sigmoid()` when trained.

### Parameters

No parameters.

### Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

### State

The state is the value calculated by the public method `$shapes_out()`.

### Super classes

`mlr3pipelines::PipeOp -> mlr3torch::PipeOpTorch -> PipeOpTorchSigmoid`

## Methods

### Public methods:

- [PipeOpTorchSigmoid\\$new\(\)](#)
- [PipeOpTorchSigmoid\\$clone\(\)](#)

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

```
PipeOpTorchSigmoid$new(id = "nn_sigmoid", param_vals = list())
```

*Arguments:*

`id` (character(1))

Identifier of the resulting object.

`param_vals` (list())

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

```
PipeOpTorchSigmoid$clone(deep = FALSE)
```

*Arguments:*

`deep` Whether to make a deep clone.

## See Also

Other PipeOps: [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm1d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm2d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm3d](#), [mlr\\_pipeops\\_nn\\_block](#), [mlr\\_pipeops\\_nn\\_celu](#), [mlr\\_pipeops\\_nn\\_conv1d](#), [mlr\\_pipeops\\_nn\\_conv2d](#), [mlr\\_pipeops\\_nn\\_conv3d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose1d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose3d](#), [mlr\\_pipeops\\_nn\\_dropout](#), [mlr\\_pipeops\\_nn\\_elu](#), [mlr\\_pipeops\\_nn\\_flatten](#), [mlr\\_pipeops\\_nn\\_ft\\_cls](#), [mlr\\_pipeops\\_nn\\_ft\\_transformer\\_block](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_glu](#), [mlr\\_pipeops\\_nn\\_hardshrink](#), [mlr\\_pipeops\\_nn\\_hardsigmoid](#), [mlr\\_pipeops\\_nn\\_hardtanh](#), [mlr\\_pipeops\\_nn\\_head](#), [mlr\\_pipeops\\_nn\\_identity](#), [mlr\\_pipeops\\_nn\\_layer\\_norm](#), [mlr\\_pipeops\\_nn\\_leaky\\_relu](#), [mlr\\_pipeops\\_nn\\_linear](#), [mlr\\_pipeops\\_nn\\_log\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_max\\_pool1d](#), [mlr\\_pipeops\\_nn\\_max\\_pool2d](#), [mlr\\_pipeops\\_nn\\_max\\_pool3d](#), [mlr\\_pipeops\\_nn\\_merge](#), [mlr\\_pipeops\\_nn\\_merge\\_cat](#), [mlr\\_pipeops\\_nn\\_merge\\_prod](#), [mlr\\_pipeops\\_nn\\_merge\\_sum](#), [mlr\\_pipeops\\_nn\\_prelu](#), [mlr\\_pipeops\\_nn\\_reglu](#), [mlr\\_pipeops\\_nn\\_relu](#), [mlr\\_pipeops\\_nn\\_relu6](#), [mlr\\_pipeops\\_nn\\_reshape](#), [mlr\\_pipeops\\_nn\\_rrelu](#), [mlr\\_pipeops\\_nn\\_selu](#), [mlr\\_pipeops\\_nn\\_softmax](#), [mlr\\_pipeops\\_nn\\_softplus](#), [mlr\\_pipeops\\_nn\\_softshrink](#), [mlr\\_pipeops\\_nn\\_softsign](#), [mlr\\_pipeops\\_nn\\_squeeze](#), [mlr\\_pipeops\\_nn\\_tanh](#), [mlr\\_pipeops\\_nn\\_tanhshrink](#), [mlr\\_pipeops\\_nn\\_threshold](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_categ](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_num](#), [mlr\\_pipeops\\_nn\\_unsqueeze](#), [mlr\\_pipeops\\_torch\\_ingress](#), [mlr\\_pipeops\\_torch\\_ingress\\_categ](#), [mlr\\_pipeops\\_torch\\_ingress\\_ltnsr](#), [mlr\\_pipeops\\_torch\\_ingress\\_num](#), [mlr\\_pipeops\\_torch\\_loss](#), [mlr\\_pipeops\\_torch\\_model](#), [mlr\\_pipeops\\_torch\\_model\\_classif](#), [mlr\\_pipeops\\_torch\\_model\\_regr](#)

## Examples

```
# Construct the PipeOp
pipeop = po("nn_sigmoid")
pipeop
# The available parameters
pipeop$param_set
```

**mlr\_pipeops\_nn\_softmax**  
*Softmax*

## Description

Applies a softmax function.

### nn\_module

Calls `torch::nn::softmax()` when trained.

### Parameters

- `dim :: integer(1)`  
A dimension along which Softmax will be computed (so every slice along dim will sum to 1).

### Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

### State

The state is the value calculated by the public method `$shapes_out()`.

### Super classes

`mlr3pipelines::PipeOp` -> `mlr3torch::PipeOpTorch` -> `PipeOpTorchSoftmax`

### Methods

#### Public methods:

- `PipeOpTorchSoftmax$new()`
- `PipeOpTorchSoftmax$clone()`

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

`PipeOpTorchSoftmax$new(id = "nn_softmax", param_vals = list())`

*Arguments:*

`id` (character(1))  
 Identifier of the resulting object.  
`param_vals` (list())  
 List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

`PipeOpTorchSoftmax$clone(deep = FALSE)`

*Arguments:*

`deep` Whether to make a deep clone.

## See Also

Other PipeOps: [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm1d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm2d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm3d](#), [mlr\\_pipeops\\_nn\\_block](#), [mlr\\_pipeops\\_nn\\_celu](#), [mlr\\_pipeops\\_nn\\_conv1d](#), [mlr\\_pipeops\\_nn\\_conv2d](#), [mlr\\_pipeops\\_nn\\_conv3d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose1d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose3d](#), [mlr\\_pipeops\\_nn\\_dropout](#), [mlr\\_pipeops\\_nn\\_elu](#), [mlr\\_pipeops\\_nn\\_flatten](#), [mlr\\_pipeops\\_nn\\_ft\\_cls](#), [mlr\\_pipeops\\_nn\\_ft\\_transformer\\_block](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_glu](#), [mlr\\_pipeops\\_nn\\_hardshrink](#), [mlr\\_pipeops\\_nn\\_hardsigmoid](#), [mlr\\_pipeops\\_nn\\_hardtanh](#), [mlr\\_pipeops\\_nn\\_head](#), [mlr\\_pipeops\\_nn\\_identity](#), [mlr\\_pipeops\\_nn\\_layer\\_norm](#), [mlr\\_pipeops\\_nn\\_leaky\\_relu](#), [mlr\\_pipeops\\_nn\\_linear](#), [mlr\\_pipeops\\_nn\\_log\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_max\\_pool1d](#), [mlr\\_pipeops\\_nn\\_max\\_pool2d](#), [mlr\\_pipeops\\_nn\\_max\\_pool3d](#), [mlr\\_pipeops\\_nn\\_merge](#), [mlr\\_pipeops\\_nn\\_merge\\_cat](#), [mlr\\_pipeops\\_nn\\_merge\\_prod](#), [mlr\\_pipeops\\_nn\\_merge\\_sum](#), [mlr\\_pipeops\\_nn\\_prelu](#), [mlr\\_pipeops\\_nn\\_reglu](#), [mlr\\_pipeops\\_nn\\_relu](#), [mlr\\_pipeops\\_nn\\_relu6](#), [mlr\\_pipeops\\_nn\\_reshape](#), [mlr\\_pipeops\\_nn\\_rrelu](#), [mlr\\_pipeops\\_nn\\_selu](#), [mlr\\_pipeops\\_nn\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_softplus](#), [mlr\\_pipeops\\_nn\\_softshrink](#), [mlr\\_pipeops\\_nn\\_softsign](#), [mlr\\_pipeops\\_nn\\_squeeze](#), [mlr\\_pipeops\\_nn\\_tanh](#), [mlr\\_pipeops\\_nn\\_tanhshrink](#), [mlr\\_pipeops\\_nn\\_threshold](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_categ](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_num](#), [mlr\\_pipeops\\_nn\\_unsqueeze](#), [mlr\\_pipeops\\_torch\\_ingress](#), [mlr\\_pipeops\\_torch\\_ingress\\_categ](#), [mlr\\_pipeops\\_torch\\_ingress\\_ltnsr](#), [mlr\\_pipeops\\_torch\\_ingress\\_num](#), [mlr\\_pipeops\\_torch\\_loss](#), [mlr\\_pipeops\\_torch\\_model](#), [mlr\\_pipeops\\_torch\\_model\\_classif](#), [mlr\\_pipeops\\_torch\\_model\\_regr](#)

## Examples

```
# Construct the PipeOp
pipeop = po("nn_softmax")
pipeop
# The available parameters
pipeop$param_set
```

---

**mlr\_pipeops\_nn\_softplus***SoftPlus Activation Function*

---

**Description**

Applies element-wise, the function  $Softplus(x) = 1/\beta * \log(1 + \exp(\beta * x))$ .

**nn\_module**

Calls [torch::nn\\_softplus\(\)](#) when trained.

**Parameters**

- `beta :: numeric(1)`  
The beta value for the Softplus formulation. Default: 1
- `threshold :: numeric(1)`  
Values above this revert to a linear function. Default: 20

**Input and Output Channels**

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

**State**

The state is the value calculated by the public method `$shapes_out()`.

**Super classes**

[mlr3pipelines::PipeOp](#) -> [mlr3torch::PipeOpTorch](#) -> [PipeOpTorchSoftPlus](#)

**Methods****Public methods:**

- [PipeOpTorchSoftPlus\\$new\(\)](#)
- [PipeOpTorchSoftPlus\\$clone\(\)](#)

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

`PipeOpTorchSoftPlus$new(id = "nn_softplus", param_vals = list())`

*Arguments:*

- `id (character(1))`  
Identifier of the resulting object.

```
param_vals (list())
```

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

```
PipeOpTorchSoftPlus$clone(deep = FALSE)
```

*Arguments:*

`deep` Whether to make a deep clone.

## See Also

Other PipeOps: [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm1d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm2d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm3d](#), [mlr\\_pipeops\\_nn\\_block](#), [mlr\\_pipeops\\_nn\\_celu](#), [mlr\\_pipeops\\_nn\\_conv1d](#), [mlr\\_pipeops\\_nn\\_conv2d](#), [mlr\\_pipeops\\_nn\\_conv3d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose1d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose3d](#), [mlr\\_pipeops\\_nn\\_dropout](#), [mlr\\_pipeops\\_nn\\_elu](#), [mlr\\_pipeops\\_nn\\_flatten](#), [mlr\\_pipeops\\_nn\\_ft\\_cls](#), [mlr\\_pipeops\\_nn\\_ft\\_transformer\\_block](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_glu](#), [mlr\\_pipeops\\_nn\\_hardshrink](#), [mlr\\_pipeops\\_nn\\_hardsigmoid](#), [mlr\\_pipeops\\_nn\\_hardtanh](#), [mlr\\_pipeops\\_nn\\_head](#), [mlr\\_pipeops\\_nn\\_identity](#), [mlr\\_pipeops\\_nn\\_layer\\_norm](#), [mlr\\_pipeops\\_nn\\_leaky\\_relu](#), [mlr\\_pipeops\\_nn\\_linear](#), [mlr\\_pipeops\\_nn\\_log\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_max\\_pool1d](#), [mlr\\_pipeops\\_nn\\_max\\_pool2d](#), [mlr\\_pipeops\\_nn\\_max\\_pool3d](#), [mlr\\_pipeops\\_nn\\_merge](#), [mlr\\_pipeops\\_nn\\_merge\\_cat](#), [mlr\\_pipeops\\_nn\\_merge\\_prod](#), [mlr\\_pipeops\\_nn\\_merge\\_sum](#), [mlr\\_pipeops\\_nn\\_prelu](#), [mlr\\_pipeops\\_nn\\_reglu](#), [mlr\\_pipeops\\_nn\\_relu](#), [mlr\\_pipeops\\_nn\\_relu6](#), [mlr\\_pipeops\\_nn\\_reshape](#), [mlr\\_pipeops\\_nn\\_rrelu](#), [mlr\\_pipeops\\_nn\\_selu](#), [mlr\\_pipeops\\_nn\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_softmax](#), [mlr\\_pipeops\\_nn\\_softshrink](#), [mlr\\_pipeops\\_nn\\_softsign](#), [mlr\\_pipeops\\_nn\\_squeeze](#), [mlr\\_pipeops\\_nn\\_tanh](#), [mlr\\_pipeops\\_nn\\_tanhshrink](#), [mlr\\_pipeops\\_nn\\_threshold](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_categ](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_num](#), [mlr\\_pipeops\\_nn\\_unsqueeze](#), [mlr\\_pipeops\\_torch\\_ingress](#), [mlr\\_pipeops\\_torch\\_ingress\\_categ](#), [mlr\\_pipeops\\_torch\\_ingress\\_ltnsr](#), [mlr\\_pipeops\\_torch\\_ingress\\_num](#), [mlr\\_pipeops\\_torch\\_loss](#), [mlr\\_pipeops\\_torch\\_model](#), [mlr\\_pipeops\\_torch\\_model\\_classif](#), [mlr\\_pipeops\\_torch\\_model\\_regr](#)

## Examples

```
# Construct the PipeOp
pipeop = po("nn_softplus")
pipeop
# The available parameters
pipeop$param_set
```

---

### mlr\_pipeops\_nn\_softshrink

*Soft Shrink Activation Function*

---

## Description

Applies the soft shrinkage function elementwise

**nn\_module**

Calls `torch::nn_softshrink()` when trained.

**Parameters**

- `lambd :: numeric(1)`

The lambda (must be no less than zero) value for the Softshrink formulation. Default: 0.5

**Input and Output Channels**

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

**State**

The state is the value calculated by the public method `$shapes_out()`.

**Super classes**

`mlr3pipelines::PipeOp -> mlr3torch::PipeOpTorch -> PipeOpTorchSoftShrink`

**Methods****Public methods:**

- `PipeOpTorchSoftShrink$new()`
- `PipeOpTorchSoftShrink$clone()`

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

`PipeOpTorchSoftShrink$new(id = "nn_softshrink", param_vals = list())`

*Arguments:*

`id (character(1))`

Identifier of the resulting object.

`param_vals (list())`

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

`PipeOpTorchSoftShrink$clone(deep = FALSE)`

*Arguments:*

`deep` Whether to make a deep clone.

**See Also**

Other PipeOps: [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm1d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm2d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm3d](#), [mlr\\_pipeops\\_nn\\_block](#), [mlr\\_pipeops\\_nn\\_celu](#), [mlr\\_pipeops\\_nn\\_conv1d](#), [mlr\\_pipeops\\_nn\\_conv2d](#), [mlr\\_pipeops\\_nn\\_conv3d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose1d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose3d](#), [mlr\\_pipeops\\_nn\\_dropout](#), [mlr\\_pipeops\\_nn\\_elu](#), [mlr\\_pipeops\\_nn\\_flatten](#), [mlr\\_pipeops\\_nn\\_ft\\_cls](#), [mlr\\_pipeops\\_nn\\_ft\\_transformer\\_block](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_glu](#), [mlr\\_pipeops\\_nn\\_hardshrink](#), [mlr\\_pipeops\\_nn\\_hardsigmoid](#), [mlr\\_pipeops\\_nn\\_hardtanh](#), [mlr\\_pipeops\\_nn\\_head](#), [mlr\\_pipeops\\_nn\\_identity](#), [mlr\\_pipeops\\_nn\\_layer\\_norm](#), [mlr\\_pipeops\\_nn\\_leaky\\_relu](#), [mlr\\_pipeops\\_nn\\_linear](#), [mlr\\_pipeops\\_nn\\_log\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_max\\_pool1d](#), [mlr\\_pipeops\\_nn\\_max\\_pool2d](#), [mlr\\_pipeops\\_nn\\_max\\_pool3d](#), [mlr\\_pipeops\\_nn\\_merge](#), [mlr\\_pipeops\\_nn\\_merge\\_cat](#), [mlr\\_pipeops\\_nn\\_merge\\_prod](#), [mlr\\_pipeops\\_nn\\_merge\\_sum](#), [mlr\\_pipeops\\_nn\\_prelu](#), [mlr\\_pipeops\\_nn\\_reglu](#), [mlr\\_pipeops\\_nn\\_relu](#), [mlr\\_pipeops\\_nn\\_relu6](#), [mlr\\_pipeops\\_nn\\_reshape](#), [mlr\\_pipeops\\_nn\\_rrelu](#), [mlr\\_pipeops\\_nn\\_selu](#), [mlr\\_pipeops\\_nn\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_softmax](#), [mlr\\_pipeops\\_nn\\_softplus](#), [mlr\\_pipeops\\_nn\\_softsign](#), [mlr\\_pipeops\\_nn\\_squeeze](#), [mlr\\_pipeops\\_nn\\_tanh](#), [mlr\\_pipeops\\_nn\\_tanhshrink](#), [mlr\\_pipeops\\_nn\\_threshold](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_categ](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_num](#), [mlr\\_pipeops\\_nn\\_unsqueeze](#), [mlr\\_pipeops\\_torch\\_ingress](#), [mlr\\_pipeops\\_torch\\_ingress\\_categ](#), [mlr\\_pipeops\\_torch\\_ingress\\_ltnsr](#), [mlr\\_pipeops\\_torch\\_ingress\\_num](#), [mlr\\_pipeops\\_torch\\_loss](#), [mlr\\_pipeops\\_torch\\_model](#), [mlr\\_pipeops\\_torch\\_model\\_classif](#), [mlr\\_pipeops\\_torch\\_model\\_regr](#)

**Examples**

```
# Construct the PipeOp
pipeop = po("nn_softshrink")
pipeop
# The available parameters
pipeop$param_set
```

---

**mlr\_pipeops\_nn\_softsign**  
*SoftSign Activation Function*

---

**Description**

Applies element-wise, the function  $SoftSign(x) = x/(1 + |x|)$

**nn\_module**

Calls `torch::nn::softsign()` when trained.

**Parameters**

No parameters.

## Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

## State

The state is the value calculated by the public method `$shapes_out()`.

## Super classes

`mlr3pipelines::PipeOp -> mlr3torch::PipeOpTorch -> PipeOpTorchSoftSign`

## Methods

### Public methods:

- `PipeOpTorchSoftSign$new()`
- `PipeOpTorchSoftSign$clone()`

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

`PipeOpTorchSoftSign$new(id = "nn_softsign", param_vals = list())`

*Arguments:*

`id` (character(1))

Identifier of the resulting object.

`param_vals` (list())

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

`PipeOpTorchSoftSign$clone(deep = FALSE)`

*Arguments:*

`deep` Whether to make a deep clone.

## See Also

Other PipeOps: `mlr_pipeops_nn_adaptive_avg_pool1d`, `mlr_pipeops_nn_adaptive_avg_pool2d`, `mlr_pipeops_nn_adaptive_avg_pool3d`, `mlr_pipeops_nn_avg_pool1d`, `mlr_pipeops_nn_avg_pool2d`, `mlr_pipeops_nn_avg_pool3d`, `mlr_pipeops_nn_batch_norm1d`, `mlr_pipeops_nn_batch_norm2d`, `mlr_pipeops_nn_batch_norm3d`, `mlr_pipeops_nn_block`, `mlr_pipeops_nn_celu`, `mlr_pipeops_nn_conv1d`, `mlr_pipeops_nn_conv2d`, `mlr_pipeops_nn_conv3d`, `mlr_pipeops_nn_conv_transpose1d`, `mlr_pipeops_nn_conv_transpose3d`, `mlr_pipeops_nn_dropout`, `mlr_pipeops_nn_elu`, `mlr_pipeops_nn_flatten`, `mlr_pipeops_nn_ft_cls`, `mlr_pipeops_nn_ft_transformer_block`, `mlr_pipeops_nn_gelu`, `mlr_pipeops_nn_gelu`, `mlr_pipeops_nn_glu`, `mlr_pipeops_nn_hardshrink`, `mlr_pipeops_nn_hardsigmoid`, `mlr_pipeops_nn_hardtanh`, `mlr_pipeops_nn_head`, `mlr_pipeops_nn_identity`, `mlr_pipeops_nn_layer_norm`, `mlr_pipeops_nn_leaky_relu`, `mlr_pipeops_nn_linear`, `mlr_pipeops_nn_log_sigmoid`, `mlr_pipeops_nn_max_pool1d`

```
mlr_pipeops_nn_max_pool2d, mlr_pipeops_nn_max_pool3d, mlr_pipeops_nn_merge, mlr_pipeops_nn_merge_cat,
mlr_pipeops_nn_merge_prod, mlr_pipeops_nn_merge_sum, mlr_pipeops_nn_prelu, mlr_pipeops_nn_reglu,
mlr_pipeops_nn_relu, mlr_pipeops_nn_relu6, mlr_pipeops_nn_reshape, mlr_pipeops_nn_rrelu,
mlr_pipeops_nn_selu, mlr_pipeops_nn_sigmoid, mlr_pipeops_nn_softmax, mlr_pipeops_nn_softplus,
mlr_pipeops_nn_softshrink, mlr_pipeops_nn_squeeze, mlr_pipeops_nn_tanh, mlr_pipeops_nn_tanhshrink,
mlr_pipeops_nn_threshold, mlr_pipeops_nn_tokenizer_categ, mlr_pipeops_nn_tokenizer_num,
mlr_pipeops_nn_unsqueeze, mlr_pipeops_torch_ingress, mlr_pipeops_torch_ingress_categ,
mlr_pipeops_torch_ingress_ltnsr, mlr_pipeops_torch_ingress_num, mlr_pipeops_torch_loss,
mlr_pipeops_torch_model, mlr_pipeops_torch_model_classif, mlr_pipeops_torch_model_regr
```

## Examples

```
# Construct the PipeOp
pipeop = po("nn_softsign")
pipeop
# The available parameters
pipeop$param_set
```

**mlr\_pipeops\_nn\_squeeze**  
*Squeeze a Tensor*

## Description

Squeezes a tensor by calling `torch::torch_squeeze()` with the given dimension `dim`.

### nn\_module

Calls `nn_squeeze()` when trained.

### Parameters

- `dim :: integer(1)`  
The dimension to squeeze. If `NULL`, all dimensions of size 1 will be squeezed. Negative values are interpreted downwards from the last dimension.

### Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

### State

The state is the value calculated by the public method `$shapes_out()`.

### Super classes

`mlr3pipelines::PipeOp -> mlr3torch::PipeOpTorch -> PipeOpTorchSqueeze`

## Methods

### Public methods:

- `PipeOpTorchSqueeze$new()`
- `PipeOpTorchSqueeze$clone()`

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

```
PipeOpTorchSqueeze$new(id = "nn_squeeze", param_vals = list())
```

*Arguments:*

`id` (character(1))

Identifier of the resulting object.

`param_vals` (list())

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

```
PipeOpTorchSqueeze$clone(deep = FALSE)
```

*Arguments:*

`deep` Whether to make a deep clone.

## See Also

Other PipeOps: [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm1d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm2d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm3d](#), [mlr\\_pipeops\\_nn\\_block](#), [mlr\\_pipeops\\_nn\\_celu](#), [mlr\\_pipeops\\_nn\\_conv1d](#), [mlr\\_pipeops\\_nn\\_conv2d](#), [mlr\\_pipeops\\_nn\\_conv3d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose1d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose3d](#), [mlr\\_pipeops\\_nn\\_dropout](#), [mlr\\_pipeops\\_nn\\_elu](#), [mlr\\_pipeops\\_nn\\_flatten](#), [mlr\\_pipeops\\_nn\\_ft\\_cls](#), [mlr\\_pipeops\\_nn\\_ft\\_transformer\\_block](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_hardshrink](#), [mlr\\_pipeops\\_nn\\_hardsigmoid](#), [mlr\\_pipeops\\_nn\\_hardtanh](#), [mlr\\_pipeops\\_nn\\_head](#), [mlr\\_pipeops\\_nn\\_identity](#), [mlr\\_pipeops\\_nn\\_layer\\_norm](#), [mlr\\_pipeops\\_nn\\_leaky\\_relu](#), [mlr\\_pipeops\\_nn\\_linear](#), [mlr\\_pipeops\\_nn\\_log\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_max\\_pool1d](#), [mlr\\_pipeops\\_nn\\_max\\_pool2d](#), [mlr\\_pipeops\\_nn\\_max\\_pool3d](#), [mlr\\_pipeops\\_nn\\_merge](#), [mlr\\_pipeops\\_nn\\_merge\\_cat](#), [mlr\\_pipeops\\_nn\\_merge\\_prod](#), [mlr\\_pipeops\\_nn\\_merge\\_sum](#), [mlr\\_pipeops\\_nn\\_prelu](#), [mlr\\_pipeops\\_nn\\_reglu](#), [mlr\\_pipeops\\_nn\\_relu](#), [mlr\\_pipeops\\_nn\\_relu6](#), [mlr\\_pipeops\\_nn\\_reshape](#), [mlr\\_pipeops\\_nn\\_rrelu](#), [mlr\\_pipeops\\_nn\\_selu](#), [mlr\\_pipeops\\_nn\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_softmax](#), [mlr\\_pipeops\\_nn\\_softplus](#), [mlr\\_pipeops\\_nn\\_softshrink](#), [mlr\\_pipeops\\_nn\\_softsign](#), [mlr\\_pipeops\\_nn\\_tanh](#), [mlr\\_pipeops\\_nn\\_tanhshrink](#), [mlr\\_pipeops\\_nn\\_threshold](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_categ](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_num](#), [mlr\\_pipeops\\_nn\\_unsqueeze](#), [mlr\\_pipeops\\_torch\\_ingress](#), [mlr\\_pipeops\\_torch\\_ingress\\_categ](#), [mlr\\_pipeops\\_torch\\_ingress\\_ltnsr](#), [mlr\\_pipeops\\_torch\\_ingress\\_num](#), [mlr\\_pipeops\\_torch\\_loss](#), [mlr\\_pipeops\\_torch\\_model](#), [mlr\\_pipeops\\_torch\\_model\\_classif](#), [mlr\\_pipeops\\_torch\\_model\\_regr](#)

## Examples

```
# Construct the PipeOp
pipeop = po("nn_squeeze")
pipeop
# The available parameters
pipeop$param_set
```

---

mlr\_pipeops\_nn\_tanh     *Tanh Activation Function*

---

## Description

Applies the element-wise function:

### nn\_module

Calls [torch::nn\\_tanh\(\)](#) when trained.

### Parameters

No parameters.

### Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

### State

The state is the value calculated by the public method `$shapes_out()`.

### Super classes

[mlr3pipelines::PipeOp](#) -> [mlr3torch::PipeOpTorch](#) -> [PipeOpTorchTanh](#)

### Methods

#### Public methods:

- [PipeOpTorchTanh\\$new\(\)](#)
- [PipeOpTorchTanh\\$clone\(\)](#)

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

`PipeOpTorchTanh$new(id = "nn_tanh", param_vals = list())`

*Arguments:*

```

  id (character(1))
    Identifier of the resulting object.
  param_vals (list())
    List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

```

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

```
PipeOpTorchTanh$clone(deep = FALSE)
```

*Arguments:*

```
deep Whether to make a deep clone.
```

## See Also

Other PipeOps: [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm1d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm2d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm3d](#), [mlr\\_pipeops\\_nn\\_block](#), [mlr\\_pipeops\\_nn\\_celu](#), [mlr\\_pipeops\\_nn\\_conv1d](#), [mlr\\_pipeops\\_nn\\_conv2d](#), [mlr\\_pipeops\\_nn\\_conv3d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose1d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose3d](#), [mlr\\_pipeops\\_nn\\_dropout](#), [mlr\\_pipeops\\_nn\\_elu](#), [mlr\\_pipeops\\_nn\\_flatten](#), [mlr\\_pipeops\\_nn\\_ft\\_cls](#), [mlr\\_pipeops\\_nn\\_ft\\_transformer\\_block](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_glu](#), [mlr\\_pipeops\\_nn\\_hardshrink](#), [mlr\\_pipeops\\_nn\\_hardsigmoid](#), [mlr\\_pipeops\\_nn\\_hardtanh](#), [mlr\\_pipeops\\_nn\\_head](#), [mlr\\_pipeops\\_nn\\_identity](#), [mlr\\_pipeops\\_nn\\_layer\\_norm](#), [mlr\\_pipeops\\_nn\\_leaky\\_relu](#), [mlr\\_pipeops\\_nn\\_linear](#), [mlr\\_pipeops\\_nn\\_log\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_max\\_pool1d](#), [mlr\\_pipeops\\_nn\\_max\\_pool2d](#), [mlr\\_pipeops\\_nn\\_max\\_pool3d](#), [mlr\\_pipeops\\_nn\\_merge](#), [mlr\\_pipeops\\_nn\\_merge\\_cat](#), [mlr\\_pipeops\\_nn\\_merge\\_prod](#), [mlr\\_pipeops\\_nn\\_merge\\_sum](#), [mlr\\_pipeops\\_nn\\_prelu](#), [mlr\\_pipeops\\_nn\\_reglu](#), [mlr\\_pipeops\\_nn\\_relu](#), [mlr\\_pipeops\\_nn\\_relu6](#), [mlr\\_pipeops\\_nn\\_reshape](#), [mlr\\_pipeops\\_nn\\_rrelu](#), [mlr\\_pipeops\\_nn\\_selu](#), [mlr\\_pipeops\\_nn\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_softmax](#), [mlr\\_pipeops\\_nn\\_softplus](#), [mlr\\_pipeops\\_nn\\_softshrink](#), [mlr\\_pipeops\\_nn\\_softsign](#), [mlr\\_pipeops\\_nn\\_squeeze](#), [mlr\\_pipeops\\_nn\\_tanhshrink](#), [mlr\\_pipeops\\_nn\\_threshold](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_categ](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_num](#), [mlr\\_pipeops\\_nn\\_unsqueeze](#), [mlr\\_pipeops\\_torch\\_ingress](#), [mlr\\_pipeops\\_torch\\_ingress\\_categ](#), [mlr\\_pipeops\\_torch\\_ingress\\_ltnsr](#), [mlr\\_pipeops\\_torch\\_ingress\\_num](#), [mlr\\_pipeops\\_torch\\_loss](#), [mlr\\_pipeops\\_torch\\_model](#), [mlr\\_pipeops\\_torch\\_model\\_classif](#), [mlr\\_pipeops\\_torch\\_model\\_regr](#)

## Examples

```

# Construct the PipeOp
pipeop = po("nn_tanh")
pipeop
# The available parameters
pipeop$param_set

```

---

**mlr\_pipeops\_nn\_tanhshrink***Tanh Shrink Activation Function*

---

**Description**

Applies element-wise,  $\text{Tanhshrink}(x) = x - \text{Tanh}(x)$

**nn\_module**

Calls `torch::nn_tanhshrink()` when trained.

**Parameters**

No parameters.

**Input and Output Channels**

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

**State**

The state is the value calculated by the public method `$shapes_out()`.

**Super classes**

`mlr3pipelines::PipeOp -> mlr3torch::PipeOpTorch -> PipeOpTorchTanhShrink`

**Methods****Public methods:**

- `PipeOpTorchTanhShrink$new()`
- `PipeOpTorchTanhShrink$clone()`

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

`PipeOpTorchTanhShrink$new(id = "nn_tanhshrink", param_vals = list())`

*Arguments:*

`id` (character(1))

Identifier of the resulting object.

`param_vals` (list())

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

```
PipeOpTorchTanhShrink$clone(deep = FALSE)
```

*Arguments:*

deep Whether to make a deep clone.

## See Also

Other PipeOps: [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm1d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm2d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm3d](#), [mlr\\_pipeops\\_nn\\_block](#), [mlr\\_pipeops\\_nn\\_celu](#), [mlr\\_pipeops\\_nn\\_conv1d](#), [mlr\\_pipeops\\_nn\\_conv2d](#), [mlr\\_pipeops\\_nn\\_conv3d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose1d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose3d](#), [mlr\\_pipeops\\_nn\\_dropout](#), [mlr\\_pipeops\\_nn\\_elu](#), [mlr\\_pipeops\\_nn\\_flatten](#), [mlr\\_pipeops\\_nn\\_ft\\_cls](#), [mlr\\_pipeops\\_nn\\_ft\\_transformer\\_block](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_glu](#), [mlr\\_pipeops\\_nn\\_hardshrink](#), [mlr\\_pipeops\\_nn\\_hardsigmoid](#), [mlr\\_pipeops\\_nn\\_hardtanh](#), [mlr\\_pipeops\\_nn\\_head](#), [mlr\\_pipeops\\_nn\\_identity](#), [mlr\\_pipeops\\_nn\\_layer\\_norm](#), [mlr\\_pipeops\\_nn\\_leaky\\_relu](#), [mlr\\_pipeops\\_nn\\_linear](#), [mlr\\_pipeops\\_nn\\_log\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_max\\_pool1d](#), [mlr\\_pipeops\\_nn\\_max\\_pool2d](#), [mlr\\_pipeops\\_nn\\_max\\_pool3d](#), [mlr\\_pipeops\\_nn\\_merge](#), [mlr\\_pipeops\\_nn\\_merge\\_cat](#), [mlr\\_pipeops\\_nn\\_merge\\_prod](#), [mlr\\_pipeops\\_nn\\_merge\\_sum](#), [mlr\\_pipeops\\_nn\\_prelu](#), [mlr\\_pipeops\\_nn\\_reglu](#), [mlr\\_pipeops\\_nn\\_relu](#), [mlr\\_pipeops\\_nn\\_relu6](#), [mlr\\_pipeops\\_nn\\_reshape](#), [mlr\\_pipeops\\_nn\\_rrelu](#), [mlr\\_pipeops\\_nn\\_selu](#), [mlr\\_pipeops\\_nn\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_softmax](#), [mlr\\_pipeops\\_nn\\_softplus](#), [mlr\\_pipeops\\_nn\\_softshrink](#), [mlr\\_pipeops\\_nn\\_softsign](#), [mlr\\_pipeops\\_nn\\_squeeze](#), [mlr\\_pipeops\\_nn\\_tanh](#), [mlr\\_pipeops\\_nn\\_threshold](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_categ](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_num](#), [mlr\\_pipeops\\_nn\\_unsqueeze](#), [mlr\\_pipeops\\_torch\\_ingress](#), [mlr\\_pipeops\\_torch\\_ingress\\_categ](#), [mlr\\_pipeops\\_torch\\_ingress\\_ltnsr](#), [mlr\\_pipeops\\_torch\\_ingress\\_num](#), [mlr\\_pipeops\\_torch\\_loss](#), [mlr\\_pipeops\\_torch\\_model](#), [mlr\\_pipeops\\_torch\\_model\\_classif](#), [mlr\\_pipeops\\_torch\\_model\\_regr](#)

## Examples

```
# Construct the PipeOp
pipeop = po("nn_tanhshrink")
pipeop
# The available parameters
pipeop$param_set
```

---

### mlr\_pipeops\_nn\_threshold

*Threshold Activation Function*

---

## Description

Thresholds each element of the input Tensor.

### nn\_module

Calls [torch::nn\\_threshold\(\)](#) when trained.

## Parameters

- `threshold` :: `numeric(1)`  
The value to threshold at.
- `value` :: `numeric(1)`  
The value to replace with.
- `inplace` :: `logical(1)`  
Can optionally do the operation in-place. Default: FALSE.

## Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

## State

The state is the value calculated by the public method `$shapes_out()`.

## Super classes

`mlr3pipelines::PipeOp` -> `mlr3torch::PipeOpTorch` -> `PipeOpTorchThreshold`

## Methods

### Public methods:

- `PipeOpTorchThreshold$new()`
- `PipeOpTorchThreshold$clone()`

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

`PipeOpTorchThreshold$new(id = "nn_threshold", param_vals = list())`

*Arguments:*

`id` (`character(1)`)

Identifier of the resulting object.

`param_vals` (`list()`)

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

`PipeOpTorchThreshold$clone(deep = FALSE)`

*Arguments:*

`deep` Whether to make a deep clone.

## See Also

Other PipeOps: [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm1d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm2d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm3d](#), [mlr\\_pipeops\\_nn\\_block](#), [mlr\\_pipeops\\_nn\\_celu](#), [mlr\\_pipeops\\_nn\\_conv1d](#), [mlr\\_pipeops\\_nn\\_conv2d](#), [mlr\\_pipeops\\_nn\\_conv3d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose1d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose3d](#), [mlr\\_pipeops\\_nn\\_dropout](#), [mlr\\_pipeops\\_nn\\_elu](#), [mlr\\_pipeops\\_nn\\_flatten](#), [mlr\\_pipeops\\_nn\\_ft\\_cls](#), [mlr\\_pipeops\\_nn\\_ft\\_transformer\\_block](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_glu](#), [mlr\\_pipeops\\_nn\\_hardshrink](#), [mlr\\_pipeops\\_nn\\_hardsigmoid](#), [mlr\\_pipeops\\_nn\\_hardtanh](#), [mlr\\_pipeops\\_nn\\_head](#), [mlr\\_pipeops\\_nn\\_identity](#), [mlr\\_pipeops\\_nn\\_layer\\_norm](#), [mlr\\_pipeops\\_nn\\_leaky\\_relu](#), [mlr\\_pipeops\\_nn\\_linear](#), [mlr\\_pipeops\\_nn\\_log\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_max\\_pool1d](#), [mlr\\_pipeops\\_nn\\_max\\_pool2d](#), [mlr\\_pipeops\\_nn\\_max\\_pool3d](#), [mlr\\_pipeops\\_nn\\_merge](#), [mlr\\_pipeops\\_nn\\_merge\\_cat](#), [mlr\\_pipeops\\_nn\\_merge\\_prod](#), [mlr\\_pipeops\\_nn\\_merge\\_sum](#), [mlr\\_pipeops\\_nn\\_prelu](#), [mlr\\_pipeops\\_nn\\_reglu](#), [mlr\\_pipeops\\_nn\\_relu](#), [mlr\\_pipeops\\_nn\\_relu6](#), [mlr\\_pipeops\\_nn\\_reshape](#), [mlr\\_pipeops\\_nn\\_rrelu](#), [mlr\\_pipeops\\_nn\\_selu](#), [mlr\\_pipeops\\_nn\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_softmax](#), [mlr\\_pipeops\\_nn\\_softplus](#), [mlr\\_pipeops\\_nn\\_softshrink](#), [mlr\\_pipeops\\_nn\\_softsign](#), [mlr\\_pipeops\\_nn\\_squeeze](#), [mlr\\_pipeops\\_nn\\_tanh](#), [mlr\\_pipeops\\_nn\\_tanhshrink](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_categ](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_num](#), [mlr\\_pipeops\\_nn\\_unsqueeze](#), [mlr\\_pipeops\\_torch\\_ingress](#), [mlr\\_pipeops\\_torch\\_ingress\\_categ](#), [mlr\\_pipeops\\_torch\\_ingress\\_ltnsr](#), [mlr\\_pipeops\\_torch\\_ingress\\_num](#), [mlr\\_pipeops\\_torch\\_loss](#), [mlr\\_pipeops\\_torch\\_model](#), [mlr\\_pipeops\\_torch\\_model\\_classif](#), [mlr\\_pipeops\\_torch\\_model\\_regr](#)

## Examples

```
# Construct the PipeOp
pipeop = po("nn_threshold", threshold = 1, value = 2)
pipeop
# The available parameters
pipeop$param_set
```

---

**mlr\_pipeops\_nn\_tokenizer\_categ**  
*Categorical Tokenizer*

---

## Description

Tokenizes categorical features into a dense embedding. For an input of shape (batch, n\_features) the output shape is (batch, n\_features, d\_token).

### nn\_module

Calls [nn\\_tokenizer\\_categ\(\)](#) when trained where the parameter cardinalities is inferred. The output shape is (batch, n\_features, d\_token).

## Parameters

- `d_token` :: `integer(1)`  
The dimension of the embedding.
- `bias` :: `logical(1)`  
Whether to use a bias. Is initialized to TRUE.
- `initialization` :: `character(1)`  
The initialization method for the embedding weights. Possible values are "uniform" (default) and "normal".
- `cardinalities` :: `integer()`  
The number of categories for each feature. Only needs to be provided when working with `lazy_tensor` inputs.

## Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

## State

The state is the value calculated by the public method `$shapes_out()`.

## Super classes

[mlr3pipelines::PipeOp](#) -> [mlr3torch::PipeOpTorch](#) -> `PipeOpTorchTokenizerCateg`

## Methods

### Public methods:

- [PipeOpTorchTokenizerCateg\\$new\(\)](#)
- [PipeOpTorchTokenizerCateg\\$clone\(\)](#)

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

`PipeOpTorchTokenizerCateg$new(id = "nn_tokenizer_categ", param_vals = list())`

*Arguments:*

`id` (`character(1)`)

Identifier of the resulting object.

`param_vals` (`list()`)

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

`PipeOpTorchTokenizerCateg$clone(deep = FALSE)`

*Arguments:*

`deep` Whether to make a deep clone.

## See Also

Other PipeOps: [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm1d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm2d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm3d](#), [mlr\\_pipeops\\_nn\\_block](#), [mlr\\_pipeops\\_nn\\_celu](#), [mlr\\_pipeops\\_nn\\_conv1d](#), [mlr\\_pipeops\\_nn\\_conv2d](#), [mlr\\_pipeops\\_nn\\_conv3d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose1d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose3d](#), [mlr\\_pipeops\\_nn\\_dropout](#), [mlr\\_pipeops\\_nn\\_elu](#), [mlr\\_pipeops\\_nn\\_flatten](#), [mlr\\_pipeops\\_nn\\_ft\\_cls](#), [mlr\\_pipeops\\_nn\\_ft\\_transformer\\_block](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_glu](#), [mlr\\_pipeops\\_nn\\_hardshrink](#), [mlr\\_pipeops\\_nn\\_hardsigmoid](#), [mlr\\_pipeops\\_nn\\_hardtanh](#), [mlr\\_pipeops\\_nn\\_head](#), [mlr\\_pipeops\\_nn\\_identity](#), [mlr\\_pipeops\\_nn\\_layer\\_norm](#), [mlr\\_pipeops\\_nn\\_leaky\\_relu](#), [mlr\\_pipeops\\_nn\\_linear](#), [mlr\\_pipeops\\_nn\\_log\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_max\\_pool1d](#), [mlr\\_pipeops\\_nn\\_max\\_pool2d](#), [mlr\\_pipeops\\_nn\\_max\\_pool3d](#), [mlr\\_pipeops\\_nn\\_merge](#), [mlr\\_pipeops\\_nn\\_merge\\_cat](#), [mlr\\_pipeops\\_nn\\_merge\\_prod](#), [mlr\\_pipeops\\_nn\\_merge\\_sum](#), [mlr\\_pipeops\\_nn\\_prelu](#), [mlr\\_pipeops\\_nn\\_reglu](#), [mlr\\_pipeops\\_nn\\_relu](#), [mlr\\_pipeops\\_nn\\_relu6](#), [mlr\\_pipeops\\_nn\\_reshape](#), [mlr\\_pipeops\\_nn\\_rrelu](#), [mlr\\_pipeops\\_nn\\_selu](#), [mlr\\_pipeops\\_nn\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_softmax](#), [mlr\\_pipeops\\_nn\\_softplus](#), [mlr\\_pipeops\\_nn\\_softshrink](#), [mlr\\_pipeops\\_nn\\_softsign](#), [mlr\\_pipeops\\_nn\\_squeeze](#), [mlr\\_pipeops\\_nn\\_tanh](#), [mlr\\_pipeops\\_nn\\_tanhshrink](#), [mlr\\_pipeops\\_nn\\_threshold](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_num](#), [mlr\\_pipeops\\_nn\\_unsqueeze](#), [mlr\\_pipeops\\_torch\\_ingress](#), [mlr\\_pipeops\\_torch\\_ingress\\_categ](#), [mlr\\_pipeops\\_torch\\_ingress\\_ltnsr](#), [mlr\\_pipeops\\_torch\\_ingress\\_num](#), [mlr\\_pipeops\\_torch\\_loss](#), [mlr\\_pipeops\\_torch\\_model](#), [mlr\\_pipeops\\_torch\\_model\\_classif](#), [mlr\\_pipeops\\_torch\\_model\\_regr](#)

## Examples

```
# Construct the PipeOp
pipeop = po("nn_tokenizer_categ", d_token = 10)
pipeop
# The available parameters
pipeop$param_set
```

---

**mlr\_pipeops\_nn\_tokenizer\_num**  
*Numeric Tokenizer*

---

## Description

Tokenizes numeric features into a dense embedding. For an input of shape (batch, n\_features) the output shape is (batch, n\_features, d\_token).

## nn\_module

Calls [nn\\_tokenizer\\_num\(\)](#) when trained where the parameter n\_features is inferred. The output shape is (batch, n\_features, d\_token).

## Parameters

- `d_token` :: `integer(1)`  
The dimension of the embedding.
- `bias` :: `logical(1)`  
Whether to use a bias. Is initialized to TRUE.
- `initialization` :: `character(1)`  
The initialization method for the embedding weights. Possible values are "uniform" (default) and "normal".

## Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

## State

The state is the value calculated by the public method `$shapes_out()`.

## Super classes

`mlr3pipelines::PipeOp` -> `mlr3torch::PipeOpTorch` -> `PipeOpTorchTokenizerNum`

## Methods

### Public methods:

- `PipeOpTorchTokenizerNum$new()`
- `PipeOpTorchTokenizerNum$clone()`

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

`PipeOpTorchTokenizerNum$new(id = "nn_tokenizer_num", param_vals = list())`

*Arguments:*

`id` (`character(1)`)

Identifier of the resulting object.

`param_vals` (`list()`)

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

`PipeOpTorchTokenizerNum$clone(deep = FALSE)`

*Arguments:*

`deep` Whether to make a deep clone.

## See Also

Other PipeOps: [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm1d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm2d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm3d](#), [mlr\\_pipeops\\_nn\\_block](#), [mlr\\_pipeops\\_nn\\_celu](#), [mlr\\_pipeops\\_nn\\_conv1d](#), [mlr\\_pipeops\\_nn\\_conv2d](#), [mlr\\_pipeops\\_nn\\_conv3d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose1d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose3d](#), [mlr\\_pipeops\\_nn\\_dropout](#), [mlr\\_pipeops\\_nn\\_elu](#), [mlr\\_pipeops\\_nn\\_flatten](#), [mlr\\_pipeops\\_nn\\_ft\\_cls](#), [mlr\\_pipeops\\_nn\\_ft\\_transformer\\_block](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_glu](#), [mlr\\_pipeops\\_nn\\_hardshrink](#), [mlr\\_pipeops\\_nn\\_hardsigmoid](#), [mlr\\_pipeops\\_nn\\_hardtanh](#), [mlr\\_pipeops\\_nn\\_head](#), [mlr\\_pipeops\\_nn\\_identity](#), [mlr\\_pipeops\\_nn\\_layer\\_norm](#), [mlr\\_pipeops\\_nn\\_leaky\\_relu](#), [mlr\\_pipeops\\_nn\\_linear](#), [mlr\\_pipeops\\_nn\\_log\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_max\\_pool1d](#), [mlr\\_pipeops\\_nn\\_max\\_pool2d](#), [mlr\\_pipeops\\_nn\\_max\\_pool3d](#), [mlr\\_pipeops\\_nn\\_merge](#), [mlr\\_pipeops\\_nn\\_merge\\_cat](#), [mlr\\_pipeops\\_nn\\_merge\\_prod](#), [mlr\\_pipeops\\_nn\\_merge\\_sum](#), [mlr\\_pipeops\\_nn\\_prelu](#), [mlr\\_pipeops\\_nn\\_reglu](#), [mlr\\_pipeops\\_nn\\_relu](#), [mlr\\_pipeops\\_nn\\_relu6](#), [mlr\\_pipeops\\_nn\\_reshape](#), [mlr\\_pipeops\\_nn\\_rrelu](#), [mlr\\_pipeops\\_nn\\_selu](#), [mlr\\_pipeops\\_nn\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_softmax](#), [mlr\\_pipeops\\_nn\\_softplus](#), [mlr\\_pipeops\\_nn\\_softshrink](#), [mlr\\_pipeops\\_nn\\_softsign](#), [mlr\\_pipeops\\_nn\\_squeeze](#), [mlr\\_pipeops\\_nn\\_tanh](#), [mlr\\_pipeops\\_nn\\_tanhshrink](#), [mlr\\_pipeops\\_nn\\_threshold](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_categ](#), [mlr\\_pipeops\\_nn\\_unsqueeze](#), [mlr\\_pipeops\\_torch\\_ingress](#), [mlr\\_pipeops\\_torch\\_ingress\\_categ](#), [mlr\\_pipeops\\_torch\\_ingress\\_ltnsr](#), [mlr\\_pipeops\\_torch\\_ingress\\_num](#), [mlr\\_pipeops\\_torch\\_loss](#), [mlr\\_pipeops\\_torch\\_model](#), [mlr\\_pipeops\\_torch\\_model\\_classif](#), [mlr\\_pipeops\\_torch\\_model\\_regr](#)

## Examples

```
# Construct the PipeOp
pipeop = po("nn_tokenizer_num", d_token = 10)
pipeop
# The available parameters
pipeop$param_set
```

---

### mlr\_pipeops\_nn\_unsqueeze

*Unsqueeze a Tensor*

---

## Description

Unsqueezes a tensor by calling [torch::torch\\_unsqueeze\(\)](#) with the given dimension `dim`.

### nn\_module

Calls [nn\\_unsqueeze\(\)](#) when trained. This internally calls [torch::torch\\_unsqueeze\(\)](#).

### Parameters

- `dim :: integer(1)`  
The dimension which to unsqueeze. Negative values are interpreted downwards from the last dimension.

## Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

## State

The state is the value calculated by the public method `$shapes_out()`.

## Super classes

`mlr3pipelines::PipeOp -> mlr3torch::PipeOpTorch -> PipeOpTorchUnsqueeze`

## Methods

### Public methods:

- `PipeOpTorchUnsqueeze$new()`
- `PipeOpTorchUnsqueeze$clone()`

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

`PipeOpTorchUnsqueeze$new(id = "nn_unsqueeze", param_vals = list())`

*Arguments:*

`id` (character(1))

Identifier of the resulting object.

`param_vals` (list())

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

`PipeOpTorchUnsqueeze$clone(deep = FALSE)`

*Arguments:*

`deep` Whether to make a deep clone.

## See Also

Other PipeOps: `mlr_pipeops_nn_adaptive_avg_pool1d`, `mlr_pipeops_nn_adaptive_avg_pool2d`, `mlr_pipeops_nn_adaptive_avg_pool3d`, `mlr_pipeops_nn_avg_pool1d`, `mlr_pipeops_nn_avg_pool2d`, `mlr_pipeops_nn_avg_pool3d`, `mlr_pipeops_nn_batch_norm1d`, `mlr_pipeops_nn_batch_norm2d`, `mlr_pipeops_nn_batch_norm3d`, `mlr_pipeops_nn_block`, `mlr_pipeops_nn_celu`, `mlr_pipeops_nn_conv1d`, `mlr_pipeops_nn_conv2d`, `mlr_pipeops_nn_conv3d`, `mlr_pipeops_nn_conv_transpose1d`, `mlr_pipeops_nn_conv_transpose3d`, `mlr_pipeops_nn_dropout`, `mlr_pipeops_nn_elu`, `mlr_pipeops_nn_flatten`, `mlr_pipeops_nn_ft_cls`, `mlr_pipeops_nn_ft_transformer_block`, `mlr_pipeops_nn_gelu`, `mlr_pipeops_nn_glu`, `mlr_pipeops_nn_hardshrink`, `mlr_pipeops_nn_hardsigmoid`, `mlr_pipeops_nn_hardtanh`, `mlr_pipeops_nn_head`, `mlr_pipeops_nn_identity`, `mlr_pipeops_nn_layer_norm`, `mlr_pipeops_nn_leaky_relu`, `mlr_pipeops_nn_linear`, `mlr_pipeops_nn_log_sigmoid`, `mlr_pipeops_nn_max_pool1d`

```
mlr_pipeops_nn_max_pool2d, mlr_pipeops_nn_max_pool3d, mlr_pipeops_nn_merge, mlr_pipeops_nn_merge_cat,
mlr_pipeops_nn_merge_prod, mlr_pipeops_nn_merge_sum, mlr_pipeops_nn_prelu, mlr_pipeops_nn_reglu,
mlr_pipeops_nn_relu, mlr_pipeops_nn_relu6, mlr_pipeops_nn_reshape, mlr_pipeops_nn_rrelu,
mlr_pipeops_nn_selu, mlr_pipeops_nn_sigmoid, mlr_pipeops_nn_softmax, mlr_pipeops_nn_softplus,
mlr_pipeops_nn_softshrink, mlr_pipeops_nn_softsign, mlr_pipeops_nn_squeeze, mlr_pipeops_nn_tanh,
mlr_pipeops_nn_tanhshrink, mlr_pipeops_nn_threshold, mlr_pipeops_nn_tokenizer_categ,
mlr_pipeops_nn_tokenizer_num, mlr_pipeops_torch_ingress, mlr_pipeops_torch_ingress_categ,
mlr_pipeops_torch_ingress_ltnsr, mlr_pipeops_torch_ingress_num, mlr_pipeops_torch_loss,
mlr_pipeops_torch_model, mlr_pipeops_torch_model_classif, mlr_pipeops_torch_model_regr
```

## Examples

```
# Construct the PipeOp
pipeop = po("nn_unsqueeze")
pipeop
# The available parameters
pipeop$param_set
```

---

mlr\_pipeops\_preproc\_torch

*Base Class for Lazy Tensor Preprocessing*

---

## Description

This PipeOp can be used to preprocess (one or more) `lazy_tensor` columns contained in an `mlr3::Task`. The preprocessing function is specified as construction argument `fn` and additional arguments to this function can be defined through the PipeOp's parameter set. The preprocessing is done per column, i.e. the number of lazy tensor output columns is equal to the number of lazy tensor input columns.

To create custom preprocessing PipeOps you can use `pipeop_preproc_torch`.

## Inheriting

In addition to specifying the construction arguments, you can overwrite the private `.shapes_out()` method. If you don't overwrite it, the output shapes are assumed to be unknown (NULL).

- `.shapes_out(shapes_in, param_vals, task)`  
`(list(), list(), TaskorNULL) -> list()\cr` This private method calculates the output shapes of the lazy This private method only has the responsibility to calculate the output shapes for one input column, i.e. the input `shapes_in` can be assumed to have exactly one shape vector for which it must calculate the output shapes and return it as a `list()` of length 1. It can also be assumed that the shape is not NULL (i.e. unknown). Also, the first dimension can be NA, i.e. is unknown (as for the batch dimension).

## Input and Output Channels

See [PipeOpTaskPreproc](#).

## State

In addition to state elements from [PipeOpTaskPreprocSimple](#), the state also contains the `$param_vals` that were set during training.

## Parameters

In addition to the parameters inherited from [PipeOpTaskPreproc](#) as well as those specified during construction as the argument `param_set` there are the following parameters:

- `stages` :: `character(1)`

The stages during which to apply the preprocessing. Can be one of "train", "predict" or "both". The initial value of this parameter is set to "train" when the PipeOp's id starts with "augment\_" and to "both" otherwise. Note that the preprocessing that is applied during `$predict()` uses the parameters that were set during `$train()` and not those that are set when performing the prediction.

## Internals

During `$train()` / `$predict()`, a [PipeOpModule](#) with one input and one output channel is created. The pipeop applies the function `fn` to the input tensor while additionally passing the parameter values (minus `stages` and `affect_columns`) to `fn`. The preprocessing graph of the lazy tensor columns is shallowly cloned and the [PipeOpModule](#) is added. This is done to avoid modifying user input and means that identical [PipeOpModules](#) can be part of different preprocessing graphs. This is only possible, because the created [PipeOpModule](#) is stateless.

At a later point in the graph, preprocessing graphs will be merged if possible to avoid unnecessary computation. This is best illustrated by example: One lazy tensor column's preprocessing graph is  $A \rightarrow B$ . Then, two branches are created  $B \rightarrow C$  and  $B \rightarrow D$ , creating two preprocessing graphs  $A \rightarrow B \rightarrow C$  and  $A \rightarrow B \rightarrow D$ . When loading the data, we want to run the preprocessing only once, i.e. we don't want to run the  $A \rightarrow B$  part twice. For this reason, `task_dataset()` will try to merge graphs and cache results from graphs. However, only graphs using the same dataset can currently be merged.

Also, the shapes created during `$train()` and `$predict()` might differ. To avoid the creation of graphs where the predict shapes are incompatible with the train shapes, the hypothetical predict shapes are already calculated during `$train()` (this is why the parameters that are set during train are also used during predict) and the [PipeOpTorchModel](#) will check the train and predict shapes for compatibility before starting the training.

Otherwise, this mechanism is very similar to the [ModelDescriptor](#) construct.

## Super classes

`mlr3pipelines::PipeOp` -> `mlr3pipelines::PipeOpTaskPreproc` -> `PipeOpTaskPreprocTorch`

## Active bindings

`fn` The preprocessing function.

`rowwise` Whether the preprocessing is applied rowwise.

## Methods

### Public methods:

- `PipeOpTaskPreprocTorch$new()`
- `PipeOpTaskPreprocTorch$shapes_out()`
- `PipeOpTaskPreprocTorch$clone()`

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

```
PipeOpTaskPreprocTorch$new(
  fn,
  id = "preproc_torch",
  param_vals = list(),
  param_set = ps(),
  packages = character(0),
  rowwise = FALSE,
  stages_init = NULL,
  tags = NULL
)
```

*Arguments:*

`fn` (function or character(2))

The preprocessing function. Must not modify its input in-place. If it is a character(2), the first element should be the namespace and the second element the name. When the preprocessing function is applied to the tensor, the tensor will be passed by position as the first argument. If the `param_set` is inferred (left as NULL) it is assumed that the first argument is the `torch_tensor`.

`id` (character(1))

The id for of the new object.

`param_vals` (named list())

Parameter values to be set after construction.

`param_set` ([ParamSet](#))

In case the function `fn` takes additional parameter besides a `torch_tensor` they can be specified as parameters. None of the parameters can have the "predict" tag. All tags should include "train".

`packages` (character())

The packages the preprocessing function depends on.

`rowwise` (logical(1))

Whether the preprocessing function is applied rowwise (and then concatenated by row) or directly to the whole tensor. In the first case there is no batch dimension.

`stages_init` (character(1))

Initial value for the `stages` parameter.

`tags` (character())

Tags for the pipeop.

**Method** `shapes_out()`: Calculates the output shapes that would result in applying the preprocessing to one or more lazy tensor columns with the provided shape. Names are ignored and only order matters. It uses the parameter values that are currently set.

*Usage:*

PipeOpTaskPreprocTorch\$shapes\_out(shapes\_in, stage = NULL, task = NULL)

*Arguments:*

shapes\_in (list() of (integer() or NULL))

The input input shapes of the lazy tensors. NULL indicates that the shape is unknown. First dimension must be NA (if it is not NULL).

stage (character(1))

The stage: either "train" or "predict".

task (Task or NULL)

The task, which is very rarely needed.

*Returns:* list() of (integer() or NULL)

**Method** clone(): The objects of this class are cloneable with this method.

*Usage:*

PipeOpTaskPreprocTorch\$clone(deep = FALSE)

*Arguments:*

deep Whether to make a deep clone.

## Examples

```
# Creating a simple task
d = data.table(
  x1 = as_lazy_tensor(matrix(rnorm(10), ncol = 1)),
  x2 = as_lazy_tensor(matrix(rnorm(10), ncol = 1)),
  x3 = as_lazy_tensor(matrix(as.double(1:10), ncol = 1)),
  y = rnorm(10)
)

taskin = as_task_regr(d, target = "y")

# Creating a simple preprocessing pipeop
po_simple = po("preproc_torch",
  # get rid of environment baggage
  fn = mlr3misc::crate(function(x, a) x + a),
  param_set = paradox::ps(a = paradox::p_int(tags = c("train", "required")))
)

po_simple$param_set$set_values(
  a = 100,
  affect_columns = selector_name(c("x1", "x2")),
  stages = "both" # use during train and predict
)

taskout_train = po_simple$train(list(taskin))[[1L]]
materialize(taskout_train$data(cols = c("x1", "x2")), rbind = TRUE)

taskout_predict_noaug = po_simple$predict(list(taskin))[[1L]]
materialize(taskout_predict_noaug$data(cols = c("x1", "x2")), rbind = TRUE)
```

```

po_simple$param_set$set_values(
  stages = "train"
)

# transformation is not applied
taskout_predict_aug = po_simple$predict(list(taskin))[[1L]]
materialize(taskout_predict_aug$data(cols = c("x1", "x2")), rbind = TRUE)

# Creating a more complex preprocessing PipeOp
PipeOpPreprocTorchPoly = R6::R6Class("PipeOpPreprocTorchPoly",
  inherit = PipeOpTaskPreprocTorch,
  public = list(
    initialize = function(id = "preproc_poly", param_vals = list()) {
      param_set = paradox::ps(
        n_degree = paradox::p_int(lower = 1L, tags = c("train", "required"))
      )
      param_set$set_values(
        n_degree = 1L
      )
      fn = mlr3misc::crate(function(x, n_degree) {
        torch::torch_cat(
          lapply(seq_len(n_degree), function(d) torch::torch_pow(x, d)),
          dim = 2L
        )
      })
    }
  )
  super$initialize(
    fn = fn,
    id = id,
    packages = character(0),
    param_vals = param_vals,
    param_set = param_set,
    stages_init = "both"
  )
),
private = list(
  .shapes_out = function(shapes_in, param_vals, task) {
    # shapes_in is a list of length 1 containing the shapes
    checkmate::assert_true(length(shapes_in[[1L]]) == 2L)
    if (shapes_in[[1L]][2L] != 1L) {
      stop("Input shape must be (NA, 1)")
    }
    list(c(NA, param_vals$n_degree))
  }
)
)

po_poly = PipeOpPreprocTorchPoly$new(
  param_vals = list(n_degree = 3L, affect_columns = selector_name("x3"))
)
po_poly$shapes_out(list(c(NA, 1L)), stage = "train")

```

---

```
taskout = po_poly$train(list(taskin))[[1L]]
materialize(taskout$data(cols = "x3"), rbind = TRUE)
```

---

`mlr_pipeops_torch`

*Base Class for Torch Module Constructor Wrappers*

---

## Description

`PipeOpTorch` is the base class for all `PipeOps` that represent neural network layers in a `Graph`. During **training**, it generates a `PipeOpModule` that wraps an `nn_module` and attaches it to the architecture, which is also represented as a `Graph` consisting mostly of `PipeOpModules` and `PipeOpNOPs`.

While the former `Graph` operates on `ModelDescriptors`, the latter operates on `tensors`.

The relationship between a `PipeOpTorch` and a `PipeOpModule` is similar to the relationship between a `nn_module_generator` (like `nn_linear`) and a `nn_module` (like the output of `nn_linear(...)`). A crucial difference is that the `PipeOpTorch` infers auxiliary parameters (like `in_features` for `nn_linear`) automatically from the intermediate tensor shapes that are being communicated through the `ModelDescriptor`.

During **prediction**, `PipeOpTorch` takes in a `Task` in each channel and outputs the same new `Task` resulting from their `feature union` in each channel. If there is only one input and output channel, the task is simply piped through.

## Parameters

The `ParamSet` is specified by the child class inheriting from `PipeOpTorch`. Usually the parameters are the arguments of the wrapped `nn_module` minus the auxiliary parameter that can be automatically inferred from the shapes of the input tensors.

## Inheriting

When inheriting from this class, one should overload either the `private$.shapes_out()` and the `private$.shape_dependent_params()` methods, or overload `private$.make_module()`.

- `.make_module(shapes_in, param_vals, task)`  
`(list(), list()) -> nn_module`

This private method is called to generate the `nn_module` that is passed as argument `module` to `PipeOpModule`. It must be overwritten, when no `module_generator` is provided. If left as is, it calls the provided `module_generator` with the arguments obtained by the private method `.shape_dependent_params()`.

- `.shapes_out(shapes_in, param_vals, task)`  
`(list(), list(), Task or NULL) -> named list()`

This private method gets a list of integer vectors (`shapes_in`), the parameter values (`param_vals`), as well as an (optional) `Task`. The `shapes_in` can be assumed to be in the same order as the input names of the `PipeOp`. The output shapes must be in the same order as the output names of the `PipeOp`. In case the output shapes depends on the task (as is the case for

[PipeOpTorchHead](#)), the function should return valid output shapes (possibly containing NAs) if the task argument is provided or not. It is important to properly handle the presence of NAs in the input shapes. By default (if construction argument `only_batch_unknown` is TRUE), only the batch dimension can be NA. If you set this to FALSE, you need to take other unknown dimensions into account. The method can also throw an error if the input shapes violate some assumptions.

- `.shape_dependent_params(shapes_in, param_vals, task)`  
`(list(), list()) -> named list()`

This private method has the same inputs as `.shapes_out`. If `.make_module()` is not overwritten, it constructs the arguments passed to `module_generator`. Usually this means that it must infer the auxiliary parameters that can be inferred from the input shapes and add it to the user-supplied parameter values (`param_vals`).

## Input and Output Channels

During *training*, all inputs and outputs are of class [ModelDescriptor](#). During *prediction*, all input and output channels are of class [Task](#).

### State

The state is the value calculated by the public method `shapes_out()`.

### Internals

During training, the `PipeOpTorch` creates a [PipeOpModule](#) for the given parameter specification and the input shapes from the incoming [ModelDescriptor](#)s using the private method `.make_module()`. The input shapes are provided by the slot `pointer_shape` of the incoming [ModelDescriptor](#)s. The channel names of this [PipeOpModule](#) are identical to the channel names of the generating [PipeOpTorch](#).

A [model descriptor union](#) of all incoming [ModelDescriptor](#)s is then created. Note that this modifies the `graph` of the first [ModelDescriptor](#) **in place** for efficiency. The [PipeOpModule](#) is added to the `graph` slot of this union and the edges that connect the sending [PipeOpModule](#)s to the input channel of this [PipeOpModule](#) are added to the graph. This is possible because every incoming [ModelDescriptor](#) contains the information about the `id` and the channel name of the sending [PipeOp](#) in the slot `pointer`.

The new graph in the `model_descriptor_union` represents the current state of the neural network architecture. It is structurally similar to the subgraph that consists of all pipeops of class [PipeOpTorch](#) and [PipeOpTorchIngress](#) that are ancestors of this [PipeOpTorch](#).

For the output, a shallow copy of the [ModelDescriptor](#) is created and the `pointer` and `pointer_shape` are updated accordingly. The shallow copy means that all [ModelDescriptor](#)s point to the same [Graph](#) which allows the graph to be modified by-reference in different parts of the code.

### Super class

[mlr3pipelines::PipeOp](#) -> [PipeOpTorch](#)

## Public fields

`module_generator` (nn\_module\_generator or NULL)

The module generator wrapped by this PipeOpTorch. If NULL, the private method `private$.make_module(shapes_in, param_vals)` must be overwritten, see section 'Inheriting'. Do not change this after construction.

## Methods

### Public methods:

- `PipeOpTorch$new()`
- `PipeOpTorch$shapes_out()`
- `PipeOpTorch$clone()`

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

```
PipeOpTorch$new(
  id,
  module_generator,
  param_set = ps(),
  param_vals = list(),
  inname = "input",
  outname = "output",
  packages = "torch",
  tags = NULL,
  only_batch_unknown = TRUE
)
```

*Arguments:*

`id` (character(1))

Identifier of the resulting object.

`module_generator` (nn\_module\_generator)

The torch module generator.

`param_set` ([ParamSet](#))

The parameter set.

`param_vals` (list())

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

`inname` (character())

The names of the [PipeOp](#)'s input channels. These will be the input channels of the generated [PipeOpModule](#). Unless the wrapped `module_generator`'s forward method (if present) has the argument ..., `inname` must be identical to those argument names in order to avoid any ambiguity.

If the forward method has the argument ..., the order of the input channels determines how the tensors will be passed to the wrapped `nn_module`.

If left as NULL (default), the argument `module_generator` must be given and the argument names of the `modue_generator`'s forward function are set as `inname`.

`outname` (character())

The names of the output channels channels. These will be the ouput channels of the generated [PipeOpModule](#) and therefore also the names of the list returned by its `$train()`. In case there is more than one output channel, the `nn_module` that is constructed by this [PipeOp](#) during training must return a named `list()`, where the names of the list are the names out the output channels. The default is "output".

`packages` (character())

The R packages this object depends on.

`tags` (character())

The tags of the [PipeOp](#). The tags "torch" is always added.

`only_batch_unknown` (logical(1))

Whether only the batch dimension can be missing in the input shapes or whether other dimensions can also be unknown. Default is TRUE.

**Method** `shapes_out()`: Calculates the output shapes for the given input shapes, parameters and task.

*Usage:*

`PipeOpTorch$shapes_out(shapes_in, task = NULL)`

*Arguments:*

`shapes_in` (list() of integer())

The input input shapes, which must be in the same order as the input channel names of the PipeOp.

`task` ([Task](#) or NULL)

The task, which is very rarely used (default is NULL). An exception is [PipeOpTorchHead](#).

*Returns:* A named `list()` containing the output shapes. The names are the names of the output channels of the PipeOp.

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

`PipeOpTorch$clone(deep = FALSE)`

*Arguments:*

`deep` Whether to make a deep clone.

## See Also

Other Graph Network: [ModelDescriptor\(\)](#), [TorchIngressToken\(\)](#), [mlr\\_learners\\_torch\\_model](#), [mlr\\_pipeops\\_module](#), [mlr\\_pipeops\\_torch\\_ingress](#), [mlr\\_pipeops\\_torch\\_ingress\\_categ](#), [mlr\\_pipeops\\_torch\\_ingress\\_num](#), [model\\_descriptor\\_to\\_learner\(\)](#), [model\\_descriptor\\_to\\_module\(\)](#), [model\\_descriptor\\_union\(\)](#), [nn\\_graph\(\)](#)

## Examples

```
## Creating a neural network
# In torch

task = tsk("iris")
```

```

network_generator = torch::nn_module(
  initialize = function(task, d_hidden) {
    d_in = length(task$feature_names)
    self$linear = torch::nn_linear(d_in, d_hidden)
    self$output = if (task$task_type == "regr") {
      torch::nn_linear(d_hidden, 1)
    } else if (task$task_type == "classif") {
      torch::nn_linear(d_hidden, output_dim_for(task))
    }
  },
  forward = function(x) {
    x = self$linear(x)
    x = torch::nnf_relu(x)
    self$output(x)
  }
)

network = network_generator(task, d_hidden = 50)
x = torch::torch_tensor(as.matrix(task$data(1, task$feature_names)))
y = torch::with_no_grad(network(x))

# In mlr3torch
network_generator = po("torch_ingress_num") %>>%
  po("nn_linear", out_features = 50) %>>%
  po("nn_head")
md = network_generator$train(task)[[1L]]
network = model_descriptor_to_module(md)
y = torch::with_no_grad(network(torch_ingress_num.input = x))

## Implementing a custom PipeOpTorch

# defining a custom module
nn_custom = nn_module("nn_custom",
  initialize = function(d_in1, d_in2, d_out1, d_out2, bias = TRUE) {
    self$linear1 = nn_linear(d_in1, d_out1, bias)
    self$linear2 = nn_linear(d_in2, d_out2, bias)
  },
  forward = function(input1, input2) {
    output1 = self$linear1(input1)
    output2 = self$linear2(input2)

    list(output1 = output1, output2 = output2)
  }
)

# wrapping the module into a custom PipeOpTorch
library(paradox)

PipeOpTorchCustom = R6::R6Class("PipeOpTorchCustom",

```

```

inherit = PipeOpTorch,
public = list(
  initialize = function(id = "nn_custom", param_vals = list()) {
    param_set = ps(
      d_out1 = p_int(lower = 1, tags = c("required", "train")),
      d_out2 = p_int(lower = 1, tags = c("required", "train")),
      bias = p_lgl(default = TRUE, tags = "train")
    )
    super$initialize(
      id = id,
      param_vals = param_vals,
      param_set = param_set,
      inname = c("input1", "input2"),
      outname = c("output1", "output2"),
      module_generator = nn_custom
    )
  }
),
private = list(
  .shape_dependent_params = function(shapes_in, param_vals, task) {
    c(param_vals,
      list(d_in1 = tail(shapes_in[["input1"]], 1), d_in2 = tail(shapes_in[["input2"]], 1)
    )
  },
  .shapes_out = function(shapes_in, param_vals, task) {
    list(
      input1 = c(head(shapes_in[["input1"]], -1), param_vals$d_out1),
      input2 = c(head(shapes_in[["input2"]], -1), param_vals$d_out2)
    )
  }
)
)

## Training

# generate input
task = tsk("iris")
task1 = task$clone()$select(paste0("Sepal.", c("Length", "Width")))
task2 = task$clone()$select(paste0("Petal.", c("Length", "Width")))
graph = gunion(list(po("torch_ingress_num_1"), po("torch_ingress_num_2")))
mds_in = graph$train(list(task1, task2), single_input = FALSE)

mds_in[[1L]][c("graph", "task", "ingress", "pointer", "pointer_shape")]
mds_in[[2L]][c("graph", "task", "ingress", "pointer", "pointer_shape")]

# creating the PipeOpTorch and training it
po_torch = PipeOpTorchCustom$new()
po_torch$param_set$values = list(d_out1 = 10, d_out2 = 20)
train_input = list(input1 = mds_in[[1L]], input2 = mds_in[[2L]])
mds_out = do.call(po_torch$train, args = list(input = train_input))
po_torch$state

# the new model descriptors

```

```

# the resulting graphs are identical
identical(mds_out[[1L]]$graph, mds_out[[2L]]$graph)
# note that as a side-effect, also one of the input graphs is modified in-place for efficiency
mds_in[[1L]]$graph$edges

# The new task has both Sepal and Petal features
identical(mds_out[[1L]]$task, mds_out[[2L]]$task)
mds_out[[2L]]$task

# The new ingress slot contains all ingressors
identical(mds_out[[1L]]$ingress, mds_out[[2L]]$ingress)
mds_out[[1L]]$ingress

# The pointer and pointer_shape slots are different
mds_out[[1L]]$pointer
mds_out[[2L]]$pointer

mds_out[[1L]]$pointer_shape
mds_out[[2L]]$pointer_shape

## Prediction
predict_input = list(input1 = task1, input2 = task2)
tasks_out = do.call(po_torch$predict, args = list(input = predict_input))
identical(tasks_out[[1L]], tasks_out[[2L]])

```

---

**mlr\_pipeops\_torch\_callbacks**  
*Callback Configuration*

---

## Description

Configures the callbacks of a deep learning model.

## Parameters

The parameters are defined dynamically from the callbacks, where the id of the respective callbacks is the respective set id.

## Input and Output Channels

There is one input channel "input" and one output channel "output". During *training*, the channels are of class [ModelDescriptor](#). During *prediction*, the channels are of class [Task](#).

## State

The state is the value calculated by the public method `shapes_out()`.

## Internals

During training the callbacks are cloned and added to the [ModelDescriptor](#).

## Super class

`mlr3pipelines::PipeOp -> PipeOpTorchCallbacks`

## Methods

### Public methods:

- `PipeOpTorchCallbacks$new()`
- `PipeOpTorchCallbacks$clone()`

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

```
PipeOpTorchCallbacks$new(  
  callbacks = list(),  
  id = "torch_callbacks",  
  param_vals = list()  
)
```

*Arguments:*

`callbacks` (list of [TorchCallbacks](#))

The callbacks (or something convertible via [as\\_torch\\_callbacks\(\)](#)). Must have unique ids. All callbacks are cloned during construction.

`id` (character(1))

Identifier of the resulting object.

`param_vals` (list())

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

```
PipeOpTorchCallbacks$clone(deep = FALSE)
```

*Arguments:*

`deep` Whether to make a deep clone.

## See Also

Other Model Configuration: [ModelDescriptor\(\)](#), [mlr\\_pipeops\\_torch\\_loss](#), [mlr\\_pipeops\\_torch\\_optimizer](#), [model\\_descriptor\\_union\(\)](#)

Other PipeOp: [mlr\\_pipeops\\_module](#), [mlr\\_pipeops\\_torch\\_optimizer](#)

## Examples

```
po_cb = po("torch_callbacks", "checkpoint")
po_cb$param_set
mdin = po("torch_ingress_num")$train(list(tsk("iris")))
mdin[[1L]]$callbacks
mdout = po_cb$train(mdin)[[1L]]
mdout$callbacks
# Can be called again
po_cb1 = po("torch_callbacks", t_clbk("progress"))
mdout1 = po_cb1$train(list(mdout))[[1L]]
mdout1$callbacks
```

---

### mlr\_pipeops\_torch\_ingress

*Entry point to Torch Network*

---

## Description

Use this as entry-point to mlr3torch-networks. Unless you are an advanced user, you should not need to use this directly but [PipeOpTorchIngressNumeric](#), [PipeOpTorchIngressCategorical](#) or [PipeOpTorchIngressLazyTensor](#).

## Parameters

Defined by the construction argument `param_set`.

## Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

## State

The state is set to the input shape.

## Internals

Creates an object of class [TorchIngressToken](#) for the given task. The purpose of this is to store the information on how to construct the torch dataloader from the task for this entry point of the network.

## Super class

[mlr3pipelines::PipeOp](#) -> [PipeOpTorchIngress](#)

## Active bindings

`feature_types` (character(1))

The features types that can be consumed by this PipeOpTorchIngress.

## Methods

### Public methods:

- `PipeOpTorchIngress$new()`
- `PipeOpTorchIngress$clone()`

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

```
PipeOpTorchIngress$new(
  id,
  param_set = ps(),
  param_vals = list(),
  packages = character(0),
  feature_types
)
```

*Arguments:*

`id` (character(1))

Identifier of the resulting object.

`param_set` ([ParamSet](#))

The parameter set.

`param_vals` (list())

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

`packages` (character())

The R packages this object depends on.

`feature_types` (character())

The feature types. See `mlr_reflections$task_feature_types` for available values, Additionally, "lazy\_tensor" is supported.

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

```
PipeOpTorchIngress$clone(deep = FALSE)
```

*Arguments:*

`deep` Whether to make a deep clone.

## See Also

Other PipeOps: `mlr_pipeops_nn_adaptive_avg_pool1d`, `mlr_pipeops_nn_adaptive_avg_pool2d`, `mlr_pipeops_nn_adaptive_avg_pool3d`, `mlr_pipeops_nn_avg_pool1d`, `mlr_pipeops_nn_avg_pool2d`, `mlr_pipeops_nn_avg_pool3d`, `mlr_pipeops_nn_batch_norm1d`, `mlr_pipeops_nn_batch_norm2d`, `mlr_pipeops_nn_batch_norm3d`, `mlr_pipeops_nn_block`, `mlr_pipeops_nn_celu`, `mlr_pipeops_nn_conv1d`,

```
mlr_pipeops_nn_conv2d, mlr_pipeops_nn_conv3d, mlr_pipeops_nn_conv_transpose1d, mlr_pipeops_nn_conv_transpose3d, mlr_pipeops_nn_dropout, mlr_pipeops_nn_elu, mlr_pipeops_nn_flatten, mlr_pipeops_nn_ft_cls, mlr_pipeops_nn_ft_transformer_block, mlr_pipeops_nn_gelu, mlr_pipeops_nn_gelu, mlr_pipeops_nn_glu, mlr_pipeops_nn_hardsigmoid, mlr_pipeops_nn_hardsigmoid, mlr_pipeops_nn_hardtanh, mlr_pipeops_nn_head, mlr_pipeops_nn_identity, mlr_pipeops_nn_layer_norm, mlr_pipeops_nn_leaky_relu, mlr_pipeops_nn_linear, mlr_pipeops_nn_log_sigmoid, mlr_pipeops_nn_max_pool1d, mlr_pipeops_nn_max_pool2d, mlr_pipeops_nn_max_pool3d, mlr_pipeops_nn_merge, mlr_pipeops_nn_merge_cat, mlr_pipeops_nn_merge_prod, mlr_pipeops_nn_merge_sum, mlr_pipeops_nn_prelu, mlr_pipeops_nn_reglu, mlr_pipeops_nn_relu, mlr_pipeops_nn_relu6, mlr_pipeops_nn_reshape, mlr_pipeops_nn_rrelu, mlr_pipeops_nn_selu, mlr_pipeops_nn_sigmoid, mlr_pipeops_nn_softmax, mlr_pipeops_nn_softplus, mlr_pipeops_nn_softshrink, mlr_pipeops_nn_softsign, mlr_pipeops_nn_squeeze, mlr_pipeops_nn_tanh, mlr_pipeops_nn_tanhshrink, mlr_pipeops_nn_threshold, mlr_pipeops_nn_tokenizer_categ, mlr_pipeops_nn_tokenizer_num, mlr_pipeops_nn_unsqueeze, mlr_pipeops_torch_ingress_categ, mlr_pipeops_torch_ingress_ltnsr, mlr_pipeops_torch_ingress_num, mlr_pipeops_torch_loss, mlr_pipeops_torch_model, mlr_pipeops_torch_model_classif, mlr_pipeops_torch_model_regr
```

Other Graph Network: [ModelDescriptor\(\)](#), [TorchIngressToken\(\)](#), [mlr\\_learners\\_torch\\_model](#), [mlr\\_pipeops\\_module](#), [mlr\\_pipeops\\_torch](#), [mlr\\_pipeops\\_torch\\_ingress\\_categ](#), [mlr\\_pipeops\\_torch\\_ingress\\_ltnsr](#), [mlr\\_pipeops\\_torch\\_ingress\\_num](#), [model\\_descriptor\\_to\\_learner\(\)](#), [model\\_descriptor\\_to\\_module\(\)](#), [model\\_descriptor\\_union\(\)](#), [nn\\_graph\(\)](#)

## mlr\_pipeops\_torch\_ingress\_categ

*Torch Entry Point for Categorical Features*

### Description

Ingress PipeOp that represents a categorical (factor(), ordered() and logical()) entry point to a torch network.

### Parameters

- `select :: logical(1)`  
Whether PipeOp should selected the supported feature types. Otherwise it will err on receiving tasks with unsupported feature types.

### Internals

Uses [batchgetter\\_categ\(\)](#).

### Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

### State

The state is set to the input shape.

## Super classes

`mlr3pipelines::PipeOp -> mlr3torch::PipeOpTorchIngress -> PipeOpTorchIngressCategorical`

## Methods

### Public methods:

- `PipeOpTorchIngressCategorical$new()`
- `PipeOpTorchIngressCategorical$clone()`

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

```
PipeOpTorchIngressCategorical$new(
  id = "torch_ingress_categ",
  param_vals = list()
)
```

*Arguments:*

`id` (character(1))  
 Identifier of the resulting object.  
`param_vals` (list())  
 List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

```
PipeOpTorchIngressCategorical$clone(deep = FALSE)
```

*Arguments:*

`deep` Whether to make a deep clone.

## See Also

Other PipeOps: `mlr_pipeops_nn_adaptive_avg_pool1d`, `mlr_pipeops_nn_adaptive_avg_pool2d`, `mlr_pipeops_nn_adaptive_avg_pool3d`, `mlr_pipeops_nn_avg_pool1d`, `mlr_pipeops_nn_avg_pool2d`, `mlr_pipeops_nn_avg_pool3d`, `mlr_pipeops_nn_batch_norm1d`, `mlr_pipeops_nn_batch_norm2d`, `mlr_pipeops_nn_batch_norm3d`, `mlr_pipeops_nn_block`, `mlr_pipeops_nn_celu`, `mlr_pipeops_nn_conv1d`, `mlr_pipeops_nn_conv2d`, `mlr_pipeops_nn_conv3d`, `mlr_pipeops_nn_conv_transpose1d`, `mlr_pipeops_nn_conv_transpose3d`, `mlr_pipeops_nn_dropout`, `mlr_pipeops_nn_elu`, `mlr_pipeops_nn_flatten`, `mlr_pipeops_nn_ft_cls`, `mlr_pipeops_nn_ft_transformer_block`, `mlr_pipeops_nn_gelu`, `mlr_pipeops_nn_gelu`, `mlr_pipeops_nn_glu`, `mlr_pipeops_nn_hardshrink`, `mlr_pipeops_nn_hardsigmoid`, `mlr_pipeops_nn_hardtanh`, `mlr_pipeops_nn_head`, `mlr_pipeops_nn_identity`, `mlr_pipeops_nn_layer_norm`, `mlr_pipeops_nn_leaky_relu`, `mlr_pipeops_nn_linear`, `mlr_pipeops_nn_log_sigmoid`, `mlr_pipeops_nn_max_pool1d`, `mlr_pipeops_nn_max_pool2d`, `mlr_pipeops_nn_max_pool3d`, `mlr_pipeops_nn_merge`, `mlr_pipeops_nn_merge_cat`, `mlr_pipeops_nn_merge_prod`, `mlr_pipeops_nn_merge_sum`, `mlr_pipeops_nn_prelu`, `mlr_pipeops_nn_reglu`, `mlr_pipeops_nn_relu`, `mlr_pipeops_nn_relu6`, `mlr_pipeops_nn_reshape`, `mlr_pipeops_nn_rrelu`, `mlr_pipeops_nn_selu`, `mlr_pipeops_nn_sigmoid`, `mlr_pipeops_nn_softmax`, `mlr_pipeops_nn_softplus`, `mlr_pipeops_nn_softshrink`, `mlr_pipeops_nn_softsign`, `mlr_pipeops_nn_squeeze`, `mlr_pipeops_nn_tanh`, `mlr_pipeops_nn_tanhshrink`, `mlr_pipeops_nn_threshold`, `mlr_pipeops_nn_tokenizer_categ`

```
mlr_pipeops_nn_tokenizer_num, mlr_pipeops_nn_unsqueeze, mlr_pipeops_torch_ingress,
mlr_pipeops_torch_ingress_ltnsr, mlr_pipeops_torch_ingress_num, mlr_pipeops_torch_loss,
mlr_pipeops_torch_model, mlr_pipeops_torch_model_classif, mlr_pipeops_torch_model_regr

Other Graph Network: ModelDescriptor\(\), TorchIngressToken\(\), mlr\_learners\_torch\_model,
mlr\_pipeops\_module, mlr\_pipeops\_torch, mlr\_pipeops\_torch\_ingress, mlr\_pipeops\_torch\_ingress\_ltnsr,
mlr\_pipeops\_torch\_ingress\_num, model\_descriptor\_to\_learner\(\), model\_descriptor\_to\_module\(\),
model\_descriptor\_union\(\), nn\_graph\(\)
```

## Examples

```
graph = po("select", selector = selector_type("factor")) %>>%
  po("torch_ingress_categ")
task = tsk("german_credit")
# The output is a model descriptor
md = graph$train(task)[[1L]]
ingress = md$ingress[[1L]]
ingress$batchgetter(task$data(1, ingress$features(task)), "cpu")
```

---

**mlr\_pipeops\_torch\_ingress\_ltnsr**  
*Ingress for Lazy Tensor*

---

## Description

Ingress for a single [lazy\\_tensor](#) column.

## Parameters

- **shape** :: `integer()` | `NULL` | `"infer"`  
The shape of the tensor, where the first dimension (batch) must be `NA`. When it is not specified, the lazy tensor input column needs to have a known shape. When it is set to `"infer"`, the shape is inferred from an example batch.

## Internals

The returned batchgetter materializes the lazy tensor column to a tensor.

## Input and Output Channels

One input channel called `"input"` and one output channel called `"output"`. For an explanation see [PipeOpTorch](#).

## State

The state is set to the input shape.

## Super classes

[mlr3pipelines::PipeOp](#) -> [mlr3torch::PipeOpTorchIngress](#) -> [PipeOpTorchIngressLazyTensor](#)

## Methods

### Public methods:

- [PipeOpTorchIngressLazyTensor\\$new\(\)](#)
- [PipeOpTorchIngressLazyTensor\\$clone\(\)](#)

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

```
PipeOpTorchIngressLazyTensor$new(
  id = "torch_ingress_ltnsr",
  param_vals = list()
)
```

*Arguments:*

`id` (character(1))  
Identifier of the resulting object.  
`param_vals` (list())  
List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

```
PipeOpTorchIngressLazyTensor$clone(deep = FALSE)
```

*Arguments:*

`deep` Whether to make a deep clone.

## See Also

Other PipeOps: [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm1d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm2d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm3d](#), [mlr\\_pipeops\\_nn\\_block](#), [mlr\\_pipeops\\_nn\\_celu](#), [mlr\\_pipeops\\_nn\\_conv1d](#), [mlr\\_pipeops\\_nn\\_conv2d](#), [mlr\\_pipeops\\_nn\\_conv3d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose1d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose3d](#), [mlr\\_pipeops\\_nn\\_dropout](#), [mlr\\_pipeops\\_nn\\_elu](#), [mlr\\_pipeops\\_nn\\_flatten](#), [mlr\\_pipeops\\_nn\\_ft\\_cls](#), [mlr\\_pipeops\\_nn\\_ft\\_transformer\\_block](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_glu](#), [mlr\\_pipeops\\_nn\\_hardshrink](#), [mlr\\_pipeops\\_nn\\_hardsigmoid](#), [mlr\\_pipeops\\_nn\\_hardtanh](#), [mlr\\_pipeops\\_nn\\_head](#), [mlr\\_pipeops\\_nn\\_identity](#), [mlr\\_pipeops\\_nn\\_layer\\_norm](#), [mlr\\_pipeops\\_nn\\_leaky\\_relu](#), [mlr\\_pipeops\\_nn\\_linear](#), [mlr\\_pipeops\\_nn\\_log\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_max\\_pool1d](#), [mlr\\_pipeops\\_nn\\_max\\_pool2d](#), [mlr\\_pipeops\\_nn\\_max\\_pool3d](#), [mlr\\_pipeops\\_nn\\_merge](#), [mlr\\_pipeops\\_nn\\_merge\\_cat](#), [mlr\\_pipeops\\_nn\\_merge\\_prod](#), [mlr\\_pipeops\\_nn\\_merge\\_sum](#), [mlr\\_pipeops\\_nn\\_prelu](#), [mlr\\_pipeops\\_nn\\_reglu](#), [mlr\\_pipeops\\_nn\\_relu](#), [mlr\\_pipeops\\_nn\\_relu6](#), [mlr\\_pipeops\\_nn\\_reshape](#), [mlr\\_pipeops\\_nn\\_rrelu](#), [mlr\\_pipeops\\_nn\\_selu](#), [mlr\\_pipeops\\_nn\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_softmax](#), [mlr\\_pipeops\\_nn\\_softplus](#), [mlr\\_pipeops\\_nn\\_softshrink](#), [mlr\\_pipeops\\_nn\\_softsign](#), [mlr\\_pipeops\\_nn\\_squeeze](#), [mlr\\_pipeops\\_nn\\_tanh](#), [mlr\\_pipeops\\_nn\\_tanhshrink](#), [mlr\\_pipeops\\_nn\\_threshold](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_categ](#)

```

mlr_pipeops_nn_tokenizer_num, mlr_pipeops_nn_unsqueeze, mlr_pipeops_torch_ingress,
mlr_pipeops_torch_ingress_categ, mlr_pipeops_torch_ingress_num, mlr_pipeops_torch_loss,
mlr_pipeops_torch_model, mlr_pipeops_torch_model_classif, mlr_pipeops_torch_model_regr

Other Graph Network: ModelDescriptor(), TorchIngressToken(), mlr_learners_torch_model,
mlr_pipeops_module, mlr_pipeops_torch, mlr_pipeops_torch_ingress, mlr_pipeops_torch_ingress_categ,
mlr_pipeops_torch_ingress_num, model_descriptor_to_learner(), model_descriptor_to_module(),
model_descriptor_union(), nn_graph()

```

## Examples

```

po_ingress = po("torch_ingress_ltnsr")
task = tsk("lazy_iris")

md = po_ingress$train(list(task))[[1L]]

ingress = md$ingress
x_batch = ingress[[1L]]$batchgetter(data = task$data(1, "x"), cache = NULL)
x_batch

# Now we try a lazy tensor with unknown shape, i.e. the shapes between the rows can differ

ds = dataset(
  initialize = function() self$x = list(torch_randn(3, 10, 10), torch_randn(3, 8, 8)),
  .getitem = function(i) list(x = self$x[[i]]),
  .length = function() 2)()

task_unknown = as_task_regr(data.table(
  x = as_lazy_tensor(ds, dataset_shapes = list(x = NULL)),
  y = rnorm(2)
), target = "y", id = "example2")

# this task (as it is) can NOT be processed by PipeOpTorchIngressLazyTensor
# It therefore needs to be preprocessed
po_resize = po("trafo_resize", size = c(6, 6))
task_unknown_resize = po_resize$train(list(task_unknown))[[1L]]

# printing the transformed column still shows unknown shapes,
# because the preprocessing pipeop cannot infer them,
# however we know that the shape is now (3, 10, 10) for all rows
task_unknown_resize$data(1:2, "x")
po_ingress$param_set$set_values(shape = c(NA, 3, 6, 6))

md2 = po_ingress$train(list(task_unknown_resize))[[1L]]

ingress2 = md2$ingress
x_batch2 = ingress2[[1L]]$batchgetter(
  data = task_unknown_resize$data(1:2, "x"),
  cache = NULL
)

x_batch2

```

---

**mlr\_pipeops\_torch\_ingress\_num**  
*Torch Entry Point for Numeric Features*

---

## Description

Ingress PipeOp that represents a numeric (integer() and numeric()) entry point to a torch network.

## Internals

Uses [batchgetter\\_num\(\)](#).

## Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

## State

The state is set to the input shape.

## Super classes

[mlr3pipelines::PipeOp](#) -> [mlr3torch::PipeOpTorchIngress](#) -> [PipeOpTorchIngressNumeric](#)

## Methods

### Public methods:

- [PipeOpTorchIngressNumeric\\$new\(\)](#)
- [PipeOpTorchIngressNumeric\\$clone\(\)](#)

**Method** [new\(\)](#): Creates a new instance of this [R6](#) class.

*Usage:*

`PipeOpTorchIngressNumeric$new(id = "torch_ingress_num", param_vals = list())`

*Arguments:*

`id` (character(1))

Identifier of the resulting object.

`param_vals` (list())

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

**Method** [clone\(\)](#): The objects of this class are cloneable with this method.

*Usage:*

`PipeOpTorchIngressNumeric$clone(deep = FALSE)`

*Arguments:*

`deep` Whether to make a deep clone.

## See Also

Other Graph Network: [ModelDescriptor\(\)](#), [TorchIngressToken\(\)](#), [mlr\\_learners\\_torch\\_model](#), [mlr\\_pipeops\\_module](#), [mlr\\_pipeops\\_torch](#), [mlr\\_pipeops\\_torch\\_ingress](#), [mlr\\_pipeops\\_torch\\_ingress\\_categ](#), [mlr\\_pipeops\\_torch\\_ingress\\_ltcsr](#), [model\\_descriptor\\_to\\_learner\(\)](#), [model\\_descriptor\\_to\\_module\(\)](#), [model\\_descriptor\\_union\(\)](#), [nn\\_graph\(\)](#)

Other PipeOps: [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm1d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm2d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm3d](#), [mlr\\_pipeops\\_nn\\_block](#), [mlr\\_pipeops\\_nn\\_celu](#), [mlr\\_pipeops\\_nn\\_conv1d](#), [mlr\\_pipeops\\_nn\\_conv2d](#), [mlr\\_pipeops\\_nn\\_conv3d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose1d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose3d](#), [mlr\\_pipeops\\_nn\\_dropout](#), [mlr\\_pipeops\\_nn\\_elu](#), [mlr\\_pipeops\\_nn\\_flatten](#), [mlr\\_pipeops\\_nn\\_ft\\_cls](#), [mlr\\_pipeops\\_nn\\_ft\\_transformer\\_block](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_glu](#), [mlr\\_pipeops\\_nn\\_hardshrink](#), [mlr\\_pipeops\\_nn\\_hardsigmoid](#), [mlr\\_pipeops\\_nn\\_hardtanh](#), [mlr\\_pipeops\\_nn\\_head](#), [mlr\\_pipeops\\_nn\\_identity](#), [mlr\\_pipeops\\_nn\\_layer\\_norm](#), [mlr\\_pipeops\\_nn\\_leaky\\_relu](#), [mlr\\_pipeops\\_nn\\_linear](#), [mlr\\_pipeops\\_nn\\_log\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_max\\_pool1d](#), [mlr\\_pipeops\\_nn\\_max\\_pool2d](#), [mlr\\_pipeops\\_nn\\_max\\_pool3d](#), [mlr\\_pipeops\\_nn\\_merge](#), [mlr\\_pipeops\\_nn\\_merge\\_cat](#), [mlr\\_pipeops\\_nn\\_merge\\_prod](#), [mlr\\_pipeops\\_nn\\_merge\\_sum](#), [mlr\\_pipeops\\_nn\\_prelu](#), [mlr\\_pipeops\\_nn\\_reglu](#), [mlr\\_pipeops\\_nn\\_relu](#), [mlr\\_pipeops\\_nn\\_relu6](#), [mlr\\_pipeops\\_nn\\_reshape](#), [mlr\\_pipeops\\_nn\\_rrelu](#), [mlr\\_pipeops\\_nn\\_selu](#), [mlr\\_pipeops\\_nn\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_softmax](#), [mlr\\_pipeops\\_nn\\_softplus](#), [mlr\\_pipeops\\_nn\\_softshrink](#), [mlr\\_pipeops\\_nn\\_softsign](#), [mlr\\_pipeops\\_nn\\_squeeze](#), [mlr\\_pipeops\\_nn\\_tanh](#), [mlr\\_pipeops\\_nn\\_tanhshrink](#), [mlr\\_pipeops\\_nn\\_threshold](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_categ](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_num](#), [mlr\\_pipeops\\_nn\\_unsqueeze](#), [mlr\\_pipeops\\_torch\\_ingress](#), [mlr\\_pipeops\\_torch\\_ingress\\_categ](#), [mlr\\_pipeops\\_torch\\_ingress\\_ltcsr](#), [mlr\\_pipeops\\_torch\\_loss](#), [mlr\\_pipeops\\_torch\\_model](#), [mlr\\_pipeops\\_torch\\_model\\_classif](#), [mlr\\_pipeops\\_torch\\_model\\_regr](#)

## Examples

```
graph = po("select", selector = selector_type(c("numeric", "integer"))) %>>%
  po("torch_ingress_num")
task = tsk("german_credit")
# The output is a model descriptor
md = graph$train(task)[[1L]]
ingress = md$ingress[[1L]]
ingress$batchgetter(task$data(1:5, ingress$features(task)), "cpu")
```

---

### mlr\_pipeops\_torch\_loss

#### *Loss Configuration*

---

## Description

Configures the loss of a deep learning model.

## Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

## State

The state is the value calculated by the public method `shapes_out()`.

## Parameters

The parameters are defined dynamically from the loss set during construction.

## Internals

During training the loss is cloned and added to the [ModelDescriptor](#).

## Super class

`mlr3pipelines::PipeOp -> PipeOpTorchLoss`

## Methods

### Public methods:

- `PipeOpTorchLoss$new()`
- `PipeOpTorchLoss$clone()`

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

`PipeOpTorchLoss$new(loss, id = "torch_loss", param_vals = list())`

*Arguments:*

`loss` ([TorchLoss](#) or `character(1)` or `nn_loss`)

The loss (or something convertible via `as_torch_loss()`).

`id` (`character(1)`)

Identifier of the resulting object.

`param_vals` (`list()`)

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

`PipeOpTorchLoss$clone(deep = FALSE)`

*Arguments:*

`deep` Whether to make a deep clone.

## See Also

Other PipeOps: `mlr_pipeops_nn_adaptive_avg_pool1d`, `mlr_pipeops_nn_adaptive_avg_pool2d`,  
`mlr_pipeops_nn_adaptive_avg_pool3d`, `mlr_pipeops_nn_avg_pool1d`, `mlr_pipeops_nn_avg_pool2d`,  
`mlr_pipeops_nn_avg_pool3d`, `mlr_pipeops_nn_batch_norm1d`, `mlr_pipeops_nn_batch_norm2d`,  
`mlr_pipeops_nn_batch_norm3d`, `mlr_pipeops_nn_block`, `mlr_pipeops_nn_celu`, `mlr_pipeops_nn_conv1d`,  
`mlr_pipeops_nn_conv2d`, `mlr_pipeops_nn_conv3d`, `mlr_pipeops_nn_conv_transpose1d`, `mlr_pipeops_nn_conv_transpose2d`

```
mlr_pipeops_nn_conv_transpose3d, mlr_pipeops_nn_dropout, mlr_pipeops_nn_elu, mlr_pipeops_nn_flatten,
mlr_pipeops_nn_ft_cls, mlr_pipeops_nn_ft_transformer_block, mlr_pipeops_nn_geglu,
mlr_pipeops_nn_gelu, mlr_pipeops_nn_glu, mlr_pipeops_nn_hardshrink, mlr_pipeops_nn_hardsigmoid,
mlr_pipeops_nn_hardtanh, mlr_pipeops_nn_head, mlr_pipeops_nn_identity, mlr_pipeops_nn_layer_norm,
mlr_pipeops_nn_leaky_relu, mlr_pipeops_nn_linear, mlr_pipeops_nn_log_sigmoid, mlr_pipeops_nn_max_pool1d,
mlr_pipeops_nn_max_pool2d, mlr_pipeops_nn_max_pool3d, mlr_pipeops_nn_merge, mlr_pipeops_nn_merge_cat,
mlr_pipeops_nn_merge_prod, mlr_pipeops_nn_merge_sum, mlr_pipeops_nn_prelu, mlr_pipeops_nn_reglu,
mlr_pipeops_nn_relu, mlr_pipeops_nn_relu6, mlr_pipeops_nn_reshape, mlr_pipeops_nn_rrelu,
mlr_pipeops_nn_selu, mlr_pipeops_nn_sigmoid, mlr_pipeops_nn_softmax, mlr_pipeops_nn_softplus,
mlr_pipeops_nn_softshrink, mlr_pipeops_nn_softsign, mlr_pipeops_nn_squeeze, mlr_pipeops_nn_tanh,
mlr_pipeops_nn_tanhshrink, mlr_pipeops_nn_threshold, mlr_pipeops_nn_tokenizer_categ,
mlr_pipeops_nn_tokenizer_num, mlr_pipeops_nn_unsqueeze, mlr_pipeops_torch_ingress,
mlr_pipeops_torch_ingress_categ, mlr_pipeops_torch_ingress_ltnsr, mlr_pipeops_torch_ingress_num,
mlr_pipeops_torch_model, mlr_pipeops_torch_model_classif, mlr_pipeops_torch_model_regr
```

Other Model Configuration: [ModelDescriptor\(\)](#), [mlr\\_pipeops\\_torch\\_callbacks](#), [mlr\\_pipeops\\_torch\\_optimizer](#), [model\\_descriptor\\_union\(\)](#)

## Examples

```
po_loss = po("torch_loss", loss = t_loss("cross_entropy"))
po_loss$param_set
mdin = po("torch_ingress_num")$train(list(tsk("iris")))
mdin[[1L]]$loss
mdout = po_loss$train(mdin)[[1L]]
mdout$loss
```

---

## mlr\_pipeops\_torch\_model

### *PipeOp Torch Model*

---

## Description

Builds a Torch Learner from a [ModelDescriptor](#) and trains it with the given parameter specification. The task type must be specified during construction.

## Parameters

### General:

The parameters of the optimizer, loss and callbacks, prefixed with "opt.", "loss." and "cb.<callback id>." respectively, as well as:

- epochs :: `integer(1)`  
The number of epochs.
- device :: `character(1)`  
The device. One of "auto", "cpu", or "cuda" or other values defined in `mlr_reflections$torch$devices`.  
The value is initialized to "auto", which will select "cuda" if possible, then try "mps" and otherwise fall back to "cpu".

- `num_threads` :: `integer(1)`  
The number of threads for intraop parallelization (if device is "cpu"). This value is initialized to 1.
- `num_interop_threads` :: `integer(1)`  
The number of threads for intraop and interop parallelization (if device is "cpu"). This value is initialized to 1. Note that this can only be set once during a session and changing the value within an R session will raise a warning.
- `seed` :: `integer(1)` or "random" or `NULL`  
The torch seed that is used during training and prediction. This value is initialized to "random", which means that a random seed will be sampled at the beginning of the training phase. This seed (either set or randomly sampled) is available via `$model$seed` after training and used during prediction. Note that by setting the seed during the training phase this will mean that by default (i.e. when seed is "random"), clones of the learner will use a different seed. If set to `NULL`, no seeding will be done.
- `tensor_dataset` :: `logical(1)` | "device"  
Whether to load all batches at once at the beginning of training and stack them. This is initialized to `FALSE`. If set to "device", the device of the tensors will be set to the value of `device`, which can avoid unnecessary moving of tensors between devices. When your dataset fits into memory this will make the loading of batches faster. Note that this should not be set for datasets that contain `lazy_tensors` with random data augmentation, as this augmentation will only be applied once at the beginning of training.

#### Evaluation:

- `measures_train` :: `Measure` or `list()` of `Measures`  
Measures to be evaluated during training.
- `measures_valid` :: `Measure` or `list()` of `Measures`  
Measures to be evaluated during validation.
- `eval_freq` :: `integer(1)`  
How often the train / validation predictions are evaluated using `measures_train`/`measures_valid`. This is initialized to 1. Note that the final model is always evaluated.

#### Early Stopping:

- `patience` :: `integer(1)`  
This activates early stopping using the validation scores. If the performance of a model does not improve for `patience` evaluation steps, training is ended. Note that the final model is stored in the learner, not the best model. This is initialized to 0, which means no early stopping. The first entry from `measures_valid` is used as the metric. This also requires to specify the `$validate` field of the Learner, as well as `measures_valid`. If this is set, the epoch after which no improvement was observed, can be accessed via the `$internal_tuned_values` field of the learner.
- `min_delta` :: `double(1)`  
The minimum improvement threshold for early stopping. Is initialized to 0.

#### Dataloader:

- `batch_size` :: `integer(1)`  
The batch size (required).

- `shuffle` :: `logical(1)`  
Whether to shuffle the instances in the dataset. This is initialized to `TRUE`, which differs from the default (`FALSE`).
- `sampler` :: `torch::sampler`  
Object that defines how the dataloader draw samples.
- `batch_sampler` :: `torch::sampler`  
Object that defines how the dataloader draws batches.
- `num_workers` :: `integer(1)`  
The number of workers for data loading (batches are loaded in parallel). The default is `0`, which means that data will be loaded in the main process.
- `collate_fn` :: `function`  
How to merge a list of samples to form a batch.
- `pin_memory` :: `logical(1)`  
Whether the dataloader copies tensors into CUDA pinned memory before returning them.
- `drop_last` :: `logical(1)`  
Whether to drop the last training batch in each epoch during training. Default is `FALSE`.
- `timeout` :: `numeric(1)`  
The timeout value for collecting a batch from workers. Negative values mean no timeout and the default is `-1`.
- `worker_init_fn` :: `function(id)`  
A function that receives the worker id (in `[1, num_workers]`) and is executed after seeding on the worker but before data loading.
- `worker_globals` :: `list() | character()`  
When loading data in parallel, this allows to export globals to the workers. If this is a character vector, the objects in the global environment with those names are copied to the workers.
- `worker_packages` :: `character()`  
Which packages to load on the workers.

Also see `torch::dataloader` for more information.

## Input and Output Channels

There is one input channel "input" that takes in `ModelDescriptor` during training and a `Task` of the specified `task_type` during prediction. The output is `NULL` during training and a `Prediction` of given `task_type` during prediction.

## State

A trained `LearnerTorchModel`.

## Internals

A `LearnerTorchModel` is created by calling `model_descriptor_to_learner()` on the provided `ModelDescriptor` that is received through the input channel. Then the parameters are set according to the parameters specified in `PipeOpTorchModel` and its `'$train()` method is called on the `[Task][mlr3::Task]` stored

## Super classes

`mlr3pipelines::PipeOp -> mlr3pipelines::PipeOpLearner -> PipeOpTorchModel`

## Methods

### Public methods:

- `PipeOpTorchModel$new()`
- `PipeOpTorchModel$clone()`

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

`PipeOpTorchModel$new(task_type, id = "torch_model", param_vals = list())`

*Arguments:*

`task_type` (character(1))  
 The task type of the model.  
`id` (character(1))  
 Identifier of the resulting object.  
`param_vals` (list())  
 List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

`PipeOpTorchModel$clone(deep = FALSE)`

*Arguments:*

`deep` Whether to make a deep clone.

## See Also

Other PipeOps: `mlr_pipeops_nn_adaptive_avg_pool1d`, `mlr_pipeops_nn_adaptive_avg_pool2d`, `mlr_pipeops_nn_adaptive_avg_pool3d`, `mlr_pipeops_nn_avg_pool1d`, `mlr_pipeops_nn_avg_pool2d`, `mlr_pipeops_nn_avg_pool3d`, `mlr_pipeops_nn_batch_norm1d`, `mlr_pipeops_nn_batch_norm2d`, `mlr_pipeops_nn_batch_norm3d`, `mlr_pipeops_nn_block`, `mlr_pipeops_nn_celu`, `mlr_pipeops_nn_conv1d`, `mlr_pipeops_nn_conv2d`, `mlr_pipeops_nn_conv3d`, `mlr_pipeops_nn_conv_transpose1d`, `mlr_pipeops_nn_conv_transpose3d`, `mlr_pipeops_nn_dropout`, `mlr_pipeops_nn_elu`, `mlr_pipeops_nn_flatten`, `mlr_pipeops_nn_ft_cls`, `mlr_pipeops_nn_ft_transformer_block`, `mlr_pipeops_nn_gelu`, `mlr_pipeops_nn_gelu`, `mlr_pipeops_nn_glu`, `mlr_pipeops_nn_hardshrink`, `mlr_pipeops_nn_hardsigmoid`, `mlr_pipeops_nn_hardtanh`, `mlr_pipeops_nn_head`, `mlr_pipeops_nn_identity`, `mlr_pipeops_nn_layer_norm`, `mlr_pipeops_nn_leaky_relu`, `mlr_pipeops_nn_linear`, `mlr_pipeops_nn_log_sigmoid`, `mlr_pipeops_nn_max_pool1d`, `mlr_pipeops_nn_max_pool2d`, `mlr_pipeops_nn_max_pool3d`, `mlr_pipeops_nn_merge`, `mlr_pipeops_nn_merge_cat`, `mlr_pipeops_nn_merge_prod`, `mlr_pipeops_nn_merge_sum`, `mlr_pipeops_nn_prelu`, `mlr_pipeops_nn_reglu`, `mlr_pipeops_nn_relu`, `mlr_pipeops_nn_relu6`, `mlr_pipeops_nn_reshape`, `mlr_pipeops_nn_rrelu`, `mlr_pipeops_nn_selu`, `mlr_pipeops_nn_sigmoid`, `mlr_pipeops_nn_softmax`, `mlr_pipeops_nn_softplus`, `mlr_pipeops_nn_softshrink`, `mlr_pipeops_nn_softsign`, `mlr_pipeops_nn_squeeze`, `mlr_pipeops_nn_tanh`, `mlr_pipeops_nn_tanhshrink`, `mlr_pipeops_nn_threshold`, `mlr_pipeops_nn_tokenizer_categ`, `mlr_pipeops_nn_tokenizer_num`, `mlr_pipeops_nn_unsqueeze`, `mlr_pipeops_torch_ingress`,

---

`mlr_pipeops_torch_ingress_categ`, `mlr_pipeops_torch_ingress_ltnsr`, `mlr_pipeops_torch_ingress_num`,  
`mlr_pipeops_torch_loss`, `mlr_pipeops_torch_model_classif`, `mlr_pipeops_torch_model_regr`

---

**mlr\_pipeops\_torch\_model\_classif**  
*PipeOp Torch Classifier*

---

## Description

Builds a torch classifier and trains it.

## Parameters

See [LearnerTorch](#)

## Input and Output Channels

There is one input channel "input" that takes in `ModelDescriptor` during training and a `Task` of the specified `task_type` during prediction. The output is `NULL` during training and a `Prediction` of given `task_type` during prediction.

## State

A trained [LearnerTorchModel](#).

## Internals

A `LearnerTorchModel` is created by calling `model_descriptor_to_learner()` on the provided `ModelDescriptor` that is received through the input channel. Then the parameters are set according to the parameters specified in `PipeOpTorchModel` and its `'$train()` method is called on the `[Task][mlr3::Task]` stored

## Super classes

`mlr3pipelines::PipeOp` -> `mlr3pipelines::PipeOpLearner` -> `mlr3torch::PipeOpTorchModel`  
 -> `PipeOpTorchModelClassif`

## Methods

### Public methods:

- `PipeOpTorchModelClassif$new()`
- `PipeOpTorchModelClassif$clone()`

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

`PipeOpTorchModelClassif$new(id = "torch_model_classif", param_vals = list())`

*Arguments:*

```

  id (character(1))
    Identifier of the resulting object.
  param_vals (list())
    List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

```

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

```
PipeOpTorchModelClassif$clone(deep = FALSE)
```

*Arguments:*

`deep` Whether to make a deep clone.

## See Also

Other PipeOps: [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm1d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm2d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm3d](#), [mlr\\_pipeops\\_nn\\_block](#), [mlr\\_pipeops\\_nn\\_celu](#), [mlr\\_pipeops\\_nn\\_conv1d](#), [mlr\\_pipeops\\_nn\\_conv2d](#), [mlr\\_pipeops\\_nn\\_conv3d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose1d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose3d](#), [mlr\\_pipeops\\_nn\\_dropout](#), [mlr\\_pipeops\\_nn\\_elu](#), [mlr\\_pipeops\\_nn\\_flatten](#), [mlr\\_pipeops\\_nn\\_ft\\_cls](#), [mlr\\_pipeops\\_nn\\_ft\\_transformer\\_block](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_glu](#), [mlr\\_pipeops\\_nn\\_hardshrink](#), [mlr\\_pipeops\\_nn\\_hardsigmoid](#), [mlr\\_pipeops\\_nn\\_hardtanh](#), [mlr\\_pipeops\\_nn\\_head](#), [mlr\\_pipeops\\_nn\\_identity](#), [mlr\\_pipeops\\_nn\\_layer\\_norm](#), [mlr\\_pipeops\\_nn\\_leaky\\_relu](#), [mlr\\_pipeops\\_nn\\_linear](#), [mlr\\_pipeops\\_nn\\_log\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_max\\_pool1d](#), [mlr\\_pipeops\\_nn\\_max\\_pool2d](#), [mlr\\_pipeops\\_nn\\_max\\_pool3d](#), [mlr\\_pipeops\\_nn\\_merge](#), [mlr\\_pipeops\\_nn\\_merge\\_cat](#), [mlr\\_pipeops\\_nn\\_merge\\_prod](#), [mlr\\_pipeops\\_nn\\_merge\\_sum](#), [mlr\\_pipeops\\_nn\\_prelu](#), [mlr\\_pipeops\\_nn\\_reglu](#), [mlr\\_pipeops\\_nn\\_relu](#), [mlr\\_pipeops\\_nn\\_relu6](#), [mlr\\_pipeops\\_nn\\_reshape](#), [mlr\\_pipeops\\_nn\\_rrelu](#), [mlr\\_pipeops\\_nn\\_selu](#), [mlr\\_pipeops\\_nn\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_softmax](#), [mlr\\_pipeops\\_nn\\_softplus](#), [mlr\\_pipeops\\_nn\\_softshrink](#), [mlr\\_pipeops\\_nn\\_softsign](#), [mlr\\_pipeops\\_nn\\_squeeze](#), [mlr\\_pipeops\\_nn\\_tanh](#), [mlr\\_pipeops\\_nn\\_tanhshrink](#), [mlr\\_pipeops\\_nn\\_threshold](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_categ](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_num](#), [mlr\\_pipeops\\_nn\\_unsqueeze](#), [mlr\\_pipeops\\_torch\\_ingress](#), [mlr\\_pipeops\\_torch\\_ingress\\_categ](#), [mlr\\_pipeops\\_torch\\_ingress\\_ltnsr](#), [mlr\\_pipeops\\_torch\\_ingress\\_num](#), [mlr\\_pipeops\\_torch\\_loss](#), [mlr\\_pipeops\\_torch\\_model](#), [mlr\\_pipeops\\_torch\\_model\\_regr](#)

## Examples

```

# simple logistic regression

# configure the model descriptor
md = as_graph(po("torch_ingress_num")) %>>%
  po("nn_head") %>>%
  po("torch_loss", "cross_entropy") %>>%
  po("torch_optimizer", "adam"))$train(tsk("iris"))[[1L]]

print(md)

# build the learner from the model descriptor and train it
po_model = po("torch_model_classif", batch_size = 50, epochs = 1)
po_model$train(list(md))

```

```
po_model$state
```

---

**mlr\_pipeops\_torch\_model\_regr**  
*Torch Regression Model*

---

## Description

Builds a torch regression model and trains it.

## Parameters

See [LearnerTorch](#)

## Input and Output Channels

There is one input channel "input" that takes in `ModelDescriptor` during training and a `Task` of the specified `task_type` during prediction. The output is `NULL` during training and a `Prediction` of given `task_type` during prediction.

## State

A trained [LearnerTorchModel](#).

## Internals

A `LearnerTorchModel` is created by calling `model_descriptor_to_learner()` on the provided `ModelDescriptor` that is received through the input channel. Then the parameters are set according to the parameters specified in `PipeOpTorchModel` and its `'$train()` method is called on the `[Task][mlr3::Task]` stored

## Super classes

```
mlr3pipelines::PipeOp -> mlr3pipelines::PipeOpLearner -> mlr3torch::PipeOpTorchModel
-> PipeOpTorchModelRegr
```

## Methods

### Public methods:

- `PipeOpTorchModelRegr$new()`
- `PipeOpTorchModelRegr$clone()`

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

```
PipeOpTorchModelRegr$new(id = "torch_model_regr", param_vals = list())
```

*Arguments:*

```

  id (character(1))
    Identifier of the resulting object.
  param_vals (list())
    List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

```

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

```
PipeOpTorchModelRegr$clone(deep = FALSE)
```

*Arguments:*

`deep` Whether to make a deep clone.

## See Also

Other PipeOps: [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_adaptive\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool1d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool2d](#), [mlr\\_pipeops\\_nn\\_avg\\_pool3d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm1d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm2d](#), [mlr\\_pipeops\\_nn\\_batch\\_norm3d](#), [mlr\\_pipeops\\_nn\\_block](#), [mlr\\_pipeops\\_nn\\_celu](#), [mlr\\_pipeops\\_nn\\_conv1d](#), [mlr\\_pipeops\\_nn\\_conv2d](#), [mlr\\_pipeops\\_nn\\_conv3d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose1d](#), [mlr\\_pipeops\\_nn\\_conv\\_transpose3d](#), [mlr\\_pipeops\\_nn\\_dropout](#), [mlr\\_pipeops\\_nn\\_elu](#), [mlr\\_pipeops\\_nn\\_flatten](#), [mlr\\_pipeops\\_nn\\_ft\\_cls](#), [mlr\\_pipeops\\_nn\\_ft\\_transformer\\_block](#), [mlr\\_pipeops\\_nn\\_gelu](#), [mlr\\_pipeops\\_nn\\_glu](#), [mlr\\_pipeops\\_nn\\_hardshrink](#), [mlr\\_pipeops\\_nn\\_hardsigmoid](#), [mlr\\_pipeops\\_nn\\_hardtanh](#), [mlr\\_pipeops\\_nn\\_head](#), [mlr\\_pipeops\\_nn\\_identity](#), [mlr\\_pipeops\\_nn\\_layer\\_norm](#), [mlr\\_pipeops\\_nn\\_leaky\\_relu](#), [mlr\\_pipeops\\_nn\\_linear](#), [mlr\\_pipeops\\_nn\\_log\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_max\\_pool1d](#), [mlr\\_pipeops\\_nn\\_max\\_pool2d](#), [mlr\\_pipeops\\_nn\\_max\\_pool3d](#), [mlr\\_pipeops\\_nn\\_merge](#), [mlr\\_pipeops\\_nn\\_merge\\_cat](#), [mlr\\_pipeops\\_nn\\_merge\\_prod](#), [mlr\\_pipeops\\_nn\\_merge\\_sum](#), [mlr\\_pipeops\\_nn\\_prelu](#), [mlr\\_pipeops\\_nn\\_reglu](#), [mlr\\_pipeops\\_nn\\_relu](#), [mlr\\_pipeops\\_nn\\_relu6](#), [mlr\\_pipeops\\_nn\\_reshape](#), [mlr\\_pipeops\\_nn\\_rrelu](#), [mlr\\_pipeops\\_nn\\_selu](#), [mlr\\_pipeops\\_nn\\_sigmoid](#), [mlr\\_pipeops\\_nn\\_softmax](#), [mlr\\_pipeops\\_nn\\_softplus](#), [mlr\\_pipeops\\_nn\\_softshrink](#), [mlr\\_pipeops\\_nn\\_softsign](#), [mlr\\_pipeops\\_nn\\_squeeze](#), [mlr\\_pipeops\\_nn\\_tanh](#), [mlr\\_pipeops\\_nn\\_tanhshrink](#), [mlr\\_pipeops\\_nn\\_threshold](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_categ](#), [mlr\\_pipeops\\_nn\\_tokenizer\\_num](#), [mlr\\_pipeops\\_nn\\_unsqueeze](#), [mlr\\_pipeops\\_torch\\_ingress](#), [mlr\\_pipeops\\_torch\\_ingress\\_categ](#), [mlr\\_pipeops\\_torch\\_ingress\\_ltnsr](#), [mlr\\_pipeops\\_torch\\_ingress\\_num](#), [mlr\\_pipeops\\_torch\\_loss](#), [mlr\\_pipeops\\_torch\\_model](#), [mlr\\_pipeops\\_torch\\_model\\_classif](#)

## Examples

```

# simple linear regression

# build the model descriptor
md = as_graph(po("torch_ingress_num") %>>%
  po("nn_head") %>>%
  po("torch_loss", "mse") %>>%
  po("torch_optimizer", "adam"))$train(tsk("mtcars"))[[1L]]

print(md)

# build the learner from the model descriptor and train it
po_model = po("torch_model_regr", batch_size = 20, epochs = 1)
po_model$train(list(md))

```

```
po_model$state
```

---

**mlr\_pipeops\_torch\_optimizer**  
*Optimizer Configuration*

---

## Description

Configures the optimizer of a deep learning model.

## Parameters

The parameters are defined dynamically from the optimizer that is set during construction.

## Input and Output Channels

There is one input channel "input" and one output channel "output". During *training*, the channels are of class [ModelDescriptor](#). During *prediction*, the channels are of class [Task](#).

## State

The state is the value calculated by the public method `shapes_out()`.

## Internals

During training, the optimizer is cloned and added to the [ModelDescriptor](#). Note that the parameter set of the stored [TorchOptimizer](#) is reference-identical to the parameter set of the pipeop itself.

## Super class

```
mlr3pipelines::PipeOp -> PipeOpTorchOptimizer
```

## Methods

### Public methods:

- [PipeOpTorchOptimizer\\$new\(\)](#)
- [PipeOpTorchOptimizer\\$clone\(\)](#)

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

```
PipeOpTorchOptimizer$new(
  optimizer = t_opt("adam"),
  id = "torch_optimizer",
  param_vals = list()
)
```

*Arguments:*

optimizer ([TorchOptimizer](#) or `character(1)` or `torch_optimizer_generator`)  
 The optimizer (or something convertible via `as_torch_optimizer()`).

id (`character(1)`)  
 Identifier of the resulting object.

param\_vals (`list()`)  
 List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

```
PipeOpTorchOptimizer$clone(deep = FALSE)
```

*Arguments:*

deep Whether to make a deep clone.

**See Also**

Other PipeOp: [mlr\\_pipeops\\_module](#), [mlr\\_pipeops\\_torch\\_callbacks](#)

Other Model Configuration: [ModelDescriptor\(\)](#), [mlr\\_pipeops\\_torch\\_callbacks](#), [mlr\\_pipeops\\_torch\\_loss](#), [model\\_descriptor\\_union\(\)](#)

**Examples**

```
po_opt = po("torch_optimizer", "sgd", lr = 0.01)
po_opt$param_set
mdin = po("torch_ingress_num")$train(list(tsk("iris")))
mdin[[1L]]$optimizer
mdout = po_opt$train(mdin)
mdout[[1L]]$optimizer
```

**mlr\_pipeops\_trafo\_adjust\_brightness**  
*Adjust Brightness Transformation*

**Description**

Calls `torchvision::transform_adjust_brightness`, see there for more information on the parameters. The preprocessing is applied to each element of a batch individually.

**Format**

`R6Class` inheriting from [PipeOpTaskPreprocTorch](#).

**Construction**

```
po("trafo_adjust_brightness")
```

**Parameters**

| Id                | Type      | Default        | Levels               | Range         |
|-------------------|-----------|----------------|----------------------|---------------|
| brightness_factor | numeric   | -              |                      | $[0, \infty)$ |
| stages            | character | -              | train, predict, both | -             |
| affect_columns    | untyped   | selector_all() |                      | -             |

---

**mlr\_pipeops\_trafo\_adjust\_gamma**  
*Adjust Gamma Transformation*

---

**Description**

Calls [torchvision::transform\\_adjust\\_gamma](#), see there for more information on the parameters. The preprocessing is applied to each element of a batch individually.

**Format**

[R6Class](#) inheriting from [PipeOpTaskPreprocTorch](#).

**Construction**

```
po("trafo_adjust_gamma")
```

**Parameters**

| Id             | Type      | Default        | Levels               | Range               |
|----------------|-----------|----------------|----------------------|---------------------|
| gamma          | numeric   | -              |                      | $[0, \infty)$       |
| gain           | numeric   | 1              |                      | $(-\infty, \infty)$ |
| stages         | character | -              | train, predict, both | -                   |
| affect_columns | untyped   | selector_all() |                      | -                   |

---

**mlr\_pipeops\_trafo\_adjust\_hue**  
*Adjust Hue Transformation*

---

**Description**

Calls `torchvision::transform_adjust_hue`, see there for more information on the parameters. The preprocessing is applied to each element of a batch individually.

**Format**

`R6Class` inheriting from `PipeOpTaskPreprocTorch`.

**Construction**

```
po("trafo_adjust_hue")
```

**Parameters**

| Id             | Type      | Default        | Levels               | Range       |
|----------------|-----------|----------------|----------------------|-------------|
| hue_factor     | numeric   | -              |                      | [-0.5, 0.5] |
| stages         | character | -              | train, predict, both | -           |
| affect_columns | untyped   | selector_all() |                      | -           |

---

**mlr\_pipeops\_trafo\_adjust\_saturation**  
*Adjust Saturation Transformation*

---

**Description**

Calls `torchvision::transform_adjust_saturation`, see there for more information on the parameters. The preprocessing is applied to each element of a batch individually.

**Format**

`R6Class` inheriting from `PipeOpTaskPreprocTorch`.

**Construction**

```
po("trafo_adjust_saturation")
```

**Parameters**

| Id                | Type      | Default        | Levels               | Range               |
|-------------------|-----------|----------------|----------------------|---------------------|
| saturation_factor | numeric   | -              |                      | $(-\infty, \infty)$ |
| stages            | character | -              | train, predict, both | -                   |
| affect_columns    | untyped   | selector_all() |                      | -                   |

---

**mlr\_pipeops\_trafo\_grayscale***Grayscale Transformation*

---

**Description**

Calls `torchvision::transform_grayscale`, see there for more information on the parameters. The preprocessing is applied to each element of a batch individually.

**Format**

`R6Class` inheriting from `PipeOpTaskPreprocTorch`.

**Construction**

```
po("trafo_grayscale")
```

**Parameters**

| Id                  | Type      | Default        | Levels               | Range  |
|---------------------|-----------|----------------|----------------------|--------|
| num_output_channels | integer   | -              |                      | [1, 3] |
| stages              | character | -              | train, predict, both | -      |
| affect_columns      | untyped   | selector_all() |                      | -      |

---

**mlr\_pipeops\_trafo\_nop** *No Transformation*

---

**Description**

Does nothing.

**Format**

`R6Class` inheriting from `PipeOpTaskPreprocTorch`.

---

**mlr\_pipeops\_trafo\_normalize**  
*Normalization Transformation*

---

**Description**

Calls [torchvision::transform\\_normalize](#), see there for more information on the parameters. The preprocessing is applied to each element of a batch individually.

**Format**

[R6Class](#) inheriting from [PipeOpTaskPreprocTorch](#).

**Construction**

```
po("trafo_normalize")
```

**Parameters**

| Id             | Type      | Default        | Levels               |
|----------------|-----------|----------------|----------------------|
| mean           | untyped   | -              |                      |
| std            | untyped   | -              |                      |
| stages         | character | -              | train, predict, both |
| affect_columns | untyped   | selector_all() |                      |

---

**mlr\_pipeops\_trafo\_pad** *Padding Transformation*

---

**Description**

Calls [torchvision::transform\\_pad](#), see there for more information on the parameters. The preprocessing is applied to each element of a batch individually.

**Format**

[R6Class](#) inheriting from [PipeOpTaskPreprocTorch](#).

**Construction**

```
po("trafo_pad")
```

**Parameters**

| Id             | Type      | Default        | Levels                             |
|----------------|-----------|----------------|------------------------------------|
| padding        | untyped   | -              |                                    |
| fill           | untyped   | 0              |                                    |
| padding_mode   | character | constant       | constant, edge, reflect, symmetric |
| stages         | character | -              | train, predict, both               |
| affect_columns | untyped   | selector_all() |                                    |

---

**mlr\_pipeops\_trafo\_reshape***Reshaping Transformation*

---

**Description**

Reshapes the tensor according to the parameter shape, by calling `torch_reshape()`. This preprocessing function is applied batch-wise.

**Format**

[R6Class](#) inheriting from [PipeOpTaskPreprocTorch](#).

**Parameters**

- `shape :: integer()`  
The desired output shape. The first dimension is the batch dimension and should usually be `-1`.

---

**mlr\_pipeops\_trafo\_resize***Resizing Transformation*

---

**Description**

Calls `torchvision::transform_resize`, see there for more information on the parameters. The preprocessing is applied to the whole batch.

**Format**

[R6Class](#) inheriting from [PipeOpTaskPreprocTorch](#).

## Construction

```
po("trafo_resize")
```

## Parameters

| Id             | Type      | Default        | Levels                                                                      |
|----------------|-----------|----------------|-----------------------------------------------------------------------------|
| size           | untyped   | -              |                                                                             |
| interpolation  | character | 2              | Undefined, Bartlett, Blackman, Bohman, Box, Catrom, Cosine, Cubic, Gaussian |
| stages         | character | -              | train, predict, both                                                        |
| affect_columns | untyped   | selector_all() |                                                                             |

---

**mlr\_pipeops\_trafo\_rgb\_to\_grayscale**  
*RGB to Grayscale Transformation*

---

## Description

Calls `torchvision::transform_rgb_to_grayscale`, see there for more information on the parameters. The preprocessing is applied to each element of a batch individually.

## Format

R6Class inheriting from `PipeOpTaskPreprocTorch`.

## Construction

```
po("trafo_rgb_to_grayscale")
```

## Parameters

| Id             | Type      | Default        | Levels               |
|----------------|-----------|----------------|----------------------|
| stages         | character | -              | train, predict, both |
| affect_columns | untyped   | selector_all() |                      |

---

**mlr\_tasks\_cifar***CIFAR Classification Tasks*

---

**Description**

The CIFAR-10 and CIFAR-100 datasets. A subset of the 80 million tiny images dataset with noisy labels was supplied to student labelers, who were asked to filter out incorrectly labeled images. The images are have datatype `torch_long()`.

CIFAR-10 contains 10 classes. CIFAR-100 contains 100 classes, which may be partitioned into 20 superclasses of 5 classes each. The CIFAR-10 and CIFAR-100 classes are mutually exclusive. See Chapter 3.1 of [the technical report](#) for more details.

The data is obtained from `torchvision::cifar10_dataset()` (or `torchvision::cifar100_dataset()`).

**Format**

`R6::R6Class` inheriting from `mlr3::TaskClassif`.

**Construction**

```
tsk("cifar10")
tsk("cifar100")
```

**Download**

The `task`'s backend is a `DataBackendLazy` which will download the data once it is requested. Other meta-data is already available before that. You can cache these datasets by setting the `mlr3torch.cache` option to `TRUE` or to a specific path to be used as the cache directory.

**Properties**

- Task type: “classif”
- Properties: “multiclass”
- Has Missings: no
- Target: “class”
- Features: “image”
- Data Dimension: 60000x4

**References**

Krizhevsky, Alex (2009). “Learning Multiple Layers of Features from Tiny Images.” *Master’s thesis, Department of Computer Science, University of Toronto*.

**Examples**

```
task_cifar10 = tsk("cifar10")
task_cifar100 = tsk("cifar100")
```

---

**mlr\_tasks\_lazy\_iris Iris Classification Task**

---

**Description**

A classification task for the popular [datasets::iris](#) data set. Just like the iris task, but the features are represented as one lazy tensor column.

**Format**

[R6::R6Class](#) inheriting from [mlr3::TaskClassif](#).

**Construction**

```
tsk("lazy_iris")
```

**Properties**

- Task type: “classif”
- Properties: “multiclass”
- Has Missings: no
- Target: “Species”
- Features: “x”
- Data Dimension: 150x3

**Source**

[https://en.wikipedia.org/wiki/Iris\\_flower\\_data\\_set](https://en.wikipedia.org/wiki/Iris_flower_data_set)

**References**

Anderson E (1936). “The Species Problem in Iris.” *Annals of the Missouri Botanical Garden*, **23**(3), 457. [doi:10.2307/2394164](https://doi.org/10.2307/2394164).

**Examples**

```
task = tsk("lazy_iris")
task
df = task$data()
materialize(df$x[1:6], rbind = TRUE)
```

---

 mlr\_tasks\_melanoma *Melanoma Image classification*


---

## Description

Classification of melanoma tumor images. The data is a preprocessed version of the 2020 SIIM-ISIC challenge where the images have been reshaped to size  $(3, 128, 128)$ .

By default only the training rows are active in the task, but the test data (that has no targets) is also included. Whether an observation is part of the train or test set is indicated by the column "test".

There are no labels for the test rows, so by default, these observations are inactive, which means that the task uses only 32701 of the 43683 observations that are defined in the underlying data backend.

The data backend also contains a more detailed diagnosis of the specific type of tumor.

Columns:

- `outcome` (factor): the target variable. Whether the tumor is benign or malignant (the positive class)
- `anatom_site_general_challenge` (factor): the location of the tumor on the patient's body
- `sex` (factor): the sex of the patient
- `age_approx` (int): approximate age of the patient at the time of imaging
- `image` (lazy\_tensor): The image (shape  $(3, 128, 128)$ ) of the tumor. `ee split` (character): Whether the observation os part of the train or test set.

## Construction

```
tsk("melanoma")
```

## Download

The `task`'s backend is a `DataBackendLazy` which will download the data once it is requested. Other meta-data is already available before that. You can cache these datasets by setting the `mlr3torch.cache` option to `TRUE` or to a specific path to be used as the cache directory.

## Properties

- Task type: "classif"
- Properties: "two-class", "groups"
- Has Missings: no
- Target: "outcome"
- Features: "sex", "anatom\_site\_general\_challenge", "age\_approx", "image"
- Data Dimension: 43683x11

## Source

[https://huggingface.co/datasets/carsonzhang/ISIC\\_2020\\_small](https://huggingface.co/datasets/carsonzhang/ISIC_2020_small)

## References

Rotemberg, V., Kurtansky, N., Betz-Stablein, B., Caffery, L., Chousakos, E., Codella, N., Combalia, M., Dusza, S., Guitera, P., Gutman, D., Halpern, A., Helba, B., Kittler, H., Kose, K., Langer, S., Lioprysz, K., Malvehy, J., Musthaq, S., Nanda, J., Reiter, O., Shih, G., Stratigos, A., Tschandl, P., Weber, J., Soyer, P. (2021). “A patient-centric dataset of images and metadata for identifying melanomas using clinical context.” *Scientific Data*, **8**, 34. doi:10.1038/s4159702100815z.

## Examples

```
task = tsk("melanoma")
```

---

mlr\_tasks\_mnist      *MNIST Image classification*

---

## Description

Classic MNIST image classification.

The underlying [DataBackend](#) contains columns "label", "image", "row\_id", "split", where the last column indicates whether the row belongs to the train or test set.

The first 60000 rows belong to the training set, the last 10000 rows to the test set.

## Construction

```
tsk("mnist")
```

## Download

The `task`'s backend is a [DataBackendLazy](#) which will download the data once it is requested. Other meta-data is already available before that. You can cache these datasets by setting the `mlr3torch.cache` option to TRUE or to a specific path to be used as the cache directory.

## Properties

- Task type: “classif”
- Properties: “multiclass”
- Has Missing: no
- Target: “label”
- Features: “image”
- Data Dimension: 70000x4

## Source

[https://torchvision.mlverse.org/reference/mnist\\_dataset.html](https://torchvision.mlverse.org/reference/mnist_dataset.html)

## References

Lecun, Y., Bottou, L., Bengio, Y., Haffner, P. (1998). “Gradient-based learning applied to document recognition.” *Proceedings of the IEEE*, **86**(11), 2278-2324. [doi:10.1109/5.726791](https://doi.org/10.1109/5.726791).

## Examples

```
task = tsk("mnist")
```

---

mlr\_tasks\_tiny\_imagenet

*Tiny ImageNet Classification Task*

---

## Description

Subset of the famous ImageNet dataset. The data is obtained from `torchvision::tiny_imagenet_dataset()`.

The underlying `DataBackend` contains columns “class”, “image”, “..row\_id”, “split”, where the last column indicates whether the row belongs to the train, validation or test set that are provided in `torchvision`.

There are no labels for the test rows, so by default, these observations are inactive, which means that the task uses only 110000 of the 120000 observations that are defined in the underlying data backend.

## Construction

```
tsk("tiny_imagenet")
```

## Download

The `task`’s backend is a `DataBackendLazy` which will download the data once it is requested. Other meta-data is already available before that. You can cache these datasets by setting the `mlr3torch.cache` option to `TRUE` or to a specific path to be used as the cache directory.

## Properties

- Task type: “classif”
- Properties: “multiclass”
- Has Missings: no
- Target: “class”
- Features: “image”
- Data Dimension: 120000x4

## References

Deng, Jia, Dong, Wei, Socher, Richard, Li, Li-Jia, Li, Kai, Fei-Fei, Li (2009). “Imagenet: A large-scale hierarchical image database.” In *2009 IEEE conference on computer vision and pattern recognition*, 248–255. IEEE.

## Examples

```
task = tsk("tiny_imagenet")
```

---

ModelDescriptor

*Represent a Model with Meta-Info*

---

## Description

Represents a *model*; possibly a complete model, possibly one in the process of being built up.

This model takes input tensors of shapes `shapes_in` and pipes them through `graph`. Input shapes get mapped to input channels of `graph`. Output shapes are named by the output channels of `graph`; it is also possible to represent no-ops on tensors, in which case names of input and output should be identical.

`ModelDescriptor` objects typically represent partial models being built up, in which case the `pointer` slot indicates a specific point in the `graph` that produces a tensor of shape `pointer_shape`, on which the `graph` should be extended. It is allowed for the `graph` in this structure to be modified by-reference in different parts of the code. However, these modifications may never add edges with elements of the `Graph` as destination. In particular, no element of `graph$input` may be removed by reference, e.g. by adding an edge to the `Graph` that has the input channel of a `PipeOp` that was previously without parent as its destination.

In most cases it is better to create a specific `ModelDescriptor` by training a `Graph` consisting (mostly) of operators `PipeOpTorchIngress`, `PipeOpTorch`, `PipeOpTorchLoss`, `PipeOpTorchOptimizer`, and `PipeOpTorchCallbacks`.

A `ModelDescriptor` can be converted to a `nn_graph` via `model_descriptor_to_module`.

## Usage

```
ModelDescriptor(  
    graph,  
    ingress,  
    task,  
    optimizer = NULL,  
    loss = NULL,  
    callbacks = NULL,  
    pointer = NULL,  
    pointer_shape = NULL  
)
```

## Arguments

|         |                                                                                                                      |
|---------|----------------------------------------------------------------------------------------------------------------------|
| graph   | ( <a href="#">Graph</a> )                                                                                            |
|         | Graph of <a href="#">PipeOpModule</a> and <a href="#">PipeOpNOP</a> operators.                                       |
| ingress | (uniquely named list of <a href="#">TorchIngressToken</a> )                                                          |
|         | List of inputs that go into <code>graph</code> . Names of this must be a subset of <code>graph\$input\$name</code> . |

|               |                                                                                                                                                                                           |
|---------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| task          | ( <a href="#">Task</a> )<br>(Training)-Task for which the model is being built. May be necessary for for some aspects of what loss to use etc.                                            |
| optimizer     | ( <a href="#">TorchOptimizer</a>   NULL)<br>Additional info: what optimizer to use.                                                                                                       |
| loss          | ( <a href="#">TorchLoss</a>   NULL)<br>Additional info: what loss to use.                                                                                                                 |
| callbacks     | (A list of <a href="#">CallbackSet</a> or NULL)<br>Additional info: what callbacks to use.                                                                                                |
| pointer       | (character(2)   NULL)<br>Indicating an element on which a model is. Points to an output channel within graph: Element 1 is the PipeOp's id and element 2 is that PipeOp's output channel. |
| pointer_shape | (integer   NULL)<br>Shape of the output indicated by pointer.                                                                                                                             |

## Value

([ModelDescriptor](#))

## See Also

Other Model Configuration: [mlr\\_pipeops\\_torch\\_callbacks](#), [mlr\\_pipeops\\_torch\\_loss](#), [mlr\\_pipeops\\_torch\\_optimizer](#), [model\\_descriptor\\_union\(\)](#)

Other Graph Network: [TorchIngressToken\(\)](#), [mlr\\_learners\\_torch\\_model](#), [mlr\\_pipeops\\_module](#), [mlr\\_pipeops\\_torch](#), [mlr\\_pipeops\\_torch\\_ingress](#), [mlr\\_pipeops\\_torch\\_ingress\\_categ](#), [mlr\\_pipeops\\_torch\\_ingress\\_num](#), [model\\_descriptor\\_to\\_learner\(\)](#), [model\\_descriptor\\_to\\_module\(\)](#), [model\\_descriptor\\_union\(\)](#), [nn\\_graph\(\)](#)

---

## model\_descriptor\_to\_learner

*Create a Torch Learner from a ModelDescriptor*

---

## Description

First a [nn\\_graph](#) is created using [model\\_descriptor\\_to\\_module](#) and then a learner is created from this module and the remaining information from the model descriptor, which must include the optimizer and loss function and optionally callbacks.

## Usage

`model_descriptor_to_learner(model_descriptor)`

## Arguments

model\_descriptor  
([ModelDescriptor](#))  
The model descriptor.

## Value

[Learner](#)

## See Also

Other Graph Network: [ModelDescriptor\(\)](#), [TorchIngressToken\(\)](#), [mlr\\_learners\\_torch\\_model](#), [mlr\\_pipeops\\_module](#), [mlr\\_pipeops\\_torch](#), [mlr\\_pipeops\\_torch\\_ingress](#), [mlr\\_pipeops\\_torch\\_ingress\\_categ](#), [mlr\\_pipeops\\_torch\\_ingress\\_ltbsr](#), [mlr\\_pipeops\\_torch\\_ingress\\_num](#), [model\\_descriptor\\_to\\_module\(\)](#), [model\\_descriptor\\_union\(\)](#), [nn\\_graph\(\)](#)

---

## model\_descriptor\_to\_module

*Create a nn\_graph from ModelDescriptor*

---

## Description

Creates the [nn\\_graph](#) from a [ModelDescriptor](#). Mostly for internal use, since the [ModelDescriptor](#) is in most circumstances harder to use than just creating [nn\\_graph](#) directly.

## Usage

```
model_descriptor_to_module(  
  model_descriptor,  
  output_pointers = NULL,  
  list_output = FALSE  
)
```

## Arguments

model\_descriptor  
([ModelDescriptor](#))  
Model Descriptor. pointer is ignored, instead output\_pointer values are used. \$graph member is modified by-reference.

output\_pointers  
(list of character)  
Collection of pointers that indicate what part of the model\_descriptor\$graph is being used for output. Entries have the format of ModelDescriptor\$pointer.

list\_output  
(logical(1))  
Whether output should be a list of tensors. If FALSE, then length(output\_pointers) must be 1.

**Value**`nn_graph`**See Also**

Other Graph Network: [ModelDescriptor\(\)](#), [TorchIngressToken\(\)](#), [mlr\\_learners\\_torch\\_model](#), [mlr\\_pipeops\\_module](#), [mlr\\_pipeops\\_torch](#), [mlr\\_pipeops\\_torch\\_ingress](#), [mlr\\_pipeops\\_torch\\_ingress\\_categ](#), [mlr\\_pipeops\\_torch\\_ingress\\_ltnsr](#), [mlr\\_pipeops\\_torch\\_ingress\\_num](#), [model\\_descriptor\\_to\\_learner\(\)](#), [model\\_descriptor\\_union\(\)](#), [nn\\_graph\(\)](#)

`model_descriptor_union`*Union of ModelDescriptors***Description**

This is a mostly internal function that is used in [PipeOpTorchs](#) with multiple input channels.

It creates the union of multiple [ModelDescriptor](#)s:

- graphs are combined (if they are not identical to begin with). The first entry's graph is modified by reference.
- PipeOps with the same ID must be identical. No new input edges may be added to PipeOps.
- Drops pointer / pointer\_shape entries.
- The new task is the [feature union](#) of the two incoming tasks.
- The optimizer and loss of both [ModelDescriptor](#)s must be identical.
- Ingress tokens and callbacks are merged, where objects with the same "id" must be identical.

**Usage**

```
model_descriptor_union(md1, md2)
```

**Arguments**

|     |                                                                                  |
|-----|----------------------------------------------------------------------------------|
| md1 | ( <a href="#">ModelDescriptor</a> ) The first <a href="#">ModelDescriptor</a> .  |
| md2 | ( <a href="#">ModelDescriptor</a> ) The second <a href="#">ModelDescriptor</a> . |

**Details**

The requirement that no new input edges may be added to PipeOps is not theoretically necessary, but since we assume that [ModelDescriptor](#) is being built from beginning to end (i.e. PipeOps never get new ancestors) we can make this assumption and simplify things. Otherwise we'd need to treat "..."-inputs special.)

**Value**`ModelDescriptor`

## See Also

Other Graph Network: [ModelDescriptor\(\)](#), [TorchIngressToken\(\)](#), [mlr\\_learners\\_torch\\_model](#), [mlr\\_pipeops\\_module](#), [mlr\\_pipeops\\_torch](#), [mlr\\_pipeops\\_torch\\_ingress](#), [mlr\\_pipeops\\_torch\\_ingress\\_categ](#), [mlr\\_pipeops\\_torch\\_ingress\\_ltnsr](#), [mlr\\_pipeops\\_torch\\_ingress\\_num](#), [model\\_descriptor\\_to\\_learner\(\)](#), [model\\_descriptor\\_to\\_module\(\)](#), [nn\\_graph\(\)](#)

Other Model Configuration: [ModelDescriptor\(\)](#), [mlr\\_pipeops\\_torch\\_callbacks](#), [mlr\\_pipeops\\_torch\\_loss](#), [mlr\\_pipeops\\_torch\\_optimizer](#)

---

nn

*Create a Neural Network Layer*

---

## Description

Retrieve a neural network layer from the [mlr\\_pipeops](#) dictionary.

## Usage

```
nn(.key, ...)
```

## Arguments

.key (character(1))

... (any)

Additional parameters, constructor arguments or fields.

## Examples

```
po1 = po("nn_linear", id = "linear")
# is the same as:
po2 = nn("linear")
```

---

nn\_ft\_cls

*CLS Token for FT-Transformer*

---

## Description

Concatenates a CLS token to the input as the last feature. The input shape is expected to be (batch, n\_features, d\_token) and the output shape is (batch, n\_features + 1, d\_token).

This is used in the [LearnerTorchFTTransformer](#).

## Usage

```
nn_ft_cls(d_token, initialization)
```

**Arguments**

**d\_token** (integer(1))  
 The dimension of the embedding.

**initialization** (character(1))  
 The initialization method for the embedding weights. Possible values are "uniform" and "normal".

**References**

Devlin, Jacob, Chang, Ming-Wei, Lee, Kenton, Toutanova, Kristina (2018). "Bert: Pre-training of deep bidirectional transformers for language understanding." *arXiv preprint arXiv:1810.04805*.

---

**nn\_ft\_transformer\_block**

*Single Transformer Block for FT-Transformer*

---

**Description**

A transformer block consisting of a multi-head self-attention mechanism followed by a feed-forward network.

This is used in [LearnerTorchFTTransformer](#).

**Usage**

```
nn_ft_transformer_block(  
  d_token,  
  attention_n_heads,  
  attention_dropout,  
  attention_initialization,  
  ffn_d_hidden = NULL,  
  ffn_d_hidden_multiplier = NULL,  
  ffn_dropout,  
  ffn_activation,  
  residual_dropout,  
  prenormalization,  
  is_first_layer,  
  attention_normalization,  
  ffn_normalization,  
  query_idx = NULL,  
  attention_bias,  
  ffn_bias_first,  
  ffn_bias_second  
)
```

**Arguments**

d\_token (integer(1))  
The dimension of the embedding.

attention\_n\_heads (integer(1))  
Number of attention heads.

attention\_dropout (numeric(1))  
Dropout probability in the attention mechanism.

attention\_INITIALIZATION (character(1))  
Initialization method for attention weights. Either "kaiming" or "xavier".

ffn\_d\_hidden (integer(1))  
Hidden dimension of the feed-forward network. Multiplied by 2 if using ReGLU or GeGLU activation.

ffn\_d\_hidden\_multiplier (numeric(1))  
Alternative way to specify the hidden dimension of the feed-forward network as d\_token \* d\_hidden\_multiplier. Also multiplied by 2 if using ReGLU or GeGLU activation.

ffn\_dropout (numeric(1))  
Dropout probability in the feed-forward network.

ffn\_activation (nn\_module)  
Activation function for the feed-forward network. Default value is nn\_reglu.

residual\_dropout (numeric(1))  
Dropout probability for residual connections.

prenormalization (logical(1))  
Whether to apply normalization before attention and FFN (TRUE) or after (TRUE).

is\_first\_layer (logical(1))  
Whether this is the first layer in the transformer stack. Default value is FALSE.

attention\_normalization (nn\_module)  
Normalization module to use for attention. Default value is nn\_layer\_norm.

ffn\_normalization (nn\_module)  
Normalization module to use for the feed-forward network. Default value is nn\_layer\_norm.

query\_idx (integer() or NULL)  
Indices of the tensor to apply attention to. Should not be set manually. If NULL, then attention is applied to the entire tensor. In the last block in a stack of transformers, this is set to -1 so that attention is applied only to the embedding of the CLS token.

```

attention_bias (logical(1))
    Whether attention has a bias. Default is TRUE

ffn_bias_first (logical(1))
    Whether the first layer in the FFN has a bias. Default is TRUE

ffn_bias_second
    (logical(1))
    Whether the second layer in the FFN has a bias. Default is TRUE

```

## References

Devlin, Jacob, Chang, Ming-Wei, Lee, Kenton, Toutanova, Kristina (2018). “Bert: Pre-training of deep bidirectional transformers for language understanding.” *arXiv preprint arXiv:1810.04805*. Gorishniy Y, Rubachev I, Khrulkov V, Babenko A (2021). “Revisiting Deep Learning for Tabular Data.” *arXiv*, **2106.11959**.

---

nn\_gegl

*GeGLU Module*

---

## Description

This module implements the Gaussian Error Linear Unit Gated Linear Unit (GeGLU) activation function. It computes  $\text{GeGLU}(x, g) = x \cdot \text{GELU}(g)$  where  $\backslash(x\backslash)$  and  $\backslash(g\backslash)$  are created by splitting the input tensor in half along the last dimension.

## Usage

`nn_gegl()`

## References

Shazeer N (2020). “GLU Variants Improve Transformer.” 2020.05202, <https://arxiv.org/abs/2002.05202>.

## Examples

```

x = torch::torch_randn(10, 10)
glu = nn_gegl()
glu(x)

```

---

**nn\_graph***Graph Network*

---

**Description**

Represents a neural network using a [Graph](#) that contains mostly [PipeOpModules](#).

**Usage**

```
nn_graph(graph, shapes_in, output_map = graph$output$name, list_output = FALSE)
```

**Arguments**

|             |                                                                                                                        |
|-------------|------------------------------------------------------------------------------------------------------------------------|
| graph       | ( <a href="#">Graph</a> )                                                                                              |
|             | The <a href="#">Graph</a> to wrap. Is <b>not</b> cloned.                                                               |
| shapes_in   | (named integer)                                                                                                        |
|             | Shape info of tensors that go into graph. Names must be <code>graph\$input\$name</code> , possibly in different order. |
| output_map  | (character)                                                                                                            |
|             | Which of graph's outputs to use. Must be a subset of <code>graph\$output\$name</code> .                                |
| list_output | (logical(1))                                                                                                           |
|             | Whether output should be a list of tensors. If FALSE (default), then <code>length(output_map)</code> must be 1.        |

**Value**

[nn\\_graph](#)

**Fields**

- **graph** :: [Graph](#)  
The graph (consisting primarily of [PipeOpModules](#)) that is wrapped by the network.
- **input\_map** :: character()  
The names of the input arguments of the network.
- **shapes\_in** :: list()  
The shapes of the input tensors of the network.
- **output\_map** :: character()  
Which output elements of the graph are returned by the `$forward()` method.
- **list\_output** :: logical(1)  
Whether the output is a list of tensors.
- **module\_list** :: [nn\\_module\\_list](#)  
The list of modules in the network.
- **list\_output** :: logical(1)  
Whether the output is a list of tensors.

**See Also**

Other Graph Network: [ModelDescriptor\(\)](#), [TorchIngressToken\(\)](#), [mlr\\_learners\\_torch\\_model](#), [mlr\\_pipeops\\_module](#), [mlr\\_pipeops\\_torch](#), [mlr\\_pipeops\\_torch\\_ingress](#), [mlr\\_pipeops\\_torch\\_ingress\\_categ](#), [mlr\\_pipeops\\_torch\\_ingress\\_ltnsr](#), [mlr\\_pipeops\\_torch\\_ingress\\_num](#), [model\\_descriptor\\_to\\_learner\(\)](#), [model\\_descriptor\\_to\\_module\(\)](#), [model\\_descriptor\\_union\(\)](#)

**Examples**

```
graph = mlr3pipelines::Graph$new()
graph$add_pipeop(po("module_1", module = nn_linear(10, 20)), clone = FALSE)
graph$add_pipeop(po("module_2", module = nn_relu()), clone = FALSE)
graph$add_pipeop(po("module_3", module = nn_linear(20, 1)), clone = FALSE)
graph$add_edge("module_1", "module_2")
graph$add_edge("module_2", "module_3")

network = nn_graph(graph, shapes_in = list(module_1.input = c(NA, 10)))

x = torch_randn(16, 10)

network(module_1.input = x)
```

**nn\_merge\_cat**

*Concatenates multiple tensors*

**Description**

Concatenates multiple tensors on a given dimension. No broadcasting rules are applied here, you must reshape the tensors before to have the same shape.

**Usage**

```
nn_merge_cat(dim = -1)
```

**Arguments**

|     |                                      |
|-----|--------------------------------------|
| dim | (integer(1))                         |
|     | The dimension for the concatenation. |

**nn\_merge\_prod**

*Product of multiple tensors*

**Description**

Calculates the product of all input tensors.

**Usage**

```
nn_merge_prod()
```

---

|              |                                |
|--------------|--------------------------------|
| nn_merge_sum | <i>Sum of multiple tensors</i> |
|--------------|--------------------------------|

---

## Description

Calculates the sum of all input tensors.

## Usage

```
nn_merge_sum()
```

---

|          |                     |
|----------|---------------------|
| nn_reglu | <i>ReGLU Module</i> |
|----------|---------------------|

---

## Description

Rectified Gated Linear Unit (ReGLU) module. Computes the output as  $\text{ReLU}(x, g) = x \cdot \text{ReLU}(g)$  where  $\backslash(x)$  and  $\backslash(g)$  are created by splitting the input tensor in half along the last dimension.

## Usage

```
nn_reglu()
```

## References

Shazeer N (2020). “GLU Variants Improve Transformer.” 2002.05202, <https://arxiv.org/abs/2002.05202>.

## Examples

```
x = torch::torch_rndn(10, 10)
reglu = nn_reglu()
reglu(x)
```

---

**nn\_reshape***Reshape*

---

**Description**

Reshape a tensor to the given shape.

**Usage**

```
nn_reshape(shape)
```

**Arguments**

|       |                           |
|-------|---------------------------|
| shape | (integer())               |
|       | The desired output shape. |

---

**nn\_squeeze***Squeeze*

---

**Description**

Squeezes a tensor by calling [torch::torch\\_squeeze\(\)](#) with the given dimension `dim`.

**Usage**

```
nn_squeeze(dim)
```

**Arguments**

|     |                           |
|-----|---------------------------|
| dim | (integer())               |
|     | The dimension to squeeze. |

---

nn\_tokenizer\_categ *Categorical Tokenizer*

---

## Description

Tokenizes categorical features into a dense embedding. For an input of shape (batch, n\_features) the output shape is (batch, n\_features, d\_token).

## Usage

```
nn_tokenizer_categ(cardinalities, d_token, bias, initialization)
```

## Arguments

|                |                |                                                                                                  |
|----------------|----------------|--------------------------------------------------------------------------------------------------|
| cardinalities  | (integer())    |                                                                                                  |
|                |                | The number of categories for each feature.                                                       |
| d_token        | (integer(1))   |                                                                                                  |
|                |                | The dimension of the embedding.                                                                  |
| bias           | (logical(1))   |                                                                                                  |
|                |                | Whether to use a bias.                                                                           |
| initialization | (character(1)) |                                                                                                  |
|                |                | The initialization method for the embedding weights. Possible values are "uniform" and "normal". |

## References

Gorishniy Y, Rubachev I, Khrulkov V, Babenko A (2021). “Revisiting Deep Learning for Tabular Data.” *arXiv*, **2106.11959**.

---

nn\_tokenizer\_num *Numeric Tokenizer*

---

## Description

Tokenizes numeric features into a dense embedding. For an input of shape (batch, n\_features) the output shape is (batch, n\_features, d\_token).

## Usage

```
nn_tokenizer_num(n_features, d_token, bias, initialization)
```

**Arguments**

|                             |                                                                                                  |
|-----------------------------|--------------------------------------------------------------------------------------------------|
| <code>n_features</code>     | <code>(integer(1))</code>                                                                        |
|                             | The number of features.                                                                          |
| <code>d_token</code>        | <code>(integer(1))</code>                                                                        |
|                             | The dimension of the embedding.                                                                  |
| <code>bias</code>           | <code>(logical(1))</code>                                                                        |
|                             | Whether to use a bias.                                                                           |
| <code>initialization</code> | <code>(character(1))</code>                                                                      |
|                             | The initialization method for the embedding weights. Possible values are "uniform" and "normal". |

**References**

Gorishniy Y, Rubachev I, Khrulkov V, Babenko A (2021). “Revisiting Deep Learning for Tabular Data.” *arXiv*, **2106.11959**.

---

|                           |                  |
|---------------------------|------------------|
| <code>nn_unsqueeze</code> | <i>Unsqueeze</i> |
|---------------------------|------------------|

---

**Description**

Unsqueezes a tensor by calling `torch::torch_unsqueeze()` with the given dimension `dim`.

**Usage**

`nn_unsqueeze(dim)`

**Arguments**

|                  |                             |
|------------------|-----------------------------|
| <code>dim</code> | <code>(integer(1))</code>   |
|                  | The dimension to unsqueeze. |

---

|                             |                                 |
|-----------------------------|---------------------------------|
| <code>output_dim_for</code> | <i>Network Output Dimension</i> |
|-----------------------------|---------------------------------|

---

**Description**

Calculates the output dimension of a neural network for a given task that is expected by **mlr3torch**. For classification, this is the number of classes (unless it is a binary classification task, where it is 1). For regression, it is 1.

**Usage**

`output_dim_for(x, ...)`

## Arguments

|     |                                     |
|-----|-------------------------------------|
| x   | (any)                               |
|     | The task.                           |
| ... | (any)                               |
|     | Additional arguments. Not used yet. |

---

pipeop\_prepoc\_torch *Create Torch Preprocessing PipeOps*

---

## Description

Function to create objects of class [PipeOpTaskPreprocTorch](#) in a more convenient way. Start by reading the documentation of [PipeOpTaskPreprocTorch](#).

## Usage

```
pipeop_prepoc_torch(  
  id,  
  fn,  
  shapes_out = NULL,  
  param_set = NULL,  
  packages = character(0),  
  rowwise = FALSE,  
  parent_env = parent.frame(),  
  stages_init = NULL,  
  tags = NULL  
)
```

## Arguments

|            |                                                                                                                                                                                                                                                                                                                                                    |
|------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| id         | (character(1))                                                                                                                                                                                                                                                                                                                                     |
|            | The id for of the new object.                                                                                                                                                                                                                                                                                                                      |
| fn         | (function)                                                                                                                                                                                                                                                                                                                                         |
|            | The preprocessing function.                                                                                                                                                                                                                                                                                                                        |
| shapes_out | (function or NULL or "infer")                                                                                                                                                                                                                                                                                                                      |
|            | The private .shapes_out(shapes_in, param_vals, task) method of <a href="#">PipeOpTaskPreprocTorch</a> (see section Inheriting). Special values are NULL and "infer": If NULL, the output shapes are unknown. Option "infer" uses <a href="#">infer_shapes</a> . Method "infer" should be correct in most cases, but might fail in some edge cases. |
| param_set  | ( <a href="#">ParamSet</a> or NULL)                                                                                                                                                                                                                                                                                                                |
|            | The parameter set. If this is left as NULL (default) the parameter set is inferred in the following way: All parameters but the first and . . . of fn are set as untyped parameters with tags 'train' and those that have no default value are tagged as 'required' as well. Default values are not annotated.                                     |

|             |                                                                                                                                                                                                 |
|-------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| packages    | (character())                                                                                                                                                                                   |
|             | The R packages this object depends on.                                                                                                                                                          |
| rowwise     | (logical(1))                                                                                                                                                                                    |
|             | Whether the preprocessing is applied row-wise.                                                                                                                                                  |
| parent_env  | (environment)                                                                                                                                                                                   |
|             | The parent environment for the R6 class.                                                                                                                                                        |
| stages_init | (character(1))                                                                                                                                                                                  |
|             | Initial value for the stages parameter. If NULL (default), will be set to "both" in case the id starts with "trafo" and to "train" if it starts with "augment". Otherwise it must be specified. |
| tags        | (character())                                                                                                                                                                                   |
|             | Tags for the pipeop                                                                                                                                                                             |

## Value

An [R6Class](#) instance inheriting from [PipeOpTaskPreprocTorch](#)

## Examples

```
PipeOpPreprocExample = pipeop_preproc_torch("preproc_example", function(x, a) x + a)
po_example = PipeOpPreprocExample$new()
po_example$param_set
```

---

## Description

A [Select](#) function subsets a character vector. They are used by the callback [CallbackSetUnfreeze](#) to select parameters to freeze or unfreeze during training.

## Usage

```
select_all()
select_none()
select_grep(pattern, ignore.case = FALSE, perl = FALSE, fixed = FALSE)
select_name(param_names, assert_present = TRUE)
select_invert(select)
```

## Arguments

|                |                                                                           |
|----------------|---------------------------------------------------------------------------|
| pattern        | See grep()                                                                |
| ignore.case    | See grep()                                                                |
| perl           | See grep()                                                                |
| fixed          | See grep()                                                                |
| param_names    | The names of the parameters that you want to select                       |
| assert_present | Whether to check that param_names is a subset of the full vector of names |
| select         | A Select                                                                  |

## Functions

- `select_all()`: `select_all` selects all elements
- `select_none()`: `select_none` selects no elements
- `select_grep()`: `select_grep` selects elements with names matching a regular expression
- `select_name()`: `select_name` selects elements with names matching the given names
- `select_invert()`: `select_invert` selects the elements NOT selected by the given selector

## Examples

```
select_all()(c("a", "b"))
select_none()(c("a", "b"))
select_grep("b$")(c("ab", "ac"))
select_name("a")(c("a", "b"))
select_invert(select_all()(c("a", "b")))
```

---

|              |                                     |
|--------------|-------------------------------------|
| task_dataset | <i>Create a Dataset from a Task</i> |
|--------------|-------------------------------------|

---

## Description

Creates a torch [dataset](#) from an mlr3 [Task](#). The resulting dataset's `$.get_batch()` method returns a list with elements `x`, `y` and `index`:

- `x` is a list with tensors, whose content is defined by the parameter `feature_ingress_tokens`.
- `y` is the target variable and its content is defined by the parameter `target_batchgetter`.
- `.index` is the index of the batch in the task's data.

The data is returned on the device specified by the parameter `device`.

## Usage

```
task_dataset(task, feature_ingress_tokens, target_batchgetter = NULL)
```

## Arguments

task [\(Task\)](#)  
 The task for which to build the [dataset](#).

feature\_ingress\_tokens  
 (named list() of [TorchIngressToken](#))  
 Each ingress token defines one item in the \$x value of a batch with corresponding names.

target\_batchgetter  
 (function(data, device))  
 A function taking in arguments data, which is a data.table containing only the target variable, and device. It must return the target as a torch [tensor](#) on the selected device.

## Value

[torch::dataset](#)

## Examples

```
task = tsk("iris")
sepal_ingress = TorchIngressToken(
  features = c("Sepal.Length", "Sepal.Width"),
  batchgetter = batchgetter_num,
  shape = c(NA, 2)
)
petal_ingress = TorchIngressToken(
  features = c("Petal.Length", "Petal.Width"),
  batchgetter = batchgetter_num,
  shape = c(NA, 2)
)
ingress_tokens = list(sepal = sepal_ingress, petal = petal_ingress)

target_batchgetter = function(data) {
  torch_tensor(data = data[[1L]], dtype = torch_float32())$unsqueeze(2)
}
dataset = task_dataset(task, ingress_tokens, target_batchgetter)
batch = dataset$.getbatch(1:10)
batch
```

---

## Description

This wraps a [CallbackSet](#) and annotates it with metadata, most importantly a [ParamSet](#). The callback is created for the given parameter values by calling the [\\$generate\(\)](#) method.

This class is usually used to configure the callback of a torch learner, e.g. when constructing a learner of in a [ModelDescriptor](#).

For a list of available callbacks, see [mlr3torch\\_callbacks](#). To conveniently retrieve a [TorchCallback](#), use [t\\_clbk\(\)](#).

## Parameters

Defined by the constructor argument `param_set`. If no parameter set is provided during construction, the parameter set is constructed by creating a parameter for each argument of the wrapped loss function, where the parameters are then of type `ParamUty`.

## Super class

[mlr3torch::TorchDescriptor](#) -> [TorchCallback](#)

## Methods

### Public methods:

- [TorchCallback\\$new\(\)](#)
- [TorchCallback\\$clone\(\)](#)

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

```
TorchCallback$new(  
  callback_generator,  
  param_set = NULL,  
  id = NULL,  
  label = NULL,  
  packages = NULL,  
  man = NULL,  
  additional_args = NULL  
)
```

*Arguments:*

`callback_generator` ([R6ClassGenerator](#))

The class generator for the callback that is being wrapped.

`param_set` ([ParamSet](#) or `NULL`)

The parameter set. If `NULL` (default) it is inferred from `callback_generator`.

`id` ([character\(1\)](#))

The id for of the new object.

`label` ([character\(1\)](#))

Label for the new instance.

`packages` ([character\(\)](#))

The R packages this object depends on.

`man` ([character\(1\)](#))

String in the format `[pkg]::[topic]` pointing to a manual page for this object. The referenced help package can be opened via method `$help()`.

`additional_args` (any)

Additional arguments if necessary. For learning rate schedulers, this is the `torch::LRScheduler`.

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

`TorchCallback$clone(deep = FALSE)`

*Arguments:*

`deep` Whether to make a deep clone.

## See Also

Other Callback: [as\\_torch\\_callback\(\)](#), [as\\_torch\\_callbacks\(\)](#), [callback\\_set\(\)](#), [mlr3torch\\_callbacks](#), [mlr\\_callback\\_set](#), [mlr\\_callback\\_set.checkpoint](#), [mlr\\_callback\\_set.progress](#), [mlr\\_callback\\_set.tb](#), [mlr\\_callback\\_set.unfreeze](#), [mlr\\_context\\_torch](#), [t\\_clbk\(\)](#), [torch\\_callback\(\)](#)

Other Torch Descriptor: [TorchDescriptor](#), [TorchLoss](#), [TorchOptimizer](#), [as\\_torch\\_callbacks\(\)](#), [as\\_torch\\_loss\(\)](#), [as\\_torch\\_optimizer\(\)](#), [mlr3torch\\_losses](#), [mlr3torch\\_optimizers](#), [t\\_clbk\(\)](#), [t\\_loss\(\)](#), [t\\_opt\(\)](#)

## Examples

```
# Create a new torch callback from an existing callback set
torch_callback = TorchCallback$new(CallbackSetCheckpoint)
# The parameters are inferred
torch_callback$param_set

# Retrieve a torch callback from the dictionary
torch_callback = t_clbk("checkpoint",
  path = tempfile(), freq = 1
)
torch_callback
torch_callback$label
torch_callback$id

# open the help page of the wrapped callback set
# torch_callback$help()

# Create the callback set
callback = torch_callback$generate()
callback
# is the same as
CallbackSetCheckpoint$new(
  path = tempfile(), freq = 1
)

# Use in a learner
learner = lrn("regr.mlp", callbacks = t_clbk("checkpoint"))
# the parameters of the callback are added to the learner's parameter set
learner$param_set
```

## Description

Abstract Base Class from which [TorchLoss](#), [TorchOptimizer](#), and [TorchCallback](#) inherit. This class wraps a generator (R6Class Generator or the torch version of such a generator) and annotates it with metadata such as a [ParamSet](#), a label, an ID, packages, or a manual page.

The parameters are the construction arguments of the wrapped generator and the parameter \$values are passed to the generator when calling the public method \$generate().

## Parameters

Defined by the constructor argument param\_set. All parameters are tagged with "train", but this is done automatically during initialize.

## Public fields

label (character(1))

Label for this object. Can be used in tables, plot and text output instead of the ID.

param\_set ([ParamSet](#))

Set of hyperparameters.

packages (character(1))

Set of required packages. These packages are loaded, but not attached.

id (character(1))

Identifier of the object. Used in tables, plot and text output.

generator The wrapped generator that is described.

man (character(1))

String in the format [pkg]::[topic] pointing to a manual page for this object.

## Active bindings

phash (character(1))

Hash (unique identifier) for this partial object, excluding some components which are varied systematically (e.g. the parameter values).

## Methods

### Public methods:

- [TorchDescriptor\\$new\(\)](#)
- [TorchDescriptor\\$print\(\)](#)
- [TorchDescriptor\\$generate\(\)](#)
- [TorchDescriptor\\$help\(\)](#)
- [TorchDescriptor\\$clone\(\)](#)

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

```
TorchDescriptor$new(
  generator,
  id = NULL,
  param_set = NULL,
  packages = NULL,
  label = NULL,
  man = NULL,
  additional_args = NULL
)
```

*Arguments:*

`generator` The wrapped generator that is described.

`id` (character(1))

    The id for of the new object.

`param_set` ([ParamSet](#))

    The parameter set.

`packages` (character())

    The R packages this object depends on.

`label` (character(1))

    Label for the new instance.

`man` (character(1))

    String in the format [pkg]::[topic] pointing to a manual page for this object. The referenced help package can be opened via method `$help()`.

`additional_args` (list())

    Additional arguments if necessary. For learning rate schedulers, this is the `torch::LRScheduler`.

**Method** `print()`: Prints the object

*Usage:*

```
TorchDescriptor$print(...)
```

*Arguments:*

... any

**Method** `generate()`: Calls the generator with the given parameter values.

*Usage:*

```
TorchDescriptor$generate()
```

**Method** `help()`: Displays the help file of the wrapped object.

*Usage:*

```
TorchDescriptor$help()
```

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

```
TorchDescriptor$clone(deep = FALSE)
```

*Arguments:*

`deep` Whether to make a deep clone.

### See Also

Other Torch Descriptor: [TorchCallback](#), [TorchLoss](#), [TorchOptimizer](#), [as\\_torch\\_callbacks\(\)](#), [as\\_torch\\_loss\(\)](#), [as\\_torch\\_optimizer\(\)](#), [mlr3torch\\_losses](#), [mlr3torch\\_optimizers](#), [t\\_clbk\(\)](#), [t\\_loss\(\)](#), [t\\_opt\(\)](#)

---

TorchIngressToken

*Torch Ingress Token*

---

### Description

This function creates an S3 class of class "TorchIngressToken", which is an internal data structure. It contains the (meta-)information of how a batch is generated from a [Task](#) and fed into an entry point of the neural network. It is stored as the `ingress` field in a [ModelDescriptor](#).

### Usage

```
TorchIngressToken(features, batchgetter, shape = NULL)
```

### Arguments

|             |                                                                                                                                                                                                                                               |
|-------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| features    | (character or <code>mlr3pipelines::Selector</code> )                                                                                                                                                                                          |
|             | Features on which the batchgetter will operate or a selector (such as <code>mlr3pipelines::selector_type</code> ).                                                                                                                            |
| batchgetter | (function)                                                                                                                                                                                                                                    |
|             | Function with two arguments: <code>data</code> and <code>device</code> . This function is given the output of <code>Task\$data(rows = batch_indices, cols = features)</code> and it should produce a tensor of shape <code>shape_out</code> . |
| shape       | (integer)                                                                                                                                                                                                                                     |
|             | Shape that batchgetter will produce. Batch dimension must be included as NA (but other dimensions can also be NA, i.e., unknown).                                                                                                             |

### Value

`TorchIngressToken` object.

### See Also

Other Graph Network: [ModelDescriptor\(\)](#), [mlr\\_learners\\_torch\\_model](#), [mlr\\_pipeops\\_module](#), [mlr\\_pipeops\\_torch](#), [mlr\\_pipeops\\_torch\\_ingress](#), [mlr\\_pipeops\\_torch\\_ingress\\_categ](#), [mlr\\_pipeops\\_torch\\_ingress](#), [mlr\\_pipeops\\_torch\\_ingress\\_num](#), [model\\_descriptor\\_to\\_learner\(\)](#), [model\\_descriptor\\_to\\_module\(\)](#), [model\\_descriptor\\_union\(\)](#), [nn\\_graph\(\)](#)

## Examples

```

# Define a task for which we want to define an ingress token
task = tsk("iris")

# We create an ingress token for two feature Sepal.Length and Petal.Length:
# We have to specify the features, the batchgetter and the shape
features = c("Sepal.Length", "Petal.Length")
# As a batchgetter we use batchgetter_num

batch_dt = task$data(rows = 1:10, cols = features)
batch_dt
batch_tensor = batchgetter_num(batch_dt, "cpu")
batch_tensor

# The shape is unknown in the first dimension (batch dimension)

ingress_token = TorchIngressToken(
  features = features,
  batchgetter = batchgetter_num,
  shape = c(NA, 2)
)
ingress_token

```

---

TorchLoss

*Torch Loss*

---

## Description

This wraps a `torch::nn::loss` and annotates it with metadata, most importantly a [ParamSet](#). The loss function is created for the given parameter values by calling the `$generate()` method.

This class is usually used to configure the loss function of a torch learner, e.g. when constructing a learner or in a [ModelDescriptor](#).

For a list of available losses, see [mlr3torch\\_losses](#). Items from this dictionary can be retrieved using `t_loss()`.

## Parameters

Defined by the constructor argument `param_set`. If no parameter set is provided during construction, the parameter set is constructed by creating a parameter for each argument of the wrapped loss function, where the parameters are then of type `ParamUty`.

## Super class

[mlr3torch::TorchDescriptor](#) -> TorchLoss

**Public fields**

`task_types` (character())  
The task types this loss supports.

**Methods****Public methods:**

- `TorchLoss$new()`
- `TorchLoss$print()`
- `TorchLoss$generate()`
- `TorchLoss$clone()`

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

```
TorchLoss$new(  
  torch_loss,  
  task_types = NULL,  
  param_set = NULL,  
  id = NULL,  
  label = NULL,  
  packages = NULL,  
  man = NULL  
)
```

*Arguments:*

`torch_loss` (nn\_loss or function)

The loss module or function that generates the loss module. Can have arguments `task` that will be provided when the loss is instantiated.

`task_types` (character())

The task types supported by this loss.

`param_set` ([ParamSet](#) or NULL)

The parameter set. If NULL (default) it is inferred from `torch_loss`.

`id` (character(1))

The id for of the new object.

`label` (character(1))

Label for the new instance.

`packages` (character())

The R packages this object depends on.

`man` (character(1))

String in the format [pkg]::[topic] pointing to a manual page for this object. The referenced help package can be opened via method `$help()`.

**Method** `print()`: Prints the object

*Usage:*

```
TorchLoss$print(...)
```

*Arguments:*

... any

**Method** `generate()`: Instantiates the loss function.

*Usage:*

`TorchLoss$generate(task = NULL)`

*Arguments:*

`task` (Task)

The task. Must be provided if the loss function requires a task.

*Returns:* `torch_loss`

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

`TorchLoss$clone(deep = FALSE)`

*Arguments:*

`deep` Whether to make a deep clone.

## See Also

Other Torch Descriptor: [TorchCallback](#), [TorchDescriptor](#), [TorchOptimizer](#), [as\\_torch\\_callbacks\(\)](#), [as\\_torch\\_loss\(\)](#), [as\\_torch\\_optimizer\(\)](#), [mlr3torch\\_losses](#), [mlr3torch\\_optimizers](#), [t\\_clbk\(\)](#), [t\\_loss\(\)](#), [t\\_opt\(\)](#)

## Examples

```
# Create a new torch loss
torch_loss = TorchLoss$new(torch_loss = nn_mse_loss, task_types = "regr")
torch_loss
# the parameters are inferred
torch_loss$param_set

# Retrieve a loss from the dictionary:
torch_loss = t_loss("mse", reduction = "mean")
# is the same as
torch_loss
torch_loss$param_set
torch_loss$label
torch_loss$task_types
torch_loss$id

# Create the loss function
loss_fn = torch_loss$generate()
loss_fn
# Is the same as
nn_mse_loss(reduction = "mean")

# open the help page of the wrapped loss function
# torch_loss$help()

# Use in a learner
```

```
learner = lrn("regr.mlp", loss = t_loss("mse"))
# The parameters of the loss are added to the learner's parameter set
learner$param_set
```

---

TorchOptimizer

*Torch Optimizer*

---

## Description

This wraps a `torch::torch_optimizer_generator` and annotates it with metadata, most importantly a `ParamSet`. The optimizer is created for the given parameter values by calling the `$generate()` method.

This class is usually used to configure the optimizer of a torch learner, e.g. when constructing a learner or in a `ModelDescriptor`.

For a list of available optimizers, see `mlr3torch_optimizers`. Items from this dictionary can be retrieved using `t_opt()`.

## Parameters

Defined by the constructor argument `param_set`. If no parameter set is provided during construction, the parameter set is constructed by creating a parameter for each argument of the wrapped loss function, where the parameters are then of type `ParamUty`.

## Super class

`mlr3torch::TorchDescriptor` -> `TorchOptimizer`

## Methods

### Public methods:

- `TorchOptimizer$new()`
- `TorchOptimizer$generate()`
- `TorchOptimizer$clone()`

**Method** `new()`: Creates a new instance of this `R6` class.

*Usage:*

```
TorchOptimizer$new(
  torch_optimizer,
  param_set = NULL,
  id = NULL,
  label = NULL,
  packages = NULL,
  man = NULL
)
```

*Arguments:*

```

torch_optimizer (torch_optimizer_generator)
  The torch optimizer.

param_set (ParamSet or NULL)
  The parameter set. If NULL (default) it is inferred from torch_optimizer.

id (character(1))
  The id for of the new object.

label (character(1))
  Label for the new instance.

packages (character())
  The R packages this object depends on.

man (character(1))
  String in the format [pkg]::[topic] pointing to a manual page for this object. The referenced help package can be opened via method $help().

```

**Method** **generate()**: Instantiates the optimizer.

*Usage:*

```
TorchOptimizer$generate(params)
```

*Arguments:*

```
params (named list() of torch_tensors)
  The parameters of the network.
```

*Returns:* **torch\_optimizer**

**Method** **clone()**: The objects of this class are cloneable with this method.

*Usage:*

```
TorchOptimizer$clone(deep = FALSE)
```

*Arguments:*

```
deep Whether to make a deep clone.
```

## See Also

Other Torch Descriptor: [TorchCallback](#), [TorchDescriptor](#), [TorchLoss](#), [as\\_torch\\_callbacks\(\)](#), [as\\_torch\\_loss\(\)](#), [as\\_torch\\_optimizer\(\)](#), [mlr3torch\\_losses](#), [mlr3torch\\_optimizers](#), [t\\_clbk\(\)](#), [t\\_loss\(\)](#), [t\\_opt\(\)](#)

## Examples

```

# Create a new torch optimizer
torch_opt = TorchOptimizer$new(optim_ignite_adam, label = "adam")
torch_opt
# If the param set is not specified, parameters are inferred but are of class ParamUty
torch_opt$param_set

# open the help page of the wrapped optimizer
# torch_opt$help()

# Retrieve an optimizer from the dictionary
torch_opt = t_opt("sgd", lr = 0.1)

```

```
torch_opt
torch_opt$param_set
torch_opt$label
torch_opt$id

# Create the optimizer for a network
net = nn_linear(10, 1)
opt = torch_opt$generate(net$parameters)

# is the same as
optim_sgd(net$parameters, lr = 0.1)

# Use in a learner
learner = lrn("regr.mlp", optimizer = t_opt("sgd"))
# The parameters of the optimizer are added to the learner's parameter set
learner$param_set
```

---

**torch\_callback***Create a Callback Descriptor*

---

## Description

Convenience function to create a custom [TorchCallback](#). All arguments that are available in [callback\\_set\(\)](#) are also available here. For more information on how to correctly implement a new callback, see [CallbackSet](#).

## Usage

```
torch_callback(
  id,
  classname = paste0("CallbackSet", capitalize(id)),
  param_set = NULL,
  packages = NULL,
  label = capitalize(id),
  man = NULL,
  on_begin = NULL,
  on_end = NULL,
  on_exit = NULL,
  on_epoch_begin = NULL,
  on_before_valid = NULL,
  on_epoch_end = NULL,
  on_batch_begin = NULL,
  on_batch_end = NULL,
  on_after_backward = NULL,
  on_batch_valid_begin = NULL,
  on_batch_valid_end = NULL,
  on_valid_end = NULL,
```

```

state_dict = NULL,
load_state_dict = NULL,
initialize = NULL,
public = NULL,
private = NULL,
active = NULL,
parent_env = parent.frame(),
inherit = CallbackSet,
lock_objects = FALSE
)

```

## Arguments

|                         |                                                                                                                             |                                |                    |  |
|-------------------------|-----------------------------------------------------------------------------------------------------------------------------|--------------------------------|--------------------|--|
| id                      | (character(1))                                                                                                              |                                |                    |  |
|                         | '                                                                                                                           | The id for the torch callback. |                    |  |
| classname               | (character(1))                                                                                                              |                                |                    |  |
|                         | The class name.                                                                                                             |                                |                    |  |
| param_set               | (ParamSet)                                                                                                                  |                                |                    |  |
|                         | The parameter set, if not present it is inferred from the \$initialize() method.                                            |                                |                    |  |
| packages                | (character())                                                                                                               |                                |                    |  |
|                         | The packages the callback depends on. Default isNULL'.                                                                      |                                |                    |  |
| label                   | (character(1))                                                                                                              |                                |                    |  |
|                         | The label for the torch callback. Defaults to the capitalized id.                                                           |                                |                    |  |
| man                     | (character(1))                                                                                                              |                                |                    |  |
|                         | String in the format [pkg]::[topic] pointing to a manual page for this object.                                              |                                |                    |  |
|                         | The referenced help package can be opened via method \$help(). The default is NULL.                                         |                                |                    |  |
| on_begin,               | on_end,                                                                                                                     | on_epoch_begin,                | on_before_valid,   |  |
| on_epoch_end,           | on_batch_begin,                                                                                                             | on_batch_end,                  | on_after_backward, |  |
| on_batch_valid_begin,   | on_batch_valid_end,                                                                                                         | on_valid_end,                  | on_exit            |  |
|                         | (function)                                                                                                                  |                                |                    |  |
|                         | Function to execute at the given stage, see section <i>Stages</i> .                                                         |                                |                    |  |
| state_dict              | (function())                                                                                                                |                                |                    |  |
|                         | The function that retrieves the state dict from the callback. This is what will be available in the learner after training. |                                |                    |  |
| load_state_dict         | (function(state_dict))                                                                                                      |                                |                    |  |
|                         | Function that loads a callback state.                                                                                       |                                |                    |  |
| initialize              | (function())                                                                                                                |                                |                    |  |
|                         | The initialization method of the callback.                                                                                  |                                |                    |  |
| public, private, active | (list())                                                                                                                    |                                |                    |  |
|                         | Additional public, private, and active fields to add to the callback.                                                       |                                |                    |  |
| parent_env              | (environment())                                                                                                             |                                |                    |  |
|                         | The parent environment for the <a href="#">R6Class</a> .                                                                    |                                |                    |  |

|              |                                                                                                                                                                                               |
|--------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| inherit      | (R6ClassGenerator)                                                                                                                                                                            |
|              | From which class to inherit. This class must either be <a href="#">CallbackSet</a> (default) or inherit from it.                                                                              |
| lock_objects | (logical(1))                                                                                                                                                                                  |
|              | Whether to lock the objects of the resulting <a href="#">R6Class</a> . If FALSE (default), values can be freely assigned to <code>self</code> without declaring them in the class definition. |

## Value

[TorchCallback](#)

## Internals

It first creates an R6 class inheriting from [CallbackSet](#) (using `callback_set()`) and then wraps this generator in a [TorchCallback](#) that can be passed to a torch learner.

## Stages

- `begin` :: Run before the training loop begins.
- `epoch_begin` :: Run he beginning of each epoch.
- `batch_begin` :: Run before the forward call.
- `after_backward` :: Run after the backward call.
- `batch_end` :: Run after the optimizer step.
- `batch_valid_begin` :: Run before the forward call in the validation loop.
- `batch_valid_end` :: Run after the forward call in the validation loop.
- `valid_end` :: Run at the end of validation.
- `epoch_end` :: Run at the end of each epoch.
- `end` :: Run after last epoch.
- `exit` :: Run at last, using `on.exit()`.

## See Also

Other Callback: [TorchCallback](#), [as\\_torch\\_callback\(\)](#), [as\\_torch\\_callbacks\(\)](#), [callback\\_set\(\)](#), [mlr3torch\\_callbacks](#), [mlr\\_callback\\_set](#), [mlr\\_callback\\_set.checkpoint](#), [mlr\\_callback\\_set.progress](#), [mlr\\_callback\\_set.tb](#), [mlr\\_callback\\_set.unfreeze](#), [mlr\\_context\\_torch](#), [t\\_clbk\(\)](#)

## Examples

```
custom_tcb = torch_callback("custom",
  initialize = function(name) {
    self$name = name
  },
  on_begin = function() {
    cat("Hello", self$name, ", we will train for ", self$ctx$total_epochs, "epochs.\n")
  },
  on_end = function() {
    cat("Training is done.\n")
```

```

        }
    )

learner = lrn("classif.torch_featureless",
  batch_size = 16,
  epochs = 1,
  callbacks = custom_tcb,
  cb.custom.name = "Marie",
  device = "cpu"
)
task = tsk("iris")
learner$train(task)

```

---

**t\_clbk***Sugar Function for Torch Callback*

---

**Description**

Retrieves one or more `TorchCallbacks` from `mlr3torch_callbacks`. Works like `mlr3::lrn()` and `mlr3::lrns()`.

**Usage**

```
t_clbk(.key, ...)
```

```
t_clbks(.keys)
```

**Arguments**

|                    |                                                          |
|--------------------|----------------------------------------------------------|
| <code>.key</code>  | <code>(character(1))</code>                              |
|                    | The key of the torch callback.                           |
| <code>...</code>   | <code>(any)</code>                                       |
|                    | See description of <code>dictionary_sugar_get()</code> . |
| <code>.keys</code> | <code>(character())</code>                               |
|                    | The keys of the callbacks.                               |

**Value**

`TorchCallback`  
`list()` of `TorchCallbacks`

**See Also**

Other Callback: [TorchCallback](#), [as\\_torch\\_callback\(\)](#), [as\\_torch\\_callbacks\(\)](#), [callback\\_set\(\)](#), [mlr3torch\\_callbacks](#), [mlr\\_callback\\_set](#), [mlr\\_callback\\_set.checkpoint](#), [mlr\\_callback\\_set.progress](#), [mlr\\_callback\\_set.tb](#), [mlr\\_callback\\_set.unfreeze](#), [mlr\\_context\\_torch](#), [torch\\_callback\(\)](#)  
Other Torch Descriptor: [TorchCallback](#), [TorchDescriptor](#), [TorchLoss](#), [TorchOptimizer](#), [as\\_torch\\_callbacks\(\)](#), [as\\_torch\\_loss\(\)](#), [as\\_torch\\_optimizer\(\)](#), [mlr3torch\\_losses](#), [mlr3torch\\_optimizers](#), [t\\_loss\(\)](#), [t\\_opt\(\)](#)

**Examples**

```
t_clbk("progress")
```

---

**t\_loss***Loss Function Quick Access*

---

**Description**

Retrieve one or more [TorchLosses](#) from [mlr3torch\\_losses](#). Works like [mlr3::lrn\(\)](#) and [mlr3::lrvs\(\)](#).

**Usage**

```
t_loss(.key, ...)
```

```
t_losses(.keys, ...)
```

**Arguments**

|       |                                                           |
|-------|-----------------------------------------------------------|
| .key  | (character(1))                                            |
|       | Key of the object to retrieve.                            |
| ...   | (any)                                                     |
|       | See description of <a href="#">dictionary_sugar_get</a> . |
| .keys | (character())                                             |
|       | The keys of the losses.                                   |

**Value**

A [TorchLoss](#)

**See Also**

Other Torch Descriptor: [TorchCallback](#), [TorchDescriptor](#), [TorchLoss](#), [TorchOptimizer](#), [as\\_torch\\_callbacks\(\)](#), [as\\_torch\\_loss\(\)](#), [as\\_torch\\_optimizer\(\)](#), [mlr3torch\\_losses](#), [mlr3torch\\_optimizers](#), [t\\_clbk\(\)](#), [t\\_opt\(\)](#)

**Examples**

```
t_loss("mse", reduction = "mean")
# get the dictionary
t_loss()

t_losses(c("mse", "l1"))
# get the dictionary
t_losses()
```

---

t\_opt*Optimizers Quick Access*

---

**Description**

Retrieves one or more [TorchOptimizers](#) from [mlr3torch\\_optimizers](#). Works like [mlr3::lrn\(\)](#) and [mlr3::lrgs\(\)](#).

**Usage**

```
t_opt(.key, ...)
t_opts(.keys, ...)
```

**Arguments**

|       |                                                           |
|-------|-----------------------------------------------------------|
| .key  | (character(1))                                            |
|       | Key of the object to retrieve.                            |
| ...   | (any)                                                     |
|       | See description of <a href="#">dictionary_sugar_get</a> . |
| .keys | (character())                                             |
|       | The keys of the optimizers.                               |

**Value**

A [TorchOptimizer](#)

**See Also**

Other Torch Descriptor: [TorchCallback](#), [TorchDescriptor](#), [TorchLoss](#), [TorchOptimizer](#), [as\\_torch\\_callbacks\(\)](#), [as\\_torch\\_loss\(\)](#), [as\\_torch\\_optimizer\(\)](#), [mlr3torch\\_losses](#), [mlr3torch\\_optimizers](#), [t\\_clbk\(\)](#), [t\\_loss\(\)](#)

Other Dictionary: [mlr3torch\\_callbacks](#), [mlr3torch\\_losses](#), [mlr3torch\\_optimizers](#)

**Examples**

```
t_opt("adam", lr = 0.1)
# get the dictionary
t_opt()
```

```
t_opts(c("adam", "sgd"))
# get the dictionary
t_opts()
```

# Index

- \* **Callback**
  - as\_torch\_callback, 10
  - as\_torch\_callbacks, 11
  - callback\_set, 14
  - mlr3torch\_callbacks, 25
  - mlr\_callback\_set, 30
  - mlr\_callback\_set.checkpoint, 33
  - mlr\_callback\_set.progress, 39
  - mlr\_callback\_set.tb, 41
  - mlr\_callback\_set.unfreeze, 42
  - mlr\_context\_torch, 43
  - t\_clbk, 276
  - torch\_callback, 273
  - TorchCallback, 262
- \* **Dictionary**
  - mlr3torch\_callbacks, 25
  - mlr3torch\_losses, 25
  - mlr3torch\_optimizers, 26
  - t\_opt, 278
- \* **Graph Network**
  - mlr\_learners\_torch\_model, 70
  - mlr\_pipeops\_module, 82
  - mlr\_pipeops\_torch, 206
  - mlr\_pipeops\_torch\_ingress, 214
  - mlr\_pipeops\_torch\_ingress\_categ, 216
  - mlr\_pipeops\_torch\_ingress\_ltnsr, 218
  - mlr\_pipeops\_torch\_ingress\_num, 221
  - model\_descriptor\_to\_learner, 246
  - model\_descriptor\_to\_module, 247
  - model\_descriptor\_union, 248
  - ModelDescriptor, 245
  - nn\_graph, 253
  - TorchIngressToken, 267
- \* **Learner**
  - mlr\_learners.ft\_transformer, 46
  - mlr\_learners.mlp, 49
  - mlr\_learners.module, 51
- mlr\_learners.tab\_resnet, 54
- mlr\_learners.torch\_featureless, 58
- mlr\_learners\_torch, 60
- mlr\_learners\_torch\_image, 68
- mlr\_learners\_torch\_model, 70
- \* **Model Configuration**
  - mlr\_pipeops\_torch\_callbacks, 212
  - mlr\_pipeops\_torch\_loss, 222
  - mlr\_pipeops\_torch\_optimizer, 232
  - model\_descriptor\_union, 248
  - ModelDescriptor, 245
- \* **PipeOps**
  - mlr\_pipeops\_nn\_adaptive\_avg\_pool1d, 85
  - mlr\_pipeops\_nn\_adaptive\_avg\_pool2d, 87
  - mlr\_pipeops\_nn\_adaptive\_avg\_pool3d, 88
  - mlr\_pipeops\_nn\_avg\_pool1d, 90
  - mlr\_pipeops\_nn\_avg\_pool2d, 92
  - mlr\_pipeops\_nn\_avg\_pool3d, 94
  - mlr\_pipeops\_nn\_batch\_norm1d, 96
  - mlr\_pipeops\_nn\_batch\_norm2d, 98
  - mlr\_pipeops\_nn\_batch\_norm3d, 100
  - mlr\_pipeops\_nn\_block, 102
  - mlr\_pipeops\_nn\_celu, 105
  - mlr\_pipeops\_nn\_conv1d, 107
  - mlr\_pipeops\_nn\_conv2d, 109
  - mlr\_pipeops\_nn\_conv3d, 111
  - mlr\_pipeops\_nn\_conv\_transpose1d, 113
  - mlr\_pipeops\_nn\_conv\_transpose2d, 115
  - mlr\_pipeops\_nn\_conv\_transpose3d, 117
  - mlr\_pipeops\_nn\_dropout, 120
  - mlr\_pipeops\_nn\_elu, 121
  - mlr\_pipeops\_nn\_flatten, 123
  - mlr\_pipeops\_nn\_ft\_cls, 127

mlr\_pipeops\_nn\_ft\_transformer\_block, 128  
mlr\_pipeops\_nn\_geglu, 130  
mlr\_pipeops\_nn\_gelu, 132  
mlr\_pipeops\_nn\_glu, 134  
mlr\_pipeops\_nn\_hardshrink, 135  
mlr\_pipeops\_nn\_hardsigmoid, 137  
mlr\_pipeops\_nn\_hardtanh, 139  
mlr\_pipeops\_nn\_head, 141  
mlr\_pipeops\_nn\_identity, 143  
mlr\_pipeops\_nn\_layer\_norm, 144  
mlr\_pipeops\_nn\_leaky\_relu, 146  
mlr\_pipeops\_nn\_linear, 148  
mlr\_pipeops\_nn\_log\_sigmoid, 150  
mlr\_pipeops\_nn\_max\_pool1d, 152  
mlr\_pipeops\_nn\_max\_pool2d, 154  
mlr\_pipeops\_nn\_max\_pool3d, 156  
mlr\_pipeops\_nn\_merge, 158  
mlr\_pipeops\_nn\_merge\_cat, 160  
mlr\_pipeops\_nn\_merge\_prod, 162  
mlr\_pipeops\_nn\_merge\_sum, 164  
mlr\_pipeops\_nn\_prelu, 166  
mlr\_pipeops\_nn\_reglu, 168  
mlr\_pipeops\_nn\_relu, 170  
mlr\_pipeops\_nn\_relu6, 172  
mlr\_pipeops\_nn\_reshape, 174  
mlr\_pipeops\_nn\_rrelu, 175  
mlr\_pipeops\_nn\_selu, 177  
mlr\_pipeops\_nn\_sigmoid, 179  
mlr\_pipeops\_nn\_softmax, 181  
mlr\_pipeops\_nn\_softplus, 183  
mlr\_pipeops\_nn\_softshrink, 184  
mlr\_pipeops\_nn\_softsign, 186  
mlr\_pipeops\_nn\_squeeze, 188  
mlr\_pipeops\_nn\_tanh, 190  
mlr\_pipeops\_nn\_tanhshrink, 192  
mlr\_pipeops\_nn\_threshold, 193  
mlr\_pipeops\_nn\_tokenizer\_categ, 195  
mlr\_pipeops\_nn\_tokenizer\_num, 197  
mlr\_pipeops\_nn\_unsqueeze, 199  
mlr\_pipeops\_torch\_ingress, 214  
mlr\_pipeops\_torch\_ingress\_categ, 216  
mlr\_pipeops\_torch\_ingress\_ltnsr, 218  
mlr\_pipeops\_torch\_ingress\_num, 221  
mlr\_pipeops\_torch\_loss, 222  
mlr\_pipeops\_torch\_model, 224  
mlr\_pipeops\_torch\_model\_classif, 228  
mlr\_pipeops\_torch\_model\_regr, 230  
\* **PipeOp**  
mlr\_pipeops\_module, 82  
mlr\_pipeops\_torch\_callbacks, 212  
mlr\_pipeops\_torch\_optimizer, 232  
\* **Torch Descriptor**  
as\_torch\_callbacks, 11  
as\_torch\_loss, 12  
as\_torch\_optimizer, 12  
mlr3torch\_losses, 25  
mlr3torch\_optimizers, 26  
t\_clbk, 276  
t\_loss, 277  
t\_opt, 278  
TorchCallback, 262  
TorchDescriptor, 265  
TorchLoss, 268  
TorchOptimizer, 271  
\* **datasets**  
mlr3torch\_callbacks, 25  
mlr3torch\_losses, 25  
mlr3torch\_optimizers, 26  
..., 239  
as.data.table, 25, 26  
as\_data\_descriptor, 8  
as\_data\_descriptor(), 17  
as\_lazy\_tensor, 9  
as\_lr\_scheduler, 10  
as\_torch\_callback, 10, 11, 16, 25, 32, 34, 40, 42, 43, 46, 264, 275, 277  
as\_torch\_callbacks, 11, 11, 12, 13, 16, 25, 26, 32, 34, 40, 42, 43, 46, 264, 267, 270, 272, 275, 277, 278  
as\_torch\_callbacks(), 213  
as\_torch\_loss, 11, 12, 13, 26, 264, 267, 270, 272, 277, 278  
as\_torch\_loss(), 223  
as\_torch\_optimizer, 11, 12, 12, 26, 264, 267, 270, 272, 272, 277, 278  
as\_torch\_optimizer(), 233  
assert\_lazy\_tensor, 7  
auto\_device, 13  
batchgetter\_categ, 13  
batchgetter\_categ(), 216

batchgetter\_num, 14  
 batchgetter\_num(), 221  
  
 callback\_set, 11, 14, 25, 32, 34, 40, 42, 43, 46, 264, 275, 277  
 callback\_set(), 31, 273, 275  
 callbacks, 61  
 CallbackSet, 14–16, 30, 43, 246, 262, 273, 275  
 CallbackSet (mlr\_callback\_set), 30  
 CallbackSetCheckpoint  
     (mlr\_callback\_set.checkpoint), 33  
 CallbackSetHistory  
     (mlr\_callback\_set.history), 34  
 CallbackSetLRScheduler, 46  
 CallbackSetLRScheduler  
     (mlr\_callback\_set.lr\_scheduler), 36  
 CallbackSetLRSchedulerOneCycle  
     (mlr\_callback\_set.lr\_scheduler\_one\_cycle), 37  
 CallbackSetLRSchedulerReduceOnPlateau  
     (mlr\_callback\_set.lr\_scheduler\_reduce\_on\_plateau), 38  
 CallbackSetProgress  
     (mlr\_callback\_set.progress), 39  
 CallbackSetTB (mlr\_callback\_set.tb), 41  
 CallbackSetUnfreeze  
     (mlr\_callback\_set.unfreeze), 42  
 ContextTorch, 31  
 ContextTorch (mlr\_context\_torch), 43  
 cross\_entropy, 16  
  
 data.table, 25, 26  
 data.table::data.table(), 28, 29  
 DataBackend, 243, 244  
 DataBackendLazy, 240, 242–244  
 DataBackendLazy (mlr\_backends\_lazy), 27  
 DataDescriptor, 8, 17, 23, 24  
 dataset, 64, 68, 261, 262  
 datasets::iris, 241  
 dictionary\_sugar\_get, 277, 278  
 dictionary\_sugar\_get(), 276  
  
 feature union, 206, 248  
  
 Graph, 17, 18, 24, 103, 206, 207, 245, 253  
 graph, 207  
  
 infer\_shapes, 19, 259  
 ingress\_categ, 20, 64  
 ingress\_categ(), 52  
 ingress\_ltnsr, 21, 64  
 ingress\_ltnsr(), 52  
 ingress\_num, 21, 64  
 ingress\_num(), 52  
 is\_lazy\_tensor, 22  
  
 lazy\_shape, 22  
 lazy\_tensor, 9, 17, 22, 23, 24, 27, 46, 47, 49, 62, 68, 82, 196, 201, 218, 225  
 lazy\_tensor(), 23  
 Learner, 44–46, 49, 51, 54, 58, 247  
 LearnerTorch, 31, 32, 44, 46, 47, 49, 54, 58, 68, 70, 228, 230  
 LearnerTorch (mlr\_learners\_torch), 60  
 LearnerTorchFeatureless  
     (mlr\_learners.torch\_featureless), 58  
     LearnerTorchFTTransformer, 127, 128, 249, 250  
     LearnerTorchFTTransformer (mlr\_learners.ft\_transformer), 46  
     LearnerTorchImage, 56  
     LearnerTorchImage  
         (mlr\_learners\_torch\_image), 68  
     LearnerTorchMLP (mlr\_learners.mlp), 49  
     LearnerTorchModel, 226, 228, 230  
     LearnerTorchModel  
         (mlr\_learners\_torch\_model), 70  
     LearnerTorchModule  
         (mlr\_learners.module), 51  
     LearnerTorchTabResNet  
         (mlr\_learners.tab\_resnet), 54  
     LearnerTorchVision  
         (mlr\_learners.torchvision), 56  
     loss, 61  
     lrn(), 46, 49, 51, 54, 58  
  
     materialize, 23  
     materialize(), 17  
     Measure, 44, 45, 62, 225  
     mlr3::as\_prediction\_data(), 64  
     mlr3::col\_info(), 27  
     mlr3::DataBackend, 27  
     mlr3::Learner, 47, 50, 52, 55, 57, 58, 65, 68, 70

`mlr3::lrn()`, 276–278  
`mlr3::lrns()`, 276–278  
`mlr3::Task`, 60, 201  
`mlr3::TaskClassif`, 240, 241  
`mlr3misc::Dictionary`, 25  
`mlr3pipelines::Graph`, 17, 82  
`mlr3pipelines::PipeOp`, 82, 85, 87, 89, 91, 93, 95, 97, 99, 101, 103, 105, 107, 110, 112, 114, 116, 118, 120, 122, 124, 125, 127, 129, 130, 132, 134, 136, 138, 139, 141, 143, 145, 147, 149, 150, 152, 155, 157, 159, 161, 163, 165, 167, 169, 170, 172, 174, 176, 178, 179, 181, 183, 185, 187, 188, 190, 192, 194, 196, 198, 200, 202, 207, 213, 214, 217, 219, 221, 223, 227, 228, 230, 232  
`mlr3pipelines::PipeOpLearner`, 227, 228, 230  
`mlr3pipelines::PipeOpTaskPreproc`, 202  
`mlr3pipelines::selector_type`, 267  
`mlr3torch` (mlr3torch-package), 6  
`mlr3torch-package`, 6  
`mlr3torch::CallbackSet`, 33, 34, 36–39, 41, 42  
`mlr3torch::CallbackSetLRScheduler`, 37, 38  
`mlr3torch::LearnerTorch`, 47, 50, 52, 55, 57, 58, 68, 70  
`mlr3torch::LearnerTorchImage`, 57  
`mlr3torch::PipeOpTorch`, 85, 87, 89, 91, 93, 95, 97, 99, 101, 103, 105, 107, 110, 112, 114, 116, 118, 120, 122, 124, 125, 127, 129, 130, 132, 134, 136, 138, 139, 141, 143, 145, 147, 149, 150, 152, 155, 157, 159, 161, 163, 165, 167, 169, 170, 172, 174, 176, 178, 179, 181, 183, 185, 187, 188, 190, 192, 194, 196, 198, 200  
`mlr3torch::PipeOpTorchIngress`, 217, 219, 221  
`mlr3torch::PipeOpTorchMerge`, 161, 163, 165  
`mlr3torch::PipeOpTorchModel`, 228, 230  
`mlr3torch::TorchDescriptor`, 263, 268, 271  
`mlr3torch_callbacks`, 11, 16, 25, 26, 32, 34, 40, 42, 43, 46, 263, 264, 275–278  
`mlr3torch_losses`, 11–13, 25, 25, 26, 264, 267, 268, 270, 272, 277, 278  
`mlr3torch_optimizers`, 11–13, 25, 26, 26, 264, 267, 270–272, 277, 278  
`mlr_backends_lazy`, 27  
`mlr_callback_set`, 11, 16, 25, 30, 34, 40, 42, 43, 46, 264, 275, 277  
`mlr_callback_set.checkpoint`, 11, 16, 25, 32, 33, 40, 42, 43, 46, 264, 275, 277  
`mlr_callback_set.history`, 34  
`mlr_callback_set.lr_scheduler`, 36  
`mlr_callback_set.lr_scheduler_one_cycle`, 37  
`mlr_callback_set.lr_scheduler_reduce_on_plateau`, 38  
`mlr_callback_set.progress`, 11, 16, 25, 32, 34, 39, 42, 43, 46, 264, 275, 277  
`mlr_callback_set.tb`, 11, 16, 25, 32, 34, 40, 41, 43, 46, 264, 275, 277  
`mlr_callback_set.unfreeze`, 11, 16, 25, 32, 34, 40, 42, 44, 46, 264, 275, 277  
`mlr_context_torch`, 11, 16, 25, 32, 34, 40, 42, 43, 44, 264, 275, 277  
`mlr_learners.ft_transformer`, 46, 50, 53, 55, 59, 68, 70, 71  
`mlr_learners.mlp`, 48, 49, 53, 55, 59, 68, 70, 71  
`mlr_learners.module`, 48, 50, 51, 55, 59, 68, 70, 71  
`mlr_learners.tab_resnet`, 48, 50, 53, 54, 59, 68, 70, 71  
`mlr_learners.torch_featureless`, 48, 50, 53, 58, 68, 70, 71  
`mlr_learners.torchvision`, 56  
`mlr_learners_torch`, 48, 50, 53, 55, 59, 60, 70, 71  
`mlr_learners_torch_image`, 48, 50, 53, 55, 59, 68, 68, 71  
`mlr_learners_torch_model`, 48, 50, 53, 55, 59, 68, 70, 70, 83, 209, 216, 218, 220, 222, 246–249, 254, 267  
`mlr_pipeops`, 249  
`mlr_pipeops_augment_center_crop`, 72  
`mlr_pipeops_augment_color_jitter`, 73  
`mlr_pipeops_augment_crop`, 74  
`mlr_pipeops_augment_hflip`, 74  
`mlr_pipeops_augment_random_affine`, 75  
`mlr_pipeops_augment_random_choice`, 76

`mlr_pipeops_augment_random_crop`, 76  
`mlr_pipeops_augment_random_horizontal_flip`,  
 77  
`mlr_pipeops_augment_random_order`, 78  
`mlr_pipeops_augment_random_resized_crop`,  
 78  
`mlr_pipeops_augment_random_vertical_flip`,  
 79  
`mlr_pipeops_augment_resized_crop`, 80  
`mlr_pipeops_augment_rotate`, 80  
`mlr_pipeops_augment_vflip`, 81  
`mlr_pipeops_module`, 71, 82, 209, 213, 216,  
 218, 220, 222, 233, 246–249, 254,  
 267  
`mlr_pipeops_nn_adaptive_avg_pool1d`, 85,  
 88, 90, 92, 94, 96, 98, 100, 102, 104,  
 106, 108, 110, 112, 115, 117, 119,  
 121, 123, 124, 128, 129, 131, 133,  
 135, 136, 138, 140, 142, 144, 146,  
 147, 149, 151, 153, 155, 158, 160,  
 162, 163, 165, 166, 168, 169, 171,  
 173, 175, 177, 178, 180, 182, 184,  
 186, 187, 189, 191, 193, 195, 197,  
 199, 200, 215, 217, 219, 222, 223,  
 227, 229, 231  
`mlr_pipeops_nn_adaptive_avg_pool2d`, 86,  
 87, 90, 92, 94, 96, 98, 100, 102, 104,  
 106, 108, 110, 112, 115, 117, 119,  
 121, 123, 124, 128, 129, 131, 133,  
 135, 136, 138, 140, 142, 144, 146,  
 147, 149, 151, 153, 155, 158, 160,  
 162, 163, 165, 166, 168, 169, 171,  
 173, 175, 177, 178, 180, 182, 184,  
 186, 187, 189, 191, 193, 195, 197,  
 199, 200, 215, 217, 219, 222, 223,  
 227, 229, 231  
`mlr_pipeops_nn_adaptive_avg_pool3d`, 86,  
 88, 88, 92, 94, 96, 98, 100, 102, 104,  
 106, 108, 110, 112, 115, 117, 119,  
 121, 123, 124, 128, 129, 131, 133,  
 135, 136, 138, 140, 142, 144, 146,  
 147, 149, 151, 153, 155, 158, 160,  
 162, 163, 165, 166, 168, 169, 171,  
 173, 175, 177, 178, 180, 182, 184,  
 186, 187, 189, 191, 193, 195, 197,  
 199, 200, 215, 217, 219, 222, 223,  
 227, 229, 231  
`mlr_pipeops_nn_avg_pool1d`, 86, 88, 90, 90,  
 94, 96, 98, 100, 102, 104, 106, 108,  
 110, 112, 115, 117, 119, 121, 123,  
 124, 128, 129, 131, 133, 135, 136,  
 138, 140, 142, 144, 146, 147, 149,  
 151, 153, 155, 158, 160, 162, 163,  
 165, 166, 168, 169, 171, 173, 175,  
 177, 178, 180, 182, 184, 186, 187,  
 189, 191, 193, 195, 197, 199, 200,  
 215, 217, 219, 222, 223, 227, 229,  
 231  
`mlr_pipeops_nn_avg_pool3d`, 86, 88, 90,  
 92, 94, 98, 100, 102, 104, 106, 108,  
 110, 112, 115, 117, 119, 121, 123,  
 124, 128, 129, 131, 133, 135, 136,  
 138, 140, 142, 144, 146, 147, 149,  
 151, 153, 155, 158, 160, 162, 163,  
 165, 166, 168, 169, 171, 173, 175,  
 177, 178, 180, 182, 184, 186, 187,  
 189, 191, 193, 195, 197, 199, 200,  
 215, 217, 219, 222, 223, 227, 229,  
 231  
`mlr_pipeops_nn_batch_norm1d`, 86, 88, 90,  
 92, 94, 96, 96, 100, 102, 104, 106,  
 108, 110, 112, 115, 117, 119, 121,  
 123, 124, 128, 129, 131, 133, 135,  
 136, 138, 140, 142, 144, 146, 147,  
 149, 151, 153, 155, 158, 160, 162,  
 163, 165, 166, 168, 169, 171, 173,  
 175, 177, 178, 180, 182, 184, 186,  
 187, 189, 191, 193, 195, 197, 199,  
 200, 215, 217, 219, 222, 223, 227,  
 229, 231  
`mlr_pipeops_nn_batch_norm2d`, 86, 88, 90,  
 92, 94, 96, 98, 98, 102, 104, 106,  
 108, 110, 112, 115, 117, 119, 121,  
 123, 124, 128, 129, 131, 133, 135,  
 136, 138, 140, 142, 144, 146, 147,



175, 177, 178, 180, 182, 184, 186, 187, 189, 191, 193, 195, 197, 199, 200, 216, 217, 219, 222, 224, 227, 229, 231

`mlr_pipeops_nn_dropout`, 86, 88, 90, 92, 94, 96, 98, 100, 102, 104, 106, 108, 110, 112, 115, 117, 119, 120, 123, 125, 128, 129, 131, 133, 135, 136, 138, 140, 142, 144, 146, 147, 149, 151, 153, 156, 158, 160, 162, 164–166, 168, 169, 171, 173, 175, 177, 178, 180, 182, 184, 186, 187, 189, 191, 193, 195, 197, 199, 200, 216, 217, 219, 222, 224, 227, 229, 231

`mlr_pipeops_nn_elu`, 86, 88, 90, 92, 94, 96, 98, 100, 102, 104, 106, 108, 110, 112, 115, 117, 119, 121, 121, 125, 128, 129, 131, 133, 135, 136, 138, 140, 142, 144, 146, 147, 149, 151, 153, 156, 158, 160, 162, 164–166, 168, 169, 171, 173, 175, 177, 178, 180, 182, 184, 186, 187, 189, 191, 193, 195, 197, 199, 200, 216, 217, 219, 222, 224, 227, 229, 231

`mlr_pipeops_nn_flatten`, 86, 88, 90, 92, 94, 96, 98, 100, 102, 104, 106, 108, 110, 112, 115, 117, 119, 121, 123, 123, 128, 129, 131, 133, 135, 136, 138, 140, 142, 144, 146, 147, 149, 151, 153, 156, 158, 160, 162, 164–166, 168, 169, 171, 173, 175, 177, 178, 180, 182, 184, 186, 187, 189, 191, 193, 195, 197, 199, 200, 216, 217, 219, 222, 224, 227, 229, 231

`mlr_pipeops_nn_fn`, 125

`mlr_pipeops_nn_ft_cls`, 86, 88, 90, 92, 94, 96, 98, 100, 102, 104, 106, 108, 110, 112, 115, 117, 119, 121, 123, 125, 127, 129, 131, 133, 135, 137, 138, 140, 142, 144, 146, 147, 149, 151, 153, 156, 158, 160, 162, 164–166, 168, 169, 171, 173, 175, 177, 178, 180, 182, 184, 186, 187, 189, 191, 193, 195, 197, 199, 200, 216, 217, 219, 222, 224, 227, 229, 231

`mlr_pipeops_nn_ft_transformer_block`, 86, 88, 90, 92, 94, 96, 98, 100, 102, 104, 106, 108, 110, 112, 115, 117, 119, 121, 123, 125, 128, 129, 131, 133, 135, 135, 138, 140, 142, 144, 146, 147, 149, 151, 153, 156, 158, 160, 162, 164–166, 168, 169, 171, 173, 175, 177, 178, 180, 182, 184, 186, 187, 189, 191, 193, 195, 197, 199, 200, 216, 217, 219, 222, 224, 227, 229, 231

`mlr_pipeops_nn_gelu`, 86, 88, 90, 92, 94, 96, 98, 100, 102, 104, 106, 108, 110, 112, 115, 117, 119, 121, 123, 125, 128, 129, 131, 132, 135, 137, 138, 140, 142, 144, 146, 147, 149, 151, 153, 156, 158, 160, 162, 164–166, 168, 169, 171, 173, 175, 177, 178, 180, 182, 184, 186, 187, 189, 191, 193, 195, 197, 199, 200, 216, 217, 219, 222, 224, 227, 229, 231

`mlr_pipeops_nn_glu`, 86, 88, 90, 92, 94, 96, 98, 100, 102, 104, 106, 108, 110, 112, 115, 117, 119, 121, 123, 125, 128, 129, 131, 133, 134, 137, 138, 140, 142, 144, 146, 147, 149, 151, 153, 156, 158, 160, 162, 164–166, 168, 169, 171, 173, 175, 177, 178, 180, 182, 184, 186, 187, 189, 191, 193, 195, 197, 199, 200, 216, 217, 219, 222, 224, 227, 229, 231

`mlr_pipeops_nn_hardshrink`, 86, 88, 90, 92, 94, 96, 98, 100, 102, 104, 106, 108, 110, 112, 115, 117, 119, 121, 123, 125, 128, 129, 131, 133, 135, 135, 138, 140, 142, 144, 146, 147, 149, 151, 153, 156, 158, 160, 162, 164–166, 168, 169, 171, 173, 175, 177, 178, 180, 182, 184, 186, 187, 189, 191, 193, 195, 197, 199, 200, 216, 217, 219, 222, 224, 227, 229, 231

231

`mlr_pipeops_nn_hardsigmoid`, 86, 88, 90, 92, 94, 96, 98, 100, 102, 104, 106, 108, 110, 112, 115, 117, 119, 121, 123, 125, 128, 129, 131, 133, 135, 137, 138, 140, 142, 144, 146, 147, 149, 151, 153, 156, 158, 160, 162, 164–166, 168, 169, 171, 173, 175, 177, 178, 180, 182, 184, 186, 187, 189, 191, 193, 195, 197, 199, 200, 216, 217, 219, 222, 224, 227, 229, 231

`mlr_pipeops_nn_hardtanh`, 86, 88, 90, 92, 94, 96, 98, 100, 102, 104, 106, 108, 110, 113, 115, 117, 119, 121, 123, 125, 128, 129, 131, 133, 135, 137, 138, 139, 142, 144, 146, 147, 149, 151, 153, 156, 158, 160, 162, 164–166, 168, 169, 171, 173, 175, 177, 178, 180, 182, 184, 186, 187, 189, 191, 193, 195, 197, 199, 200, 216, 217, 219, 222, 224, 227, 229, 231

`mlr_pipeops_nn_head`, 86, 88, 90, 92, 94, 96, 98, 100, 102, 104, 106, 108, 110, 113, 115, 117, 119, 121, 123, 125, 128, 129, 131, 133, 135, 137, 138, 140, 141, 144, 146, 147, 149, 151, 153, 156, 158, 160, 162, 164–166, 168, 169, 171, 173, 175, 177, 178, 180, 182, 184, 186, 187, 189, 191, 193, 195, 197, 199, 200, 216, 217, 219, 222, 224, 227, 229, 231

`mlr_pipeops_nn_identity`, 86, 88, 90, 92, 94, 96, 98, 100, 102, 104, 106, 108, 110, 113, 115, 117, 119, 121, 123, 125, 128, 130, 131, 133, 135, 137, 138, 140, 142, 143, 146, 147, 149, 151, 153, 156, 158, 160, 162, 164–166, 168, 169, 171, 173, 175, 177, 178, 180, 182, 184, 186, 187, 189, 191, 193, 195, 197, 199, 200, 216, 217, 219, 222, 224, 227, 229, 231

`mlr_pipeops_nn_layer_norm`, 86, 88, 90, 92, 94, 96, 98, 100, 102, 104, 106, 108, 110, 113, 115, 117, 119, 121, 123, 125, 128, 130, 131, 133, 135, 137,

138, 140, 142, 144, 144, 147, 149, 151, 153, 156, 158, 160, 162, 164–166, 168, 169, 171, 173, 175, 177, 178, 180, 182, 184, 186, 187, 189, 191, 193, 195, 197, 199, 200, 216, 217, 219, 222, 224, 227, 229, 231

`mlr_pipeops_nn_leaky_relu`, 86, 88, 90, 92, 94, 96, 98, 100, 102, 104, 106, 108, 110, 113, 115, 117, 119, 121, 123, 125, 128, 130, 131, 133, 135, 137, 138, 140, 142, 144, 146, 146, 149, 151, 153, 156, 158, 160, 162, 164–166, 168, 169, 171, 173, 175, 177, 178, 180, 182, 184, 186, 187, 189, 191, 193, 195, 197, 199, 200, 216, 217, 219, 222, 224, 227, 229, 231

`mlr_pipeops_nn_linear`, 86, 88, 90, 92, 94, 96, 98, 100, 102, 104, 106, 108, 110, 113, 115, 117, 119, 121, 123, 125, 128, 130, 131, 133, 135, 137, 138, 140, 142, 144, 146, 147, 148, 151, 153, 156, 158, 160, 162, 164–166, 168, 169, 171, 173, 175, 177, 178, 180, 182, 184, 186, 187, 189, 191, 193, 195, 197, 199, 200, 216, 217, 219, 222, 224, 227, 229, 231

`mlr_pipeops_nn_log_sigmoid`, 86, 88, 90, 92, 94, 96, 98, 100, 102, 104, 106, 108, 110, 113, 115, 117, 119, 121, 123, 125, 128, 130, 131, 133, 135, 137, 138, 140, 142, 144, 146, 147, 149, 150, 153, 156, 158, 160, 162, 164–166, 168, 169, 171, 173, 175, 177, 178, 180, 182, 184, 186, 187, 189, 191, 193, 195, 197, 199, 200, 216, 217, 219, 222, 224, 227, 229, 231

`mlr_pipeops_nn_max_pool1d`, 86, 88, 90, 92, 94, 96, 98, 100, 102, 104, 106, 108, 110, 113, 115, 117, 119, 121, 123, 125, 128, 130, 131, 133, 135, 137, 138, 140, 142, 144, 146, 147, 149, 151, 152, 156, 158, 160, 162, 164–166, 168, 169, 171, 173, 175, 177, 178, 180, 182, 184, 186, 187, 189, 191, 193, 195, 197, 199, 200,

216, 217, 219, 222, 224, 227, 229, 231

`mlr_pipeops_nn_max_pool2d`, 86, 88, 90, 92, 94, 96, 98, 100, 102, 104, 106, 108, 110, 113, 115, 117, 119, 121, 123, 125, 128, 130, 131, 133, 135, 137, 138, 140, 142, 144, 146, 147, 149, 151, 153, 154, 158, 160, 162, 164–166, 168, 169, 171, 173, 175, 177, 179, 180, 182, 184, 186, 188, 189, 191, 193, 195, 197, 199, 201, 216, 217, 219, 222, 224, 227, 229, 231

`mlr_pipeops_nn_max_pool3d`, 86, 88, 90, 92, 94, 96, 98, 100, 102, 104, 106, 108, 110, 113, 115, 117, 119, 121, 123, 125, 128, 130, 131, 133, 135, 137, 138, 140, 142, 144, 146, 148, 149, 151, 153, 156, 158, 160, 162, 164–166, 168, 169, 171, 173, 175, 177, 179, 180, 182, 184, 186, 188, 189, 191, 193, 195, 197, 199, 201, 216, 217, 219, 222, 224, 227, 229, 231

`mlr_pipeops_nn_merge`, 86, 88, 90, 92, 94, 96, 98, 100, 102, 104, 106, 108, 110, 113, 115, 117, 119, 121, 123, 125, 128, 130, 131, 133, 135, 137, 138, 140, 142, 144, 146, 148, 149, 151, 153, 156, 158, 158, 162, 164–166, 168, 169, 171, 173, 175, 177, 179, 180, 182, 184, 186, 188, 189, 191, 193, 195, 197, 199, 201, 216, 217, 219, 222, 224, 227, 229, 231

`mlr_pipeops_nn_merge_cat`, 86, 88, 90, 92, 94, 96, 98, 100, 102, 104, 106, 108, 110, 113, 115, 117, 119, 121, 123, 125, 128, 130, 131, 133, 135, 137, 138, 140, 142, 144, 146, 148, 149, 151, 153, 156, 158, 160, 160, 164–166, 168, 169, 171, 173, 175, 177, 179, 180, 182, 184, 186, 188, 189, 191, 193, 195, 197, 199, 201, 216, 217, 219, 222, 224, 227, 229, 231

`mlr_pipeops_nn_merge_prod`, 86, 88, 90, 92, 94, 96, 98, 100, 102, 104, 106, 108, 110, 113, 115, 117, 119, 121, 123, 125, 128, 130, 131, 133, 135, 137, 138, 140, 142, 144, 146, 148, 149, 151, 153, 156, 158, 160, 162, 164–166, 168, 169, 170, 173, 175, 177, 179, 180, 182, 184, 186, 188, 189, 191, 193, 195, 197, 199, 201, 216, 217, 219, 222, 224, 227, 229, 231

`mlr_pipeops_nn_reglu`, 86, 88, 90, 92, 94, 96, 98, 100, 102, 104, 106, 108, 110, 113, 115, 117, 119, 121, 123, 125, 128, 130, 131, 133, 135, 137, 138, 140, 142, 144, 146, 148, 149, 151, 153, 156, 158, 160, 162, 164–166, 168, 169, 171, 173, 175, 177, 179, 180, 182, 184, 186, 188, 189, 191, 193, 195, 197, 199, 201, 216, 217, 219, 222, 224, 227, 229, 231

`mlr_pipeops_nn_relu`, 86, 88, 90, 92, 94, 96, 98, 100, 102, 104, 106, 108, 110, 113, 115, 117, 119, 121, 123, 125, 128, 130, 131, 133, 135, 137, 138, 140, 142, 144, 146, 148, 149, 151, 153, 156, 158, 160, 162, 164–166, 168, 169, 170, 173, 175, 177, 179, 180, 182, 184, 186, 188, 189, 191, 193, 195, 197, 199, 201, 216, 217, 219, 222, 224, 227, 229, 231

`mlr_pipeops_nn_relu6`, 86, 88, 90, 92, 94, 96, 98, 100, 102, 104, 106, 108, 110, 113, 115, 117, 119, 121, 123, 125, 128, 130, 131, 133, 135, 137, 138, 140, 142, 144, 146, 148, 149, 151, 153, 156, 158, 160, 162, 164, 166, 168, 169, 171, 172, 175, 177, 179, 180, 182, 184, 186, 188, 189, 191, 193, 195, 197, 199, 201, 216, 217, 219, 222, 224, 227, 229, 231

`mlr_pipeops_nn_reshape`, 86, 88, 90, 92, 94, 96, 98, 100, 102, 104, 106, 108, 110, 113, 115, 117, 119, 121, 123, 125, 128, 130, 131, 133, 135, 137, 138, 140, 142, 144, 146, 148, 149, 151, 153, 156, 158, 160, 162, 164, 166, 168, 169, 171, 173, 174, 177, 179, 180, 182, 184, 186, 188, 189, 191, 193, 195, 197, 199, 201, 216, 217, 219, 222, 224, 227, 229, 231

`mlr_pipeops_nn_rrelu`, 86, 88, 90, 92, 94, 96, 98, 100, 102, 104, 106, 108, 110, 113, 115, 117, 119, 121, 123, 125, 128, 130, 131, 133, 135, 137, 138, 140, 142, 144, 146, 148, 149, 151, 153, 156, 158, 160, 162, 164, 166, 168, 169, 171, 173, 175, 177, 179, 180, 182, 184, 186, 188, 189, 191, 193, 195, 197, 199, 201, 216, 217, 219, 222, 224, 227, 229, 231

`mlr_pipeops_nn_selu`, 86, 88, 90, 92, 94, 96, 98, 100, 102, 104, 106, 108, 110, 113, 115, 117, 119, 121, 123, 125, 128, 130, 131, 133, 135, 137, 138, 140, 142, 144, 146, 148, 149, 151, 153, 156, 158, 160, 162, 164, 166, 168, 169, 171, 173, 175, 177, 179, 180, 182, 184, 186, 188, 189, 191, 193, 195, 197, 199, 201, 216, 217, 219, 222, 224, 227, 229, 231

`mlr_pipeops_nn_sigmoid`, 86, 88, 90, 92, 94, 96, 98, 100, 102, 104, 106, 108, 110, 113, 115, 117, 119, 121, 123, 125, 128, 130, 131, 133, 135, 137, 138, 140, 142, 144, 146, 148, 149, 151, 153, 156, 158, 160, 162, 164, 166, 168, 169, 171, 173, 175, 177, 179, 180, 182, 184, 186, 188, 189, 191, 193, 195, 197, 199, 201, 216, 217, 219, 222, 224, 227, 229, 231

`mlr_pipeops_nn_squeeze`, 86, 88, 90, 92, 94, 96, 98, 100, 102, 104, 106, 108, 110, 113, 115, 117, 119, 121, 123, 125, 128, 130, 131, 133, 135, 137, 138, 140, 142, 144, 146, 148, 149, 151, 153, 156, 158, 160, 162, 164, 166, 168, 169, 171, 173, 175, 177, 179, 180, 182, 184, 186, 188, 189, 191, 193, 195, 197, 199, 201, 216, 217, 219, 222, 224, 227, 229, 231

168, 169, 171, 173, 175, 177, 179, 180, 182, 184, 186, 188, 188, 191, 193, 195, 197, 199, 201, 216, 217, 219, 222, 224, 227, 229, 231  
`mlr_pipeops_nn_tanh`, 86, 88, 90, 92, 94, 96, 98, 100, 102, 104, 106, 108, 110, 113, 115, 117, 119, 121, 123, 125, 128, 130, 131, 133, 135, 137, 138, 140, 142, 144, 146, 148, 149, 151, 153, 156, 158, 160, 162, 164, 166, 168, 169, 171, 173, 175, 177, 179, 180, 182, 184, 186, 188, 189, 190, 193, 195, 197, 199, 201, 216, 217, 219, 222, 224, 227, 229, 231  
`mlr_pipeops_nn_tanhshrink`, 86, 88, 90, 92, 94, 96, 98, 100, 102, 104, 106, 108, 111, 113, 115, 117, 119, 121, 123, 125, 128, 130, 131, 133, 135, 137, 138, 140, 142, 144, 146, 148, 149, 151, 153, 156, 158, 160, 162, 164, 166, 168, 169, 171, 173, 175, 177, 179, 180, 182, 184, 186, 188, 189, 191, 192, 195, 197, 199, 201, 216, 217, 219, 222, 224, 227, 229, 231  
`mlr_pipeops_nn_threshold`, 86, 88, 90, 92, 94, 96, 98, 100, 102, 104, 106, 108, 111, 113, 115, 117, 119, 121, 123, 125, 128, 130, 131, 133, 135, 137, 138, 140, 142, 144, 146, 148, 149, 151, 153, 156, 158, 160, 162, 164, 166, 168, 170, 171, 173, 175, 177, 179, 180, 182, 184, 186, 188, 189, 191, 193, 195, 197, 199, 201, 216, 217, 219, 222, 224, 227, 229, 231  
`mlr_pipeops_nn_tokenizer_categ`, 86, 88, 90, 92, 94, 96, 98, 100, 102, 104, 106, 108, 111, 113, 115, 117, 119, 121, 123, 125, 128, 130, 131, 133, 135, 137, 138, 140, 142, 144, 146, 148, 149, 151, 153, 156, 158, 160, 162, 164, 166, 168, 170, 171, 173, 175, 177, 179, 180, 182, 184, 186, 188, 189, 191, 193, 195, 197, 199, 201, 216, 217, 219, 222, 224, 227, 229, 231  
`mlr_pipeops_nn_tokenizer_num`, 86, 88, 90, 92, 94, 96, 98, 100, 102, 104, 106, 108, 111, 113, 115, 117, 119, 121, 123, 125, 128, 130, 131, 133, 135, 137, 138, 140, 142, 144, 146, 148, 149, 151, 153, 156, 158, 160, 162, 164, 166, 168, 170, 171, 173, 175, 177, 179, 180, 182, 184, 186, 188, 189, 191, 193, 195, 197, 199, 201, 209, 214, 218, 220, 222, 224, 227, 229, 231, 246–249, 254, 267  
`mlr_pipeops_torch`, 71, 83, 206, 216, 218, 220, 222, 246–249, 254, 267  
`mlr_pipeops_torch_callbacks`, 83, 212, 224, 233, 246, 249  
`mlr_pipeops_torch_ingress`, 71, 83, 86, 88, 90, 92, 94, 96, 98, 100, 102, 104, 106, 108, 111, 113, 115, 117, 119, 121, 123, 125, 128, 130, 131, 133, 135, 137, 138, 140, 142, 144, 146, 148, 149, 151, 154, 156, 158, 160, 162, 164, 166, 168, 170, 171, 173, 175, 177, 179, 180, 182, 184, 186, 188, 189, 191, 193, 195, 197, 199, 201, 209, 214, 218, 220, 222, 224, 227, 229, 231, 246–249, 254, 267  
`mlr_pipeops_torch_ingress_categ`, 71, 83, 86, 88, 90, 92, 94, 96, 98, 100, 102, 104, 106, 108, 111, 113, 115, 117, 119, 121, 123, 125, 128, 130, 131, 133, 135, 137, 138, 140, 142, 144, 146, 148, 149, 151, 154, 156, 158, 160, 162, 164, 166, 168, 170, 171, 173, 175, 177, 179, 180, 182, 184, 186, 188, 189, 191, 193, 195, 197, 199, 201, 209, 216, 218, 220, 222, 224, 227, 229, 231, 246–249, 254, 267  
`mlr_pipeops_torch_ingress_ltnsr`, 71, 83, 86, 88, 90, 92, 94, 96, 98, 100, 102,

104, 106, 108, 111, 113, 115, 117, 119, 121, 123, 125, 128, 130, 131, 133, 135, 137, 138, 140, 142, 144, 146, 148, 149, 151, 154, 156, 158, 160, 162, 164, 166, 168, 170, 171, 173, 175, 177, 179, 180, 182, 184, 186, 188, 189, 191, 193, 195, 197, 199, 201, 209, 216, 218, 218, 222, 224, 228, 229, 231, 246–249, 254, 267

`mlr_pipeops_torch_ingress_num`, 71, 83, 86, 88, 90, 92, 94, 96, 98, 100, 102, 104, 106, 108, 111, 113, 115, 117, 119, 121, 123, 125, 128, 130, 131, 133, 135, 137, 138, 140, 142, 144, 146, 148, 149, 151, 154, 156, 158, 160, 162, 164, 166, 168, 170, 171, 173, 175, 177, 179, 180, 182, 184, 186, 188, 189, 191, 193, 195, 197, 199, 201, 209, 216, 218, 220, 221, 224, 228, 229, 231, 246–249, 254, 267

`mlr_pipeops_torch_loss`, 86, 88, 90, 92, 94, 96, 98, 100, 102, 104, 106, 108, 111, 113, 115, 117, 119, 121, 123, 125, 128, 130, 131, 133, 135, 137, 138, 140, 142, 144, 146, 148, 149, 151, 154, 156, 158, 160, 162, 164, 166, 168, 170, 171, 173, 175, 177, 179, 180, 182, 184, 186, 188, 189, 191, 193, 195, 197, 199, 201, 213, 216, 218, 220, 222, 222, 228, 229, 231, 233, 246, 249

`mlr_pipeops_torch_model`, 86, 88, 90, 92, 94, 96, 98, 100, 102, 104, 106, 108, 111, 113, 115, 117, 119, 121, 123, 125, 128, 130, 131, 133, 135, 137, 138, 140, 142, 144, 146, 148, 149, 151, 154, 156, 158, 160, 162, 164, 166, 168, 170, 171, 173, 175, 177, 179, 180, 182, 184, 186, 188, 189, 191, 193, 195, 197, 199, 201, 216, 218, 220, 222, 224, 228, 229, 231, 233, 246, 249

`mlr_pipeops_torch_model`, 86, 88, 90, 92, 94, 96, 98, 100, 102, 104, 106, 108, 111, 113, 115, 117, 119, 121, 123, 125, 128, 130, 131, 133, 135, 137, 138, 140, 142, 144, 146, 148, 149, 151, 154, 156, 158, 160, 162, 164, 166, 168, 170, 171, 173, 175, 177, 179, 180, 182, 184, 186, 188, 189, 191, 193, 195, 197, 199, 201, 216, 218, 220, 222, 224, 228, 229, 231, 233, 246, 249

`mlr_pipeops_torch_model_classif`, 86, 88, 90, 92, 94, 96, 98, 100, 102, 104, 106, 108, 111, 113, 115, 117, 119, 121, 123, 125, 128, 130, 131, 133, 135, 137, 138, 140, 142, 144, 146, 148, 149, 151, 154, 156, 158, 160, 162, 164, 166, 168, 170, 171, 173, 175, 177, 179, 180, 182, 184, 186, 188, 189, 191, 193, 195, 197, 199, 201, 216, 218, 220, 222, 224, 228, 229, 231, 233, 246, 249

`mlr_pipeops_torch_model_regr`, 86, 88, 90, 92, 94, 96, 98, 100, 102, 104, 106, 108, 111, 113, 115, 117, 119, 121, 123, 125, 128, 130, 131, 133, 135, 137, 138, 140, 142, 144, 146, 148, 149, 151, 154, 156, 158, 160, 162, 164, 166, 168, 170, 171, 173, 175, 177, 179, 180, 182, 184, 186, 188, 189, 191, 193, 195, 197, 199, 201, 216, 218, 220, 222, 224, 228, 229, 230

`mlr_pipeops_torch_optimizer`, 83, 213, 224, 232, 246, 249

`mlr_pipeops_trafo_adjust_brightness`, 233

`mlr_pipeops_trafo_adjust_gamma`, 234

`mlr_pipeops_trafo_adjust_hue`, 235

`mlr_pipeops_trafo_adjust_saturation`, 235

`mlr_pipeops_trafo_grayscale`, 236

`mlr_pipeops_trafo_nop`, 236

`mlr_pipeops_trafo_normalize`, 237

`mlr_pipeops_trafo_pad`, 237

`mlr_pipeops_trafo_reshape`, 238

`mlr_pipeops_trafo_resize`, 238

`mlr_pipeops_trafo_rgb_to_grayscale`, 239

`mlr_reflections$learner_predict_types`, 53, 67, 70

`mlr_reflections$learner_properties`, 66, 69

`mlr_reflections$task_feature_types`, 66, 215

`mlr_tasks_cifar`, 240

`mlr_tasks_cifar10`(`mlr_tasks_cifar`), 240

`mlr_tasks_cifar100`(`mlr_tasks_cifar`), 240

`mlr_tasks_lazy_iris`, 241

`mlr_tasks_melanoma`, 242

`mlr_tasks_mnist`, 243

`mlr_tasks_tiny_imagenet`, 244

model descriptor union, 207

**model\_descriptor\_to\_learner**, 71, 83, 209, 216, 218, 220, 222, 246, 246, 248, 249, 254, 267  
**model\_descriptor\_to\_learner()**, 226, 228, 230  
**model\_descriptor\_to\_module**, 71, 83, 209, 216, 218, 220, 222, 245–247, 247, 249, 254, 267  
**model\_descriptor\_union**, 71, 83, 207, 209, 213, 216, 218, 220, 222, 224, 233, 246–248, 248, 254, 267  
**ModelDescriptor**, 71, 82, 83, 202, 206, 207, 209, 212, 213, 216, 218, 220, 222–224, 226, 228, 230, 232, 233, 245, 247–249, 254, 263, 267, 268, 271  
**module**, 83  
**network**, 61  
**nn**, 249  
**nn\_adaptive\_avg\_pool1d()**, 85  
**nn\_adaptive\_avg\_pool2d()**, 87  
**nn\_adaptive\_avg\_pool3d()**, 89  
**nn\_avg\_pool1d()**, 90  
**nn\_avg\_pool2d()**, 92  
**nn\_avg\_pool3d()**, 94  
**nn\_bce\_with\_logits\_loss**, 16  
**nn\_conv\_transpose1d**, 113  
**nn\_conv\_transpose2d**, 115  
**nn\_conv\_transpose3d**, 118  
**nn\_cross\_entropy\_loss**, 16  
**nn\_ft\_cls**, 249  
**nn\_ft\_cls()**, 127  
**nn\_ft\_transformer\_block**, 250  
**nn\_ft\_transformer\_block()**, 129  
**nn\_gelu**, 130, 252  
**nn\_graph**, 71, 83, 209, 216, 218, 220, 222, 245–249, 253, 253, 267  
**nn\_linear**, 206  
**nn\_merge\_cat**, 254  
**nn\_merge\_cat()**, 160  
**nn\_merge\_prod**, 254  
**nn\_merge\_prod()**, 162  
**nn\_merge\_sum**, 255  
**nn\_merge\_sum()**, 164  
**nn\_module**, 64, 71, 82, 83, 206  
**nn\_module()**, 65, 70  
**nn\_module\_list**, 253  
**nn\_relu**, 168, 255  
**nn\_relu**, 49  
**nn\_reshape**, 256  
**nn\_reshape()**, 174  
**nn\_sequential**, 123  
**nn\_squeeze**, 256  
**nn\_squeeze()**, 188  
**nn\_tokenizer\_categ**, 257  
**nn\_tokenizer\_categ()**, 195  
**nn\_tokenizer\_num**, 257  
**nn\_tokenizer\_num()**, 197  
**nn\_unsqueeze**, 258  
**nn\_unsqueeze()**, 199  
**optimizer**, 61  
**output\_dim\_for**, 258  
**output\_dim\_for()**, 64  
**ParamSet**, 52, 64–66, 69, 103, 126, 159, 203, 206, 208, 215, 259, 262, 265, 266, 268, 269, 271  
**ParamUty**, 271  
**PipeOp**, 24, 141, 206, 208, 209  
**pipeop\_prepoc\_torch**, 201, 259  
**PipeOpModule**, 17, 202, 206–209, 245, 253  
**PipeOpModule (mlr\_pipeops\_module)**, 82  
**PipeOpNOP**, 206, 245  
**PipeOpPreprocTorchAugmentCenterCrop**  
    (**mlr\_pipeops\_augment\_center\_crop**), 72  
**PipeOpPreprocTorchAugmentColorJitter**  
    (**mlr\_pipeops\_augment\_color\_jitter**), 73  
**PipeOpPreprocTorchAugmentCrop**  
    (**mlr\_pipeops\_augment\_crop**), 74  
**PipeOpPreprocTorchAugmentHflip**  
    (**mlr\_pipeops\_augment\_hflip**), 74  
**PipeOpPreprocTorchAugmentRandomAffine**  
    (**mlr\_pipeops\_augment\_random\_affine**), 75  
**PipeOpPreprocTorchAugmentRandomChoice**  
    (**mlr\_pipeops\_augment\_random\_choice**), 76  
**PipeOpPreprocTorchAugmentRandomCrop**  
    (**mlr\_pipeops\_augment\_random\_crop**), 76  
**PipeOpPreprocTorchAugmentRandomHorizontalFlip**  
    (**mlr\_pipeops\_augment\_random\_horizontal\_flip**), 77

PipeOpPreprocTorchAugmentRandomOrder PipeOpTaskPreprocSimple, 202  
(mlr\_pipeops\_augment\_random\_order), PipeOpTaskPreprocTorch, 72–81, 126,  
78 233–239, 259, 260

PipeOpPreprocTorchAugmentRandomResizedCrop PipeOpTaskPreprocTorch  
(mlr\_pipeops\_augment\_random\_resized\_crop), (mlr\_pipeops\_preproc\_torch),  
78 201

PipeOpPreprocTorchAugmentRandomVerticalFlip PipeOpTorch, 82, 85, 87, 89, 91, 92, 94, 97,  
(mlr\_pipeops\_augment\_random\_vertical\_flip), 99, 101, 103, 105, 107, 109, 111,  
79 114, 115, 118, 120, 122, 124–126,  
130, 132, 134, 136, 137, 141, 143,  
145, 147, 148, 150, 152, 155, 157,  
159, 161, 163, 164, 167, 168, 170,  
172, 174, 176, 178, 179, 181, 183,  
185, 187, 188, 190, 192, 194, 196,  
198, 200, 206, 207, 214, 216, 218,  
221, 222, 245, 248

PipeOpPreprocTorchAugmentVflip PipeOpTorch (mlr\_pipeops\_torch), 206  
(mlr\_pipeops\_augment\_vflip), 81

PipeOpPreprocTorchTrafoAdjustBrightness PipeOpTorchAdaptiveAvgPool1D  
(mlr\_pipeops\_trafo\_adjust\_brightness), (mlr\_pipeops\_nn\_adaptive\_avg\_pool1d),  
233 85

PipeOpPreprocTorchTrafoAdjustGamma PipeOpTorchAdaptiveAvgPool2D  
(mlr\_pipeops\_trafo\_adjust\_gamma), (mlr\_pipeops\_nn\_adaptive\_avg\_pool2d),  
234 87

PipeOpPreprocTorchTrafoAdjustHue PipeOpTorchAdaptiveAvgPool3D  
(mlr\_pipeops\_trafo\_adjust\_hue), (mlr\_pipeops\_nn\_adaptive\_avg\_pool3d),  
235 88

PipeOpPreprocTorchTrafoAdjustSaturation PipeOpTorchAvgPool1D  
(mlr\_pipeops\_trafo\_adjust\_saturation), (mlr\_pipeops\_nn\_avg\_pool1d), 90  
235

PipeOpPreprocTorchTrafoGrayscale PipeOpTorchAvgPool2D  
(mlr\_pipeops\_trafo\_grayscale), (mlr\_pipeops\_nn\_avg\_pool2d), 92  
236

PipeOpPreprocTorchTrafoNop PipeOpTorchAvgPool3D  
(mlr\_pipeops\_trafo\_nop), 236 (mlr\_pipeops\_nn\_avg\_pool3d), 94

PipeOpPreprocTorchTrafoNormalize PipeOpTorchBatchNorm1D  
(mlr\_pipeops\_trafo\_normalize), (mlr\_pipeops\_nn\_batch\_norm1d),  
237 96

PipeOpPreprocTorchTrafoPad PipeOpTorchBatchNorm2D  
(mlr\_pipeops\_trafo\_pad), 237 (mlr\_pipeops\_nn\_batch\_norm2d),  
238 98

PipeOpPreprocTorchTrafoReshape PipeOpTorchBatchNorm3D  
(mlr\_pipeops\_trafo\_reshape), (mlr\_pipeops\_nn\_batch\_norm3d),  
238 100

PipeOpPreprocTorchTrafoResize PipeOpTorchBlock  
(mlr\_pipeops\_trafo\_resize), 238 (mlr\_pipeops\_nn\_block), 102

PipeOpPreprocTorchTrafoRgbToGrayscale PipeOpTorchCallbacks, 245  
(mlr\_pipeops\_trafo\_rgb\_to\_grayscale), (mlr\_pipeops\_torch\_callbacks),  
239 212

PipeOpTaskPreproc, 201, 202 PipeOpTorchCELU (mlr\_pipeops\_nn\_celu),

- 105
- PipeOpTorchConv1D
  - (mlr\_pipeops\_nn\_conv1d), 107
- PipeOpTorchConv2D
  - (mlr\_pipeops\_nn\_conv2d), 109
- PipeOpTorchConv3D
  - (mlr\_pipeops\_nn\_conv3d), 111
- PipeOpTorchConvTranspose1D
  - (mlr\_pipeops\_nn\_conv\_transpose1d), 113
- PipeOpTorchConvTranspose2D
  - (mlr\_pipeops\_nn\_conv\_transpose2d), 115
- PipeOpTorchConvTranspose3D
  - (mlr\_pipeops\_nn\_conv\_transpose3d), 117
- PipeOpTorchDropout
  - (mlr\_pipeops\_nn\_dropout), 120
- PipeOpTorchELU (mlr\_pipeops\_nn\_elu), 121
- PipeOpTorchFlatten
  - (mlr\_pipeops\_nn\_flatten), 123
- PipeOpTorchFn (mlr\_pipeops\_nn\_fn), 125
- PipeOpTorchFTCLS
  - (mlr\_pipeops\_nn\_ft\_cls), 127
- PipeOpTorchFTTransformerBlock, 47
- PipeOpTorchFTTransformerBlock
  - (mlr\_pipeops\_nn\_ft\_transformer\_block), PipeOpTorchLoss
  - (mlr\_pipeops\_torch\_loss), 222
- PipeOpTorchGeGLU
  - (mlr\_pipeops\_nn\_geglu), 130
- PipeOpTorchGELU (mlr\_pipeops\_nn\_gelu), 132
- PipeOpTorchGLU (mlr\_pipeops\_nn\_glu), 134
- PipeOpTorchHardShrink
  - (mlr\_pipeops\_nn\_hardshrink), 135
- PipeOpTorchHardSigmoid
  - (mlr\_pipeops\_nn\_hardsigmoid), 137
- PipeOpTorchHardTanh
  - (mlr\_pipeops\_nn\_hardtanh), 139
- PipeOpTorchHead, 207, 209
- PipeOpTorchHead (mlr\_pipeops\_nn\_head), 141
- PipeOpTorchIdentity
  - (mlr\_pipeops\_nn\_identity), 143
- PipeOpTorchIngress, 82, 207, 245
- PipeOpTorchIngress
  - (mlr\_pipeops\_torch\_ingress), 214
- PipeOpTorchIngressCategorical, 214
- PipeOpTorchIngressCategorical
  - (mlr\_pipeops\_torch\_ingress\_categ), 216
- PipeOpTorchIngressLazyTensor, 214
- PipeOpTorchIngressLazyTensor
  - (mlr\_pipeops\_torch\_ingress\_ltnsr), 218
- PipeOpTorchIngressNumeric, 214
- PipeOpTorchIngressNumeric
  - (mlr\_pipeops\_torch\_ingress\_num), 221
- PipeOpTorchLayerNorm
  - (mlr\_pipeops\_nn\_layer\_norm), 144
- PipeOpTorchLeakyReLU
  - (mlr\_pipeops\_nn\_leaky\_relu), 146
- PipeOpTorchLinear
  - (mlr\_pipeops\_nn\_linear), 148
- PipeOpTorchLogSigmoid
  - (mlr\_pipeops\_nn\_log\_sigmoid), 150
- PipeOpTorchLoss, 245
- PipeOpTorchMaxPool1D
  - (mlr\_pipeops\_nn\_max\_pool1d), 152
- PipeOpTorchMaxPool2D
  - (mlr\_pipeops\_nn\_max\_pool2d), 154
- PipeOpTorchMaxPool3D
  - (mlr\_pipeops\_nn\_max\_pool3d), 156
- PipeOpTorchMerge
  - (mlr\_pipeops\_nn\_merge), 158
- PipeOpTorchMergeCat, 158
- PipeOpTorchMergeCat
  - (mlr\_pipeops\_nn\_merge\_cat), 160
- PipeOpTorchMergeProd, 158
- PipeOpTorchMergeProd
  - (mlr\_pipeops\_nn\_merge\_prod), 162
- PipeOpTorchMergeSum, 158
- PipeOpTorchMergeSum

- PipeOpTorchModel (mlr\_pipeops\_nn\_merge\_sum), 164
- PipeOpTorchModel, 202
- PipeOpTorchModel (mlr\_pipeops\_torch\_model), 224
- PipeOpTorchModelClassif (mlr\_pipeops\_torch\_model\_classif), 228
- PipeOpTorchModelRegr (mlr\_pipeops\_torch\_model\_regr), 230
- PipeOpTorchOptimizer, 245
- PipeOpTorchOptimizer (mlr\_pipeops\_torch\_optimizer), 232
- PipeOpTorchPReLU (mlr\_pipeops\_nn\_prelu), 166
- PipeOpTorchReLU (mlr\_pipeops\_nn\_relu), 168
- PipeOpTorchReLU (mlr\_pipeops\_nn\_relu), 170
- PipeOpTorchReLU6 (mlr\_pipeops\_nn\_relu6), 172
- PipeOpTorchReshape (mlr\_pipeops\_nn\_reshape), 174
- PipeOpTorchRReLU (mlr\_pipeops\_nn\_rrelu), 175
- PipeOpTorchSELU (mlr\_pipeops\_nn\_selu), 177
- PipeOpTorchSigmoid (mlr\_pipeops\_nn\_sigmoid), 179
- PipeOpTorchSoftmax (mlr\_pipeops\_nn\_softmax), 181
- PipeOpTorchSoftPlus (mlr\_pipeops\_nn\_softplus), 183
- PipeOpTorchSoftShrink (mlr\_pipeops\_nn\_softshrink), 184
- PipeOpTorchSoftSign (mlr\_pipeops\_nn\_softsign), 186
- PipeOpTorchSqueeze (mlr\_pipeops\_nn\_squeeze), 188
- PipeOpTorchTanh (mlr\_pipeops\_nn\_tanh), 190
- PipeOpTorchTanhShrink (mlr\_pipeops\_nn\_tanhshrink), 192
- PipeOpTorchThreshold (mlr\_pipeops\_nn\_threshold), 193
- PipeOpTorchTokenizerCateg (mlr\_pipeops\_nn\_tokenizer\_categ), 195
- PipeOpTorchTokenizerNum (mlr\_pipeops\_nn\_tokenizer\_num), 197
- PipeOpTorchUnsqueeze (mlr\_pipeops\_nn\_unsqueeze), 199
- R6, 18, 28, 33, 37–39, 41, 42, 45, 47, 50, 52, 55, 57, 59, 66, 69, 70, 83, 85, 87, 89, 91, 93, 95, 97, 99, 101, 103, 105, 108, 110, 112, 114, 116, 118, 120, 122, 124, 126, 127, 129, 131, 132, 134, 136, 138, 139, 141, 143, 145, 147, 149, 150, 153, 155, 157, 159, 161, 163, 165, 167, 169, 171, 172, 174, 176, 178, 180, 181, 183, 185, 187, 189, 190, 192, 194, 196, 198, 200, 203, 208, 213, 215, 217, 219, 221, 223, 227, 228, 230, 232, 263, 266, 269, 271
- R6::R6Class, 240, 241
- R6Class, 15, 72–81, 233–239, 260, 274, 275
- Select, 260, 260
- select\_all (Select), 260
- select\_grep (Select), 260
- select\_invert (Select), 260
- select\_name (Select), 260
- select\_none (Select), 260
- t\_clbk, 11–13, 16, 25, 26, 32, 34, 40, 42, 43, 46, 264, 267, 270, 272, 275, 276, 277, 278
- t\_clbk(), 25, 263
- t\_clbks (t\_clbk), 276
- t\_loss, 11–13, 26, 264, 267, 270, 272, 277, 277, 278
- t\_loss(), 25, 268
- t\_losses (t\_loss), 277
- t\_opt, 11–13, 25, 26, 264, 267, 270, 272, 277, 278
- t\_opt(), 271
- t\_opts (t\_opt), 278
- Task, 44, 45, 56, 64, 68, 204, 206, 207, 209, 212, 232, 246, 261, 262, 267
- task, 240, 242–244
- task\_dataset, 64, 261

task\_dataset(), 202  
 TaskClassif, 61  
 TaskRegr, 61  
 tensor, 83, 262  
 tensors, 206  
 torch:::dataloader, 44, 45, 64  
 torch:::dataset, 17, 18, 64, 262  
 torch:::lr\_cosine\_annealing(), 36  
 torch:::lr\_lambda(), 36  
 torch:::lr\_multiplicative(), 36  
 torch:::lr\_one\_cycle(), 36, 37  
 torch:::lr\_reduce\_on\_plateau(), 36, 38  
 torch:::lr\_scheduler(), 36  
 torch:::lr\_step(), 36  
 torch:::nn\_batch\_norm1d(), 96  
 torch:::nn\_batch\_norm2d(), 98  
 torch:::nn\_batch\_norm3d(), 100  
 torch:::nn\_celu(), 105  
 torch:::nn\_conv1d(), 107  
 torch:::nn\_conv2d(), 109  
 torch:::nn\_conv3d(), 111  
 torch:::nn\_dropout(), 120  
 torch:::nn\_elu(), 122  
 torch:::nn\_flatten(), 123  
 torch:::nn\_gelu(), 132  
 torch:::nn\_glu(), 134  
 torch:::nn\_hardshrink(), 135  
 torch:::nn\_hardsigmoid(), 137  
 torch:::nn\_hardtanh(), 139  
 torch:::nn\_identity(), 143  
 torch:::nn\_layer\_norm(), 144  
 torch:::nn\_leaky\_relu(), 146  
 torch:::nn\_linear(), 141, 148  
 torch:::nn\_log\_sigmoid(), 150  
 torch:::nn\_max\_pool1d(), 152  
 torch:::nn\_max\_pool2d(), 154  
 torch:::nn\_max\_pool3d(), 156  
 torch:::nn\_module, 44–46, 64  
 torch:::nn\_prelu(), 166  
 torch:::nn\_relu(), 170  
 torch:::nn\_relu6(), 172  
 torch:::nn\_rrelu(), 175  
 torch:::nn\_selu(), 177  
 torch:::nn\_sigmoid(), 179  
 torch:::nn\_softmax(), 181  
 torch:::nn\_softplus(), 183  
 torch:::nn\_softshrink(), 185  
 torch:::nn\_softsign(), 186

torch:::nn\_tanh(), 190  
 torch:::nn\_tanhshrink(), 192  
 torch:::nn\_threshold(), 193  
 torch:::optimizer, 44, 46  
 torch:::sampler, 63, 226  
 torch:::torch\_reshape(), 174  
 torch:::torch\_squeeze(), 188, 256  
 torch:::torch\_unsqueeze(), 199, 258  
 torch\_callback, 11, 16, 25, 32, 34, 40, 42,  
     43, 46, 264, 273, 277  
 torch\_callback(), 14, 31  
 torch\_float, 61  
 torch\_long, 61  
 torch\_tensor, 16, 18, 64, 203, 272  
 TorchCallback, 10–14, 16, 25, 26, 30–32, 34,  
     40, 42, 43, 46, 48, 50, 53, 55, 57, 59,  
     65, 67, 69, 71, 213, 262, 263, 265,  
     267, 270, 272, 273, 275–278  
 TorchDescriptor, 11–13, 26, 264, 265, 270,  
     272, 277, 278  
 TorchIngressToken, 20, 21, 64, 71, 83, 209,  
     214, 216, 218, 220, 222, 246–249,  
     254, 262, 267  
 TorchIngressToken(), 52, 71  
 TorchLoss, 11–13, 26, 48, 50, 53, 55, 57, 59,  
     65, 67, 69, 71, 223, 246, 264, 265,  
     267, 268, 272, 277, 278  
 TorchOptimizer, 11–13, 26, 48, 50, 52, 55,  
     57, 59, 65, 67, 69, 71, 232, 233, 246,  
     264, 265, 267, 270, 271, 277, 278  
 torchvision:::cifar10\_dataset(), 240  
 torchvision:::tiny\_imagenet\_dataset(),  
     244  
 torchvision:::transform\_adjust\_brightness,  
     233  
 torchvision:::transform\_adjust\_gamma,  
     234  
 torchvision:::transform\_adjust\_hue, 235  
 torchvision:::transform\_adjust\_saturation,  
     235  
 torchvision:::transform\_center\_crop, 72  
 torchvision:::transform\_color\_jitter,  
     73  
 torchvision:::transform\_crop, 74  
 torchvision:::transform\_grayscale, 236  
 torchvision:::transform\_hflip, 74  
 torchvision:::transform\_normalize, 237  
 torchvision:::transform\_pad, 237

torchvision::transform\_random\_affine,  
    75  
torchvision::transform\_random\_choice,  
    76  
torchvision::transform\_random\_crop, 76  
torchvision::transform\_random\_horizontal\_flip,  
    77  
torchvision::transform\_random\_order,  
    78  
torchvision::transform\_random\_resized\_crop,  
    78  
torchvision::transform\_random\_vertical\_flip,  
    79  
torchvision::transform\_resize, 238  
torchvision::transform\_resized\_crop,  
    80  
torchvision::transform\_rgb\_to\_grayscale,  
    239  
torchvision::transform\_rotate, 80  
torchvision::transform\_vflip, 81